MULTNOMAH COUNTY SURVEYOR SURVEY / PLAT CHECK SHEET

SURVEYOR		DATE OF SURVEY/PLAT
DATE RECEIVED	CHECKED BY	DATE CHECKED
PROJECT/PLAT NAME		ORDER NO.

PLEASE RETURN COPY OF THIS CHECK SHEET WITH ALL NEW SUBMITTALS

YES NO N/A

- 1. Final paper copies will be accepted for review. Must be in <u>final form</u>, with surveyor's seal <u>and</u> original signature. Plat material Archival. Black pigment based permanent nature ink on 4 mil (min) double matte polyester film (3 mil O.K. for surveys).
- 2. Sizes for Surveys: 18" X 24" ONLY including a 1/2" margin (17" X 23" drafting area) with 2½" "Recording Stamp" in the upper right hand corner on each sheet (see website for example). Sizes for Plats: 18" X 24" including a 1" margin (16" X 22" drafting area). Make all surveys/plats in the landscape view.
- Sheets numbered if more than one sheet. For plats over two sheets, a face sheet and index page is required.
- 4. All lines, lettering and symbols shall be of such a size, spacing and density to be clearly legible and reproducible. Minimum size lettering template "80" or 0.08 inches when using all upper case letters and "100" or 0.1 inches when using upper and lower case letters, or hand lettering.
- 5. Location by 1/4 Section, Section, Township, Range, W.M., City, County and State. **Location verified?**
- 6. Date of monumentation, Scale (**standard engineering scales**, such as 1"=10', 20', 30', 40', 50', or 60'). **For plats**, prior approval **is required** for the use of other scales, and North arrow. Please include a graphic Scale.
- 7. Surveyor's Stamp, original signature with expiration date on all pages.
- 8. Surveyor's business name and address.
- 9. If a "Property Line Adjustment" survey, must identify old and new property line. Show new line as solid line in bold. Show old line as dashed. Include areas of Tracts. Reference recording numbers for adjustment deeds. Site Land Use Case No.
- 10. A detailed description of found and set monuments; Size (length of set), type, color, condition, how marked, how set or found, and origin. Make sure that symbols match the legend (same size and shape). Define abbreviations in legend.
- 11. Measured course and distance to an **existing** (monumented) Section corner, 1/4 corner, 1/16 corner, D.L.C. corner or a corner of a recorded subdivision, partition or condominium plat.
- 12. Name and right of way width of shown streets or roads.
- 13. Minimum curve data Delta, radius, arc length (arc length shall be shown on curve only when remote table is used, if possible), chord bearing and distance indicated by arrow when near arc.
- 14. Narrative Must be on the face of the plat. Narrative must:
 - 1. Explain the purpose of survey.
 - 2. Explain basis on which lines were established.
 - 3. Explain which found monuments and deed elements controlled the line established or re-established.
- 15. Basis of Bearing (monuments used and citation of record) in note form or in the narrative. Also label on map.
- Bearing/Angles shown in degrees, minutes and seconds, and distance in feet and hundredths of a foot
- 17. The relationship of **all shown** found monuments by course and distance, or fallings to the monuments set, or by coordinates.
- 18. Bearing and distance on all lot, tract or parcel lines. Solid, **bold line** around subject property. **Survey must be corrected and returned to county surveyor within 30 days.** Any map that is not corrected and returned to the county surveyor within 30 days may be forwarded to the State Board of Engineering Examiners for Engineering and Land Surveying for action, as provided in ORS 209.250 (11).

Revised: January 3, 2022