



## SHIPPING DOCUMENTS (PAPERS)\*

The shipping document provides vital information when responding to a hazardous materials/dangerous goods\*\* incident. The shipping document contains information needed to identify the materials involved. Use this information to initiate protective actions for your own safety and the safety of the public. The shipping document contains the 4-digit ID number (see yellow-bordered pages) preceded by the letters UN or NA, the proper shipping name (see blue-bordered pages), the hazard class or division of the material(s), and, where appropriate, the Packing Group. The shipping document will also display a 24-hour emergency response telephone number. In addition, there must be information available that describes the hazards of the material which can be used in the mitigation of an incident. The information must be entered on or be with the shipping document. This requirement may be satisfied by attaching a guide from the ERG2008 to the shipping document, or by having the entire guidebook available for ready reference. Shipping documents are required for most dangerous goods in transportation. Shipping documents are kept in

- the cab of the motor vehicle,
- the possession of the train crew member,
- a holder on the bridge of a vessel, or
- an aircraft pilot's possession.

EMERGENCY CONTACT 1-000-000-0000	<div style="border: 1px solid black; padding: 2px; display: inline-block;">EXAMPLE OF EMERGENCY CONTACT TELEPHONE NUMBER</div>
NO. & TYPE OF PACKAGES	<div style="border: 1px solid black; padding: 2px; display: inline-block; text-align: center;">HAZARD CLASS OR DIVISION NO.</div>
1 TANKTRUCK	UN1219 ISOPROPANOL 3 II 12,000 LITERS
	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; padding: 2px; text-align: center;">ID NUMBER</div> <div style="border: 1px solid black; padding: 2px; text-align: center;">SHIPPING NAME</div> <div style="border: 1px solid black; padding: 2px; text-align: center;">PACKING GROUP</div> </div>

### EXAMPLE OF PLACARD AND PANEL WITH ID NUMBER

The 4-digit ID Number may be shown on the diamond-shaped placard or on an adjacent orange panel displayed on the ends and sides of a cargo tank, vehicle or rail car.



A Numbered Placard

or

A Placard and an Orange Panel



1219

\* For the purposes of this guidebook, the terms shipping document/shipping paper are synonymous.

\*\* For the purposes of this guidebook, the terms hazardous materials/dangerous goods are synonymous.

**BEFORE AN EMERGENCY – BECOME FAMILIAR WITH THIS GUIDEBOOK!** In the U.S., according to the requirements of the U.S. Department of Labor's Occupational Safety and Health Administration (OSHA, 29 CFR 1910.120), and regulations issued by the U.S. Environmental Protection Agency (EPA, 40 CFR Part 311), first responders must be trained regarding the use of this guidebook.

**RESIST RUSHING IN !**  
**APPROACH INCIDENT FROM UPWIND**  
**STAY CLEAR OF ALL SPILLS, VAPORS, FUMES, SMOKE AND SUSPICIOUS SOURCES**

**HOW TO USE THIS GUIDEBOOK DURING AN INCIDENT INVOLVING DANGEROUS GOODS**

**STEP ONE:** IDENTIFY THE MATERIAL. USE ANY OF THE FOLLOWING:

- **IDENTIFICATION NUMBER (4-DIGIT ID) FROM A PLACARD, ORANGE PANEL, SHIPPING PAPER OR PACKAGE** (after UN/NA)
- **NAME OF THE MATERIAL FROM A SHIPPING DOCUMENT OR PACKAGE**

**STEP TWO:** IDENTIFY 3-DIGIT GUIDE NUMBER USE:

- **ID NUMBER INDEX in yellow-bordered pages** or
- **NAME OF MATERIAL INDEX in blue-bordered pages**

Guide number supplemented with the letter "P" indicates that the material may undergo violent polymerization if subjected to heat or contamination.

**INDEX ENTRIES HIGHLIGHTED IN GREEN** are TIH (Toxic Inhalation Hazard) material, a chemical warfare agent or a Dangerous Water Reactive Material (produces toxic gas upon contact with water).

**IDENTIFY ID NUMBER AND NAME OF MATERIAL IN TABLE 1 – INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES** (the green-bordered pages). **IF NECESSARY, BEGIN PROTECTIVE ACTIONS IMMEDIATELY** (see Protective Actions page 296). If no protective action required, use the information jointly with the 3-digit guide.

**STEP THREE:** TURN TO THE NUMBERED GUIDE (the orange-bordered pages) **READ CAREFULLY.**

**USE GUIDE 112 FOR ALL EXPLOSIVES EXCEPT FOR EXPLOSIVES 1.4 (EXPLOSIVES C) WHERE GUIDE 114 IS TO BE CONSULTED.**

**NOTE:** IF ABOVE STEPS CANNOT BE COMPLETED AND PLACARD IS VISIBLE: Turn to pages 16-17; use 3-digit guide next to placard; **PROCEED TO NUMBERED GUIDE** (orange-bordered pages). If shipping document is available, call emergency response telephone number listed. If document or emergency response telephone is not available, **IMMEDIATELY CALL** the appropriate **emergency response agency listed in the back of this guidebook**. Provide as much information as possible, such as the name of the carrier (trucking company or railroad) and vehicle number. **IF A REFERENCE TO A GUIDE CANNOT BE FOUND AND THIS INCIDENT IS BELIEVED TO INVOLVE DANGEROUS GOODS, TURN TO GUIDE 111 NOW, AND USE IT UNTIL ADDITIONAL INFORMATION BECOMES AVAILABLE.**

**AS A LAST RESORT:** IF ONLY THE CONTAINER CAN BE IDENTIFIED, CONSULT THE TABLE OF RAIL CAR AND ROAD TRAILER IDENTIFICATION CHART (pages 18-19). REMEMBER THAT THE INFORMATION ASSOCIATED WITH THESE CONTAINERS IS FOR WORST CASE SCENARIOS.

## ERG2008 USER'S GUIDE

The 2008 Emergency Response Guidebook (ERG2008) was developed jointly by Transport Canada (TC), the U.S. Department of Transportation (DOT), the Secretariat of Transport and Communications of Mexico (SCT) and with the collaboration of CIQUIME (Centro de Información Química para Emergencias) of Argentina, for use by fire fighters, police, and other emergency services personnel who may be the first to arrive at the scene of a transportation incident involving dangerous goods. **It is primarily a guide to aid first responders in quickly identifying the specific or generic hazards of the material(s) involved in the incident, and protecting themselves and the general public during the initial response phase of the incident.** For the purposes of this guidebook, the “initial response phase” is that period following arrival at the scene of an incident during which the presence and/or identification of dangerous goods is confirmed, protective actions and area securement are initiated, and assistance of qualified personnel is requested. It is not intended to provide information on the physical or chemical properties of dangerous goods.

This guidebook will assist responders in making initial decisions upon arriving at the scene of a dangerous goods incident. It should not be considered as a substitute for emergency response training, knowledge or sound judgment. ERG2008 does not address all possible circumstances that may be associated with a dangerous goods incident. It is primarily designed for use at a dangerous goods incident occurring on a highway or railroad. Be mindful that there may be limited value in its application at fixed facility locations.

ERG2008 incorporates dangerous goods lists from the most recent United Nations Recommendations as well as from other international and national regulations. Explosives are not listed individually by either proper shipping name or ID Number. They do, however, appear under the general heading “Explosives” on the first page of the ID Number index (yellow-bordered pages) and alphabetically in the Name of Material index (blue-bordered pages). Also, the letter “**P**” following the guide number in the yellow-bordered and blue-bordered pages identifies those materials which present a polymerization hazard under certain conditions, for example: Acrolein, stabilized **131P**.

First responders at the scene of a dangerous goods incident should seek additional specific information about any material in question as soon as possible. The information received by contacting the appropriate emergency response agency, by calling the emergency response telephone number on the shipping document, or by consulting the information on or accompanying the shipping document, may be more specific and accurate than this guidebook in providing guidance for the materials involved.

**BEFORE AN EMERGENCY – BECOME FAMILIAR WITH THIS GUIDEBOOK!** In the U.S., according to the requirements of the U.S. Department of Labor’s Occupational Safety and Health Administration (OSHA, 29 CFR 1910.120), and regulations issued by the U.S. Environmental Protection Agency (EPA, 40 CFR Part 311), first responders must be trained regarding the use of this guidebook.

## GUIDEBOOK CONTENTS

**1-Yellow-bordered pages:** Index list of dangerous goods in numerical order of ID number. This section quickly identifies the guide to be consulted from the ID Number of the material involved. This list displays the 4-digit ID number of the material followed by its assigned emergency response guide and the material name.

<b>For example:</b>	<b>ID No.</b> 1090	<b>GUIDE No.</b> 127	<b>Name of Material</b> Acetone
---------------------	-----------------------	-------------------------	------------------------------------

**2-Blue-bordered pages:** Index list of dangerous goods in alphabetical order of material name. This section quickly identifies the guide to be consulted from the name of the material involved. This list displays the name of the material followed by its assigned emergency response guide and 4-digit ID number.

<b>For example:</b>	<b>Name of Material</b> Sulfuric acid	<b>GUIDE No.</b> 137	<b>ID No.</b> 1830
---------------------	--	-------------------------	-----------------------

**3-Orange-bordered pages:** This section is the most important section of the guidebook because it is where all safety recommendations are provided. It comprises a total of 62 individual guides, presented in a two-page format. Each guide provides safety recommendations and emergency response information to protect yourself and the public. The left hand page provides safety related information whereas the right hand page provides emergency response guidance and activities for fire situations, spill or leak incidents and first aid. Each guide is designed to cover a group of materials which possess similar chemical and toxicological characteristics.

The guide title identifies the general hazards of the dangerous goods covered.

**For example:**     **GUIDE 124** - Gases-Toxic and/or Corrosive-Oxidizing.

Each guide is divided into three main sections: the first section describes **potential hazards** that the material may display in terms of fire/explosion and health effects upon exposure. The highest potential is listed first. The emergency responder should consult this section first. This allows the responder to make decisions regarding the protection of the emergency response team as well as the surrounding population.

The second section outlines suggested **public safety** measures based on the situation at hand. It provides general information regarding immediate isolation of the incident site, recommended type of protective clothing and respiratory protection. Suggested evacuation distances are listed for small and large spills and for fire situations (fragmentation hazard). It also directs the reader to consult the tables listing Toxic Inhalation Hazard (TIH) materials, chemical warfare agents and water-reactive materials (green-bordered pages) when the material is highlighted in the yellow-bordered and blue-bordered pages.

The third section covers **emergency response** actions, including first aid. It outlines special precautions for incidents which involve fire, spill or chemical exposure. Several

recommendations are listed under each part which will further assist in the decision making process. The information on first aid is general guidance prior to seeking medical care.

**4-Green-bordered pages:** This section contains two tables. Table 1 lists, by ID number order, TIH materials, including certain chemical warfare agents, and water-reactive materials which produce toxic gases upon contact with water. This table provides two different types of recommended safe distances which are “Initial isolation distances” and “Protective action distances.” The materials are highlighted in green for easy identification in both numeric (yellow-bordered pages) and alphabetic (blue-bordered pages) lists of the guidebook. This table provides distances for both small (approximately 200 liters or less for liquids and 300 kilograms or less for solids when spilled in water) and large spills (more than 200 liters for liquids and more than 300 kilograms for solids when spilled in water) for all highlighted materials. The list is further subdivided into daytime and nighttime situations. This is necessary due to varying atmospheric conditions which greatly affect the size of the hazardous area. The distances change from daytime to nighttime due to different mixing and dispersion conditions in the air. During the night, the air is generally calmer and this causes the material to disperse less and therefore create a toxic zone which is greater than would usually occur during the day. During the day, a more active atmosphere will cause a greater dispersion of the material resulting in a lower concentration of the material in the surrounding air. The actual area where toxic levels are reached will be smaller (due to increased dispersion). In fact, it is the quantity or concentration of the material vapor that poses problems not its mere presence. Table 2 lists, by ID number order, materials which produce large amounts of Toxic Inhalation Hazard (TIH) gases when spilled in water and identifies the TIH gases produced. These Water Reactive materials are easily identified in Table 1 as their name is immediately followed by (when spilled in water). Note, however, if this material is NOT spilled in water, Table 1 and Table 2 do not apply and safety distances will be found within the appropriate orange guide.

The “Initial Isolation Distance” is a distance within which all persons should be considered for evacuation in all directions from the actual spill/leak source. It is a distance (radius) which defines a circle (Initial Isolation Zone) within which persons may be exposed to dangerous concentrations upwind of the source and may be exposed to life threatening concentrations downwind of the source. For example, in the case of Compressed gas, toxic, n.o.s., ID No. 1955, Inhalation Hazard Zone A, the isolation distance for small spills is 100 meters, therefore, representing an evacuation circle of 200 meters in diameter.

For the same material, the “Protective Action Distance” for a small spill is 0.5 kilometers for a daytime incident and 2.1 kilometers for a nighttime incident, these distances represent a downwind distance from the spill/leak source within which Protective Actions could be implemented. Protective Actions are those steps taken to preserve the health and safety of emergency responders and the public. People in this area could be evacuated and/or sheltered in-place. For more information, consult pages 293 to 299.

**What is a TIH?** It is a gas or volatile liquid which is known to be so toxic to humans as to pose a hazard to health during transportation, or in the absence of adequate data on human

toxicity, is presumed to be toxic to humans because when tested on laboratory animals it has a Lethal Concentration 50 (LC50) value of not more than 5000 ppm.

It is important to note that even though the term zone is used, the hazard zones do not represent any actual area or distance. The assignment of the zones is strictly a function of their Lethal Concentration 50 (LC50); for example, TIH Zone A is more toxic than Zone D. All distances which are listed in the green-bordered pages are calculated by the use of mathematical models for each TIH material. For the assignment of hazard zones refer to the glossary.

## **ISOLATION AND EVACUATION DISTANCES**

Isolation or evacuation distances are shown in the guides (orange-bordered pages) and in the Table 1 - Initial Isolation and Protective Action Distances (green-bordered pages). This may confuse users not thoroughly familiar with ERG2008.

It is important to note that some guides refer only to non-TIH materials (36 guides), some refer to both TIH and non-TIH materials (21 guides) and some (5 guides) refer only to TIH or Water-reactive materials (WRM). A guide refers to both TIH and non-TIH materials (for example see GUIDE 131) when the following sentence appears under the title EVACUATION-Spill: "See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under 'PUBLIC SAFETY.'" A guide refers only to TIH or WRM materials (for example see GUIDE 124) when the following sentence appears under the title EVACUATION-Spill: "See Table 1 - Initial Isolation and Protective Action Distances". If the previous sentences do not appear in a guide, then this particular guide refers only to non-TIH materials (for example see GUIDE 128).

In order to identify appropriate isolation and protective action distances, use the following:

If you are dealing with a **TIH/WRM/Chemical warfare** material (highlighted entries in the index lists), the isolation and evacuation distances are found directly in the green-bordered pages. The guides (orange-bordered pages) also remind the user to refer to the green-bordered pages for evacuation specific information involving highlighted materials.

If you are dealing with a **non-TIH material but the guide refers to both TIH and non-TIH materials**, an immediate isolation distance is provided under the heading PUBLIC SAFETY as a precautionary measure to prevent injuries. It applies to the non-TIH materials only. In addition, for evacuation purposes, the guide informs the user under the title EVACUATION-Spill to increase, for non-highlighted materials, in the downwind direction, if necessary, the immediate isolation distance listed under "PUBLIC SAFETY". For example, GUIDE 131 – Flammable Liquids-Toxic, instructs the user to: "As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions." In case of a large spill, the isolation area could be expanded from 50 meters to a distance deemed as safe by the On-scene commander and emergency responders.

If you are dealing with a **non-TIH material and the guide refers only to non-TIH materials**, the immediate isolation and evacuation distances are specified as actual distances in the guide (orange-bordered pages) and are not referenced in the green-bordered pages.

## SAFETY PRECAUTIONS

**APPROACH CAUTIOUSLY FROM UPWIND.** If wind direction allows, consider approaching the incident from uphill. Resist the urge to rush in; others cannot be helped until the situation has been fully assessed.

**SECURE THE SCENE.** Without entering the immediate hazard area, isolate the area and assure the safety of people and the environment, keep people away from the scene and outside the safety perimeter. Allow enough room to move and remove your own equipment.

**IDENTIFY THE HAZARDS.** Placards, container labels, shipping documents, material safety data sheets, Rail Car and Road Trailer Identification Charts, and/or knowledgeable persons on the scene are valuable information sources. Evaluate all available information and consult the recommended guide to reduce immediate risks. **Additional information, provided by the shipper or obtained from another authoritative source, may change some of the emphasis or details found in the guide.** Remember, the guide provides only the most important and worst case scenario information for the initial response in relation to a family or class of dangerous goods. As more material-specific information becomes available, the response should be tailored to the situation.

**ASSESS THE SITUATION.** Consider the following:

- Is there a fire, a spill or a leak?
- What are the weather conditions?
- What is the terrain like?
- Who/what is at risk: people, property or the environment?
- What actions should be taken: Is an evacuation necessary?  
Is diking necessary? What resources (human and equipment) are required and are readily available?
- What can be done immediately?

**OBTAIN HELP.** Advise your headquarters to notify responsible agencies and call for assistance from qualified personnel.

**DECIDE ON SITE ENTRY.** Any efforts made to rescue persons, protect property or the environment must be weighed against the possibility that you could become part of the problem. Enter the area only when wearing appropriate protective gear (see PROTECTIVE CLOTHING, page 348).

**RESPOND.** Respond in an appropriate manner. Establish a command post and lines of communication. Rescue casualties where possible and evacuate if necessary. Maintain control of the site. Continually reassess the situation and modify the response accordingly. The first duty is to consider the safety of people in the immediate area, including your own.

**ABOVE ALL.** Do not walk into or touch spilled material. Avoid inhalation of fumes, smoke and vapors, even if no dangerous goods are known to be involved. Do not assume that gases or vapors are harmless because of lack of a smell—odorless gases or vapors may be harmful. Use **CAUTION** when handling empty containers because they may still present hazards until they are cleaned and purged of all residues.



## WHO TO CALL FOR ASSISTANCE

Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Follow the steps outlined in your organization's standard operating procedures and/or local emergency response plan for obtaining qualified assistance. Generally, the notification sequence and requests for technical information beyond what is available in this guidebook should occur in the following order:

### **1. ORGANIZATION/AGENCY**

Notify your organization/agency. This will set in motion a series of events based upon the information provided. Actions may range from dispatching additional trained personnel to the scene to activating the local emergency response plan. Ensure that local fire and police departments have been notified.

### **2. EMERGENCY RESPONSE TELEPHONE NUMBER**

Locate and call the telephone number listed on the shipping document. The person answering the phone at the listed emergency response number must be knowledgeable of the materials and mitigation actions to be taken, or must have immediate access to a person who has the required knowledge.

### **3. NATIONAL ASSISTANCE**

Contact the appropriate emergency response agency listed on the inside back cover of this guidebook when the emergency response telephone number is not available from the shipping papers. Upon receipt of a call describing the nature of the incident, the agency will provide immediate advice on handling the early stages of the incident. The agency will also contact the shipper or manufacturer of the material for more detailed information and request on-scene assistance when necessary.

Collect and provide as much of the following information as can safely be obtained to your chain-of-command and specialists contacted for technical guidance:

Your name, call back telephone number, FAX number

Location and nature of problem (spill, fire, etc.)

Name and identification number of material(s) involved

Shipper/consignee/point of origin

Carrier name, rail car or truck number

Container type and size

Quantity of material transported/released

Local conditions (weather, terrain, proximity to schools, hospitals, waterways, etc.)

Injuries and exposures

Local emergency services that have been notified

## CANADA

### 1. CANUTEC

**CANUTEC** is the **Canadian Transport Emergency Centre** operated by the Transport Dangerous Goods Directorate of Transport Canada.

**CANUTEC** provides a national bilingual (French and English) advisory service and is staffed by professional scientists experienced and trained in interpreting technical information and providing emergency response advice.

**In an emergency, CANUTEC may be called collect at  
613-996-6666 (24 hours)  
\*666 cellular (Press Star 666, Canada only)**

In a non-emergency situation, please call the information line at 613-992-4624 (24 hours).

### 2. PROVINCIAL AGENCIES

Although technical information and emergency response assistance can be obtained from **CANUTEC**, there are federal and provincial regulations requiring the reporting of dangerous goods incidents to certain authorities.

The following list of provincial agencies is supplied for your convenience.

<b>Province</b>	<b>Emergency Authority and/or Telephone Number</b>
Alberta .....	Local Police and Provincial Authorities 1-800-272-9600* or 780-422-9600
British Columbia .....	Local Police and Provincial Authorities 1-800-663-3456
Manitoba .....	Provincial Authority 204-945-4888 and Local Police or fire brigade, as appropriate
New Brunswick .....	Local Police or 1-800-565-1633** or 902-426-6030
Newfoundland and Labrador .....	Local Police and 709-772-2083
Northwest Territories .....	867-920-8130
Nova Scotia .....	Local Police or 1-800-565-1633** or 902-426-6030
Nunavut Territory .....	Local Police and 1-800-693-1666 or 867-979-6262
Ontario .....	Local Police
Prince Edward Island .....	Local Police or 1-800-565-1633** or 902-426-6030
Quebec .....	Local Police
Saskatchewan .....	Local Police or 1-800-667-7525
Yukon Territory .....	867-667-7244

\* This number is not accessible from outside Alberta.

\*\* This number is not accessible from outside of New Brunswick, Nova Scotia or Prince Edward Island.

NOTE:

1. The appropriate federal agency must be notified in the case of rail, air or marine incidents.
2. The nearest police department must be notified in the case of lost, stolen or misplaced explosives, radioactive materials or infectious substances.
3. **CANUTEC must** be notified in the case of:
  - a. lost, stolen or misplaced infectious substances;
  - b. an incident involving infectious substances;
  - c. an accidental release from a cylinder that has suffered a catastrophic failure;
  - d. an incident where the shipping documents display **CANUTEC's** telephone number 613-996-6666 as the emergency telephone number; or
  - e. a dangerous goods incident in which a railway vehicle, a ship, an aircraft, an aerodrome or an air cargo facility is involved.

## UNITED STATES

1. **CHEMTREC®**, a 24-hour emergency response communication service, can be reached as follows:

CALL **CHEMTREC®** (24 hours)

**1-800-424-9300**

(Toll-free in the U.S., Canada, and the U.S. Virgin Islands)

For calls originating elsewhere:

**703-527-3887** (Collect calls are accepted)

2. **CHEMTEL, INC.**, a 24-hour emergency response communication service, can be reached as follows:

CALL **CHEMTEL, INC.** (24 hours)

**1-888-255-3924**

(Toll-free in the U.S., Canada, Puerto Rico and the U.S. Virgin Islands)

For calls originating elsewhere:

**813-248-0585** (Collect calls are accepted)

3. **INFOTRAC**, a 24-hour emergency response communication service, can be reached as follows:

CALL **INFOTRAC** (24 hours)

**1-800-535-5053**

(Toll-free in the U.S., Canada, and the U.S. Virgin Islands)

For calls originating elsewhere:

**352-323-3500** (Collect calls are accepted)

4. **3E COMPANY**, a 24-hour emergency response communication service, can be reached as follows:

CALL **3E COMPANY** (24 hours)

**1-800-451-8346**

(Toll-free in the U.S., Canada, and the U.S. Virgin Islands)

For calls originating elsewhere:

**760-602-8703** (Collect calls are accepted)

The emergency response information services shown above have requested to be listed as providers of emergency response information and have agreed to provide emergency response information to all callers. They maintain periodically updated lists of state and Federal radiation authorities who provide information and technical assistance on handling incidents involving radioactive materials.

**5. MILITARY SHIPMENTS**

For assistance at incidents involving materials being shipped by, for, or to the Department of Defense (DOD), call one of the following numbers (24 hours):

**703-697-0218** (call collect) (U.S. Army Operations Center) for incidents involving explosives and ammunition.

**1-800-851-8061** (toll-free in the U.S.) (Defense Logistics Agency) for incidents involving dangerous goods other than explosives and ammunition.

**6. NATIONWIDE POISON CONTROL CENTER (United States Only)**

Emergency and information calls are answered by the nearest Poison Center (24 hours):

**1-800-222-1222** (toll-free in the U.S.).

The above numbers are for **emergencies** only.

**NATIONAL RESPONSE CENTER (NRC)**

The NRC, which is operated by the U.S. Coast Guard, receives reports required when dangerous goods and hazardous substances are spilled. After receiving notification of an incident, the NRC will immediately notify the appropriate Federal On-Scene Coordinator and concerned Federal agencies. Federal law requires that anyone who releases into the environment a reportable quantity of a hazardous substance (including oil when water is, or may be affected) or a material identified as a marine pollutant, must **immediately** notify the NRC. When in doubt as to whether the amount released equals the required reporting levels for these materials, the NRC should be notified.

**CALL NRC (24 hours)**

**1-800-424-8802**

(Toll-free in the U.S., Canada, and the U.S. Virgin Islands)

**202-267-2675** in the District of Columbia

Calling the emergency response telephone number, CHEMTREC®, CHEMTEL, INC., INFOTRAC or 3E COMPANY, does not constitute compliance with regulatory requirements to call the NRC.

## MEXICO

1. **SETIQ** (Emergency Transportation System for the Chemical Industry), a service of the National Association of Chemical Industries (ANIQ), can be reached as follows:

CALL **SETIQ** (24 hours)

**01-800-00-214-00** in the Mexican Republic

For calls originating in Mexico City and the Metropolitan Area

**5559-1588**

For calls originating elsewhere, call

**+52-55-5559-1588**

2. **CENACOM**, the National Center for Communications of the Civil Protection Agency, can be reached as follows:

CALL **CENACOM** (24 hours)

**01-800-00-413-00** in the Mexican Republic

For calls originating in Mexico City and the Metropolitan Area

**5128-0000 exts. 11470, 11471, 11472, 11473, 11474, 11475, 11476 and 11477**

For calls originating elsewhere, call

**+52-55-5128-0000 exts. 11470, 11471, 11472, 11474, 11475 and 11476**

## ARGENTINA

1. **CIQUIME** (Chemistry Information Center for Emergencies) a 24-hour emergency response information service, can be reached as follows:

CALL **CIQUIME** (24 hours)

**0-800-222-2933** in the Republic of Argentina

For calls originating elsewhere, call

**+54-11-4613-1100**

## BRAZIL

1. **PRÓ-QUÍMICA** a 24-hour emergency response information service, can be reached as follows:

CALL **PRÓ-QUÍMICA** (24 hours)

**0-800-118270** in the Federal Republic of Brazil

For calls originating elsewhere, call

**+55-11-232-1144**

## COLOMBIA

1. **CISPROQUIM** a 24-hour emergency response information service, can be reached as follows:

CALL **CISPROQUIM** (24 hours)

**01-800-091-6012** in Colombia

For calls originating in Bogotá, Colombia call

**288-6012**

For calls originating elsewhere, call

**+57-1-288-6012**

## HAZARD CLASSIFICATION SYSTEM

The hazard class of dangerous goods is indicated either by its class (or division) number or name. Placards are used to identify the class or division of a material. The hazard class or division number must be displayed in the lower corner of a placard and is required for both primary and subsidiary hazard classes and divisions, if applicable. For other than Class 7 or the OXYGEN placard, text indicating a hazard (for example, "CORROSIVE") is not required. Text is shown only in the U.S. The hazard class or division number and subsidiary hazard classes or division numbers placed in parentheses (when applicable), must appear on the shipping document after each proper shipping name.

### **Class 1 - Explosives**

Division 1.1	Explosives with a mass explosion hazard
Division 1.2	Explosives with a projection hazard
Division 1.3	Explosives with predominantly a fire hazard
Division 1.4	Explosives with no significant blast hazard
Division 1.5	Very insensitive explosives with a mass explosion hazard
Division 1.6	Extremely insensitive articles

### **Class 2 - Gases**

Division 2.1	Flammable gases
Division 2.2	Non-flammable, non-toxic* gases
Division 2.3	Toxic* gases

### **Class 3 - Flammable liquids (and Combustible liquids [U.S.]**

### **Class 4 - Flammable solids; Spontaneously combustible materials; and Dangerous when wet materials/Water-reactive substances**

Division 4.1	Flammable solids
Division 4.2	Spontaneously combustible materials
Division 4.3	Water-reactive substances/Dangerous when wet materials

### **Class 5 - Oxidizing substances and Organic peroxides**

Division 5.1	Oxidizing substances
Division 5.2	Organic peroxides

### **Class 6 - Toxic\* substances and Infectious substances**

Division 6.1	Toxic* substances
Division 6.2	Infectious substances

### **Class 7 - Radioactive materials**

### **Class 8 - Corrosive substances**

### **Class 9 - Miscellaneous hazardous materials/Products, Substances or Organisms**

\* The words "poison" or "poisonous" are synonymous with the word "toxic".



## INTRODUCTION TO THE TABLE OF PLACARDS




### **USE THIS TABLE ONLY IF YOU HAVE NOT BEEN ABLE TO IDENTIFY THE MATERIAL(S) IN TRANSPORT BY ID NUMBER OR SHIPPING NAME**

The next two pages display the placards used on transport vehicles carrying dangerous goods. As you approach a reported or suspected dangerous goods incident involving a placarded vehicle:

- 1. Approach the incident cautiously from upwind to a point from which you can safely identify and/or read the placard or orange panel information.** If wind direction allows, consider approaching the incident from uphill. Use binoculars, if available.
- 2. Match the vehicle placard(s) with one of the placards displayed on the next two pages.**
- 3. Consult the numbered guide associated with the sample placard. Use that information for now.** For example, a FLAMMABLE (Class 3) placard leads to **GUIDE 127**. A CORROSIVE (Class 8) placard leads to **GUIDE 153**. If multiple placards point to more than one guide, initially use the most conservative guide (i.e., the guide requiring the greatest degree of protective actions).
- 4. Remember that the guides associated with the placards provide the most significant risk and/or hazard information.**
- 5. When specific information, such as ID number or shipping name, becomes available, the more specific guide recommended for that material must be consulted.**
- 6. If GUIDE 111 is being used because only the DANGER/DANGEROUS placard is displayed or the nature of the spilled, leaking, or burning material is not known, as soon as possible, get more specific information concerning the material(s) involved.**
- 7. Asterisks (\*) on orange placards represent explosives “Compatibility Group” letters; refer to the Glossary (page 357).**
- 8. Double asterisks (\*\*) on orange placards represent the division of the explosive.**


# TABLE OF PLACARDS AND INITIAL

USE THIS TABLE ONLY IF MATERIALS CANNOT BE SPECIFICALLY IDENTIFIED BY



# RESPONSE GUIDE TO USE ON-SCENE

USING THE SHIPPING DOCUMENT, NUMBERED PLACARD, OR ORANGE PANEL NUMBER





**DANGER**



THIS UNIT IS UNDER FUMIGATION WITH \_\_\_\_\_ APPLIED ON \_\_\_\_\_

Date \_\_\_\_\_ Time \_\_\_\_\_

**DO NOT ENTER**

 **DANGER** 

This unit is under fumigation with \_\_\_\_\_ Cette unité est sous fumigation avec \_\_\_\_\_

(Name of fumigant) (Nom du fumigant)

Applied on \_\_\_\_\_ Depuis le \_\_\_\_\_

Date \_\_\_\_\_ Date \_\_\_\_\_

Time \_\_\_\_\_ Hours \_\_\_\_\_


DO NOT ENTER DÉFENSE D'ENTRER

**INHALATION HAZARD**




**MARINE POLLUTANT**

## RAIL CAR IDENTIFICATION CHART\*





Hopper Car  
Dry Bulk

140




Box Car  
Mixed Cargo

111





Pressure Tank Car  
Compressed Liquefied Gases

117



Low Pressure Tank Car  
Liquids

131





**CAUTION:** Emergency response personnel must be aware that rail tank cars vary widely in construction, fittings and purpose. Tank cars could transport products that may be solids, liquids or gases. The products may be under pressure. It is essential that products be identified by consulting shipping documents or train consist or contacting dispatch centers before emergency response is initiated.

The information stenciled on the sides or ends of tank cars, as illustrated above, may be used to identify the product utilizing:

- a. the commodity name shown; or
- b. the other information shown, especially reporting marks and car number which, when supplied to a dispatch center, will facilitate the identification of the product.


\* The recommended guides should be considered as last resort if the material cannot be identified by any other means.

## ROAD TRAILER IDENTIFICATION CHART\*




DOT406, TC406, SCT-306  
Non-pressure Liquid Tank  
(MC306, TC306)

131




MC338, TC338, SCT-338  
Cryogenic Liquid Tank  
(TC341, CGA341)

117





DOT407, TC407, SCT-307  
Low Pressure Chemical Tank  
(MC307, TC307)

137





Compressed Gas/  
Tube Trailer

117





DOT412, TC412, SCT-312  
Corrosive Liquid Tank  
(MC312, TC312)

137




Dry Bulk Cargo  
Trailer

134





MC331, TC331, SCT-331  
High Pressure Tank

117




Mixed Cargo

111



DOT407, TC407, DOT412, TC412  
Vacuum Loaded Tank  
(TC350)

137



Intermodal Tank

117

**CAUTION:** This chart depicts only the most general shapes of road trailers. Emergency response personnel must be aware that there are many variations of road trailers, not illustrated above, that are used for shipping chemical products. The suggested guides are for the most hazardous products that may be transported in these trailer types.

\* The recommended guides should be considered as last resort if the material cannot be identified by any other means.

## HAZARD IDENTIFICATION CODES DISPLAYED ON SOME INTERMODAL CONTAINERS

Hazard identification codes, referred to as “hazard identification numbers” (also referred to as the Kemler Code) under European and some South American regulations, may be found in the top half of an orange panel on some intermodal bulk containers. The 4-digit identification number is in the bottom half of the orange panel.



The hazard identification code in the top half of the orange panel consists of two or three digits. In general, the digits indicate the following hazards:

- 2 - EMISSION OF GAS DUE TO PRESSURE OR CHEMICAL REACTION
  - 3 - FLAMMABILITY OF LIQUIDS (VAPORS) AND GASES OR SELF-HEATING LIQUID
  - 4 - FLAMMABILITY OF SOLIDS OR SELF-HEATING SOLID
  - 5 - OXIDIZING (FIRE-INTENSIFYING) EFFECT
  - 6 - TOXICITY OR RISK OF INFECTION
  - 7 - RADIOACTIVITY
  - 8 - CORROSIVITY
  - 9 - MISCELLANEOUS DANGEROUS SUBSTANCE
- Doubling of a digit indicates an intensification of that particular hazard (i.e. 33, 66, 88).
  - Where the hazard associated with a material can be adequately indicated by a single digit, the digit is followed by a zero (i.e. 30, 40, 50).
  - A hazard identification code prefixed by the letter “X” indicates that the material will react dangerously with water (i.e. X88).
  - When 9 appears as a 2<sup>nd</sup> or 3<sup>rd</sup> digit, this may present a risk of spontaneous violent reaction.

**HAZARD IDENTIFICATION CODES**  
**DISPLAYED ON SOME INTERMODAL CONTAINERS**

The hazard identification codes listed below have the following meanings:

20	Asphyxiant gas
22	Refrigerated liquefied gas, asphyxiant
223	Refrigerated liquefied gas, flammable
225	Refrigerated liquefied gas, oxidizing (fire-intensifying)
23	Flammable gas
236	Flammable gas, toxic
239	Flammable gas which can spontaneously lead to violent reaction
25	Oxidizing (fire-intensifying) gas
26	Toxic gas
263	Toxic gas, flammable
265	Toxic gas, oxidizing (fire-intensifying)
266	Highly toxic gas
268	Toxic gas, corrosive
<hr/>	
30	Flammable liquid
323	Flammable liquid which reacts with water, emitting flammable gas
X323	Flammable liquid which reacts dangerously with water, emitting flammable gas
33	Highly flammable liquid
333	Pyrophoric liquid
X333	Pyrophoric liquid which reacts dangerously with water
336	Highly flammable liquid, toxic
338	Highly flammable liquid, corrosive
X338	Highly flammable liquid, corrosive, which reacts dangerously with water
339	Highly flammable liquid which can spontaneously lead to violent reaction
36	Flammable liquid, toxic, or self-heating liquid, toxic
362	Flammable liquid, toxic, which reacts with water, emitting flammable gas
X362	Flammable liquid, toxic, which reacts dangerously with water, emitting flammable gas
368	Flammable liquid, toxic, corrosive
38	Flammable liquid, corrosive or self-heating liquid, corrosive
382	Flammable liquid, corrosive, which reacts with water, emitting flammable gas
X382	Flammable liquid, corrosive, which reacts dangerously with water, emitting flammable gas
39	Flammable liquid which can spontaneously lead to violent reaction
<hr/>	
40	Flammable solid, or self-reactive material, or self-heating material
423	Solid which reacts with water, emitting flammable gas

**HAZARD IDENTIFICATION CODES**  
**DISPLAYED ON SOME INTERMODAL CONTAINERS**

X423	Flammable solid which reacts dangerously with water, emitting flammable gas
43	Spontaneously flammable (pyrophoric) solid
44	Flammable solid, in the molten state at an elevated temperature
446	Flammable solid, toxic, in the molten state at an elevated temperature
46	Flammable solid, toxic, or self-heating solid, toxic
462	Toxic solid which reacts with water, emitting flammable gas
X462	Solid which reacts dangerously with water, emitting toxic gas
48	Flammable or self-heating solid, corrosive
482	Corrosive solid which reacts with water, emitting flammable gas
X482	Solid which reacts dangerously with water, emitting corrosive gas
<hr/>	
50	Oxidizing (fire-intensifying) substance
539	Flammable organic peroxide
55	Strongly oxidizing (fire-intensifying) substance
556	Strongly oxidizing (fire-intensifying) substance, toxic
558	Strongly oxidizing (fire-intensifying) substance, corrosive
559	Strongly oxidizing (fire-intensifying) substance which can spontaneously lead to violent reaction
56	Oxidizing (fire-intensifying) substance, toxic
568	Oxidizing (fire-intensifying) substance, toxic, corrosive
58	Oxidizing (fire-intensifying) substance, corrosive
59	Oxidizing (fire intensifying) substance which can spontaneously lead to violent reaction
<hr/>	
60	Toxic material
606	Infectious substance
623	Toxic liquid which reacts with water, emitting flammable gas
63	Toxic liquid, flammable
638	Toxic liquid, flammable, corrosive
639	Toxic liquid, flammable, which can spontaneously lead to violent reaction
64	Toxic solid, flammable or self-heating
642	Toxic solid which reacts with water, emitting flammable gas
65	Toxic material, oxidizing (fire-intensifying)
66	Highly toxic material
663	Highly toxic liquid, flammable
664	Highly toxic solid, flammable or self-heating
665	Highly toxic material, oxidizing (fire-intensifying)
668	Highly toxic material, corrosive



**HAZARD IDENTIFICATION CODES**  
**DISPLAYED ON SOME INTERMODAL CONTAINERS**

669	Highly toxic material which can spontaneously lead to violent reaction
68	Toxic material, corrosive
69	Toxic material which can spontaneously lead to violent reaction
<hr/>	
70	Radioactive material
72	Radioactive gas
723	Radioactive gas, flammable
73	Radioactive liquid, flammable
74	Radioactive solid, flammable
75	Radioactive material, oxidizing (fire-intensifying)
76	Radioactive material, toxic
78	Radioactive material, corrosive
<hr/>	
80	Corrosive material
X80	Corrosive material which reacts dangerously with water
823	Corrosive liquid which reacts with water, emitting flammable gas
83	Corrosive liquid, flammable
X83	Corrosive liquid, flammable, which reacts dangerously with water
839	Corrosive liquid, flammable, which can spontaneously lead to violent reaction
X839	Corrosive liquid, flammable, which can spontaneously lead to violent reaction and which reacts dangerously with water
84	Corrosive solid, flammable or self-heating
842	Corrosive solid which reacts with water, emitting flammable gas
85	Corrosive material, oxidizing (fire-intensifying)
856	Corrosive material, oxidizing (fire-intensifying) and toxic
86	Corrosive material, toxic
88	Highly corrosive material
X88	Highly corrosive material which reacts dangerously with water
883	Highly corrosive liquid, flammable
884	Highly corrosive solid, flammable or self-heating
885	Highly corrosive material, oxidizing (fire-intensifying)
886	Highly corrosive material, toxic
X886	Highly corrosive material, toxic, which reacts dangerously with water
89	Corrosive material which can spontaneously lead to violent reaction
<hr/>	
90	Miscellaneous dangerous substance; environmentally hazardous substance
99	Miscellaneous dangerous substance transported at elevated temperature

## PIPELINE TRANSPORTATION

Hazardous materials are transported in North America through millions of miles of underground pipelines. Products commonly transported through these pipeline systems include natural gas, crude oil, gasoline, diesel fuel, and jet fuel. Although the pipelines are buried, there are aboveground structures and signs indicating the presence of underground pipelines.

### Liquid Pipelines

Surface indications of a liquid pipeline leak can include:

- Liquids bubbling from the ground
- “Oil slick” on flowing or standing water
- Flames that appear to be coming from the ground
- Vapor clouds

**Structures** – Storage Tanks, Valves, Pump Stations, Aerial Patrol Markers

**Signs** – Will often appear at road, railroad, and water crossings. Signs may also be posted at property boundaries. The signs will include the operator’s name, product transported, and an emergency phone number for the operator. Warning, Caution, or Danger will appear on the signs.



## Gas Pipelines

Surface indications of a gas pipeline leak can include:

- Hissing, roaring, or blowing sound
- Dirt or water being blown in the air
- Continuous bubbling in wet or flooded areas
- Flames that appear to be coming from the ground
- Dead or brown vegetation in an otherwise green field
- In winter, melted snow over the pipeline

Gas **Transmission** pipelines are large-diameter, steel lines transporting flammable, toxic, or corrosive gas at very high pressure.

**Structures** – Compressor Station Buildings, Valves, Metering Stations, and Aerial Patrol Markers

**Signs** – Will often appear at road, railroad, and water crossings. Signs may also be posted at property boundaries. The signs will include the operator's name, product transported, and an emergency phone number for the operator. Warning, Caution, or Danger will appear on the signs.



Natural gas **Distribution** pipelines are typically smaller-diameter, lower-pressure pipelines and may be steel, plastic, or cast iron. Natural gas is delivered directly to customers through distribution pipelines.

Regulator stations, customer meters & regulators, and valve box covers are generally the only aboveground indications of gas distribution pipelines.

Should you notice a leak or a spill, remember to only approach from upwind and uphill, identify the emergency telephone number for the company and then call that number as well as 911. Be cautious concerning the risks of asphyxiation, flammability as well as the danger of a potential explosion.

If you know the material involved, identify the three-digit guide number by looking up the name in the alphabetical list (blue-bordered pages) and then by using the three-digit guide number, consult the recommendations outlined in the recommended guide.

**Note:** If an entry is highlighted in green in either the yellow-bordered or blue-bordered pages AND THERE IS NO FIRE, go directly to Table 1 - Initial Isolation and Protective Action Distances (green bordered pages) and look up the ID number and name of material to obtain initial isolation and protective action distances. IF THERE IS A FIRE, or IF A FIRE IS INVOLVED, ALSO CONSULT the assigned guide (orange-bordered pages) and apply as appropriate the evacuation information shown under PUBLIC SAFETY. Please remember that, if the name in Table 1 is shown with (when spilled in water), and the material has not been spilled in water, Table 1 does not apply and safety distances can be found within the appropriate guide.

ID No.	Guide No.	Name of Material
---	112	Ammonium nitrate-fuel oil mixtures
---	158	Biological agents
---	112	Blasting agent, n.o.s.
---	112	Explosive A
---	112	Explosive B
---	114	Explosive C
---	112	Explosives, division 1.1, 1.2, 1.3, 1.5 or 1.6
---	114	Explosives, division 1.4
---	153	Toxins
1001	116	Acetylene
1001	116	Acetylene, dissolved
1002	122	Air, compressed
1003	122	Air, refrigerated liquid (cryogenic liquid)
1003	122	Air, refrigerated liquid (cryogenic liquid), non-pressurized
1005	125	Ammonia, anhydrous
1005	125	Anhydrous ammonia
1006	121	Argon
1006	121	Argon, compressed
1008	125	Boron trifluoride
1008	125	Boron trifluoride, compressed
1009	126	Bromotrifluoromethane
1009	126	Refrigerant gas R-13B1
1010	116P	Butadienes, stabilized
1010	116P	Butadienes and hydrocarbon mixture, stabilized
1011	115	Butane
1011	115	Butane mixture
1012	115	Butylene
1013	120	Carbon dioxide

ID No.	Guide No.	Name of Material
1013	120	Carbon dioxide, compressed
1014	122	Carbon dioxide and Oxygen mixture
1014	122	Carbon dioxide and Oxygen mixture, compressed
1014	122	Oxygen and Carbon dioxide mixture
1014	122	Oxygen and Carbon dioxide mixture, compressed
1015	126	Carbon dioxide and Nitrous oxide mixture
1015	126	Nitrous oxide and Carbon dioxide mixture
1016	119	Carbon monoxide
1016	119	Carbon monoxide, compressed
1017	124	Chlorine
1018	126	Chlorodifluoromethane
1018	126	Refrigerant gas R-22
1020	126	Chloropentafluoroethane
1020	126	Refrigerant gas R-115
1021	126	1-Chloro-1,2,2,2-tetrafluoroethane
1021	126	Chlorotetrafluoroethane
1021	126	Refrigerant gas R-124
1022	126	Chlorotrifluoromethane
1022	126	Refrigerant gas R-13
1023	119	Coal gas
1023	119	Coal gas, compressed
1026	119	Cyanogen
1026	119	Cyanogen gas
1027	115	Cyclopropane
1028	126	Dichlorodifluoromethane
1028	126	Refrigerant gas R-12
1029	126	Dichlorofluoromethane
1029	126	Refrigerant gas R-21

**ID Guide** **Name of Material**  
**No. No.**

1030 **115** 1,1-Difluoroethane  
1030 **115** Difluoroethane  
1030 **115** Refrigerant gas R-152a  
1032 **118** Dimethylamine, anhydrous  
1033 **115** Dimethyl ether  
1035 **115** Ethane  
1035 **115** Ethane, compressed  
1036 **118** Ethylamine  
1037 **115** Ethyl chloride  
1038 **115** Ethylene, refrigerated liquid  
(cryogenic liquid)  
1039 **115** Ethyl methyl ether  
1039 **115** Methyl ethyl ether  
1040 **119P** Ethylene oxide  
1040 **119P** Ethylene oxide with Nitrogen  
1041 **115** Carbon dioxide and Ethylene  
oxide mixture, with more than  
9% but not more than 87%  
Ethylene oxide  
1041 **115** Carbon dioxide and Ethylene  
oxide mixtures, with more  
than 6% Ethylene oxide  
1041 **115** Ethylene oxide and Carbon  
dioxide mixture, with more  
than 9% but not more than  
87% Ethylene oxide  
1041 **115** Ethylene oxide and Carbon  
dioxide mixtures, with more  
than 6 % Ethylene oxide  
1043 **125** Fertilizer, ammoniating solution,  
with free Ammonia  
1044 **126** Fire extinguishers with  
compressed gas  
1044 **126** Fire extinguishers with  
liquefied gas  
1045 **124** Fluorine  
1045 **124** Fluorine, compressed

**ID Guide** **Name of Material**  
**No. No.**

1046 **121** Helium  
1046 **121** Helium, compressed  
1048 **125** Hydrogen bromide, anhydrous  
1049 **115** Hydrogen  
1049 **115** Hydrogen, compressed  
1050 **125** Hydrogen chloride, anhydrous  
1051 **117** AC  
1051 **117** Hydrocyanic acid, aqueous  
solutions, with more than 20%  
Hydrogen cyanide  
1051 **117** Hydrogen cyanide, anhydrous,  
stabilized  
1051 **117** Hydrogen cyanide, stabilized  
1052 **125** Hydrogen fluoride, anhydrous  
1053 **117** Hydrogen sulfide  
1053 **117** Hydrogen sulphide  
1055 **115** Isobutylene  
1056 **121** Krypton  
1056 **121** Krypton, compressed  
1057 **115** Lighter refills (cigarettes)  
(flammable gas)  
1057 **115** Lighters (cigarettes)  
(flammable gas)  
1058 **120** Liquefied gases, non-flammable,  
charged with Nitrogen,  
Carbon dioxide or Air  
1060 **116P** Methylacetylene and  
Propadiene mixture,  
stabilized  
1060 **116P** Propadiene and  
Methylacetylene mixture,  
stabilized  
1061 **118** Methylamine, anhydrous  
1062 **123** Methyl bromide  
1063 **115** Methyl chloride

**ID Guide**  
**No. No.**

1063 **115** Refrigerant gas R-40  
1064 **117** Methyl mercaptan  
1065 **121** Neon  
1065 **121** Neon, compressed  
1066 **121** Nitrogen  
1066 **121** Nitrogen, compressed  
1067 **124** Dinitrogen tetroxide  
1067 **124** Nitrogen dioxide  
1069 **125** Nitrosyl chloride  
1070 **122** Nitrous oxide  
1070 **122** Nitrous oxide, compressed  
1071 **119** Oil gas  
1071 **119** Oil gas, compressed  
1072 **122** Oxygen  
1072 **122** Oxygen, compressed  
1073 **122** Oxygen, refrigerated liquid  
(cryogenic liquid)  
1075 **115** Butane  
1075 **115** Butane mixture  
1075 **115** Butylene  
1075 **115** Isobutane  
1075 **115** Isobutane mixture  
1075 **115** Isobutylene  
1075 **115** Liquefied petroleum gas  
1075 **115** LPG  
1075 **115** Petroleum gases, liquefied  
1075 **115** Propane  
1075 **115** Propane mixture  
1075 **115** Propylene  
1076 **125** CG  
1076 **125** Diphosgene  
1076 **125** DP  
1076 **125** Phosgene

**ID Guide**  
**No. No.**

1077 **115** Propylene  
1078 **126** Dispersant gas, n.o.s.  
1078 **126** Refrigerant gas, n.o.s.  
1079 **125** Sulfur dioxide  
1079 **125** Sulphur dioxide  
1080 **126** Sulfur hexafluoride  
1080 **126** Sulphur hexafluoride  
1081 **116P** Tetrafluoroethylene, stabilized  
1082 **119P** Trifluorochloroethylene,  
stabilized  
1083 **118** Trimethylamine, anhydrous  
1085 **116P** Vinyl bromide, stabilized  
1086 **116P** Vinyl chloride, stabilized  
1087 **116P** Vinyl methyl ether, stabilized  
1088 **127** Acetal  
1089 **129** Acetaldehyde  
1090 **127** Acetone  
1091 **127** Acetone oils  
1092 **131P** Acrolein, stabilized  
1093 **131P** Acrylonitrile, stabilized  
1098 **131** Allyl alcohol  
1099 **131** Allyl bromide  
1100 **131** Allyl chloride  
1104 **129** Amyl acetates  
1105 **129** Amyl alcohols  
1105 **129** Pentanols  
1106 **132** Amylamines  
1107 **129** Amyl chloride  
1108 **128** n-Amylene  
1108 **128** 1-Pentene  
1109 **129** Amyl formates  
1110 **127** n-Amyl methyl ketone  
1110 **127** Amyl methyl ketone

**ID Guide** **Name of Material**  
**No. No.**

1110 **127** Methyl amyl ketone  
1111 **130** Amyl mercaptan  
1112 **140** Amyl nitrate  
1113 **129** Amyl nitrite  
1114 **130** Benzene  
1120 **129** Butanols  
1123 **129** Butyl acetates  
1125 **132** n-Butylamine  
1126 **130** 1-Bromobutane  
1126 **130** n-Butyl bromide  
1127 **130** Butyl chloride  
1127 **130** Chlorobutanes  
1128 **129** n-Butyl formate  
1129 **129** Butyraldehyde  
1130 **128** Camphor oil  
1131 **131** Carbon bisulfide  
1131 **131** Carbon bisulphide  
1131 **131** Carbon disulfide  
1131 **131** Carbon disulphide  
1133 **128** Adhesives (flammable)  
1134 **130** Chlorobenzene  
**1135 131 Ethylene chlorohydrin**  
1136 **128** Coal tar distillates, flammable  
1139 **127** Coating solution  
**1143 131P Crotonaldehyde**  
**1143 131P Crotonaldehyde, stabilized**  
1144 **128** Crotonylene  
1145 **128** Cyclohexane  
1146 **128** Cyclopentane  
1147 **130** Decahydronaphthalene  
1148 **129** Diacetone alcohol  
1149 **128** Butyl ethers  
1149 **128** Dibutyl ethers

**ID Guide** **Name of Material**  
**No. No.**

1150 **130P** 1,2-Dichloroethylene  
1150 **130P** Dichloroethylene  
1152 **130** Dichloropentanes  
1153 **127** Ethylene glycol diethyl ether  
1154 **132** Diethylamine  
1155 **127** Diethyl ether  
1155 **127** Ethyl ether  
1156 **127** Diethyl ketone  
1157 **128** Diisobutyl ketone  
1158 **132** Diisopropylamine  
1159 **127** Diisopropyl ether  
1160 **132** Dimethylamine, aqueous solution  
1160 **132** Dimethylamine, solution  
1161 **129** Dimethyl carbonate  
**1162 155 Dimethyldichlorosilane**  
**1163 131 1,1-Dimethylhydrazine**  
**1163 131 Dimethylhydrazine, unsymmetrical**  
1164 **130** Dimethyl sulfide  
1164 **130** Dimethyl sulphide  
1165 **127** Dioxane  
1166 **127** Dioxolane  
1167 **128P** Divinyl ether, stabilized  
1169 **127** Extracts, aromatic, liquid  
1170 **127** Ethanol  
1170 **127** Ethanol, solution  
1170 **127** Ethyl alcohol  
1170 **127** Ethyl alcohol, solution  
1171 **127** Ethylene glycol monoethyl ether  
1172 **129** Ethylene glycol monoethyl ether acetate  
1173 **129** Ethyl acetate  
1175 **130** Ethylbenzene



**ID No. Guide No. Name of Material**

1176 **129** Ethyl borate  
1177 **130** 2-Ethylbutyl acetate  
1177 **130** Ethylbutyl acetate  
1178 **130** 2-Ethylbutyraldehyde  
1179 **127** Ethyl butyl ether  
1180 **130** Ethyl butyrate  
1181 **155** Ethyl chloroacetate  
1182 **155** Ethyl chloroformate  
1183 **139** Ethyldichlorosilane  
1184 **131** Ethylene dichloride  
1185 **131P** Ethyleneimine, stabilized  
1188 **127** Ethylene glycol monomethyl ether  
1189 **129** Ethylene glycol monomethyl ether acetate  
1190 **129** Ethyl formate  
1191 **129** Ethylhexaldehydes  
1191 **129** Octyl aldehydes  
1192 **129** Ethyl lactate  
1193 **127** Ethyl methyl ketone  
1193 **127** Methyl ethyl ketone  
1194 **131** Ethyl nitrite, solution  
1195 **129** Ethyl propionate  
1196 **155** Ethyltrichlorosilane  
1197 **127** Extracts, flavoring, liquid  
1197 **127** Extracts, flavouring, liquid  
1198 **132** Formaldehyde, solution, flammable  
1198 **132** Formaldehyde, solutions (Formalin)  
1199 **132P** Furaldehydes  
1199 **132P** Furfural  
1199 **132P** Furfuraldehydes  
1201 **127** Fusel oil

**ID No. Guide No. Name of Material**

1202 **128** Diesel fuel  
1202 **128** Fuel oil  
1202 **128** Fuel oil, no. 1,2,4,5,6  
1202 **128** Gas oil  
1202 **128** Heating oil, light  
1203 **128** Gasohol  
1203 **128** Gasoline  
1203 **128** Motor spirit  
1203 **128** Petrol  
1204 **127** Nitroglycerin, solution in alcohol, with not more than 1% Nitroglycerin  
1206 **128** Heptanes  
1207 **130** Hexaldehyde  
1208 **128** Hexanes  
1208 **128** Neohexane  
1210 **129** Ink, printer's, flammable  
1210 **129** Printing ink, flammable  
1210 **129** Printing ink related material  
1212 **129** Isobutanol  
1212 **129** Isobutyl alcohol  
1213 **129** Isobutyl acetate  
1214 **132** Isobutylamine  
1216 **128** Isooctenes  
1218 **130P** Isoprene, stabilized  
1219 **129** Isopropanol  
1219 **129** Isopropyl alcohol  
1220 **129** Isopropyl acetate  
1221 **132** Isopropylamine  
1222 **130** Isopropyl nitrate  
1223 **128** Kerosene  
1224 **127** Ketones, liquid, n.o.s.

**ID Guide Name of Material**  
**No. No.**

1226 **128** Lighters for cigars, cigarettes  
(flammable liquid)

1228 **131** Mercaptan mixture, liquid,  
flammable, poisonous, n.o.s.

1228 **131** Mercaptan mixture, liquid,  
flammable, toxic, n.o.s.

1228 **131** Mercaptans, liquid, flammable,  
poisonous, n.o.s.

1228 **131** Mercaptans, liquid, flammable,  
toxic, n.o.s.

1229 **129** Mesityl oxide

1230 **131** Methanol

1230 **131** Methyl alcohol

1231 **129** Methyl acetate

1233 **130** Methylamyl acetate

1234 **127** Methylal

1235 **132** Methylamine, aqueous solution

1237 **129** Methyl butyrate

1238 **155** Methyl chloroformate

1239 **131** Methyl chloromethyl ether

1242 **139** Methylchlorosilane

1243 **129** Methyl formate

1244 **131** Methylhydrazine

1245 **127** Methyl isobutyl ketone

1246 **127P** Methyl isopropenyl ketone,  
stabilized

1247 **129P** Methyl methacrylate monomer,  
stabilized

1248 **129** Methyl propionate

1249 **127** Methyl propyl ketone

1250 **155** Methyltrichlorosilane

1251 **131P** Methyl vinyl ketone, stabilized

1259 **131** Nickel carbonyl

1261 **129** Nitromethane

**ID Guide Name of Material**  
**No. No.**

1262 **128** Isooctane

1262 **128** Octanes

1263 **128** Paint (flammable)

1263 **128** Paint related material  
(flammable)

1264 **129** Paraldehyde

1265 **128** Isopentane

1265 **128** n-Pentane

1265 **128** Pentanes

1266 **127** Perfumery products, with  
flammable solvents

1267 **128** Petroleum crude oil

1268 **128** Petroleum distillates, n.o.s.

1268 **128** Petroleum products, n.o.s.

1270 **128** Oil, petroleum

1270 **128** Petroleum oil

1272 **129** Pine oil

1274 **129** n-Propanol

1274 **129** normal Propyl alcohol

1274 **129** Propyl alcohol, normal

1275 **129** Propionaldehyde

1276 **129** n-Propyl acetate

1277 **132** Monopropylamine

1277 **132** Propylamine

1278 **129** 1-Chloropropane

1278 **129** Propyl chloride

1279 **130** 1,2-Dichloropropane

1279 **130** Dichloropropane

1279 **130** Propylene dichloride

1280 **127P** Propylene oxide

1281 **129** Propyl formates

1282 **129** Pyridine

1286 **127** Rosin oil

ID No.	Guide No.	Name of Material
1287	127	Rubber solution
1288	128	Shale oil
1289	132	Sodium methylate, solution in alcohol
1292	129	Ethyl silicate
1292	129	Tetraethyl silicate
1293	127	Tinctures, medicinal
1294	130	Toluene
1295	139	Trichlorosilane
1296	132	Triethylamine
1297	132	Trimethylamine, aqueous solution
1298	155	Trimethylchlorosilane
1299	128	Turpentine
1300	128	Turpentine substitute
1301	129P	Vinyl acetate, stabilized
1302	127P	Vinyl ethyl ether, stabilized
1303	130P	Vinylidene chloride, stabilized
1304	127P	Vinyl isobutyl ether, stabilized
1305	155P	Vinyltrichlorosilane
1305	155P	Vinyltrichlorosilane, stabilized
1306	129	Wood preservatives, liquid
1307	130	Xylenes
1308	170	Zirconium metal, liquid suspension
1308	170	Zirconium suspended in a flammable liquid
1308	170	Zirconium suspended in a liquid (flammable)
1309	170	Aluminum powder, coated
1310	113	Ammonium picrate, wetted with not less than 10% water
1312	133	Borneol
1313	133	Calcium resinate

ID No.	Guide No.	Name of Material
1314	133	Calcium resinate, fused
1318	133	Cobalt resinate, precipitated
1320	113	Dinitrophenol, wetted with not less than 15% water
1321	113	Dinitrophenolates, wetted with not less than 15% water
1322	113	Dinitroresorcinol, wetted with not less than 15% water
1323	170	Ferrocium
1324	133	Films, nitrocellulose base
1325	133	Flammable solid, n.o.s.
1325	133	Flammable solid, organic, n.o.s.
1325	133	Fusee (rail or highway)
1325	133	Medicines, flammable, solid, n.o.s.
1326	170	Hafnium powder, wetted with not less than 25% water
1327	133	Bhusa, wet, damp or contaminated with oil
1327	133	Hay, wet, damp or contaminated with oil
1327	133	Straw, wet, damp or contaminated with oil
1328	133	Hexamethylenetetramine
1328	133	Hexamine
1330	133	Manganese resinate
1331	133	Matches, "strike anywhere"
1332	133	Metaldehyde
1333	170	Cerium, slabs, ingots or rods
1334	133	Naphthalene, crude
1334	133	Naphthalene, refined
1336	113	Nitroguanidine (Picrite), wetted with not less than 20% water
1336	113	Nitroguanidine, wetted with not less than 20% water

**ID Guide Name of Material**  
**No. No.**

1336 **113** Picrite, wetted

1337 **113** Nitrostarch, wetted with not less than 20% water

1337 **113** Nitrostarch, wetted with not less than 30% solvent

1338 **133** Phosphorus, amorphous

1338 **133** Phosphorus, amorphous, red

1338 **133** Red phosphorus

1338 **133** Red phosphorus, amorphous

1339 **139** Phosphorus heptasulfide, free from yellow and white Phosphorus

1339 **139** Phosphorus heptasulphide, free from yellow and white Phosphorus

1340 **139** Phosphorus pentasulfide, free from yellow and white Phosphorus

1340 **139** Phosphorus pentasulphide, free from yellow and white Phosphorus

1341 **139** Phosphorus sesquisulfide, free from yellow and white Phosphorus

1341 **139** Phosphorus sesquisulphide, free from yellow and white Phosphorus

1343 **139** Phosphorus trisulfide, free from yellow and white Phosphorus

1343 **139** Phosphorus trisulphide, free from yellow and white Phosphorus

1344 **113** Picric acid, wet, with not less than 10% water

1344 **113** Picric acid, wetted with not less than 30% water

1344 **113** Trinitrophenol, wetted with not less than 30% water

**ID Guide Name of Material**  
**No. No.**

1345 **133** Rubber scrap, powdered or granulated

1345 **133** Rubber shoddy, powdered or granulated

1346 **170** Silicon powder, amorphous

1347 **113** Silver picrate, wetted with not less than 30% water

1348 **113** Sodium dinitro-o-cresolate, wetted with not less than 15% water

1348 **113** Sodium dinitro-ortho-cresolate, wetted

1349 **113** Sodium picramate, wetted with not less than 20% water

1350 **133** Sulfur

1350 **133** Sulphur

1352 **170** Titanium powder, wetted with not less than 25% water

1353 **133** Fabrics impregnated with weakly nitrated Nitrocellulose, n.o.s.

1353 **133** Fibers impregnated with weakly nitrated Nitrocellulose, n.o.s.

1353 **133** Fibres impregnated with weakly nitrated Nitrocellulose, n.o.s.

1353 **133** Toe puffs, nitrocellulose base

1354 **113** Trinitrobenzene, wetted with not less than 30% water

1355 **113** Trinitrobenzoic acid, wetted with not less than 30% water

1356 **113** TNT, wetted with not less than 30% water

1356 **113** Trinitrotoluene, wetted with not less than 30% water

1357 **113** Urea nitrate, wetted with not less than 20% water

1358 **170** Zirconium metal, powder, wet

ID No.	Guide No.	Name of Material
1358	170	Zirconium powder, wetted with not less than 25% water
1360	139	Calcium phosphide
1361	133	Carbon, animal or vegetable origin
1361	133	Charcoal
1362	133	Carbon, activated
1363	135	Copra
1364	133	Cotton waste, oily
1365	133	Cotton
1365	133	Cotton, wet
1366	135	Diethylzinc
1369	135	p-Nitrosodimethylaniline
1370	135	Dimethylzinc
1372	133	Fiber, animal or vegetable, n.o.s., burnt, wet or damp
1372	133	Fibers, animal or vegetable, burnt, wet or damp
1372	133	Fibres, animal or vegetable, burnt, wet or damp
1373	133	Fabrics, animal or vegetable or synthetic, n.o.s. with oil
1373	133	Fibers, animal or vegetable or synthetic, n.o.s. with oil
1373	133	Fibres, animal or vegetable or synthetic, n.o.s. with oil
1374	133	Fish meal, unstabilized
1374	133	Fish scrap, unstabilized
1376	135	Iron oxide, spent
1376	135	Iron sponge, spent
1378	170	Metal catalyst, wetted
1379	133	Paper, unsaturated oil treated
1380	135	Pentaborane
1381	136	Phosphorus, white, dry or under water or in solution

ID No.	Guide No.	Name of Material
1381	136	Phosphorus, yellow, dry or under water or in solution
1381	136	White phosphorus, dry
1381	136	White phosphorus, in solution
1381	136	White phosphorus, under water
1381	136	Yellow phosphorus, dry
1381	136	Yellow phosphorus, in solution
1381	136	Yellow phosphorus, under water
1382	135	Potassium sulfide, anhydrous
1382	135	Potassium sulfide, with less than 30% water of crystallization
1382	135	Potassium sulfide, with less than 30% water of hydration
1382	135	Potassium sulphide, anhydrous
1382	135	Potassium sulphide, with less than 30% water of crystallization
1382	135	Potassium sulphide, with less than 30% water of hydration
1383	135	Aluminum powder, pyrophoric
1383	135	Pyrophoric alloy, n.o.s.
1383	135	Pyrophoric metal, n.o.s.
1384	135	Sodium dithionite
1384	135	Sodium hydrosulfite
1384	135	Sodium hydrosulphite
1385	135	Sodium sulfide, anhydrous
1385	135	Sodium sulfide, with less than 30% water of crystallization
1385	135	Sodium sulphide, anhydrous
1385	135	Sodium sulphide, with less than 30% water of crystallization
1386	135	Seed cake, with more than 1.5% oil and not more than 11% moisture
1387	133	Wool waste, wet

**ID Guide Name of Material**  
**No. No.**

1389 **138** Alkali metal amalgam  
1389 **138** Alkali metal amalgam, liquid  
1389 **138** Alkali metal amalgam, solid  
1390 **139** Alkali metal amides  
1391 **138** Alkali metal dispersion  
1391 **138** Alkaline earth metal dispersion  
1392 **138** Alkaline earth metal amalgam  
1392 **138** Alkaline earth metal amalgam,  
liquid  
1393 **138** Alkaline earth metal alloy, n.o.s.  
1394 **138** Aluminum carbide  
1395 **139** Aluminum ferrosilicon powder  
1396 **138** Aluminum powder, uncoated  
**1397 139** Aluminum phosphide  
1398 **138** Aluminum silicon powder,  
uncoated  
1400 **138** Barium  
1401 **138** Calcium  
1402 **138** Calcium carbide  
1403 **138** Calcium cyanamide, with more  
than 0.1% Calcium carbide  
1404 **138** Calcium hydride  
1405 **138** Calcium silicide  
1406 **138** Calcium silicon  
1407 **138** Caesium  
1407 **138** Cesium  
1408 **139** Ferrosilicon  
1409 **138** Hydrides, metal, n.o.s.  
1409 **138** Metal hydrides, water-reactive,  
n.o.s.  
1410 **138** Lithium aluminum hydride  
1411 **138** Lithium aluminum hydride,  
ethereal

**ID Guide Name of Material**  
**No. No.**

**1412 139** Lithium amide  
1413 **138** Lithium borohydride  
1414 **138** Lithium hydride  
1415 **138** Lithium  
1417 **138** Lithium silicon  
1418 **138** Magnesium alloys powder  
1418 **138** Magnesium powder  
**1419 139** Magnesium aluminum phosphide  
1420 **138** Potassium, metal alloys  
1420 **138** Potassium, metal alloys, liquid  
1421 **138** Alkali metal alloy, liquid, n.o.s.  
1422 **138** Potassium sodium alloys  
1422 **138** Potassium sodium alloys, liquid  
1422 **138** Sodium potassium alloys  
1422 **138** Sodium potassium alloys, liquid  
1423 **138** Rubidium  
1423 **138** Rubidium metal  
1426 **138** Sodium borohydride  
1427 **138** Sodium hydride  
1428 **138** Sodium  
1431 **138** Sodium methylate  
1431 **138** Sodium methylate, dry  
**1432 139** Sodium phosphide  
1433 **139** Stannic phosphides  
1435 **138** Zinc ashes  
1435 **138** Zinc dross  
1435 **138** Zinc residue  
1435 **138** Zinc skimmings  
1436 **138** Zinc dust  
1436 **138** Zinc powder  
1437 **138** Zirconium hydride  
1438 **140** Aluminum nitrate  
1439 **141** Ammonium dichromate

**ID Guide Name of Material**  
**No. No.**

1442 **143** Ammonium perchlorate  
1444 **140** Ammonium persulfate  
1444 **140** Ammonium persulphate  
1445 **141** Barium chlorate  
1445 **141** Barium chlorate, solid  
1446 **141** Barium nitrate  
1447 **141** Barium perchlorate  
1447 **141** Barium perchlorate, solid  
1448 **141** Barium permanganate  
1449 **141** Barium peroxide  
1450 **141** Bromates, inorganic, n.o.s.  
1451 **140** Caesium nitrate  
1451 **140** Cesium nitrate  
1452 **140** Calcium chlorate  
1453 **140** Calcium chlorite  
1454 **140** Calcium nitrate  
1455 **140** Calcium perchlorate  
1456 **140** Calcium permanganate  
1457 **140** Calcium peroxide  
1458 **140** Borate and Chlorate mixtures  
1458 **140** Chlorate and Borate mixtures  
1459 **140** Chlorate and Magnesium chloride mixture  
1459 **140** Chlorate and Magnesium chloride mixture, solid  
1459 **140** Magnesium chloride and Chlorate mixture  
1459 **140** Magnesium chloride and Chlorate mixture, solid  
1461 **140** Chlorates, inorganic, n.o.s.  
1462 **143** Chlorites, inorganic, n.o.s.  
1463 **141** Chromic acid, solid  
1463 **141** Chromium trioxide, anhydrous  
1465 **140** Didymium nitrate

**ID Guide Name of Material**  
**No. No.**

1466 **140** Ferric nitrate  
1467 **143** Guanidine nitrate  
1469 **141** Lead nitrate  
1470 **141** Lead perchlorate  
1470 **141** Lead perchlorate, solid  
1470 **141** Lead perchlorate, solution  
1471 **140** Lithium hypochlorite, dry  
1471 **140** Lithium hypochlorite mixture  
1471 **140** Lithium hypochlorite mixtures, dry  
1472 **143** Lithium peroxide  
1473 **140** Magnesium bromate  
1474 **140** Magnesium nitrate  
1475 **140** Magnesium perchlorate  
1476 **140** Magnesium peroxide  
1477 **140** Nitrates, inorganic, n.o.s.  
1479 **140** Oxidizing solid, n.o.s.  
1481 **140** Perchlorates, inorganic, n.o.s.  
1482 **140** Permanganates, inorganic, n.o.s.  
1483 **140** Peroxides, inorganic, n.o.s.  
1484 **140** Potassium bromate  
1485 **140** Potassium chlorate  
1486 **140** Potassium nitrate  
1487 **140** Potassium nitrate and Sodium nitrite mixture  
1487 **140** Sodium nitrite and Potassium nitrate mixture  
1488 **140** Potassium nitrite  
1489 **140** Potassium perchlorate  
1490 **140** Potassium permanganate  
1491 **144** Potassium peroxide  
1492 **140** Potassium persulfate  
1492 **140** Potassium persulphate

**ID Guide**  
**No. No.**

1493 **140** Silver nitrate  
1494 **141** Sodium bromate  
1495 **140** Sodium chlorate  
1496 **143** Sodium chlorite  
1498 **140** Sodium nitrate  
1499 **140** Potassium nitrate and Sodium nitrate mixture  
1499 **140** Sodium nitrate and Potassium nitrate mixture  
1500 **140** Sodium nitrite  
1502 **140** Sodium perchlorate  
1503 **140** Sodium permanganate  
1504 **144** Sodium peroxide  
1505 **140** Sodium persulfate  
1505 **140** Sodium persulphate  
1506 **143** Strontium chlorate  
1506 **143** Strontium chlorate, solid  
1506 **143** Strontium chlorate, solution  
1507 **140** Strontium nitrate  
1508 **140** Strontium perchlorate  
1509 **143** Strontium peroxide  
1510 **143** Tetranitromethane  
1511 **140** Urea hydrogen peroxide  
1512 **140** Zinc ammonium nitrite  
1513 **140** Zinc chlorate  
1514 **140** Zinc nitrate  
1515 **140** Zinc permanganate  
1516 **143** Zinc peroxide  
1517 **113** Zirconium picramate, wetted with not less than 20% water  
1541 **155** Acetone cyanohydrin, stabilized  
1544 **151** Alkaloids, solid, n.o.s. (poisonous)

**ID Guide**  
**No. No.**

1544 **151** Alkaloid salts, solid, n.o.s. (poisonous)  
1545 **155** Allyl isothiocyanate, stabilized  
1546 **151** Ammonium arsenate  
1547 **153** Aniline  
1548 **153** Aniline hydrochloride  
1549 **157** Antimony compound, inorganic, n.o.s.  
1549 **157** Antimony compound, inorganic, solid, n.o.s.  
1549 **157** Antimony tribromide, solid  
1549 **157** Antimony tribromide, solution  
1549 **157** Antimony trifluoride, solid  
1549 **157** Antimony trifluoride, solution  
1550 **151** Antimony lactate  
1551 **151** Antimony potassium tartrate  
1553 **154** Arsenic acid, liquid  
1554 **154** Arsenic acid, solid  
1555 **151** Arsenic bromide  
1556 **152** Arsenic compound, liquid, n.o.s.  
1556 **152** Arsenic compound, liquid, n.o.s., inorganic  
1556 **152** MD  
1556 **152** Methylchloroarsine  
1556 **152** PD  
1557 **152** Arsenic compound, solid, n.o.s.  
1557 **152** Arsenic compound, solid, n.o.s., inorganic  
1557 **152** Arsenic sulfide  
1557 **152** Arsenic sulphide  
1557 **152** Arsenic trisulfide  
1557 **152** Arsenic trisulphide  
1557 **152** Arsenic  
1558 **152** Arsenic  
1559 **151** Arsenic pentoxide



**ID Guide**  
**No. No.**

1560 157 Arsenic chloride  
1560 157 Arsenic trichloride  
1561 151 Arsenic trioxide  
1562 152 Arsenical dust  
1564 154 Barium compound, n.o.s.  
1565 157 Barium cyanide  
1566 154 Beryllium compound, n.o.s.  
1567 134 Beryllium powder  
1569 131 Bromoacetone  
1570 152 Brucine  
1571 113 Barium azide, wetted with not less than 50% water  
1572 151 Cacodylic acid  
1573 151 Calcium arsenate  
1574 151 Calcium arsenate and Calcium arsenite mixture, solid  
1574 151 Calcium arsenite, solid  
1574 151 Calcium arsenite and Calcium arsenate mixture, solid  
1575 157 Calcium cyanide  
1577 153 Chlorodinitrobenzenes  
1577 153 Chlorodinitrobenzenes, liquid  
1577 153 Chlorodinitrobenzenes, solid  
1577 153 Dinitrochlorobenzenes  
1578 152 Chloronitrobenzenes  
1578 152 Chloronitrobenzenes, liquid  
1578 152 Chloronitrobenzenes, solid  
1579 153 4-Chloro-o-toluidine hydrochloride  
1579 153 4-Chloro-o-toluidine hydrochloride, solid  
1580 154 Chloropicrin  
1581 123 Chloropicrin and Methyl bromide mixture

**ID Guide**  
**No. No.**

1581 123 Methyl bromide and Chloropicrin mixture  
1582 119 Chloropicrin and Methyl chloride mixture  
1582 119 Methyl chloride and Chloropicrin mixture  
1583 154 Chloropicrin mixture, n.o.s.  
1585 151 Copper acetoarsenite  
1586 151 Copper arsenite  
1587 151 Copper cyanide  
1588 157 Cyanides, inorganic, n.o.s.  
1588 157 Cyanides, inorganic, solid, n.o.s.  
1589 125 CK  
1589 125 Cyanogen chloride, stabilized  
1590 153 Dichloroanilines  
1590 153 Dichloroanilines, liquid  
1590 153 Dichloroanilines, solid  
1591 152 o-Dichlorobenzene  
1593 160 Dichloromethane  
1593 160 Methylene chloride  
1594 152 Diethyl sulfate  
1594 152 Diethyl sulphate  
1595 156 Dimethyl sulfate  
1595 156 Dimethyl sulphate  
1596 153 Dinitroanilines  
1597 152 Dinitrobenzenes  
1597 152 Dinitrobenzenes, liquid  
1597 152 Dinitrobenzenes, solid  
1598 153 Dinitro-o-cresol  
1599 153 Dinitrophenol, solution  
1600 152 Dinitrotoluenes, molten  
1601 151 Disinfectant, solid, poisonous, n.o.s.  
1601 151 Disinfectant, solid, toxic, n.o.s.

**ID Guide**  
**No. No.**

1601 **151** Disinfectants, solid, n.o.s.  
(poisonous)

1602 **151** Dye, liquid, poisonous, n.o.s.

1602 **151** Dye, liquid, toxic, n.o.s.

1602 **151** Dye intermediate, liquid,  
poisonous, n.o.s.

1602 **151** Dye intermediate, liquid, toxic,  
n.o.s.

1603 **155** Ethyl bromoacetate

1604 **132** Ethylenediamine

1605 **154** Ethylene dibromide

1606 **151** Ferric arsenate

1607 **151** Ferric arsenite

1608 **151** Ferrous arsenate

1610 **159** Halogenated irritating liquid, n.o.s.

1611 **151** Hexaethyl tetraphosphate

1611 **151** Hexaethyl tetraphosphate, liquid

1611 **151** Hexaethyl tetraphosphate, solid

1612 **123** Hexaethyl tetraphosphate and  
compressed gas mixture

1613 **154** Hydrocyanic acid, aqueous  
solution, with less than 5%  
Hydrogen cyanide

1613 **154** Hydrocyanic acid, aqueous  
solution, with not more than  
20% Hydrogen cyanide

1613 **154** Hydrogen cyanide, aqueous  
solution, with not more than  
20% Hydrogen cyanide

1614 **152** Hydrogen cyanide, stabilized  
(absorbed)

1616 **151** Lead acetate

1617 **151** Lead arsenates

1618 **151** Lead arsenites

1620 **151** Lead cyanide

1621 **151** London purple

**ID Guide**  
**No. No.**

1622 **151** Magnesium arsenate

1623 **151** Mercuric arsenate

1624 **154** Mercuric chloride

1625 **141** Mercuric nitrate

1626 **157** Mercuric potassium cyanide

1627 **141** Mercurous nitrate

1629 **151** Mercury acetate

1630 **151** Mercury ammonium chloride

1631 **154** Mercury benzoate

1634 **154** Mercuric bromide

1634 **154** Mercurous bromide

1634 **154** Mercury bromides

1636 **154** Mercuric cyanide

1636 **154** Mercury cyanide

1637 **151** Mercury gluconate

1638 **151** Mercury iodide

1639 **151** Mercury nucleate

1640 **151** Mercury oleate

1641 **151** Mercury oxide

1642 **151** Mercuric oxycyanide

1642 **151** Mercury oxycyanide,  
desensitized

1643 **151** Mercury potassium iodide

1644 **151** Mercury salicylate

1645 **151** Mercuric sulfate

1645 **151** Mercuric sulphate

1645 **151** Mercury sulfate

1645 **151** Mercury sulphate

1646 **151** Mercury thiocyanate

1647 **151** Ethylene dibromide and Methyl  
bromide mixture, liquid

1647 **151** Methyl bromide and Ethylene  
dibromide mixture, liquid

1648 **127** Acetonitrile

ID No.	Guide No.	Name of Material
1648	127	Methyl cyanide
1649	131	Motor fuel anti-knock mixture
1649	131	Tetraethyl lead, liquid
1650	153	beta-Naphthylamine
1650	153	beta-Naphthylamine, solid
1650	153	Naphthylamine (beta)
1650	153	Naphthylamine (beta), solid
1651	153	Naphthylthiourea
1652	153	Naphthylurea
1653	151	Nickel cyanide
1654	151	Nicotine
1655	151	Nicotine compound, solid, n.o.s.
1655	151	Nicotine preparation, solid, n.o.s.
1656	151	Nicotine hydrochloride
1656	151	Nicotine hydrochloride, liquid
1656	151	Nicotine hydrochloride, solid
1656	151	Nicotine hydrochloride, solution
1657	151	Nicotine salicylate
1658	151	Nicotine sulfate, solid
1658	151	Nicotine sulfate, solution
1658	151	Nicotine sulphate, solid
1658	151	Nicotine sulphate, solution
1659	151	Nicotine tartrate
1660	124	Nitric oxide
1660	124	Nitric oxide, compressed
1661	153	Nitroanilines
1662	152	Nitrobenzene
1663	153	Nitrophenols
1664	152	Nitrotoluenes
1664	152	Nitrotoluenes, liquid
1664	152	Nitrotoluenes, solid
1665	152	Nitroxylenes
1665	152	Nitroxylenes, liquid

ID No.	Guide No.	Name of Material
1665	152	Nitroxylenes, solid
1669	151	Pentachloroethane
1670	157	Perchloromethyl mercaptan
1671	153	Phenol, solid
1672	151	Phenylcarbylamine chloride
1673	153	Phenylenediamines
1674	151	Phenylmercuric acetate
1677	151	Potassium arsenate
1678	154	Potassium arsenite
1679	157	Potassium cuprocyanide
1680	157	Potassium cyanide
1680	157	Potassium cyanide, solid
1683	151	Silver arsenite
1684	151	Silver cyanide
1685	151	Sodium arsenate
1686	154	Sodium arsenite, aqueous solution
1687	153	Sodium azide
1688	152	Sodium cacodylate
1689	157	Sodium cyanide
1689	157	Sodium cyanide, solid
1690	154	Sodium fluoride
1690	154	Sodium fluoride, solid
1691	151	Strontium arsenite
1692	151	Strychnine
1692	151	Strychnine salts
1693	159	Tear gas devices
1693	159	Tear gas substance, liquid, n.o.s.
1693	159	Tear gas substance, solid, n.o.s.
1694	159	Bromobenzyl cyanides
1694	159	Bromobenzyl cyanides, liquid
1694	159	Bromobenzyl cyanides, solid
1694	159	CA

**ID Guide**  
**No. No.**

1695 131 Chloroacetone, stabilized  
1697 153 Chloroacetophenone  
1697 153 Chloroacetophenone, liquid  
1697 153 Chloroacetophenone, solid  
1697 153 CN  
1698 154 Adamsite  
1698 154 Diphenylamine chloroarsine  
1698 154 DM  
1699 151 DA  
1699 151 Diphenylchloroarsine  
1699 151 Diphenylchloroarsine, liquid  
1699 151 Diphenylchloroarsine, solid  
1700 159 Tear gas candles  
1700 159 Tear gas grenades  
1701 152 Xylyl bromide  
1701 152 Xylyl bromide, liquid  
1702 151 1,1,2,2-Tetrachloroethane  
1702 151 Tetrachloroethane  
1704 153 Tetraethyl dithiopyrophosphate  
1704 153 Tetraethyl dithiopyrophosphate,  
mixture, dry or liquid  
1707 151 Thallium compound, n.o.s.  
1707 151 Thallium sulfate, solid  
1707 151 Thallium sulphate, solid  
1708 153 Toluidines  
1708 153 Toluidines, liquid  
1708 153 Toluidines, solid  
1709 151 2,4-Toluenediamine  
1709 151 2,4-Toluylenediamine  
1709 151 2,4-Toluylenediamine, solid  
1710 160 Trichloroethylene  
1711 153 Xylidines  
1711 153 Xylidines, liquid

**ID Guide**  
**No. No.**

1711 153 Xylidines, solid  
1712 151 Zinc arsenate  
1712 151 Zinc arsenate and Zinc arsenite  
mixture  
1712 151 Zinc arsenite  
1712 151 Zinc arsenite and Zinc arsenate  
mixture  
1713 151 Zinc cyanide  
1714 139 Zinc phosphide  
1715 137 Acetic anhydride  
1716 156 Acetyl bromide  
1717 155 Acetyl chloride  
1718 153 Acid butyl phosphate  
1718 153 Butyl acid phosphate  
1719 154 Caustic alkali liquid, n.o.s.  
1722 155 Allyl chlorocarbonate  
1722 155 Allyl chloroformate  
1723 132 Allyl iodide  
1724 155 Allyltrimethylsilane, stabilized  
1725 137 Aluminum bromide, anhydrous  
1726 137 Aluminum chloride, anhydrous  
1727 154 Ammonium bifluoride, solid  
1727 154 Ammonium hydrogendifluoride,  
solid  
1727 154 Ammonium hydrogen fluoride,  
solid  
1728 155 Amyltrimethylsilane  
1729 156 Anisoyl chloride  
1730 157 Antimony pentachloride, liquid  
1731 157 Antimony pentachloride,  
solution  
1732 157 Antimony pentafluoride  
1733 157 Antimony trichloride  
1733 157 Antimony trichloride, liquid

ID No.	Guide No.	Name of Material
--------	-----------	------------------

1733	157	Antimony trichloride, solid
1733	157	Antimony trichloride, solution
1736	137	Benzoyl chloride
1737	156	Benzyl bromide
1738	156	Benzyl chloride
1739	137	Benzyl chloroformate
1740	154	Hydrogendifluorides, n.o.s.
1740	154	Hydrogendifluorides, solid, n.o.s.
1741	125	Boron trichloride
1742	157	Boron trifluoride acetic acid complex
1742	157	Boron trifluoride acetic acid complex, liquid
1743	157	Boron trifluoride propionic acid complex
1743	157	Boron trifluoride propionic acid complex, liquid
1744	154	Bromine
1744	154	Bromine, solution
1744	154	Bromine, solution (Inhalation Hazard Zone A)
1744	154	Bromine, solution (Inhalation Hazard Zone B)
1745	144	Bromine pentafluoride
1746	144	Bromine trifluoride
1747	155	Butyltrichlorosilane
1748	140	Calcium hypochlorite, dry
1748	140	Calcium hypochlorite mixture, dry, with more than 39% available Chlorine (8.8% available Oxygen)
1749	124	Chlorine trifluoride
1750	153	Chloroacetic acid, liquid
1750	153	Chloroacetic acid, solution

ID No.	Guide No.	Name of Material
--------	-----------	------------------

1751	153	Chloroacetic acid, solid
1752	156	Chloroacetyl chloride
1753	156	Chlorophenyltrichlorosilane
1754	137	Chlorosulfonic acid
1754	137	Chlorosulfonic acid and Sulfur trioxide mixture
1754	137	Chlorosulphonic acid
1754	137	Chlorosulphonic acid and Sulphur trioxide mixture
1754	137	Sulfur trioxide and Chlorosulfonic acid mixture
1754	137	Sulphur trioxide and Chlorosulphonic acid mixture
1755	154	Chromic acid, solution
1756	154	Chromic fluoride, solid
1757	154	Chromic fluoride, solution
1758	137	Chromium oxychloride
1759	154	Corrosive solid, n.o.s.
1759	154	Ferrous chloride, solid
1759	154	Medicines, corrosive, solid, n.o.s.
1760	154	Chemical kit
1760	154	Compound, cleaning liquid (corrosive)
1760	154	Compound, tree or weed killing, liquid (corrosive)
1760	154	Corrosive liquid, n.o.s.
1760	154	Ferrous chloride, solution
1760	154	Medicines, corrosive, liquid, n.o.s.
1760	154	Titanium sulfate, solution
1760	154	Titanium sulphate, solution
1761	154	Cupriethylenediamine, solution
1762	156	Cyclohexenyltrichlorosilane
1763	156	Cyclohexyltrichlorosilane
1764	153	Dichloroacetic acid

**ID Guide Name of Material**  
**No. No.**

1765 **156** Dichloroacetyl chloride  
1766 **156** Dichlorophenyltrichlorosilane  
1767 **155** Diethylchlorosilane  
1768 **154** Difluorophosphoric acid,  
anhydrous  
1769 **156** Diphenyldichlorosilane  
1770 **153** Diphenylmethyl bromide  
1771 **156** Dodecyltrichlorosilane  
1773 **157** Ferric chloride  
1773 **157** Ferric chloride, anhydrous  
1774 **154** Fire extinguisher charges,  
corrosive liquid  
1775 **154** Fluoboric acid  
1775 **154** Fluoroboric acid  
1776 **154** Fluorophosphoric acid,  
anhydrous  
1777 **137** Fluorosulfonic acid  
1777 **137** Fluorosulphonic acid  
1778 **154** Fluorosilicic acid  
1778 **154** Fluosilicic acid  
1778 **154** Hydrofluorosilicic acid  
1779 **153** Formic acid  
1779 **153** Formic acid, with more than 85%  
acid  
1780 **156** Fumaryl chloride  
1781 **156** Hexadecyltrichlorosilane  
1782 **154** Hexafluorophosphoric acid  
1783 **153** Hexamethylenediamine,  
solution  
1784 **156** Hexyltrichlorosilane  
1786 **157** Hydrofluoric acid and Sulfuric  
acid mixture  
1786 **157** Hydrofluoric acid and Sulphuric  
acid mixture

**ID Guide Name of Material**  
**No. No.**

1786 **157** Sulfuric acid and Hydrofluoric  
acid mixture  
1786 **157** Sulphuric acid and Hydrofluoric  
acid mixture  
1787 **154** Hydriodic acid  
1787 **154** Hydriodic acid, solution  
1788 **154** Hydrobromic acid  
1788 **154** Hydrobromic acid, solution  
1789 **157** Hydrochloric acid  
1789 **157** Hydrochloric acid, solution  
1789 **157** Muriatic acid  
1790 **157** Hydrofluoric acid  
1790 **157** Hydrofluoric acid, solution  
1791 **154** Hypochlorite solution  
1791 **154** Hypochlorite solution, with more  
than 5% available Chlorine  
1792 **157** Iodine monochloride  
1793 **153** Isopropyl acid phosphate  
1794 **154** Lead sulfate, with more than 3%  
free acid  
1794 **154** Lead sulphate, with more than  
3% free acid  
1796 **157** Nitrating acid mixture  
1798 **157** Aqua regia  
1798 **157** Nitrohydrochloric acid  
1799 **156** Nonyltrichlorosilane  
1800 **156** Octadecyltrichlorosilane  
1801 **156** Octyltrichlorosilane  
1802 **140** Perchloric acid, with not more  
than 50% acid  
1803 **153** Phenolsulfonic acid, liquid  
1803 **153** Phenolsulphonic acid, liquid  
1804 **156** Phenyltrichlorosilane  
1805 **154** Phosphoric acid

ID No.	Guide No.	Name of Material
1805	154	Phosphoric acid, liquid
1805	154	Phosphoric acid, solid
1805	154	Phosphoric acid, solution
1806	137	Phosphorus pentachloride
1807	137	Phosphorus pentoxide
1808	137	Phosphorus tribromide
1809	137	Phosphorus trichloride
1810	137	Phosphorus oxychloride
1811	154	Potassium hydrogendifluoride
1811	154	Potassium hydrogen difluoride, solid
1812	154	Potassium fluoride
1812	154	Potassium fluoride, solid
1813	154	Caustic potash, dry, solid
1813	154	Potassium hydroxide, dry, solid
1813	154	Potassium hydroxide, flake
1813	154	Potassium hydroxide, solid
1814	154	Caustic potash, liquid
1814	154	Caustic potash, solution
1814	154	Potassium hydroxide, solution
1815	132	Propionyl chloride
1816	155	Propyltrichlorosilane
1817	137	Pyrosulfuryl chloride
1817	137	Pyrosulphuryl chloride
1818	157	Silicon tetrachloride
1819	154	Sodium aluminate, solution
1823	154	Caustic soda, bead
1823	154	Caustic soda, flake
1823	154	Caustic soda, granular
1823	154	Caustic soda, solid
1823	154	Sodium hydroxide, bead
1823	154	Sodium hydroxide, dry
1823	154	Sodium hydroxide, flake

ID No.	Guide No.	Name of Material
1823	154	Sodium hydroxide, granular
1823	154	Sodium hydroxide, solid
1824	154	Caustic soda, solution
1824	154	Sodium hydroxide, solution
1825	157	Sodium monoxide
1826	157	Nitrating acid mixture, spent
1827	137	Stannic chloride, anhydrous
1827	137	Tin tetrachloride
1828	137	Sulfur chlorides
1828	137	Sulphur chlorides
1829	137	Sulfur trioxide, inhibited
1829	137	Sulfur trioxide, stabilized
1829	137	Sulfur trioxide, uninhibited
1829	137	Sulphur trioxide, inhibited
1829	137	Sulphur trioxide, stabilized
1829	137	Sulphur trioxide, uninhibited
1830	137	Sulfuric acid
1830	137	Sulfuric acid, with more than 51% acid
1830	137	Sulphuric acid
1830	137	Sulphuric acid, with more than 51% acid
1831	137	Sulfuric acid, fuming
1831	137	Sulfuric acid, fuming, with less than 30% free Sulfur trioxide
1831	137	Sulfuric acid, fuming, with not less than 30% free Sulfur trioxide
1831	137	Sulphuric acid, fuming
1831	137	Sulphuric acid, fuming, with less than 30% free Sulphur trioxide
1831	137	Sulphuric acid, fuming, with not less than 30% free Sulphur trioxide
1832	137	Sulfuric acid, spent

**ID Guide** **Name of Material**  
**No. No.**

1832 **137** Sulphuric acid, spent  
1833 **154** Sulfurous acid  
1833 **154** Sulphurous acid  
1834 **137** Sulfuryl chloride  
1834 **137** Sulphuryl chloride  
1835 **153** Tetramethylammonium hydroxide  
1835 **153** Tetramethylammonium hydroxide, solution  
1836 **137** Thionyl chloride  
1837 **157** Thiophosphoryl chloride  
1838 **137** Titanium tetrachloride  
1839 **153** Trichloroacetic acid  
1840 **154** Zinc chloride, solution  
1841 **171** Acetaldehyde ammonia  
1843 **141** Ammonium dinitro-o-cresolate  
1843 **141** Ammonium dinitro-o-cresolate, solid  
1845 **120** Carbon dioxide, solid  
1845 **120** Dry ice  
1846 **151** Carbon tetrachloride  
1847 **153** Potassium sulfide, hydrated, with not less than 30% water of crystallization  
1847 **153** Potassium sulfide, hydrated, with not less than 30% water of hydration  
1847 **153** Potassium sulphide, hydrated, with not less than 30% water of crystallization  
1847 **153** Potassium sulphide, hydrated, with not less than 30% water of hydration  
1848 **132** Propionic acid  
1848 **132** Propionic acid, with not less than 10% and less than 90% acid

**ID Guide** **Name of Material**  
**No. No.**

1849 **153** Sodium sulfide, hydrated, with not less than 30% water  
1849 **153** Sodium sulphide, hydrated, with not less than 30% water  
1851 **151** Medicine, liquid, poisonous, n.o.s.  
1851 **151** Medicine, liquid, toxic, n.o.s.  
1854 **135** Barium alloys, pyrophoric  
1855 **135** Calcium, metal and alloys, pyrophoric  
1855 **135** Calcium, pyrophoric  
1855 **135** Calcium alloys, pyrophoric  
1856 **133** Rags, oily  
1857 **133** Textile waste, wet  
1858 **126** Hexafluoropropylene  
1858 **126** Refrigerant gas R-1216  
1859 **125** Silicon tetrafluoride  
1859 **125** Silicon tetrafluoride, compressed  
1860 **116P** Vinyl fluoride, stabilized  
1862 **130** Ethyl crotonate  
1863 **128** Fuel, aviation, turbine engine  
1865 **131** n-Propyl nitrate  
1866 **127** Resin solution  
1868 **134** Decaborane  
1869 **138** Magnesium  
1869 **138** Magnesium, in pellets, turnings or ribbons  
1869 **138** Magnesium alloys, with more than 50% Magnesium, in pellets, turnings or ribbons  
1870 **138** Potassium borohydride  
1871 **170** Titanium hydride  
1872 **141** Lead dioxide  
1873 **143** Perchloric acid, with more than 50% but not more than 72% acid



ID No.	Guide No.	Name of Material
1884	157	Barium oxide
1885	153	Benzidine
1886	156	Benzylidene chloride
1887	160	Bromochloromethane
1888	151	Chloroform
1889	157	Cyanogen bromide
1891	131	Ethyl bromide
1892	151	ED
1892	151	Ethylchloroarsine
1894	151	Phenylmercuric hydroxide
1895	151	Phenylmercuric nitrate
1897	160	Perchloroethylene
1897	160	Tetrachloroethylene
1898	156	Acetyl iodide
1902	153	Diisooctyl acid phosphate
1903	153	Disinfectant, liquid, corrosive, n.o.s.
1903	153	Disinfectants, corrosive, liquid, n.o.s.
1905	154	Selenic acid
1906	153	Acid, sludge
1906	153	Sludge acid
1907	154	Soda lime, with more than 4% Sodium hydroxide
1908	154	Chlorite solution
1908	154	Chlorite solution, with more than 5% available Chlorine
1908	154	Sodium chlorite, solution, with more than 5% available Chlorine
1910	157	Calcium oxide
1911	119	Diborane
1911	119	Diborane, compressed
1911	119	Diborane mixtures

ID No.	Guide No.	Name of Material
1912	115	Methyl chloride and Methylene chloride mixture
1912	115	Methylene chloride and Methyl chloride mixture
1913	120	Neon, refrigerated liquid (cryogenic liquid)
1914	130	Butyl propionates
1915	127	Cyclohexanone
1916	152	2,2'-Dichlorodiethyl ether
1916	152	Dichloroethyl ether
1917	129P	Ethyl acrylate, stabilized
1918	130	Cumene
1918	130	Isopropylbenzene
1919	129P	Methyl acrylate, stabilized
1920	128	Nonanes
1921	131P	Propyleneimine, stabilized
1922	132	Pyrrrolidine
1923	135	Calcium dithionite
1923	135	Calcium hydrosulfite
1923	135	Calcium hydrosulphite
1928	135	Methyl magnesium bromide in Ethyl ether
1929	135	Potassium dithionite
1929	135	Potassium hydrosulfite
1929	135	Potassium hydrosulphite
1931	171	Zinc dithionite
1931	171	Zinc hydrosulfite
1931	171	Zinc hydrosulphite
1932	135	Zirconium scrap
1935	157	Cyanide solution, n.o.s.
1938	156	Bromoacetic acid
1938	156	Bromoacetic acid, solution
1939	137	Phosphorus oxybromide
1939	137	Phosphorus oxybromide, solid

**ID Guide Name of Material**  
**No. No.**

1940	153	Thioglycolic acid
1941	171	Dibromodifluoromethane
1942	140	Ammonium nitrate, with not more than 0.2% combustible substances
1944	133	Matches, safety
1945	133	Matches, wax "vesta"
1950	126	Aerosol dispensers
1950	126	Aerosols
1951	120	Argon, refrigerated liquid (cryogenic liquid)
1952	126	Carbon dioxide and Ethylene oxide mixtures, with not more than 6% Ethylene oxide
1952	126	Carbon dioxide and Ethylene oxide mixtures, with not more than 9% Ethylene oxide
1952	126	Ethylene oxide and Carbon dioxide mixtures, with not more than 6% Ethylene oxide
1952	126	Ethylene oxide and Carbon dioxide mixtures, with not more than 9% Ethylene oxide
1953	119	Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone A)
1953	119	Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone B)
1953	119	Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone C)
1953	119	Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone D)
1953	119	Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone A)

**ID Guide Name of Material**  
**No. No.**

1953	119	Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone B)
1953	119	Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone C)
1953	119	Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone D)
1953	119	Compressed gas, poisonous, flammable, n.o.s.
1953	119	Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)
1953	119	Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone B)
1953	119	Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)
1953	119	Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone D)
1953	119	Compressed gas, toxic, flammable, n.o.s.
1953	119	Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone A)
1953	119	Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone B)
1953	119	Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone C)
1953	119	Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone D)
1954	115	Compressed gas, flammable, n.o.s.
1954	115	Dispersant gas, n.o.s. (flammable)

ID No.	Guide No.	Name of Material	ID No.	Guide No.	Name of Material
1954	115	Insecticide gas, flammable, n.o.s.	1956	126	Compressed gas, n.o.s.
1954	115	Refrigerant gas, n.o.s. (flammable)	1956	126	Hexafluoropropylene oxide
1954	115	Refrigerating machines, containing flammable, non-poisonous, non-corrosive, liquefied gas	1957	115	Deuterium
1955	123	Compressed gas, poisonous, n.o.s.	1957	115	Deuterium, compressed
1955	123	Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone A)	1958	126	1,2-Dichloro-1,1,2,2-tetrafluoroethane
1955	123	Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone B)	1958	126	Dichlorotetrafluoroethane
1955	123	Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone C)	1958	126	Refrigerant gas R-114
1955	123	Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone D)	1959	116P	1,1-Difluoroethylene
1955	123	Compressed gas, toxic, n.o.s.	1959	116P	Refrigerant gas R-1132a
1955	123	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone A)	1960	115	Engine starting fluid
1955	123	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone B)	1961	115	Ethane, refrigerated liquid
1955	123	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone C)	1961	115	Ethane-Propane mixture, refrigerated liquid
1955	123	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone D)	1961	115	Propane-Ethane mixture, refrigerated liquid
1955	123	Organic phosphate compound mixed with compressed gas	1962	116P	Ethylene
1955	123	Organic phosphate mixed with compressed gas	1962	116P	Ethylene, compressed
1955	123	Organic phosphorus compound mixed with compressed gas	1963	120	Helium, refrigerated liquid (cryogenic liquid)
1956	126	Accumulators, pressurized, pneumatic or hydraulic	1964	115	Hydrocarbon gas, compressed, n.o.s.
			1964	115	Hydrocarbon gas mixture, compressed, n.o.s.
			1965	115	Hydrocarbon gas, liquefied, n.o.s.
			1965	115	Hydrocarbon gas mixture, liquefied, n.o.s.
			1966	115	Hydrogen, refrigerated liquid (cryogenic liquid)
			1967	123	Insecticide gas, poisonous, n.o.s.
			1967	123	Insecticide gas, toxic, n.o.s.
			1967	123	Parathion and compressed gas mixture
			1968	126	Insecticide gas, n.o.s.

**ID Guide Name of Material**  
**No. No.**

1969	115	Isobutane
1969	115	Isobutane mixture
1970	120	Krypton, refrigerated liquid (cryogenic liquid)
1971	115	Methane
1971	115	Methane, compressed
1971	115	Natural gas, compressed
1972	115	Liquefied natural gas (cryogenic liquid)
1972	115	LNG (cryogenic liquid)
1972	115	Methane, refrigerated liquid (cryogenic liquid)
1972	115	Natural gas, refrigerated liquid (cryogenic liquid)
1973	126	Chlorodifluoromethane and Chloropentafluoroethane mixture
1973	126	Chloropentafluoroethane and Chlorodifluoromethane mixture
1973	126	Refrigerant gas R-502
1974	126	Bromochlorodifluoromethane
1974	126	Chlorodifluorobromomethane
1974	126	Refrigerant gas R-12B1
1975	124	Dinitrogen tetroxide and Nitric oxide mixture
1975	124	Nitric oxide and Dinitrogen tetroxide mixture
1975	124	Nitric oxide and Nitrogen dioxide mixture
1975	124	Nitric oxide and Nitrogen tetroxide mixture
1975	124	Nitrogen dioxide and Nitric oxide mixture
1975	124	Nitrogen tetroxide and Nitric oxide mixture

**ID Guide Name of Material**  
**No. No.**

1976	126	Octafluorocyclobutane
1976	126	Refrigerant gas RC-318
1977	120	Nitrogen, refrigerated liquid (cryogenic liquid)
1978	115	Propane
1978	115	Propane mixture
1979	121	Rare gases mixture
1979	121	Rare gases mixture, compressed
1980	121	Oxygen and Rare gases mixture
1980	121	Oxygen and Rare gases mixture, compressed
1980	121	Rare gases and Oxygen mixture
1980	121	Rare gases and Oxygen mixture, compressed
1981	121	Nitrogen and Rare gases mixture
1981	121	Nitrogen and Rare gases mixture, compressed
1981	121	Rare gases and Nitrogen mixture
1981	121	Rare gases and Nitrogen mixture, compressed
1982	126	Refrigerant gas R-14
1982	126	Refrigerant gas R-14, compressed
1982	126	Tetrafluoromethane
1982	126	Tetrafluoromethane, compressed
1983	126	1-Chloro-2,2,2-trifluoroethane
1983	126	Chlorotrifluoroethane
1983	126	Refrigerant gas R-133a
1984	126	Refrigerant gas R-23
1984	126	Trifluoromethane
1986	131	Alcohols, flammable, poisonous, n.o.s.
1986	131	Alcohols, flammable, toxic, n.o.s.

ID No.	Guide No.	Name of Material
1986	131	Alcohols, poisonous, n.o.s.
1986	131	Alcohols, toxic, n.o.s.
1986	131	Denatured alcohol (toxic)
1986	131	Propargyl alcohol
1987	127	Alcohols, n.o.s.
1987	127	Denatured alcohol
1988	131	Aldehydes, flammable, poisonous, n.o.s.
1988	131	Aldehydes, flammable, toxic, n.o.s.
1988	131	Aldehydes, poisonous, n.o.s.
1988	131	Aldehydes, toxic, n.o.s.
1989	129	Aldehydes, n.o.s.
1990	129	Benzaldehyde
1991	131P	Chloroprene, stabilized
1992	131	Flammable liquid, poisonous, n.o.s.
1992	131	Flammable liquid, toxic, n.o.s.
1993	128	Combustible liquid, n.o.s.
1993	128	Compound, cleaning liquid (flammable)
1993	128	Compound, tree or weed killing, liquid (flammable)
1993	128	Diesel fuel
1993	128	Flammable liquid, n.o.s.
1993	128	Fuel oil
1993	128	Medicines, flammable, liquid, n.o.s.
1993	128	Refrigerating machine
1994	131	Iron pentacarbonyl
1999	130	Asphalt
1999	130	Tars, liquid
2000	133	Celluloid, in blocks, rods, rolls, sheets, tubes, etc., except scrap

ID No.	Guide No.	Name of Material
2001	133	Cobalt naphthenates, powder
2002	135	Celluloid, scrap
2003	135	Metal alkyls, n.o.s.
2003	135	Metal alkyls, water-reactive, n.o.s.
2003	135	Metal aryls, n.o.s.
2003	135	Metal aryls, water-reactive, n.o.s.
2004	135	Magnesium diamide
2005	135	Magnesium diphenyl
2006	135	Plastic, nitrocellulose-based, spontaneously combustible, n.o.s.
2006	135	Plastics, nitrocellulose-based, self-heating, n.o.s.
2008	135	Zirconium powder, dry
2009	135	Zirconium, dry, finished sheets, strips or coiled wire
2010	138	Magnesium hydride
2011	139	Magnesium phosphide
2012	139	Potassium phosphide
2013	139	Strontium phosphide
2014	140	Hydrogen peroxide, aqueous solution, with not less than 20% but not more than 60% Hydrogen peroxide (stabilized as necessary)
2015	143	Hydrogen peroxide, aqueous solution, stabilized, with more than 60% Hydrogen peroxide
2015	143	Hydrogen peroxide, stabilized
2016	151	Ammunition, poisonous, non-explosive
2016	151	Ammunition, toxic, non-explosive

**ID Guide**  
**No. No.**

**Name of Material**

2017 **159** Ammunition, tear-producing,  
non-explosive

2018 **152** Chloroanilines, solid

2019 **152** Chloroanilines, liquid

2020 **153** Chlorophenols, solid

2021 **153** Chlorophenols, liquid

2022 **153** Cresylic acid

2023 **131P** 1-Chloro-2,3-epoxypropane

2023 **131P** Epichlorohydrin

2024 **151** Mercury compound, liquid, n.o.s.

2025 **151** Mercury compound, solid, n.o.s.

2026 **151** Phenylmercuric compound,  
n.o.s.

2027 **151** Sodium arsenite, solid

2028 **153** Bombs, smoke, non-explosive,  
with corrosive liquid, without  
initiating device

2029 **132** Hydrazine, anhydrous

2029 **132** Hydrazine, aqueous solutions,  
with more than 64% Hydrazine

2030 **153** Hydrazine, aqueous solution,  
with more than 37% Hydrazine

2030 **153** Hydrazine, aqueous solution,  
with not less than 37% but not  
more than 64% Hydrazine

2030 **153** Hydrazine hydrate

2031 **157** Nitric acid, other than red fuming

2032 **157** Nitric acid, fuming

2032 **157** Nitric acid, red fuming

2033 **154** Potassium monoxide

2034 **115** Hydrogen and Methane mixture,  
compressed

2034 **115** Methane and Hydrogen mixture,  
compressed

2035 **115** Refrigerant gas R-143a

**ID Guide**  
**No. No.**

**Name of Material**

2035 **115** 1,1,1-Trifluoroethane

2035 **115** Trifluoroethane, compressed

2036 **121** Xenon

2036 **121** Xenon, compressed

2037 **115** Gas cartridges

2037 **115** Receptacles, small, containing  
gas

2038 **152** Dinitrotoluenes

2038 **152** Dinitrotoluenes, liquid

2038 **152** Dinitrotoluenes, solid

2044 **115** 2,2-Dimethylpropane

2045 **130** Isobutyl aldehyde

2045 **130** Isobutyraldehyde

2046 **130** Cymenes

2047 **129** Dichloropropenes

2048 **130** Dicyclopentadiene

2049 **130** Diethylbenzene

2050 **128** Diisobutylene, isomeric  
compounds

2051 **132** 2-Dimethylaminoethanol

2051 **132** Dimethylethanolamine

2052 **128** Dipentene

2053 **129** Methylamyl alcohol

2053 **129** Methyl isobutyl carbinol

2053 **129** M.I.B.C.

2054 **132** Morpholine

2055 **128P** Styrene monomer, stabilized

2056 **127** Tetrahydrofuran

2057 **128** Tripropylene

2058 **129** Valeraldehyde

2059 **127** Nitrocellulose, solution,  
flammable

2059 **127** Nitrocellulose, solution, in a  
flammable liquid

ID No.	Guide No.	Name of Material
2067	140	Ammonium nitrate fertilizers
2068	140	Ammonium nitrate fertilizers, with Calcium carbonate
2069	140	Ammonium nitrate fertilizers, with Ammonium sulfate
2069	140	Ammonium nitrate fertilizers, with Ammonium sulphate
2069	140	Ammonium nitrate mixed fertilizers
2070	143	Ammonium nitrate fertilizers, with Phosphate or Potash
2071	140	Ammonium nitrate fertilizer, with not more than 0.4% combustible material
2071	140	Ammonium nitrate fertilizers
2072	140	Ammonium nitrate fertilizer, n.o.s.
2072	140	Ammonium nitrate fertilizers
2073	125	Ammonia, solution, with more than 35% but not more than 50% Ammonia
2074	153P	Acrylamide
2074	153P	Acrylamide, solid
2075	153	Chloral, anhydrous, stabilized
2076	153	Cresols
2076	153	Cresols, liquid
2076	153	Cresols, solid
2077	153	alpha-Naphthylamine
2077	153	Naphthylamine (alpha)
2078	156	Toluene diisocyanate
2079	154	Diethylenetriamine
2186	125	Hydrogen chloride, refrigerated liquid
2187	120	Carbon dioxide, refrigerated liquid
2188	119	Arsine
2188	119	SA

ID No.	Guide No.	Name of Material
2189	119	Dichlorosilane
2190	124	Oxygen difluoride
2190	124	Oxygen difluoride, compressed
2191	123	Sulfuryl fluoride
2191	123	Sulphuryl fluoride
2192	119	Germane
2193	126	Hexafluoroethane
2193	126	Hexafluoroethane, compressed
2193	126	Refrigerant gas R-116
2193	126	Refrigerant gas R-116, compressed
2194	125	Selenium hexafluoride
2195	125	Tellurium hexafluoride
2196	125	Tungsten hexafluoride
2197	125	Hydrogen iodide, anhydrous
2198	125	Phosphorus pentafluoride
2198	125	Phosphorus pentafluoride, compressed
2199	119	Phosphine
2200	116P	Propadiene, stabilized
2201	122	Nitrous oxide, refrigerated liquid
2202	117	Hydrogen selenide, anhydrous
2203	116	Silane
2203	116	Silane, compressed
2204	119	Carbonyl sulfide
2204	119	Carbonyl sulphide
2205	153	Adiponitrile
2206	155	Isocyanate solution, poisonous, n.o.s.
2206	155	Isocyanate solution, toxic, n.o.s.
2206	155	Isocyanate solutions, n.o.s.
2206	155	Isocyanates, n.o.s.
2206	155	Isocyanates, poisonous, n.o.s.

**ID Guide**  
**No. No.**

2206 **155** Isocyanates, toxic, n.o.s.  
2208 **140** Bleaching powder  
2208 **140** Calcium hypochlorite mixture,  
dry, with more than 10% but  
not more than 39% available  
Chlorine  
2209 **132** Formaldehyde, solutions  
(Formalin) (corrosive)  
2210 **135** Maneb  
2210 **135** Maneb preparation, with not less  
than 60% Maneb  
2211 **133** Polymeric beads, expandable  
2211 **133** Polystyrene beads, expandable  
2212 **171** Asbestos  
2212 **171** Asbestos, blue  
2212 **171** Asbestos, brown  
2212 **171** Blue asbestos  
2212 **171** Brown asbestos  
2213 **133** Paraformaldehyde  
2214 **156** Phthalic anhydride  
2215 **156** Maleic acid  
2215 **156** Maleic anhydride  
2215 **156** Maleic anhydride, molten  
2216 **171** Fish meal, stabilized  
2216 **171** Fish scrap, stabilized  
2217 **135** Seed cake, with not more than  
1.5% oil and not more than  
11% moisture  
2218 **132P** Acrylic acid, stabilized  
2219 **129** Allyl glycidyl ether  
2222 **128** Anisole  
2224 **152** Benzointrile  
2225 **156** Benzenesulfonyl chloride  
2225 **156** Benzenesulphonyl chloride

**ID Guide**  
**No. No.**

2226 **156** Benzotrighloride  
2227 **130P** n-Butyl methacrylate, stabilized  
2232 **153** Chloroacetaldehyde  
2232 **153** 2-Chloroethanal  
2233 **152** Chloroanisidines  
2234 **130** Chlorobenzotrifluorides  
2235 **153** Chlorobenzyl chlorides  
2235 **153** Chlorobenzyl chlorides, liquid  
2236 **156** 3-Chloro-4-methylphenyl  
isocyanate  
2236 **156** 3-Chloro-4-methylphenyl  
isocyanate, liquid  
2237 **153** Chloronitroanilines  
2238 **129** Chlorotoluenes  
2239 **153** Chlorotoluidines  
2239 **153** Chlorotoluidines, liquid  
2239 **153** Chlorotoluidines, solid  
2240 **154** Chromosulfuric acid  
2240 **154** Chromosulphuric acid  
2241 **128** Cycloheptane  
2242 **128** Cycloheptene  
2243 **130** Cyclohexyl acetate  
2244 **129** Cyclopentanol  
2245 **128** Cyclopentanone  
2246 **128** Cyclopentene  
2247 **128** n-Decane  
2248 **132** Di-n-butylamine  
2249 **131** Dichlorodimethyl ether,  
symmetrical  
2250 **156** Dichlorophenyl isocyanates  
2251 **128P** Bicyclo[2.2.1]hepta-2,5-diene,  
stabilized  
2251 **128P** 2,5-Norbornadiene, stabilized  
2252 **127** 1,2-Dimethoxyethane



**ID Guide**  
**No. No.**

2253 **153** N,N-Dimethylaniline  
2254 **133** Matches, fusee  
2256 **130** Cyclohexene  
2257 **138** Potassium  
2257 **138** Potassium, metal  
2258 **132** 1,2-Propylenediamine  
2258 **132** 1,3-Propylenediamine  
2259 **153** Triethylenetetramine  
2260 **132** Tripropylamine  
2261 **153** Xylenols  
2261 **153** Xylenols, solid  
2262 **156** Dimethylcarbamoyl chloride  
2263 **128** Dimethylcyclohexanes  
2264 **132** N,N-Dimethylcyclohexylamine  
2264 **132** Dimethylcyclohexylamine  
2265 **129** N,N-Dimethylformamide  
2266 **132** Dimethyl-N-propylamine  
2267 **156** Dimethyl thiophosphoryl  
chloride  
2269 **153** 3,3'-Iminodipropylamine  
2270 **132** Ethylamine, aqueous solution,  
with not less than 50% but not  
more than 70% Ethylamine  
2271 **128** Ethyl amyl ketone  
2272 **153** N-Ethylaniline  
2273 **153** 2-Ethylaniline  
2274 **153** N-Ethyl-N-benzylaniline  
2275 **129** 2-Ethylbutanol  
2276 **132** 2-Ethylhexylamine  
2277 **130P** Ethyl methacrylate  
2277 **130P** Ethyl methacrylate, stabilized  
2278 **128** n-Heptene  
2279 **151** Hexachlorobutadiene  
2280 **153** Hexamethylenediamine, solid

**ID Guide**  
**No. No.**

2281 **156** Hexamethylene diisocyanate  
2282 **129** Hexanols  
2283 **130P** Isobutyl methacrylate, stabilized  
2284 **131** Isobutyronitrile  
2285 **156** Isocyanatobenzotrifluorides  
2286 **128** Pentamethylheptane  
2287 **128** Isoheptenes  
2288 **128** Isohexenes  
2289 **153** Isophoronediamine  
2290 **156** IPDI  
2290 **156** Isophorone diisocyanate  
2291 **151** Lead compound, soluble, n.o.s.  
2293 **128** 4-Methoxy-4-methylpentan-2-one  
2294 **153** N-Methylaniline  
2295 **155** Methyl chloroacetate  
2296 **128** Methylcyclohexane  
2297 **128** Methylcyclohexanone  
2298 **128** Methylcyclopentane  
2299 **155** Methyl dichloroacetate  
2300 **153** 2-Methyl-5-ethylpyridine  
2301 **128** 2-Methylfuran  
2302 **127** 5-Methylhexan-2-one  
2303 **128** Isopropenylbenzene  
2304 **133** Naphthalene, molten  
2305 **153** Nitrobenzenesulfonic acid  
2305 **153** Nitrobenzenesulphonic acid  
2306 **152** Nitrobenzotrifluorides  
2306 **152** Nitrobenzotrifluorides, liquid  
2307 **152** 3-Nitro-4-chlorobenzotrifluoride  
2308 **157** Nitrosylsulfuric acid  
2308 **157** Nitrosylsulfuric acid, liquid  
2308 **157** Nitrosylsulfuric acid, solid  
2308 **157** Nitrosylsulphuric acid

**ID Guide**  
**No. No.**

2308 **157** Nitrosylsulphuric acid, liquid  
2308 **157** Nitrosylsulphuric acid, solid  
2309 **128P** Octadiene  
2310 **131** Pentan-2,4-dione  
2310 **131** 2,4-Pentanedione  
2310 **131** Pentane-2,4-dione  
2311 **153** Phenetidines  
2312 **153** Phenol, molten  
2313 **129** Picolines  
2315 **171** Articles containing Polychlorinated biphenyls (PCB)  
2315 **171** PCB  
2315 **171** Polychlorinated biphenyls  
2315 **171** Polychlorinated biphenyls, liquid  
2315 **171** Polychlorinated biphenyls, solid  
2316 **157** Sodium cuprocyanide, solid  
2317 **157** Sodium cuprocyanide, solution  
2318 **135** Sodium hydrosulfide, solid, with less than 25% water of crystallization  
2318 **135** Sodium hydrosulfide, with less than 25% water of crystallization  
2318 **135** Sodium hydrosulphide, solid, with less than 25% water of crystallization  
2318 **135** Sodium hydrosulphide, with less than 25% water of crystallization  
2319 **128** Terpene hydrocarbons, n.o.s.  
2320 **153** Tetraethylenepentamine  
2321 **153** Trichlorobenzenes, liquid  
2322 **152** Trichlorobutene  
2323 **130** Triethyl phosphite  
2324 **128** Triisobutylene

**ID Guide**  
**No. No.**

2325 **129** 1,3,5-Trimethylbenzene  
2326 **153** Trimethylcyclohexylamine  
2327 **153** Trimethylhexamethylenediamines  
2328 **156** Trimethylhexamethylene diisocyanate  
2329 **130** Trimethyl phosphite  
2330 **128** Undecane  
2331 **154** Zinc chloride, anhydrous  
2332 **129** Acetaldehyde oxime  
2333 **131** Allyl acetate  
2334 **131** Allylamine  
2335 **131** Allyl ethyl ether  
2336 **131** Allyl formate  
2337 **131** Phenyl mercaptan  
2338 **127** Benzotrifluoride  
2339 **130** 2-Bromobutane  
2340 **130** 2-Bromoethyl ethyl ether  
2341 **130** 1-Bromo-3-methylbutane  
2342 **130** Bromomethylpropanes  
2343 **130** 2-Bromopentane  
2344 **129** 2-Bromopropane  
2344 **129** Bromopropanes  
2345 **130** 3-Bromopropyne  
2346 **127** Butanedione  
2346 **127** Diacetyl  
2347 **130** Butyl mercaptan  
2348 **129P** Butyl acrylates, stabilized  
2350 **127** Butyl methyl ether  
2351 **129** Butyl nitrites  
2352 **127P** Butyl vinyl ether, stabilized  
2353 **132** Butyryl chloride  
2354 **131** Chloromethyl ethyl ether  
2356 **129** 2-Chloropropane

ID No.	Guide No.	Name of Material	ID No.	Guide No.	Name of Material
2357	132	Cyclohexylamine	2385	129	Ethyl isobutyrate
2358	128P	Cyclooctatetraene	2386	132	1-Ethylpiperidine
2359	132	Diallylamine	2387	130	Fluorobenzene
2360	131P	Diallyl ether	2388	130	Fluorotoluenes
2361	132	Diisobutylamine	2389	128	Furan
2362	130	1,1-Dichloroethane	2390	129	2-Iodobutane
2363	129	Ethyl mercaptan	2391	129	Iodomethylpropanes
2364	128	n-Propyl benzene	2392	129	Iodopropanes
2366	128	Diethyl carbonate	2393	129	Isobutyl formate
2367	130	alpha-Methylvaleraldehyde	2394	129	Isobutyl propionate
2367	130	Methyl valeraldehyde (alpha)	2395	132	Isobutyryl chloride
2368	128	alpha-Pinene	2396	131P	Methacrylaldehyde, stabilized
2368	128	Pinene (alpha)	2397	127	3-Methylbutan-2-one
2369	152	Ethylene glycol monobutyl ether	2398	127	Methyl tert-butyl ether
2370	128	1-Hexene	2399	132	1-Methylpiperidine
2371	128	Isopentenenes	2400	130	Methyl isovalerate
2372	129	1,2-Di-(dimethylamino)ethane	2401	132	Piperidine
2373	127	Diethoxymethane	2402	130	Propanethiols
2374	127	3,3-Diethoxypropene	2403	129P	Isopropenyl acetate
2375	129	Diethyl sulfide	2404	131	Propionitrile
2375	129	Diethyl sulphide	2405	129	Isopropyl butyrate
2376	127	2,3-Dihydropyran	2406	127	Isopropyl isobutyrate
2377	127	1,1-Dimethoxyethane	2407	155	Isopropyl chloroformate
2378	131	2-Dimethylaminoacetonitrile	2409	129	Isopropyl propionate
2379	132	1,3-Dimethylbutylamine	2410	129	1,2,3,6-Tetrahydropyridine
2380	127	Dimethyldiethoxysilane	2410	129	1,2,5,6-Tetrahydropyridine
2381	130	Dimethyl disulfide	2411	131	Butyronitrile
2381	130	Dimethyl disulphide	2412	130	Tetrahydrothiophene
2382	131	1,2-Dimethylhydrazine	2413	128	Tetrapropyl orthotitanate
2382	131	Dimethylhydrazine, symmetrical	2414	130	Thiophene
2383	132	Dipropylamine	2416	129	Trimethyl borate
2384	127	Di-n-propyl ether	2417	125	Carbonyl fluoride
2384	127	Dipropyl ether	2417	125	Carbonyl fluoride, compressed

**ID Guide**  
**No. No.**

2418 **125** Sulfur tetrafluoride  
2418 **125** Sulphur tetrafluoride  
2419 **116** Bromotrifluoroethylene  
2420 **125** Hexafluoroacetone  
2421 **124** Nitrogen trioxide  
2422 **126** Octafluorobut-2-ene  
2422 **126** Refrigerant gas R-1318  
2424 **126** Octafluoropropane  
2424 **126** Refrigerant gas R-218  
2426 **140** Ammonium nitrate, liquid (hot concentrated solution)  
2427 **140** Potassium chlorate, aqueous solution  
2427 **140** Potassium chlorate, solution  
2428 **140** Sodium chlorate, aqueous solution  
2429 **140** Calcium chlorate, aqueous solution  
2429 **140** Calcium chlorate, solution  
2430 **153** Alkyl phenols, solid, n.o.s. (including C2-C12 homologues)  
2431 **153** Anisidines  
2431 **153** Anisidines, liquid  
2431 **153** Anisidines, solid  
2432 **153** N,N-Diethylaniline  
2433 **152** Chloronitrotoluenes  
2433 **152** Chloronitrotoluenes, liquid  
2433 **152** Chloronitrotoluenes, solid  
2434 **156** Dibenzylidichlorosilane  
2435 **156** Ethylphenyldichlorosilane  
2436 **129** Thioacetic acid  
2437 **156** Methylphenyldichlorosilane  
2438 **132** Trimethylacetyl chloride

**ID Guide**  
**No. No.**

2439 **154** Sodium hydrogendifluoride  
2440 **154** Stannic chloride, pentahydrate  
2440 **154** Tin tetrachloride, pentahydrate  
2441 **135** Titanium trichloride, pyrophoric  
2441 **135** Titanium trichloride mixture, pyrophoric  
2442 **156** Trichloroacetyl chloride  
2443 **137** Vanadium oxytrichloride  
2444 **137** Vanadium tetrachloride  
2445 **135** Lithium alkyls  
2445 **135** Lithium alkyls, liquid  
2446 **153** Nitroresols  
2446 **153** Nitroresols, solid  
2447 **136** Phosphorus, white, molten  
2447 **136** White phosphorus, molten  
2447 **136** Yellow phosphorus, molten  
2448 **133** Sulfur, molten  
2448 **133** Sulphur, molten  
2451 **122** Nitrogen trifluoride  
2451 **122** Nitrogen trifluoride, compressed  
2452 **116P** Ethylacetylene, stabilized  
2453 **115** Ethyl fluoride  
2453 **115** Refrigerant gas R-161  
2454 **115** Methyl fluoride  
2454 **115** Refrigerant gas R-41  
2455 **116** Methyl nitrite  
2456 **130P** 2-Chloropropene  
2457 **128** 2,3-Dimethylbutane  
2458 **130** Hexadiene  
2459 **128** 2-Methyl-1-butene  
2460 **128** 2-Methyl-2-butene  
2461 **128** Methylpentadiene  
2463 **138** Aluminum hydride

ID No.	Guide No.	Name of Material	ID No.	Guide No.	Name of Material
2464	141	Beryllium nitrate	2486	155	Isobutyl isocyanate
2465	140	Dichloroisocyanuric acid, dry	2487	155	Phenyl isocyanate
2465	140	Dichloroisocyanuric acid salts	2488	155	Cyclohexyl isocyanate
2465	140	Sodium dichloroisocyanurate	2490	153	Dichloroisopropyl ether
2465	140	Sodium dichloro-s-triazinetriene	2491	153	Ethanolamine
2466	143	Potassium superoxide	2491	153	Ethanolamine, solution
2467	140	Sodium percarbonates	2491	153	Monoethanolamine
2468	140	Trichloroisocyanuric acid, dry	2493	132	Hexamethyleneimine
2468	140	(mono)-(Trichloro)-tetra-(monopotassium dichloro)-penta-s-triazinetriene, dry	2495	144	Iodine pentafluoride
2469	140	Zinc bromate	2496	156	Propionic anhydride
2470	152	Phenylacetonitrile, liquid	2498	129	1,2,3,6-Tetrahydrobenzaldehyde
2471	154	Osmium tetroxide	2501	152	1-Aziridinyl phosphine oxide (Tris)
2473	154	Sodium arsanilate	2501	152	Tri-(1-aziridinyl)phosphine oxide, solution
2474	157	Thiophosgene	2501	152	Tris-(1-aziridinyl)phosphine oxide, solution
2475	157	Vanadium trichloride	2502	132	Valeryl chloride
2477	131	Methyl isothiocyanate	2503	137	Zirconium tetrachloride
2478	155	Isocyanate solution, flammable, poisonous, n.o.s.	2504	159	Acetylene tetrabromide
2478	155	Isocyanate solution, flammable, toxic, n.o.s.	2504	159	Tetrabromoethane
2478	155	Isocyanate solutions, n.o.s.	2505	154	Ammonium fluoride
2478	155	Isocyanates, flammable, poisonous, n.o.s.	2506	154	Ammonium hydrogen sulfate
2478	155	Isocyanates, flammable, toxic, n.o.s.	2506	154	Ammonium hydrogen sulphate
2478	155	Isocyanates, n.o.s.	2507	154	Chloroplatinic acid, solid
2480	155	Methyl isocyanate	2508	156	Molybdenum pentachloride
2481	155	Ethyl isocyanate	2509	154	Potassium hydrogen sulfate
2482	155	n-Propyl isocyanate	2509	154	Potassium hydrogen sulphate
2483	155	Isopropyl isocyanate	2511	153	2-Chloropropionic acid
2484	155	tert-Butyl isocyanate	2511	153	2-Chloropropionic acid, solid
2485	155	n-Butyl isocyanate	2511	153	2-Chloropropionic acid, solution
			2512	152	Aminophenols
			2513	156	Bromoacetyl bromide

**ID Guide** **Name of Material**  
**No. No.**

2514 **130** Bromobenzene  
2515 **159** Bromoform  
2516 **151** Carbon tetrabromide  
2517 **115** 1-Chloro-1,1-difluoroethane  
2517 **115** Chlorodifluoroethanes  
2517 **115** Difluorochloroethanes  
2517 **115** Refrigerant gas R-142b  
2518 **153** 1,5,9-Cyclododecatriene  
2520 **130P** Cyclooctadienes  
2521 **131P** Diketene, stabilized  
2522 **153P** 2-Dimethylaminoethyl methacrylate  
2522 **153P** Dimethylaminoethyl methacrylate  
2524 **129** Ethyl orthoformate  
2525 **156** Ethyl oxalate  
2526 **132** Furfurylamine  
2527 **129P** Isobutyl acrylate, stabilized  
2528 **130** Isobutyl isobutyrate  
2529 **132** Isobutyric acid  
2530 **132** Isobutyric anhydride  
2531 **153P** Methacrylic acid, stabilized  
2533 **156** Methyl trichloroacetate  
2534 **119** Methylchlorosilane  
2535 **132** 4-Methylmorpholine  
2535 **132** N-Methylmorpholine  
2535 **132** Methylmorpholine  
2536 **127** Methyltetrahydrofuran  
2538 **133** Nitronaphthalene  
2541 **128** Terpinolene  
2542 **153** Tributylamine  
2545 **135** Hafnium powder, dry  
2546 **135** Titanium powder, dry

**ID Guide** **Name of Material**  
**No. No.**

2547 **143** Sodium superoxide  
2548 **124** Chlorine pentafluoride  
2552 **151** Hexafluoroacetone hydrate  
2552 **151** Hexafluoroacetone hydrate, liquid  
2554 **130P** Methylallyl chloride  
2555 **113** Nitrocellulose with water, not less than 25% water  
2556 **113** Nitrocellulose with alcohol  
2556 **113** Nitrocellulose with not less than 25% alcohol  
2557 **133** Nitrocellulose  
2557 **133** Nitrocellulose mixture, without pigment  
2557 **133** Nitrocellulose mixture, without plasticizer  
2557 **133** Nitrocellulose mixture, with pigment  
2557 **133** Nitrocellulose mixture, with pigment and plasticizer  
2557 **133** Nitrocellulose mixture, with plasticizer  
2558 **131** Epibromohydrin  
2560 **129** 2-Methylpentan-2-ol  
2561 **128** 3-Methyl-1-butene  
2564 **153** Trichloroacetic acid, solution  
2565 **153** Dicyclohexylamine  
2567 **154** Sodium pentachlorophenate  
2570 **154** Cadmium compound  
2571 **156** Alkylsulfuric acids  
2571 **156** Alkylsulphuric acids  
2571 **156** Ethylsulfuric acid  
2571 **156** Ethylsulphuric acid  
2572 **153** Phenylhydrazine  
2573 **141** Thallium chlorate

ID No.	Guide No.	Name of Material
2574	151	Tricresyl phosphate
2576	137	Phosphorus oxybromide, molten
2577	156	Phenylacetyl chloride
2578	157	Phosphorus trioxide
2579	153	Piperazine
2580	154	Aluminum bromide, solution
2581	154	Aluminum chloride, solution
2582	154	Ferric chloride, solution
2583	153	Alkyl sulfonic acids, solid, with more than 5% free Sulfuric acid
2583	153	Alkyl sulphonic acids, solid, with more than 5% free Sulphuric acid
2583	153	Aryl sulfonic acids, solid, with more than 5% free Sulfuric acid
2583	153	Aryl sulphonic acids, solid, with more than 5% free Sulphuric acid
2584	153	Alkyl sulfonic acids, liquid, with more than 5% free Sulfuric acid
2584	153	Alkyl sulphonic acids, liquid, with more than 5% free Sulphuric acid
2584	153	Aryl sulfonic acids, liquid, with more than 5% free Sulfuric acid
2584	153	Aryl sulphonic acids, liquid, with more than 5% free Sulphuric acid
2584	153	Dodecylbenzenesulfonic acid
2584	153	Dodecylbenzenesulphonic acid
2585	153	Alkyl sulfonic acids, solid, with not more than 5% free Sulfuric acid

ID No.	Guide No.	Name of Material
2585	153	Alkyl sulphonic acids, solid, with not more than 5% free Sulphuric acid
2585	153	Aryl sulfonic acids, solid, with not more than 5% free Sulfuric acid
2585	153	Aryl sulphonic acids, solid, with not more than 5% free Sulphuric acid
2586	153	Alkyl sulfonic acids, liquid, with not more than 5% free Sulfuric acid
2586	153	Alkyl sulphonic acids, liquid, with not more than 5% free Sulphuric acid
2586	153	Aryl sulfonic acids, liquid, with not more than 5% free Sulfuric acid
2586	153	Aryl sulphonic acids, liquid, with not more than 5% free Sulphuric acid
2587	153	Benzoquinone
2588	151	Pesticide, solid, poisonous
2588	151	Pesticide, solid, poisonous, n.o.s.
2588	151	Pesticide, solid, toxic, n.o.s.
2589	155	Vinyl chloroacetate
2590	171	Asbestos, white
2590	171	White asbestos
2591	120	Xenon, refrigerated liquid (cryogenic liquid)
2599	126	Chlorotrifluoromethane and Trifluoromethane azeotropic mixture with approximately 60% Chlorotrifluoromethane
2599	126	Refrigerant gas R-13 and Refrigerant gas R-23 azeotropic mixture with 60% Refrigerant gas R-13

**ID Guide**  
**No. No.**

2599 **126** Refrigerant gas R-23 and Refrigerant gas R-13 azeotropic mixture with 60% Refrigerant gas R-13

2599 **126** Refrigerant gas R-503 (azeotropic mixture of Refrigerant gas R-13 and Refrigerant gas R-23 with approximately 60% Refrigerant gas R-13)

2599 **126** Trifluoromethane and Chlorotrifluoromethane azeotropic mixture with approximately 60% Chlorotrifluoromethane

**2600 119** Carbon monoxide and Hydrogen mixture

**2600 119** Carbon monoxide and Hydrogen mixture, compressed

**2600 119** Hydrogen and Carbon monoxide mixture

**2600 119** Hydrogen and Carbon monoxide mixture, compressed

2601 **115** Cyclobutane

2602 **126** Dichlorodifluoromethane and Difluoroethane azeotropic mixture with approximately 74% Dichlorodifluoromethane

2602 **126** Difluoroethane and Dichlorodifluoromethane azeotropic mixture with approximately 74% Dichlorodifluoromethane

2602 **126** Refrigerant gas R-12 and Refrigerant gas R-152a azeotropic mixture with 74% Refrigerant gas R-12

2602 **126** Refrigerant gas R-152a and Refrigerant gas R-12 azeotropic mixture with 74% Refrigerant gas R-12

**ID Guide**  
**No. No.**

2602 **126** Refrigerant gas R-500 (azeotropic mixture of Refrigerant gas R-12 and Refrigerant gas R-152a with approximately 74% Refrigerant gas R-12)

2603 **131** Cycloheptatriene

2604 **132** Boron trifluoride diethyl etherate

**2605 155** Methoxymethyl isocyanate

**2606 155** Methyl orthosilicate

2607 **129P** Acrolein dimer, stabilized

2608 **129** Nitropropanes

2609 **156** Triallyl borate

2610 **132** Triallylamine

2611 **131** Propylene chlorohydrin

2612 **127** Methyl propyl ether

2614 **129** Methallyl alcohol

2615 **127** Ethyl propyl ether

2616 **129** Triisopropyl borate

2617 **129** Methylcyclohexanols

2618 **130P** Vinyltoluenes, stabilized

2619 **132** Benzyldimethylamine

2620 **130** Amyl butyrates

2621 **127** Acetyl methyl carbinol

2622 **131P** Glycidaldehyde

2623 **133** Firelighters, solid, with flammable liquid

2624 **138** Magnesium silicide

2626 **140** Chloric acid, aqueous solution, with not more than 10% Chloric acid

2627 **140** Nitrites, inorganic, n.o.s.

2628 **151** Potassium fluoroacetate

2629 **151** Sodium fluoroacetate

2630 **151** Selenates



**ID Guide**  
**No. No.**

2630 **151** Selenites  
2630 **151** Sodium selenite  
2642 **154** Fluoroacetic acid  
2643 **155** Methyl bromoacetate  
2644 **151** Methyl iodide  
2645 **153** Phenacyl bromide  
2646 **151** Hexachlorocyclopentadiene  
2647 **153** Malononitrile  
2648 **154** 1,2-Dibromobutan-3-one  
2649 **153** 1,3-Dichloroacetone  
2650 **153** 1,1-Dichloro-1-nitroethane  
2651 **153** 4,4'-Diaminodiphenylmethane  
2653 **156** Benzyl iodide  
2655 **151** Potassium fluorosilicate  
2655 **151** Potassium silicofluoride  
2656 **154** Quinoline  
2657 **153** Selenium disulfide  
2657 **153** Selenium disulphide  
2658 **152** Selenium powder  
2659 **151** Sodium chloroacetate  
2660 **153** Mononitrotoluidines  
2660 **153** Nitrotoluidines (mono)  
2661 **153** Hexachloroacetone  
2662 **153** Hydroquinone  
2662 **153** Hydroquinone, solid  
2664 **160** Dibromomethane  
2666 **156** Ethyl cyanoacetate  
2667 **152** Butyltoluenes  
2668 **131** Chloroacetonitrile  
2669 **152** Chlorocresols  
2669 **152** Chlorocresols, liquid  
2669 **152** Chlorocresols, solid  
2669 **152** Chlorocresols, solution

**ID Guide**  
**No. No.**

2670 **157** Cyanuric chloride  
2671 **153** Aminopyridines  
2672 **154** Ammonia, solution, with more than 10% but not more than 35% Ammonia  
2672 **154** Ammonium hydroxide  
2672 **154** Ammonium hydroxide, with more than 10% but not more than 35% Ammonia  
2673 **151** 2-Amino-4-chlorophenol  
2674 **154** Sodium fluorosilicate  
2674 **154** Sodium silicofluoride  
2676 **119** Stibine  
2677 **154** Rubidium hydroxide, solution  
2678 **154** Rubidium hydroxide  
2678 **154** Rubidium hydroxide, solid  
2679 **154** Lithium hydroxide, solution  
2680 **154** Lithium hydroxide  
2680 **154** Lithium hydroxide, monohydrate  
2680 **154** Lithium hydroxide, solid  
2681 **154** Caesium hydroxide, solution  
2681 **154** Cesium hydroxide, solution  
2682 **157** Caesium hydroxide  
2682 **157** Cesium hydroxide  
2683 **132** Ammonium sulfide, solution  
2683 **132** Ammonium sulphide, solution  
2684 **132** 3-Diethylaminopropylamine  
2684 **132** Diethylaminopropylamine  
2685 **132** N,N-Diethylethylenediamine  
2686 **132** 2-Diethylaminoethanol  
2686 **132** Diethylaminoethanol  
2687 **133** Dicyclohexylammonium nitrite  
2688 **159** 1-Bromo-3-chloropropane  
2688 **159** 1-Chloro-3-bromopropane

**ID Guide**  
**No. No.**

2689 **153** Glycerol alpha-monochlorohydrin  
2690 **152** N,n-Butylimidazole  
2691 **137** Phosphorus pentabromide  
2692 **157** Boron tribromide  
2693 **154** Bisulfites, aqueous solution, n.o.s.  
2693 **154** Bisulfites, inorganic, aqueous solution, n.o.s.  
2693 **154** Bisulphites, aqueous solution, n.o.s.  
2693 **154** Bisulphites, inorganic, aqueous solution, n.o.s.  
2698 **156** Tetrahydrophthalic anhydrides  
2699 **154** Trifluoroacetic acid  
2705 **153P** 1-Pentol  
2707 **127** Dimethyldioxanes  
2708 **127** Butoxyl  
2709 **128** Butylbenzenes  
2710 **128** Dipropyl ketone  
2711 **129** Dibromobenzene  
2713 **153** Acridine  
2714 **133** Zinc resinate  
2715 **133** Aluminum resinate  
2716 **153** 1,4-Butynediol  
2717 **133** Camphor  
2717 **133** Camphor, synthetic  
2719 **141** Barium bromate  
2720 **141** Chromium nitrate  
2721 **141** Copper chlorate  
2722 **140** Lithium nitrate  
2723 **140** Magnesium chlorate  
2724 **140** Manganese nitrate  
2725 **140** Nickel nitrate

**ID Guide**  
**No. No.**

2726 **140** Nickel nitrite  
2727 **141** Thallium nitrate  
2728 **140** Zirconium nitrate  
2729 **152** Hexachlorobenzene  
2730 **152** Nitroanisoles  
2730 **152** Nitroanisoles, liquid  
2730 **152** Nitroanisoles, solid  
2732 **152** Nitrobromobenzenes  
2732 **152** Nitrobromobenzenes, liquid  
2732 **152** Nitrobromobenzenes, solid  
2733 **132** Alkylamines, n.o.s.  
2733 **132** Amines, flammable, corrosive, n.o.s.  
2733 **132** Polyalkylamines, n.o.s.  
2733 **132** Polyamines, flammable, corrosive, n.o.s.  
2734 **132** Alkylamines, n.o.s.  
2734 **132** Amines, liquid, corrosive, flammable, n.o.s.  
2734 **132** Polyalkylamines, n.o.s.  
2734 **132** Polyamines, liquid, corrosive, flammable, n.o.s.  
2735 **153** Alkylamines, n.o.s.  
2735 **153** Amines, liquid, corrosive, n.o.s.  
2735 **153** Polyalkylamines, n.o.s.  
2735 **153** Polyamines, liquid, corrosive, n.o.s.  
2738 **153** N-Butylaniline  
2739 **156** Butyric anhydride  
2740 **155** n-Propyl chloroformate  
2741 **141** Barium hypochlorite, with more than 22% available Chlorine  
2742 **155** sec-Butyl chloroformate  
2742 **155** Chloroformates, n.o.s.

<b>ID No.</b>	<b>Guide No.</b>	<b>Name of Material</b>	<b>ID No.</b>	<b>Guide No.</b>	<b>Name of Material</b>
2742	155	Chloroformates, poisonous, corrosive, flammable, n.o.s.	2761	151	Aldrin, solid
2742	155	Chloroformates, toxic, corrosive, flammable, n.o.s.	2761	151	Dieldrin
2742	155	Isobutyl chloroformate	2761	151	Organochlorine pesticide, solid, poisonous
2743	155	n-Butyl chloroformate	2761	151	Organochlorine pesticide, solid, toxic
2744	155	Cyclobutyl chloroformate	2762	131	Aldrin, liquid
2745	157	Chloromethyl chloroformate	2762	131	Organochlorine pesticide, liquid, flammable, poisonous
2746	156	Phenyl chloroformate	2762	131	Organochlorine pesticide, liquid, flammable, toxic
2747	156	tert-Butylcyclohexyl chloroformate	2763	151	Triazine pesticide, solid, poisonous
2748	156	2-Ethylhexyl chloroformate	2763	151	Triazine pesticide, solid, toxic
2749	130	Tetramethylsilane	2764	131	Triazine pesticide, liquid, flammable, poisonous
2750	153	1,3-Dichloropropanol-2	2764	131	Triazine pesticide, liquid, flammable, toxic
2751	155	Diethylthiophosphoryl chloride	2765	152	Phenoxy pesticide, solid, poisonous
2752	127	1,2-Epoxy-3-ethoxypropane	2765	152	Phenoxy pesticide, solid, toxic
2753	153	N-Ethylbenzyltoluidines	2766	131	Phenoxy pesticide, liquid, flammable, poisonous
2753	153	N-Ethylbenzyltoluidines, liquid	2766	131	Phenoxy pesticide, liquid, flammable, toxic
2753	153	N-Ethylbenzyltoluidines, solid	2767	151	Phenyl urea pesticide, solid, poisonous
2754	153	N-Ethyltoluidines	2767	151	Phenyl urea pesticide, solid, toxic
2757	151	Carbamate pesticide, solid, poisonous	2768	131	Phenyl urea pesticide, liquid, flammable, poisonous
2757	151	Carbamate pesticide, solid, toxic	2768	131	Phenyl urea pesticide, liquid, flammable, toxic
2758	131	Carbamate pesticide, liquid, flammable, poisonous	2769	151	Benzoic derivative pesticide, solid, poisonous
2758	131	Carbamate pesticide, liquid, flammable, toxic	2769	151	Benzoic derivative pesticide, solid, toxic
2759	151	Arsenical pesticide, solid, poisonous			
2759	151	Arsenical pesticide, solid, toxic			
2760	131	Arsenical pesticide, liquid, flammable, poisonous			
2760	131	Arsenical pesticide, liquid, flammable, toxic			

**ID Guide**  
**No. No.**

**Name of Material**

2770 **131** Benzoic derivative pesticide, liquid, flammable, poisonous  
2770 **131** Benzoic derivative pesticide, liquid, flammable, toxic  
2771 **151** Dithiocarbamate pesticide, solid, poisonous  
2771 **151** Dithiocarbamate pesticide, solid, toxic  
2771 **151** Thiocarbamate pesticide, solid, poisonous  
2771 **151** Thiocarbamate pesticide, solid, toxic  
2772 **131** Dithiocarbamate pesticide, liquid, flammable, poisonous  
2772 **131** Dithiocarbamate pesticide, liquid, flammable, toxic  
2772 **131** Thiocarbamate pesticide, liquid, flammable, poisonous  
2772 **131** Thiocarbamate pesticide, liquid, flammable, toxic  
2773 **151** Phthalimide derivative pesticide, solid, poisonous  
2773 **151** Phthalimide derivative pesticide, solid, toxic  
2774 **131** Phthalimide derivative pesticide, liquid, flammable, poisonous  
2774 **131** Phthalimide derivative pesticide, liquid, flammable, toxic  
2775 **151** Copper based pesticide, solid, poisonous  
2775 **151** Copper based pesticide, solid, toxic  
2776 **131** Copper based pesticide, liquid, flammable, poisonous  
2776 **131** Copper based pesticide, liquid, flammable, toxic  
2777 **151** Mercury based pesticide, solid, poisonous

**ID Guide**  
**No. No.**

**Name of Material**

2777 **151** Mercury based pesticide, solid, toxic  
2778 **131** Mercury based pesticide, liquid, flammable, poisonous  
2778 **131** Mercury based pesticide, liquid, flammable, toxic  
2779 **153** Substituted nitrophenol pesticide, solid, poisonous  
2779 **153** Substituted nitrophenol pesticide, solid, toxic  
2780 **131** Substituted nitrophenol pesticide, liquid, flammable, poisonous  
2780 **131** Substituted nitrophenol pesticide, liquid, flammable, toxic  
2781 **151** Bipyridilium pesticide, solid, poisonous  
2781 **151** Bipyridilium pesticide, solid, toxic  
2782 **131** Bipyridilium pesticide, liquid, flammable, poisonous  
2782 **131** Bipyridilium pesticide, liquid, flammable, toxic  
2783 **152** Methyl parathion, solid  
2783 **152** Organophosphorus pesticide, solid, poisonous  
2783 **152** Organophosphorus pesticide, solid, toxic  
2783 **152** Parathion  
2783 **152** Tetraethyl pyrophosphate, solid  
2784 **131** Organophosphorus pesticide, liquid, flammable, poisonous  
2784 **131** Organophosphorus pesticide, liquid, flammable, toxic  
2785 **152** 4-Thiapentanal  
2785 **152** Thia-4-pentanal

ID No.	Guide No.	Name of Material
2786	153	Organotin pesticide, solid, poisonous
2786	153	Organotin pesticide, solid, toxic
2787	131	Organotin pesticide, liquid, flammable, poisonous
2787	131	Organotin pesticide, liquid, flammable, toxic
2788	153	Organotin compound, liquid, n.o.s.
2789	132	Acetic acid, glacial
2789	132	Acetic acid, solution, more than 80% acid
2790	153	Acetic acid, solution, more than 10% but not more than 80% acid
2793	170	Ferrous metal borings, shavings, turnings or cuttings
2794	154	Batteries, wet, filled with acid
2795	154	Batteries, wet, filled with alkali
2796	157	Battery fluid, acid
2796	157	Sulfuric acid, with not more than 51% acid
2796	157	Sulphuric acid, with not more than 51% acid
2797	154	Battery fluid, alkali
2797	154	Battery fluid, alkali, with battery
2797	154	Battery fluid, alkali, with electronic equipment or actuating device
2798	137	Benzene phosphorus dichloride
2798	137	Phenylphosphorus dichloride
2799	137	Benzene phosphorus thiodichloride
2799	137	Phenylphosphorus thiodichloride
2800	154	Batteries, wet, non-spillable
2801	154	Dye, liquid, corrosive, n.o.s.

ID No.	Guide No.	Name of Material
2801	154	Dye intermediate, liquid, corrosive, n.o.s.
2802	154	Copper chloride
2803	172	Gallium
2805	138	Lithium hydride, fused solid
2806	138	Lithium nitride
2807	171	Magnetized material
2809	172	Mercury
2809	172	Mercury metal
2810	153	Buzz
2810	153	BZ
2810	153	Compound, tree or weed killing, liquid (toxic)
2810	153	CS
2810	153	DC
2810	153	GA
2810	153	GB
2810	153	GD
2810	153	GF
2810	153	H
2810	153	HD
2810	153	HL
2810	153	HN-1
2810	153	HN-2
2810	153	HN-3
2810	153	L (Lewisite)
2810	153	Lewisite
2810	153	Mustard
2810	153	Mustard Lewisite
2810	153	Poison B, liquid, n.o.s.
2810	153	Poisonous liquid, n.o.s.
2810	153	Poisonous liquid, n.o.s. (Inhalation Hazard Zone A)

**ID Guide**  
**No. No.**

2810 **153** Poisonous liquid, n.o.s.  
(Inhalation Hazard Zone B)

2810 **153** Poisonous liquid, organic, n.o.s.

2810 **153** Poisonous liquid, organic, n.o.s.  
(Inhalation Hazard Zone A)

2810 **153** Poisonous liquid, organic, n.o.s.  
(Inhalation Hazard Zone B)

2810 **153** Sarin

2810 **153** Soman

2810 **153** Tabun

2810 **153** Thickened GD

2810 **153** Toxic liquid, n.o.s.

2810 **153** Toxic liquid, n.o.s. (Inhalation  
Hazard Zone A)

2810 **153** Toxic liquid, n.o.s. (Inhalation  
Hazard Zone B)

2810 **153** Toxic liquid, organic, n.o.s.

2810 **153** Toxic liquid, organic, n.o.s.  
(Inhalation Hazard Zone A)

2810 **153** Toxic liquid, organic, n.o.s.  
(Inhalation Hazard Zone B)

2810 **153** VX

2811 **154** CX

2811 **154** Poisonous solid, organic, n.o.s.

2811 **154** Selenium oxide

2811 **154** Toxic solid, organic, n.o.s.

2812 **154** Sodium aluminate, solid

2813 **138** Water-reactive solid, n.o.s.

2814 **158** Infectious substance, affecting  
humans

2815 **153** N-Aminoethylpiperazine

2817 **154** Ammonium bifluoride, solution

2817 **154** Ammonium hydrogendifluoride,  
solution

2817 **154** Ammonium hydrogen fluoride,  
solution

**ID Guide**  
**No. No.**

2818 **154** Ammonium polysulfide, solution

2818 **154** Ammonium polysulphide,  
solution

2819 **153** Amyl acid phosphate

2820 **153** Butyric acid

2821 **153** Phenol solution

2822 **153** 2-Chloropyridine

2823 **153** Crotonic acid

2823 **153** Crotonic acid, liquid

2823 **153** Crotonic acid, solid

2826 **155** Ethyl chlorothioformate

2829 **153** Caproic acid

2829 **153** Hexanoic acid

2830 **139** Lithium ferrosilicon

2831 **160** 1,1,1-Trichloroethane

2834 **154** Phosphorous acid

2834 **154** Phosphorous acid, ortho

2835 **138** Sodium aluminum hydride

2837 **154** Bisulfates, aqueous solution

2837 **154** Bisulphates, aqueous solution

2837 **154** Sodium bisulfate, solution

2837 **154** Sodium bisulphate, solution

2837 **154** Sodium hydrogen sulfate,  
solution

2837 **154** Sodium hydrogen sulphate,  
solution

2838 **129P** Vinyl butyrate, stabilized

2839 **153** Aldol

2840 **129** Butyraldoxime

2841 **131** Di-n-amylamine

2842 **129** Nitroethane

2844 **138** Calcium manganese silicon

2845 **135** Ethyl phosphonous dichloride,  
anhydrous

ID No.	Guide No.	Name of Material
2845	135	Methyl phosphonous dichloride
2845	135	Pyrophoric liquid, n.o.s.
2845	135	Pyrophoric liquid, organic, n.o.s.
2846	135	Pyrophoric solid, n.o.s.
2846	135	Pyrophoric solid, organic, n.o.s.
2849	153	3-Chloropropanol-1
2850	128	Propylene tetramer
2851	157	Boron trifluoride, dihydrate
2852	113	Dipicryl sulfide, wetted with not less than 10% water
2852	113	Dipicryl sulphide, wetted with not less than 10% water
2853	151	Magnesium fluorosilicate
2853	151	Magnesium silicofluoride
2854	151	Ammonium fluorosilicate
2854	151	Ammonium silicofluoride
2855	151	Zinc fluorosilicate
2855	151	Zinc silicofluoride
2856	151	Fluorosilicates, n.o.s.
2856	151	Silicofluorides, n.o.s.
2857	126	Refrigerating machines, containing Ammonia solutions (UN2672)
2857	126	Refrigerating machines, containing non-flammable, non-poisonous gases
2857	126	Refrigerating machines, containing non-flammable, non-toxic gases
2858	170	Zirconium, dry, coiled wire, finished metal sheets or strips
2859	154	Ammonium metavanadate
2861	151	Ammonium polyvanadate
2862	151	Vanadium pentoxide

ID No.	Guide No.	Name of Material
2863	154	Sodium ammonium vanadate
2864	151	Potassium metavanadate
2865	154	Hydroxylamine sulfate
2865	154	Hydroxylamine sulphate
2869	157	Titanium trichloride mixture
2870	135	Aluminum borohydride
2870	135	Aluminum borohydride in devices
2871	170	Antimony powder
2872	159	Dibromochloropropanes
2873	153	Dibutylaminoethanol
2874	153	Furfuryl alcohol
2875	151	Hexachlorophene
2876	153	Resorcinol
2878	170	Titanium sponge granules
2878	170	Titanium sponge powders
2879	157	Selenium oxychloride
2880	140	Calcium hypochlorite, hydrated, with not less than 5.5% but not more than 16% water
2880	140	Calcium hypochlorite, hydrated mixture, with not less than 5.5% but not more than 16% water
2881	135	Metal catalyst, dry
2881	135	Nickel catalyst, dry
2900	158	Infectious substance, affecting animals only
2901	124	Bromine chloride
2902	151	Pesticide, liquid, poisonous, n.o.s.
2902	151	Pesticide, liquid, toxic, n.o.s.
2903	131	Pesticide, liquid, poisonous, flammable, n.o.s.
2903	131	Pesticide, liquid, toxic, flammable, n.o.s.

<b>ID No.</b>	<b>Guide No.</b>	<b>Name of Material</b>	<b>ID No.</b>	<b>Guide No.</b>	<b>Name of Material</b>
2904	154	Chlorophenates, liquid	2910	161	Radioactive material, excepted package, limited quantity of material
2904	154	Chlorophenolates, liquid	2911	161	Radioactive material, excepted package, instruments or articles
2904	154	Phenolates, liquid	2912	162	Radioactive material, low specific activity (LSA), n.o.s.
2905	154	Chlorophenates, solid	2912	162	Radioactive material, low specific activity (LSA-I) non fissile or fissile-excepted
2905	154	Chlorophenolates, solid	2913	162	Radioactive material, surface contaminated objects (SCO)
2905	154	Phenolates, solid	2913	162	Radioactive material, surface contaminated objects (SCO-I) non fissile or fissile-excepted
2907	133	Isosorbide dinitrate mixture	2913	162	Radioactive material, surface contaminated objects (SCO-II) non fissile or fissile-excepted
2908	161	Radioactive material, excepted package, empty packaging	2915	163	Radioactive material, Type A package non-special form, non fissile or fissile-excepted
2909	161	Radioactive material, excepted package, articles manufactured from depleted Uranium	2916	163	Radioactive material, Type B(U) package non fissile or fissile-excepted
2909	161	Radioactive material, excepted package, articles manufactured from natural Thorium	2917	163	Radioactive material, Type B(M) package non fissile or fissile-excepted
2909	161	Radioactive material, excepted package, articles manufactured from natural Uranium	2918	165	Radioactive material, fissile, n.o.s.
2910	161	Radioactive material, excepted package, articles manufactured from depleted Uranium	2919	163	Radioactive material, transported under special arrangement non fissile or fissile-excepted
2910	161	Radioactive material, excepted package, articles manufactured from natural Thorium	2920	132	Corrosive liquid, flammable, n.o.s.
2910	161	Radioactive material, excepted package, articles manufactured from natural Uranium	2920	132	Dichlorobutene
2910	161	Radioactive material, excepted package, empty packaging	2921	134	Corrosive solid, flammable, n.o.s.
2910	161	Radioactive material, excepted package, instruments or articles			



ID No.	Guide No.	Name of Material
2922	154	Corrosive liquid, poisonous, n.o.s.
2922	154	Corrosive liquid, toxic, n.o.s.
2922	154	Sodium hydrosulfide, solution
2922	154	Sodium hydrosulphide, solution
2923	154	Corrosive solid, poisonous, n.o.s.
2923	154	Corrosive solid, toxic, n.o.s.
2924	132	Flammable liquid, corrosive, n.o.s.
2925	134	Flammable solid, corrosive, n.o.s.
2925	134	Flammable solid, corrosive, organic, n.o.s.
2926	134	Flammable solid, poisonous, n.o.s.
2926	134	Flammable solid, poisonous, organic, n.o.s.
2926	134	Flammable solid, toxic, organic, n.o.s.
2927	154	Ethyl phosphonothioic dichloride, anhydrous
2927	154	Ethyl phosphorodichloridate
2927	154	Poisonous liquid, corrosive, n.o.s.
2927	154	Poisonous liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)
2927	154	Poisonous liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)
2927	154	Poisonous liquid, corrosive, organic, n.o.s.
2927	154	Poisonous liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone A)
2927	154	Poisonous liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone B)
2927	154	Toxic liquid, corrosive, n.o.s.

ID No.	Guide No.	Name of Material
2927	154	Toxic liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)
2927	154	Toxic liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)
2927	154	Toxic liquid, corrosive, organic, n.o.s.
2927	154	Toxic liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone A)
2927	154	Toxic liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone B)
2928	154	Poisonous solid, corrosive, n.o.s.
2928	154	Toxic solid, corrosive, organic, n.o.s.
2929	131	Poisonous liquid, flammable, n.o.s.
2929	131	Poisonous liquid, flammable, n.o.s. (Inhalation Hazard Zone A)
2929	131	Poisonous liquid, flammable, n.o.s. (Inhalation Hazard Zone B)
2929	131	Poisonous liquid, flammable, organic, n.o.s.
2929	131	Poisonous liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone A)
2929	131	Poisonous liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone B)
2929	131	Toxic liquid, flammable, n.o.s.
2929	131	Toxic liquid, flammable, n.o.s. (Inhalation Hazard Zone A)
2929	131	Toxic liquid, flammable, n.o.s. (Inhalation Hazard Zone B)
2929	131	Toxic liquid, flammable, organic, n.o.s.

**ID Guide Name of Material**  
**No. No.**

2929	131	Toxic liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone A)
2929	131	Toxic liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone B)
2930	134	Poisonous solid, flammable, n.o.s.
2930	134	Poisonous solid, flammable, organic, n.o.s.
2930	134	Toxic solid, flammable, n.o.s.
2930	134	Toxic solid, flammable, organic, n.o.s.
2931	151	Vanadyl sulfate
2931	151	Vanadyl sulphate
2933	129	Methyl 2-chloropropionate
2934	129	Isopropyl 2-chloropropionate
2935	129	Ethyl 2-chloropropionate
2936	153	Thiolactic acid
2937	153	alpha-Methylbenzyl alcohol
2937	153	alpha-Methylbenzyl alcohol, liquid
2937	153	Methylbenzyl alcohol (alpha)
2938	152	Methyl benzoate
2940	135	Cyclooctadiene phosphines
2940	135	9-Phosphabicyclononanes
2941	153	Fluoroanilines
2942	153	2-Trifluoromethylaniline
2943	129	Tetrahydrofurfurylamine
2945	132	N-Methylbutylamine
2946	153	2-Amino-5-diethylaminopentane
2947	155	Isopropyl chloroacetate
2948	153	3-Trifluoromethylaniline
2949	154	Sodium hydrosulfide, with not less than 25% water of crystallization

**ID Guide Name of Material**  
**No. No.**

2949	154	Sodium hydrosulphide, with not less than 25% water of crystallization
2950	138	Magnesium granules, coated
2956	149	5-tert-Butyl-2,4,6-trinitro-m-xylene
2956	149	Musk xylene
2965	139	Boron trifluoride dimethyl etherate
2966	153	Thioglycol
2967	154	Sulfamic acid
2967	154	Sulphamic acid
2968	135	Maneb, stabilized
2968	135	Maneb preparation, stabilized
2969	171	Castor beans, meal, pomace or flake
2974	164	Radioactive material, special form, n.o.s.
2975	162	Thorium metal, pyrophoric
2976	162	Thorium nitrate, solid
2977	166	Radioactive material, Uranium hexafluoride, fissile
2977	166	Uranium hexafluoride, fissile containing more than 1% Uranium-235
2978	166	Radioactive material, Uranium hexafluoride
2978	166	Uranium hexafluoride
2978	166	Uranium hexafluoride non fissile or fissile-excepted
2979	162	Uranium metal, pyrophoric
2980	162	Uranyl nitrate, hexahydrate, solution
2981	162	Uranyl nitrate, solid
2982	163	Radioactive material, n.o.s.

ID No.	Guide No.	Name of Material
2983	129P	Ethylene oxide and Propylene oxide mixture, with not more than 30% Ethylene oxide
2983	129P	Propylene oxide and Ethylene oxide mixture, with not more than 30% Ethylene oxide
2984	140	Hydrogen peroxide, aqueous solution, with not less than 8% but less than 20% Hydrogen peroxide
2985	155	Chlorosilanes, flammable, corrosive, n.o.s.
2985	155	Chlorosilanes, n.o.s.
2986	155	Chlorosilanes, corrosive, flammable, n.o.s.
2986	155	Chlorosilanes, n.o.s.
2987	156	Chlorosilanes, corrosive, n.o.s.
2987	156	Chlorosilanes, n.o.s.
2988	139	Chlorosilanes, n.o.s.
2988	139	Chlorosilanes, water-reactive, flammable, corrosive, n.o.s.
2989	133	Lead phosphite, dibasic
2990	171	Life-saving appliances, self-inflating
2991	131	Carbamate pesticide, liquid, poisonous, flammable
2991	131	Carbamate pesticide, liquid, toxic, flammable
2992	151	Carbamate pesticide, liquid, poisonous
2992	151	Carbamate pesticide, liquid, toxic
2993	131	Arsenical pesticide, liquid, poisonous, flammable
2993	131	Arsenical pesticide, liquid, toxic, flammable
2994	151	Arsenical pesticide, liquid, poisonous

ID No.	Guide No.	Name of Material
2994	151	Arsenical pesticide, liquid, toxic
2995	131	Organochlorine pesticide, liquid, poisonous, flammable
2995	131	Organochlorine pesticide, liquid, toxic, flammable
2996	151	Organochlorine pesticide, liquid, poisonous
2996	151	Organochlorine pesticide, liquid, toxic
2997	131	Triazine pesticide, liquid, poisonous, flammable
2997	131	Triazine pesticide, liquid, toxic, flammable
2998	151	Triazine pesticide, liquid, poisonous
2998	151	Triazine pesticide, liquid, toxic
2999	131	Phenoxy pesticide, liquid, poisonous, flammable
2999	131	Phenoxy pesticide, liquid, toxic, flammable
3000	152	Phenoxy pesticide, liquid, poisonous
3000	152	Phenoxy pesticide, liquid, toxic
3001	131	Phenyl urea pesticide, liquid, poisonous, flammable
3001	131	Phenyl urea pesticide, liquid, toxic, flammable
3002	151	Phenyl urea pesticide, liquid, poisonous
3002	151	Phenyl urea pesticide, liquid, toxic
3003	131	Benzoic derivative pesticide, liquid, poisonous, flammable
3003	131	Benzoic derivative pesticide, liquid, toxic, flammable
3004	151	Benzoic derivative pesticide, liquid, poisonous

<b>ID No.</b>	<b>Guide No.</b>	<b>Name of Material</b>	<b>ID No.</b>	<b>Guide No.</b>	<b>Name of Material</b>
3004	151	Benzoic derivative pesticide, liquid, toxic	3012	151	Mercury based pesticide, liquid, poisonous
3005	131	Dithiocarbamate pesticide, liquid, poisonous, flammable	3012	151	Mercury based pesticide, liquid, toxic
3005	131	Dithiocarbamate pesticide, liquid, toxic, flammable	3013	131	Substituted nitrophenol pesticide, liquid, poisonous, flammable
3005	131	Thiocarbamate pesticide, liquid, poisonous, flammable	3013	131	Substituted nitrophenol pesticide, liquid, toxic, flammable
3005	131	Thiocarbamate pesticide, liquid, toxic, flammable	3014	153	Substituted nitrophenol pesticide, liquid, poisonous
3006	151	Dithiocarbamate pesticide, liquid, poisonous	3014	153	Substituted nitrophenol pesticide, liquid, toxic
3006	151	Dithiocarbamate pesticide, liquid, toxic	3015	131	Bipyridilium pesticide, liquid, poisonous, flammable
3006	151	Thiocarbamate pesticide, liquid, poisonous	3015	131	Bipyridilium pesticide, liquid, toxic, flammable
3006	151	Thiocarbamate pesticide, liquid, toxic	3016	151	Bipyridilium pesticide, liquid, poisonous
3007	131	Phthalimide derivative pesticide, liquid, poisonous, flammable	3016	151	Bipyridilium pesticide, liquid, toxic
3007	131	Phthalimide derivative pesticide, liquid, toxic, flammable	3017	131	Organophosphorus pesticide, liquid, poisonous, flammable
3008	151	Phthalimide derivative pesticide, liquid, poisonous	3017	131	Organophosphorus pesticide, liquid, toxic, flammable
3008	151	Phthalimide derivative pesticide, liquid, toxic	3018	152	Methyl parathion, liquid
3009	131	Copper based pesticide, liquid, poisonous, flammable	3018	152	Organophosphorus pesticide, liquid, poisonous
3009	131	Copper based pesticide, liquid, toxic, flammable	3018	152	Organophosphorus pesticide, liquid, toxic
3010	151	Copper based pesticide, liquid, poisonous	3018	152	Tetraethyl pyrophosphate, liquid
3010	151	Copper based pesticide, liquid, toxic	3019	131	Organotin pesticide, liquid, poisonous, flammable
3011	131	Mercury based pesticide, liquid, poisonous, flammable	3019	131	Organotin pesticide, liquid, toxic, flammable
3011	131	Mercury based pesticide, liquid, toxic, flammable	3020	153	Organotin pesticide, liquid, poisonous

ID No.	Guide No.	Name of Material
3020	153	Organotin pesticide, liquid, toxic
3021	131	Pesticide, liquid, flammable, poisonous, n.o.s.
3021	131	Pesticide, liquid, flammable, toxic, n.o.s.
3022	127P	1,2-Butylene oxide, stabilized
3023	131	2-Methyl-2-heptanethiol
3023	131	tert-Octyl mercaptan
3024	131	Coumarin derivative pesticide, liquid, flammable, poisonous
3024	131	Coumarin derivative pesticide, liquid, flammable, toxic
3025	131	Coumarin derivative pesticide, liquid, poisonous, flammable
3025	131	Coumarin derivative pesticide, liquid, toxic, flammable
3026	151	Coumarin derivative pesticide, liquid, poisonous
3026	151	Coumarin derivative pesticide, liquid, toxic
3027	151	Coumarin derivative pesticide, solid, poisonous
3027	151	Coumarin derivative pesticide, solid, toxic
3028	154	Batteries, dry, containing Potassium hydroxide solid
3048	157	Aluminum phosphide pesticide
3049	138	Metal alkyl halides, n.o.s.
3049	138	Metal alkyl halides, water-reactive, n.o.s.
3049	138	Metal aryl halides, n.o.s.
3049	138	Metal aryl halides, water-reactive, n.o.s.
3050	138	Metal alkyl hydrides, n.o.s.
3050	138	Metal alkyl hydrides, water-reactive, n.o.s.

ID No.	Guide No.	Name of Material
3050	138	Metal aryl hydrides, n.o.s.
3050	138	Metal aryl hydrides, water-reactive, n.o.s.
3051	135	Aluminum alkyls
3052	135	Aluminum alkyl halides
3052	135	Aluminum alkyl halides, liquid
3052	135	Aluminum alkyl halides, solid
3053	135	Magnesium alkyls
3054	129	Cyclohexanethiol
3054	129	Cyclohexyl mercaptan
3055	154	2-(2-Aminoethoxy)ethanol
3056	129	n-Heptaldehyde
3057	125	Trifluoroacetyl chloride
3064	127	Nitroglycerin, solution in alcohol, with more than 1% but not more than 5% Nitroglycerin
3065	127	Alcoholic beverages
3066	153	Paint (corrosive)
3066	153	Paint related material (corrosive)
3070	126	Dichlorodifluoromethane and Ethylene oxide mixture, with not more than 12.5% Ethylene oxide
3070	126	Dichlorodifluoromethane and Ethylene oxide mixtures, with not more than 12% Ethylene oxide
3070	126	Ethylene oxide and Dichlorodifluoromethane mixture, with not more than 12.5% Ethylene oxide
3070	126	Ethylene oxide and Dichlorodifluoromethane mixtures, with not more than 12% Ethylene oxide

**ID Guide**  
**No. No.**

- 3071 131 Mercaptan mixture, liquid, poisonous, flammable, n.o.s.
- 3071 131 Mercaptan mixture, liquid, toxic, flammable, n.o.s.
- 3071 131 Mercaptans, liquid, poisonous, flammable, n.o.s.
- 3071 131 Mercaptans, liquid, toxic, flammable, n.o.s.
- 3072 171 Life-saving appliances, not self-inflating
- 3073 131P Vinylpyridines, stabilized
- 3076 138 Aluminum alkyl hydrides
- 3077 171 Environmentally hazardous substances, solid, n.o.s.
- 3077 171 Hazardous waste, solid, n.o.s.
- 3077 171 Other regulated substances, solid, n.o.s.
- 3078 138 Cerium, turnings or gritty powder
- 3079 131P Methacrylonitrile, stabilized
- 3080 155 Isocyanate solution, poisonous, flammable, n.o.s.
- 3080 155 Isocyanate solution, toxic, flammable, n.o.s.
- 3080 155 Isocyanate solutions, n.o.s.
- 3080 155 Isocyanates, n.o.s.
- 3080 155 Isocyanates, poisonous, flammable, n.o.s.
- 3080 155 Isocyanates, toxic, flammable, n.o.s.
- 3082 171 Environmentally hazardous substances, liquid, n.o.s.
- 3082 171 Hazardous waste, liquid, n.o.s.
- 3082 171 Other regulated substances, liquid, n.o.s.
- 3083 124 Perchloryl fluoride

**ID Guide**  
**No. No.**

- 3084 140 Corrosive solid, oxidizing, n.o.s.
- 3085 140 Oxidizing solid, corrosive, n.o.s.
- 3086 141 Poisonous solid, oxidizing, n.o.s.
- 3086 141 Toxic solid, oxidizing, n.o.s.
- 3087 141 Oxidizing solid, poisonous, n.o.s.
- 3087 141 Oxidizing solid, toxic, n.o.s.
- 3088 135 Self-heating solid, organic, n.o.s.
- 3089 170 Metal powder, flammable, n.o.s.
- 3090 138 Lithium batteries
- 3090 138 Lithium batteries, liquid or solid cathode
- 3090 138 Lithium metal batteries (including lithium alloy batteries)
- 3091 138 Lithium batteries contained in equipment
- 3091 138 Lithium batteries packed with equipment
- 3091 138 Lithium metal batteries contained in equipment (including lithium alloy batteries)
- 3091 138 Lithium metal batteries packed with equipment (including lithium alloy batteries)
- 3092 129 1-Methoxy-2-propanol
- 3093 140 Corrosive liquid, oxidizing, n.o.s.
- 3094 138 Corrosive liquid, water-reactive, n.o.s.
- 3094 138 Corrosive liquid, which in contact with water emits flammable gases, n.o.s.
- 3095 136 Corrosive solid, self-heating, n.o.s.
- 3096 138 Corrosive solid, water-reactive, n.o.s.

ID No.	Guide No.	Name of Material
3096	138	Corrosive solid, which in contact with water emits flammable gases, n.o.s.
3097	140	Flammable solid, oxidizing, n.o.s.
3098	140	Oxidizing liquid, corrosive, n.o.s.
3099	142	Oxidizing liquid, poisonous, n.o.s.
3099	142	Oxidizing liquid, toxic, n.o.s.
3100	135	Oxidizing solid, self-heating, n.o.s.
3101	146	Organic peroxide type B, liquid
3102	146	Organic peroxide type B, solid
3103	146	Organic peroxide type C, liquid
3104	146	Organic peroxide type C, solid
3105	145	Organic peroxide type D, liquid
3106	145	Organic peroxide type D, solid
3107	145	Organic peroxide type E, liquid
3108	145	Organic peroxide type E, solid
3109	145	Organic peroxide type F, liquid
3110	145	Organic peroxide type F, solid
3111	148	Organic peroxide type B, liquid, temperature controlled
3112	148	Organic peroxide type B, solid, temperature controlled
3113	148	Organic peroxide type C, liquid, temperature controlled
3114	148	Organic peroxide type C, solid, temperature controlled
3115	148	Organic peroxide type D, liquid, temperature controlled
3116	148	Organic peroxide type D, solid, temperature controlled
3117	148	Organic peroxide type E, liquid, temperature controlled
3118	148	Organic peroxide type E, solid, temperature controlled

ID No.	Guide No.	Name of Material
3119	148	Organic peroxide type F, liquid, temperature controlled
3120	148	Organic peroxide type F, solid, temperature controlled
3121	144	Oxidizing solid, water-reactive, n.o.s.
3122	142	Poisonous liquid, oxidizing, n.o.s.
3122	142	Poisonous liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)
3122	142	Poisonous liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)
3122	142	Toxic liquid, oxidizing, n.o.s.
3122	142	Toxic liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)
3122	142	Toxic liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)
3123	139	Poisonous liquid, water-reactive, n.o.s.
3123	139	Poisonous liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)
3123	139	Poisonous liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)
3123	139	Poisonous liquid, which in contact with water emits flammable gases, n.o.s.
3123	139	Poisonous liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone A)
3123	139	Poisonous liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone B)

**ID Guide No. No. Name of Material**

- 3123 **139** Toxic liquid, water-reactive, n.o.s.
- 3123 **139** Toxic liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)
- 3123 **139** Toxic liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)
- 3123 **139** Toxic liquid, which in contact with water emits flammable gases, n.o.s.
- 3123 **139** Toxic liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone A)
- 3123 **139** Toxic liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone B)
- 3124 **136** Poisonous solid, self-heating, n.o.s.
- 3124 **136** Toxic solid, self-heating, n.o.s.
- 3125 **139** Poisonous solid, water-reactive, n.o.s.
- 3125 **139** Poisonous solid, which in contact with water emits flammable gases, n.o.s.
- 3125 **139** Toxic solid, water-reactive, n.o.s.
- 3125 **139** Toxic solid, which in contact with water emits flammable gases, n.o.s.
- 3126 **136** Self-heating solid, corrosive, organic, n.o.s.
- 3127 **135** Self-heating solid, oxidizing, n.o.s.
- 3128 **136** Self-heating solid, poisonous, organic, n.o.s.

**ID Guide No. No. Name of Material**

- 3128 **136** Self-heating solid, toxic, organic, n.o.s.
- 3129 **138** Water-reactive liquid, corrosive, n.o.s.
- 3130 **139** Water-reactive liquid, poisonous, n.o.s.
- 3130 **139** Water-reactive liquid, toxic, n.o.s.
- 3131 **138** Water-reactive solid, corrosive, n.o.s.
- 3132 **138** Water-reactive solid, flammable, n.o.s.
- 3133 **138** Water-reactive solid, oxidizing, n.o.s.
- 3134 **139** Water-reactive solid, poisonous, n.o.s.
- 3134 **139** Water-reactive solid, toxic, n.o.s.
- 3135 **138** Water-reactive solid, self-heating, n.o.s.
- 3136 **120** Trifluoromethane, refrigerated liquid
- 3137 **140** Oxidizing solid, flammable, n.o.s.
- 3138 **115** Acetylene, Ethylene and Propylene in mixture, refrigerated liquid containing at least 71.5% Ethylene with not more than 22.5% Acetylene and not more than 6% Propylene
- 3138 **115** Ethylene, Acetylene and Propylene in mixture, refrigerated liquid containing at least 71.5% Ethylene with not more than 22.5% Acetylene and not more than 6% Propylene



ID No.	Guide No.	Name of Material
3138	115	Propylene, Ethylene and Acetylene in mixture, refrigerated liquid containing at least 71.5% Ethylene with not more than 22.5% Acetylene and not more than 6% Propylene
3139	140	Oxidizing liquid, n.o.s.
3140	151	Alkaloids, liquid, n.o.s. (poisonous)
3140	151	Alkaloid salts, liquid, n.o.s. (poisonous)
3141	157	Antimony compound, inorganic, liquid, n.o.s.
3142	151	Disinfectant, liquid, poisonous, n.o.s.
3142	151	Disinfectant, liquid, toxic, n.o.s.
3142	151	Disinfectants, liquid, n.o.s. (poisonous)
3143	151	Dye, solid, poisonous, n.o.s.
3143	151	Dye, solid, toxic, n.o.s.
3143	151	Dye intermediate, solid, poisonous, n.o.s.
3143	151	Dye intermediate, solid, toxic, n.o.s.
3144	151	Nicotine compound, liquid, n.o.s.
3144	151	Nicotine preparation, liquid, n.o.s.
3145	153	Alkyl phenols, liquid, n.o.s. (including C2-C12 homologues)
3146	153	Organotin compound, solid, n.o.s.
3147	154	Dye, solid, corrosive, n.o.s.
3147	154	Dye intermediate, solid, corrosive, n.o.s.
3148	138	Water-reactive liquid, n.o.s.

ID No.	Guide No.	Name of Material
3149	140	Hydrogen peroxide and Peroxyacetic acid mixture, with acid(s), water and not more than 5% Peroxyacetic acid, stabilized
3150	115	Devices, small, hydrocarbon gas powered, with release device
3150	115	Hydrocarbon gas refills for small devices, with release device
3151	171	Polyhalogenated biphenyls, liquid
3151	171	Polyhalogenated terphenyls, liquid
3152	171	Polyhalogenated biphenyls, solid
3152	171	Polyhalogenated terphenyls, solid
3153	115	Perfluoromethyl vinyl ether
3153	115	Perfluoro(methyl vinyl ether)
3154	115	Perfluoroethyl vinyl ether
3154	115	Perfluoro(ethyl vinyl ether)
3155	154	Pentachlorophenol
3156	122	Compressed gas, oxidizing, n.o.s.
3157	122	Liquefied gas, oxidizing, n.o.s.
3158	120	Gas, refrigerated liquid, n.o.s.
3159	126	Refrigerant gas R-134a
3159	126	1,1,1,2-Tetrafluoroethane
3160	119	Liquefied gas, poisonous, flammable, n.o.s.
3160	119	Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)
3160	119	Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone B)

**ID Guide Name of Material**  
**No. No.**

3160 119 Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)

3160 119 Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone D)

3160 119 Liquefied gas, toxic, flammable, n.o.s.

3160 119 Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone A)

3160 119 Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone B)

3160 119 Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone C)

3160 119 Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone D)

3161 115 Liquefied gas, flammable, n.o.s.

3162 123 Liquefied gas, poisonous, n.o.s.

3162 123 Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone A)

3162 123 Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone B)

3162 123 Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone C)

3162 123 Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone D)

3162 123 Liquefied gas, toxic, n.o.s.

3162 123 Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone A)

3162 123 Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone B)

3162 123 Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone C)

3162 123 Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone D)

**ID Guide Name of Material**  
**No. No.**

3163 126 Liquefied gas, n.o.s.

3164 126 Articles, pressurized, hydraulic (containing non-flammable gas)

3164 126 Articles, pressurized, pneumatic (containing non-flammable gas)

3165 131 Aircraft hydraulic power unit fuel tank

3166 128 Engines, internal combustion, flammable gas powered

3166 128 Engines, internal combustion, flammable liquid powered

3166 128 Engines, internal combustion, including when fitted in machinery or vehicles

3166 128 Vehicle, flammable gas powered

3166 128 Vehicle, flammable liquid powered

3167 115 Gas sample, non-pressurized, flammable, n.o.s., not refrigerated liquid

3168 119 Gas sample, non-pressurized, poisonous, flammable, n.o.s., not refrigerated liquid

3168 119 Gas sample, non-pressurized, toxic, flammable, n.o.s., not refrigerated liquid

3169 123 Gas sample, non-pressurized, poisonous, n.o.s., not refrigerated liquid

3169 123 Gas sample, non-pressurized, toxic, n.o.s., not refrigerated liquid

3170 138 Aluminum dross

3170 138 Aluminum processing by-products

3170 138 Aluminum remelting by-products

ID No.	Guide No.	Name of Material
3170	138	Aluminum smelting by-products
3171	154	Battery-powered equipment (wet battery)
3171	154	Battery-powered vehicle (wet battery)
3171	154	Wheelchair, electric, with batteries
3172	153	Toxins, extracted from living sources, liquid, n.o.s.
3172	153	Toxins, extracted from living sources, n.o.s.
3172	153	Toxins, extracted from living sources, solid, n.o.s.
3174	135	Titanium disulfide
3174	135	Titanium disulphide
3175	133	Solids containing flammable liquid, n.o.s.
3176	133	Flammable solid, organic, molten, n.o.s.
3178	133	Flammable solid, inorganic, n.o.s.
3178	133	Smokeless powder for small arms
3179	134	Flammable solid, poisonous, inorganic, n.o.s.
3179	134	Flammable solid, toxic, inorganic, n.o.s.
3180	134	Flammable solid, corrosive, inorganic, n.o.s.
3180	134	Flammable solid, inorganic, corrosive, n.o.s.
3181	133	Metal salts of organic compounds, flammable, n.o.s.
3182	170	Metal hydrides, flammable, n.o.s.
3183	135	Self-heating liquid, organic, n.o.s.
3184	136	Self-heating liquid, poisonous, organic, n.o.s.

ID No.	Guide No.	Name of Material
3184	136	Self-heating liquid, toxic, organic, n.o.s.
3185	136	Self-heating liquid, corrosive, organic, n.o.s.
3186	135	Self-heating liquid, inorganic, n.o.s.
3187	136	Self-heating liquid, poisonous, inorganic, n.o.s.
3187	136	Self-heating liquid, toxic, inorganic, n.o.s.
3188	136	Self-heating liquid, corrosive, inorganic, n.o.s.
3189	135	Metal powder, self-heating, n.o.s.
3189	135	Self-heating metal powders, n.o.s.
3190	135	Self-heating solid, inorganic, n.o.s.
3191	136	Self-heating solid, inorganic, poisonous, n.o.s.
3191	136	Self-heating solid, inorganic, toxic, n.o.s.
3191	136	Self-heating solid, poisonous, inorganic, n.o.s.
3191	136	Self-heating solid, toxic, inorganic, n.o.s.
3192	136	Self-heating solid, corrosive, inorganic, n.o.s.
3194	135	Pyrophoric liquid, inorganic, n.o.s.
3200	135	Pyrophoric solid, inorganic, n.o.s.
3203	135	Pyrophoric organometallic compound, n.o.s.
3203	135	Pyrophoric organometallic compound, water-reactive, n.o.s.
3205	135	Alkaline earth metal alcoholates, n.o.s.
3206	136	Alkali metal alcoholates, self-heating, corrosive, n.o.s.

**ID Guide Name of Material**  
**No. No.**

3207	138	Organometallic compound, water-reactive, flammable, n.o.s.
3207	138	Organometallic compound dispersion, water-reactive, flammable, n.o.s.
3207	138	Organometallic compound solution, water-reactive, flammable, n.o.s.
3208	138	Metallic substance, water-reactive, n.o.s.
3209	138	Metallic substance, water-reactive, self-heating, n.o.s.
3210	140	Chlorates, inorganic, aqueous solution, n.o.s.
3211	140	Perchlorates, inorganic, aqueous solution, n.o.s.
3212	140	Hypochlorites, inorganic, n.o.s.
3213	140	Bromates, inorganic, aqueous solution, n.o.s.
3214	140	Permanganates, inorganic, aqueous solution, n.o.s.
3215	140	Persulfates, inorganic, n.o.s.
3215	140	Persulphates, inorganic, n.o.s.
3216	140	Persulfates, inorganic, aqueous solution, n.o.s.
3216	140	Persulphates, inorganic, aqueous solution, n.o.s.
3217	140	Percarbonates, inorganic, n.o.s.
3218	140	Nitrates, inorganic, aqueous solution, n.o.s.
3219	140	Nitrites, inorganic, aqueous solution, n.o.s.
3220	126	Pentafluoroethane
3220	126	Refrigerant gas R-125
3221	149	Self-reactive liquid type B
3222	149	Self-reactive solid type B

**ID Guide Name of Material**  
**No. No.**

3223	149	Self-reactive liquid type C
3224	149	Self-reactive solid type C
3225	149	Self-reactive liquid type D
3226	149	Self-reactive solid type D
3227	149	Self-reactive liquid type E
3228	149	Self-reactive solid type E
3229	149	Self-reactive liquid type F
3230	149	Self-reactive solid type F
3231	150	Self-reactive liquid type B, temperature controlled
3232	150	Self-reactive solid type B, temperature controlled
3233	150	Self-reactive liquid type C, temperature controlled
3234	150	Self-reactive solid type C, temperature controlled
3235	150	Self-reactive liquid type D, temperature controlled
3236	150	Self-reactive solid type D, temperature controlled
3237	150	Self-reactive liquid type E, temperature controlled
3238	150	Self-reactive solid type E, temperature controlled
3239	150	Self-reactive liquid type F, temperature controlled
3240	150	Self-reactive solid type F, temperature controlled
3241	133	2-Bromo-2-nitropropane-1,3-diol
3242	149	Azodicarbonamide
3243	151	Solids containing poisonous liquid, n.o.s.
3243	151	Solids containing toxic liquid, n.o.s.
3244	154	Solids containing corrosive liquid, n.o.s.

ID No.	Guide No.	Name of Material
3245	171	Genetically modified micro-organisms
3245	171	Genetically modified organisms
3246	156	Methanesulfonyl chloride
3246	156	Methanesulphonyl chloride
3247	140	Sodium peroxoborate, anhydrous
3248	131	Medicine, liquid, flammable, poisonous, n.o.s.
3248	131	Medicine, liquid, flammable, toxic, n.o.s.
3249	151	Medicine, solid, poisonous, n.o.s.
3249	151	Medicine, solid, toxic, n.o.s.
3250	153	Chloroacetic acid, molten
3251	133	Isosorbide-5-mononitrate
3252	115	Difluoromethane
3252	115	Refrigerant gas R-32
3253	154	Disodium trioxosilicate
3253	154	Disodium trioxosilicate, pentahydrate
3254	135	Tributylphosphane
3254	135	Tributylphosphine
3255	135	tert-Butyl hypochlorite
3256	128	Elevated temperature liquid, flammable, n.o.s., with flash point above 37.8°C (100°F), at or above its flash point
3256	128	Elevated temperature liquid, flammable, n.o.s., with flash point above 60.5°C (141°F), at or above its flash point
3257	128	Elevated temperature liquid, n.o.s., at or above 100°C (212°F), and below its flash point

ID No.	Guide No.	Name of Material
3258	171	Elevated temperature solid, n.o.s., at or above 240°C (464°F)
3259	154	Amines, solid, corrosive, n.o.s.
3259	154	Polyamines, solid, corrosive, n.o.s.
3260	154	Corrosive solid, acidic, inorganic, n.o.s.
3261	154	Corrosive solid, acidic, organic, n.o.s.
3262	154	Corrosive solid, basic, inorganic, n.o.s.
3263	154	Corrosive solid, basic, organic, n.o.s.
3264	154	Corrosive liquid, acidic, inorganic, n.o.s.
3265	153	Corrosive liquid, acidic, organic, n.o.s.
3266	154	Corrosive liquid, basic, inorganic, n.o.s.
3267	153	Corrosive liquid, basic, organic, n.o.s.
3268	171	Air bag inflators
3268	171	Air bag inflators, pyrotechnic
3268	171	Air bag modules
3268	171	Air bag modules, pyrotechnic
3268	171	Seat-belt modules
3268	171	Seat-belt pre-tensioners
3268	171	Seat-belt pre-tensioners, pyrotechnic
3269	128	Polyester resin kit
3270	133	Nitrocellulose membrane filters
3271	127	Ethers, n.o.s.
3272	127	Esters, n.o.s.
3273	131	Nitriles, flammable, poisonous, n.o.s.

**ID Guide No. No. Name of Material**

3273	131	Nitriles, flammable, toxic, n.o.s.
3274	132	Alcoholates solution, n.o.s., in alcohol
3275	131	Nitriles, poisonous, flammable, n.o.s.
3275	131	Nitriles, toxic, flammable, n.o.s.
3276	151	Nitriles, poisonous, liquid, n.o.s.
3276	151	Nitriles, poisonous, n.o.s.
3276	151	Nitriles, toxic, liquid, n.o.s.
3276	151	Nitriles, toxic, n.o.s.
3277	154	Chloroformates, poisonous, corrosive, n.o.s.
3277	154	Chloroformates, toxic, corrosive, n.o.s.
3278	151	Organophosphorus compound, poisonous, liquid, n.o.s.
3278	151	Organophosphorus compound, poisonous, n.o.s.
3278	151	Organophosphorus compound, toxic, liquid, n.o.s.
3278	151	Organophosphorus compound, toxic, n.o.s.
3279	131	Organophosphorus compound, poisonous, flammable, n.o.s.
3279	131	Organophosphorus compound, toxic, flammable, n.o.s.
3280	151	Organoarsenic compound, liquid, n.o.s.
3280	151	Organoarsenic compound, n.o.s.
3281	151	Metal carbonyls, liquid, n.o.s.
3281	151	Metal carbonyls, n.o.s.
3282	151	Organometallic compound, poisonous, liquid, n.o.s.
3282	151	Organometallic compound, poisonous, n.o.s.

**ID Guide No. No. Name of Material**

3282	151	Organometallic compound, toxic, liquid, n.o.s.
3282	151	Organometallic compound, toxic, n.o.s.
3283	151	Selenium compound, n.o.s.
3283	151	Selenium compound, solid, n.o.s.
3284	151	Tellurium compound, n.o.s.
3285	151	Vanadium compound, n.o.s.
3286	131	Flammable liquid, poisonous, corrosive, n.o.s.
3286	131	Flammable liquid, toxic, corrosive, n.o.s.
3287	151	Poisonous liquid, inorganic, n.o.s.
3287	151	Poisonous liquid, inorganic, n.o.s. (Inhalation Hazard Zone A)
3287	151	Poisonous liquid, inorganic, n.o.s. (Inhalation Hazard Zone B)
3287	151	Toxic liquid, inorganic, n.o.s.
3287	151	Toxic liquid, inorganic, n.o.s. (Inhalation Hazard Zone A)
3287	151	Toxic liquid, inorganic, n.o.s. (Inhalation Hazard Zone B)
3288	151	Poisonous solid, inorganic, n.o.s.
3288	151	Toxic solid, inorganic, n.o.s.
3289	154	Poisonous liquid, corrosive, inorganic, n.o.s.
3289	154	Poisonous liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone A)
3289	154	Poisonous liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone B)

ID No.	Guide No.	Name of Material
3289	154	Toxic liquid, corrosive, inorganic, n.o.s.
3289	154	Toxic liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone A)
3289	154	Toxic liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone B)
3290	154	Poisonous solid, corrosive, inorganic, n.o.s.
3290	154	Toxic solid, corrosive, inorganic, n.o.s.
3291	158	(Bio)Medical waste, n.o.s.
3291	158	Clinical waste, unspecified, n.o.s.
3291	158	Medical waste, n.o.s.
3291	158	Regulated medical waste, n.o.s.
3292	138	Batteries, containing Sodium
3292	138	Cells, containing Sodium
3293	152	Hydrazine, aqueous solution, with not more than 37% Hydrazine
3294	131	Hydrogen cyanide, solution in alcohol, with not more than 45% Hydrogen cyanide
3295	128	Hydrocarbons, liquid, n.o.s.
3296	126	Heptafluoropropane
3296	126	Refrigerant gas R-227
3297	126	Chlorotetrafluoroethane and Ethylene oxide mixture, with not more than 8.8% Ethylene oxide
3297	126	Ethylene oxide and Chlorotetrafluoroethane mixture, with not more than 8.8% Ethylene oxide

ID No.	Guide No.	Name of Material
3298	126	Ethylene oxide and Pentafluoroethane mixture, with not more than 7.9% Ethylene oxide
3298	126	Pentafluoroethane and Ethylene oxide mixture, with not more than 7.9% Ethylene oxide
3299	126	Ethylene oxide and Tetrafluoroethane mixture, with not more than 5.6% Ethylene oxide
3299	126	Tetrafluoroethane and Ethylene oxide mixture, with not more than 5.6% Ethylene oxide
3300	119P	Carbon dioxide and Ethylene oxide mixture, with more than 87% Ethylene oxide
3300	119P	Ethylene oxide and Carbon dioxide mixture, with more than 87% Ethylene oxide
3301	136	Corrosive liquid, self-heating, n.o.s.
3302	152	2-Dimethylaminoethyl acrylate
3303	124	Compressed gas, poisonous, oxidizing, n.o.s.
3303	124	Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone A)
3303	124	Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone B)
3303	124	Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone C)
3303	124	Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone D)
3303	124	Compressed gas, toxic, oxidizing, n.o.s.

**ID Guide No. No. Name of Material**

3303 124 Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone A)

3303 124 Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone B)

3303 124 Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone C)

3303 124 Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone D)

3304 123 Compressed gas, poisonous, corrosive, n.o.s.

3304 123 Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone A)

3304 123 Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone B)

3304 123 Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone C)

3304 123 Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone D)

3304 123 Compressed gas, toxic, corrosive, n.o.s.

3304 123 Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone A)

3304 123 Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone B)

3304 123 Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone C)

3304 123 Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone D)

**ID Guide No. No. Name of Material**

3305 119 Compressed gas, poisonous, flammable, corrosive, n.o.s.

3305 119 Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)

3305 119 Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)

3305 119 Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)

3305 119 Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)

3305 119 Compressed gas, toxic, flammable, corrosive, n.o.s.

3305 119 Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)

3305 119 Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)

3305 119 Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)

3305 119 Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)

3306 124 Compressed gas, poisonous, oxidizing, corrosive, n.o.s.

3306 124 Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)

3306 124 Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone B)

3306 124 Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)



**ID Guide Name of Material**  
**No. No.**

3306 124 Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)

3306 124 Compressed gas, toxic, oxidizing, corrosive, n.o.s.

3306 124 Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)

3306 124 Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone B)

3306 124 Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)

3306 124 Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)

3307 124 Liquefied gas, poisonous, oxidizing, n.o.s.

3307 124 Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone A)

3307 124 Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone B)

3307 124 Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone C)

3307 124 Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone D)

3307 124 Liquefied gas, toxic, oxidizing, n.o.s.

3307 124 Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone A)

3307 124 Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone B)

**ID Guide Name of Material**  
**No. No.**

3307 124 Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone C)

3307 124 Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone D)

3308 123 Liquefied gas, poisonous, corrosive, n.o.s.

3308 123 Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone A)

3308 123 Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone B)

3308 123 Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone C)

3308 123 Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone D)

3308 123 Liquefied gas, toxic, corrosive, n.o.s.

3308 123 Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone A)

3308 123 Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone B)

3308 123 Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone C)

3308 123 Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone D)

3309 119 Liquefied gas, poisonous, flammable, corrosive, n.o.s.

3309 119 Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)

**ID Guide No. No. Name of Material**

3309	119	Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)
3309	119	Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)
3309	119	Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)
3309	119	Liquefied gas, toxic, flammable, corrosive, n.o.s.
3309	119	Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)
3309	119	Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)
3309	119	Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)
3309	119	Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)
3310	124	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s.
3310	124	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)
3310	124	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone B)
3310	124	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)
3310	124	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)
3310	124	Liquefied gas, toxic, oxidizing, corrosive, n.o.s.

**ID Guide No. No. Name of Material**

3310	124	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)
3310	124	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone B)
3310	124	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)
3310	124	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)
3311	122	Gas, refrigerated liquid, oxidizing, n.o.s.
3312	115	Gas, refrigerated liquid, flammable, n.o.s.
3313	135	Organic pigments, self-heating
3314	171	Plastic molding compound
3314	171	Plastics moulding compound
3315	151	Chemical sample, poisonous
3315	151	Chemical sample, poisonous liquid
3315	151	Chemical sample, poisonous solid
3315	151	Chemical sample, toxic
3315	151	Chemical sample, toxic liquid
3315	151	Chemical sample, toxic solid
3316	171	Chemical kit
3316	171	First aid kit
3317	113	2-Amino-4,6-dinitrophenol, wetted with not less than 20% water
3318	125	Ammonia solution, with more than 50% Ammonia
3319	113	Nitroglycerin mixture, desensitized, solid, n.o.s., with more than 2% but not more than 10% Nitroglycerin

ID No.	Guide No.	Name of Material	ID No.	Guide No.	Name of Material
3319	113	Nitroglycerin mixture with more than 2% but not more than 10% Nitroglycerin, desensitized	3332	164	Radioactive material, Type A package, special form, non fissile or fissile-excepted
3320	157	Sodium borohydride and Sodium hydroxide solution, with not more than 12% Sodium borohydride and not more than 40% Sodium hydroxide	3333	165	Radioactive material, Type A package, special form, fissile
3321	162	Radioactive material, low specific activity (LSA-II) non fissile or fissile-excepted	3334	171	Aviation regulated liquid, n.o.s.
3322	162	Radioactive material, low specific activity (LSA-III) non fissile or fissile-excepted	3334	171	Self-defense spray, non-pressurized
3323	163	Radioactive material, Type C package	3335	171	Aviation regulated solid, n.o.s.
3324	165	Radioactive material, low specific activity (LSA-II), fissile	3336	130	Mercaptan mixture, liquid, flammable, n.o.s.
3325	165	Radioactive material, low specific activity (LSA-III), fissile	3336	130	Mercaptans, liquid, flammable, n.o.s.
3326	165	Radioactive material, surface contaminated objects (SCO-I), fissile	3337	126	Refrigerant gas R-404A
3326	165	Radioactive material, surface contaminated objects (SCO-II), fissile	3338	126	Refrigerant gas R-407A
3327	165	Radioactive material, Type A package, fissile, non-special form	3339	126	Refrigerant gas R-407B
3328	165	Radioactive material, Type B(U) package, fissile	3340	126	Refrigerant gas R-407C
3329	165	Radioactive material, Type B(M) package, fissile	3341	135	Thiourea dioxide
3330	165	Radioactive material, Type C package, fissile	3342	135	Xanthates
3331	165	Radioactive material, transported under special arrangement, fissile	3343	113	Nitroglycerin mixture, desensitized, liquid, flammable, n.o.s., with not more than 30% Nitroglycerin
			3344	113	Pentaerythrite tetranitrate mixture, desensitized, solid, n.o.s., with more than 10% but not more than 20% PETN
			3344	113	Pentaerythritol tetranitrate mixture, desensitized, solid, n.o.s., with more than 10% but not more than 20% PETN
			3344	113	PETN mixture, desensitized, solid, n.o.s., with more than 10% but not more than 20% PETN
			3345	153	Phenoxyacetic acid derivative pesticide, solid, poisonous

**ID Guide Name of Material**  
**No. No.**

3345	153	Phenoxyacetic acid derivative pesticide, solid, toxic
3346	131	Phenoxyacetic acid derivative pesticide, liquid, flammable, poisonous
3346	131	Phenoxyacetic acid derivative pesticide, liquid, flammable, toxic
3347	131	Phenoxyacetic acid derivative pesticide, liquid, poisonous, flammable
3347	131	Phenoxyacetic acid derivative pesticide, liquid, toxic, flammable
3348	153	Phenoxyacetic acid derivative pesticide, liquid, poisonous
3348	153	Phenoxyacetic acid derivative pesticide, liquid, toxic
3349	151	Pyrethroid pesticide, solid, poisonous
3349	151	Pyrethroid pesticide, solid, toxic
3350	131	Pyrethroid pesticide, liquid, flammable, poisonous
3350	131	Pyrethroid pesticide, liquid, flammable, toxic
3351	131	Pyrethroid pesticide, liquid, poisonous, flammable
3351	131	Pyrethroid pesticide, liquid, toxic, flammable
3352	151	Pyrethroid pesticide, liquid, poisonous
3352	151	Pyrethroid pesticide, liquid, toxic
3353	126	Air bag inflators, compressed gas
3353	126	Air bag modules, compressed gas
3353	126	Seat-belt pre-tensioners, compressed gas
3354	115	Insecticide gas, flammable, n.o.s.

**ID Guide Name of Material**  
**No. No.**

3355	119	Insecticide gas, poisonous, flammable, n.o.s.
3355	119	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)
3355	119	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone B)
3355	119	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)
3355	119	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone D)
3355	119	Insecticide gas, toxic, flammable, n.o.s.
3355	119	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone A)
3355	119	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone B)
3355	119	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone C)
3355	119	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone D)
3356	140	Oxygen generator, chemical
3356	140	Oxygen generator, chemical, spent
3357	113	Nitroglycerin mixture, desensitized, liquid, n.o.s., with not more than 30% Nitroglycerin
3358	115	Refrigerating machines, containing flammable, non-poisonous, liquefied gases

ID No.	Guide No.	Name of Material
3358	115	Refrigerating machines, containing flammable, non-toxic, liquefied gases
3359	171	Fumigated unit
3360	133	Fibers, vegetable, dry
3360	133	Fibres, vegetable, dry
3361	156	Chlorosilanes, poisonous, corrosive, n.o.s.
3361	156	Chlorosilanes, toxic, corrosive, n.o.s.
3362	155	Chlorosilanes, poisonous, corrosive, flammable, n.o.s.
3362	155	Chlorosilanes, toxic, corrosive, flammable, n.o.s.
3363	171	Dangerous goods in apparatus
3363	171	Dangerous goods in machinery
3364	113	Picric acid, wetted with not less than 10% water
3364	113	Trinitrophenol, wetted with not less than 10% water
3365	113	Picryl chloride, wetted with not less than 10% water
3365	113	Trinitrochlorobenzene, wetted with not less than 10% water
3366	113	TNT, wetted with not less than 10% water
3366	113	Trinitrotoluene, wetted with not less than 10% water
3367	113	Trinitrobenzene, wetted with not less than 10% water
3368	113	Trinitrobenzoic acid, wetted with not less than 10% water
3369	113	Sodium dinitro-o-cresolate, wetted with not less than 10% water
3370	113	Urea nitrate, wetted with not less than 10% water

ID No.	Guide No.	Name of Material
3371	129	2-Methylbutanal
3372	138	Organometallic compound, solid, water-reactive, flammable, n.o.s.
3373	158	Biological substance, category B
3373	158	Clinical specimens
3373	158	Diagnostic specimens
3374	116	Acetylene, solvent free
3375	140	Ammonium nitrate emulsion
3375	140	Ammonium nitrate gel
3375	140	Ammonium nitrate suspension
3376	113	4-Nitrophenylhydrazine, with not less than 30% water
3377	140	Sodium perborate monohydrate
3378	140	Sodium carbonate peroxyhydrate
3379	128	Desensitized explosive, liquid, n.o.s.
3380	133	Desensitized explosive, solid, n.o.s.
3381	151	Poisonous by inhalation liquid, n.o.s. (Inhalation Hazard Zone A)
3381	151	Toxic by inhalation liquid, n.o.s. (Inhalation Hazard Zone A)
3382	151	Poisonous by inhalation liquid, n.o.s. (Inhalation Hazard Zone B)
3382	151	Toxic by inhalation liquid, n.o.s. (Inhalation Hazard Zone B)
3383	131	Poisonous by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone A)
3383	131	Toxic by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone A)

**ID Guide Name of Material**  
**No. No.**

3384	131	Poisonous by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone B)
3384	131	Toxic by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone B)
3385	139	Poisonous by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)
3385	139	Toxic by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)
3386	139	Poisonous by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)
3386	139	Toxic by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)
3387	142	Poisonous by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)
3387	142	Toxic by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)
3388	142	Poisonous by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)
3388	142	Toxic by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)
3389	154	Poisonous by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)
3389	154	Toxic by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)
3390	154	Poisonous by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)

**ID Guide Name of Material**  
**No. No.**

3390	154	Toxic by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)
3391	135	Organometallic substance, solid, pyrophoric
3392	135	Organometallic substance, liquid, pyrophoric
3393	135	Organometallic substance, solid, pyrophoric, water-reactive
3394	135	Organometallic substance, liquid, pyrophoric, water-reactive
3395	135	Organometallic substance, solid, water-reactive
3396	138	Organometallic substance, solid, water-reactive, flammable
3397	138	Organometallic substance, solid, water-reactive, self-heating
3398	135	Organometallic substance, liquid, water-reactive
3399	138	Organometallic substance, liquid, water-reactive, flammable
3400	138	Organometallic substance, solid, self-heating
3401	138	Alkali metal amalgam, solid
3402	138	Alkaline earth metal amalgam, solid
3403	138	Potassium, metal alloys, solid
3404	138	Potassium sodium alloys, solid
3404	138	Sodium potassium alloys, solid
3405	141	Barium chlorate, solution
3406	141	Barium perchlorate, solution
3407	140	Chlorate and Magnesium chloride mixture, solution

ID No.	Guide No.	Name of Material
3407	140	Magnesium chloride and Chlorate mixture, solution
3408	141	Lead perchlorate, solution
3409	152	Chloronitrobenzenes, liquid
3410	153	4-Chloro-o-toluidine hydrochloride, solution
3411	153	beta-Naphthylamine, solution
3411	153	Naphthylamine (beta), solution
3412	153	Formic acid, with not less than 5% but less than 10% acid
3412	153	Formic acid, with not less than 10% but not more than 85% acid
3413	157	Potassium cyanide, solution
3414	157	Sodium cyanide, solution
3415	154	Sodium fluoride, solution
3416	153	Chloroacetophenone, liquid
3417	152	Xylyl bromide, solid
3418	151	2,4-Toluylenediamine, solution
3419	157	Boron trifluoride acetic acid complex, solid
3420	157	Boron trifluoride propionic acid complex, solid
3421	154	Potassium hydrogen difluoride, solution
3422	154	Potassium fluoride, solution
3423	153	Tetramethylammonium hydroxide, solid
3424	141	Ammonium dinitro-o-cresolate, solution
3425	156	Bromoacetic acid, solid
3426	153P	Acrylamide, solution
3427	153	Chlorobenzyl chlorides, solid
3428	156	3-Chloro-4-methylphenyl isocyanate, solid
3429	153	Chlorotoluidines, liquid

ID No.	Guide No.	Name of Material
3430	153	Xylenols, liquid
3431	152	Nitrobenzotrifluorides, solid
3432	171	Polychlorinated biphenyls, solid
3433	135	Lithium alkyls, solid
3434	153	Nitrocresols, liquid
3435	153	Hydroquinone, solution
3436	151	Hexafluoroacetone hydrate, solid
3437	152	Chlorocresols, solid
3438	153	alpha-Methylbenzyl alcohol, solid
3439	151	Nitriles, poisonous, solid, n.o.s.
3439	151	Nitriles, toxic, solid, n.o.s.
3440	151	Selenium compound, liquid, n.o.s.
3441	153	Chlorodinitrobenzenes, solid
3442	153	Dichloroanilines, solid
3443	152	Dinitrobenzenes, solid
3444	151	Nicotine hydrochloride, solid
3445	151	Nicotine sulfate, solid
3445	151	Nicotine sulphate, solid
3446	152	Nitrotoluenes, solid
3447	152	Nitroxylenes, solid
3448	159	Tear gas substance, solid, n.o.s.
3449	159	Bromobenzyl cyanides, solid
3450	151	Diphenylchloroarsine, solid
3451	153	Toluidines, solid
3452	153	Xylidines, solid
3453	154	Phosphoric acid, solid
3454	152	Dinitrotoluenes, solid
3455	153	Cresols, solid
3456	157	Nitrosylsulfuric acid, solid
3456	157	Nitrosylsulphuric acid, solid

**ID Guide**  
**No. No.**

3457 **152** Chloronitrotoluenes, solid  
3458 **152** Nitroanisoles, solid  
3459 **152** Nitrobromobenzenes, solid  
3460 **153** N-Ethylbenzyltoluidines, solid  
3461 **135** Aluminum alkyl halides, solid  
3462 **153** Toxins, extracted from living sources, solid, n.o.s.  
3463 **132** Propionic acid, with not less than 90% acid  
3464 **151** Organophosphorus compound, poisonous, solid, n.o.s.  
3464 **151** Organophosphorus compound, toxic, solid, n.o.s.  
3465 **151** Organoarsenic compound, solid, n.o.s.  
3466 **151** Metal carbonyls, solid, n.o.s.  
3467 **151** Organometallic compound, poisonous, solid, n.o.s.  
3467 **151** Organometallic compound, toxic, solid, n.o.s.  
3468 **115** Hydrogen in a metal hydride storage system  
3468 **115** Hydrogen in a metal hydride storage system contained in equipment  
3468 **115** Hydrogen in a metal hydride storage system packed with equipment  
3469 **132** Paint, flammable, corrosive  
3469 **132** Paint related material, flammable, corrosive  
3470 **132** Paint, corrosive, flammable  
3470 **132** Paint related material, corrosive, flammable  
3471 **154** Hydrogendifluorides, solution, n.o.s.

**ID Guide**  
**No. No.**

3472 **153** Crotonic acid, liquid  
3473 **128** Fuel cell cartridges contained in equipment, containing flammable liquids  
3473 **128** Fuel cell cartridges containing flammable liquids  
3473 **128** Fuel cell cartridges packed with equipment, containing flammable liquids  
3474 **113** 1-Hydroxybenzotriazole, anhydrous, wetted with not less than 20% water  
3475 **127** Ethanol and gasoline mixture, with more than 10% ethanol  
3475 **127** Ethanol and motor spirit mixture, with more than 10% ethanol  
3475 **127** Ethanol and petrol mixture, with more than 10% ethanol  
3475 **127** Gasoline and ethanol mixture, with more than 10% ethanol  
3475 **127** Motor spirit and ethanol mixture, with more than 10% ethanol  
3475 **127** Petrol and ethanol mixture, with more than 10% ethanol  
3476 **138** Fuel cell cartridges contained in equipment, containing water-reactive substances  
3476 **138** Fuel cell cartridges, containing water-reactive substances  
3476 **138** Fuel cell cartridges packed with equipment, containing water-reactive substances  
3477 **153** Fuel cell cartridges contained in equipment, containing corrosive substances  
3477 **153** Fuel cell cartridges, containing corrosive substances



<b>ID No.</b>	<b>Guide No.</b>	<b>Name of Material</b>
3477	153	Fuel cell cartridges packed with equipment, containing corrosive substances
3478	115	Fuel cell cartridges contained in equipment, containing liquefied flammable gas
3478	115	Fuel cell cartridges, containing liquefied flammable gas
3478	115	Fuel cell cartridges packed with equipment, containing liquefied flammable gas
3479	115	Fuel cell cartridges contained in equipment, containing hydrogen in metal hydride
3479	115	Fuel cell cartridges, containing hydrogen in metal hydride
3479	115	Fuel cell cartridges packed with equipment, containing hydrogen in metal hydride
3480	147	Lithium ion batteries (including lithium ion polymer batteries)
3481	147	Lithium ion batteries contained in equipment (including lithium ion polymer batteries)
3481	147	Lithium ion batteries packed with equipment (including lithium ion polymer batteries)
8000	171	Consumer commodity
8013	171	Gas generator assemblies
8038	171	Heat producing article
9035	123	Gas identification set
9163	171	Zirconium sulfate
9163	171	Zirconium sulphate
9191	143	Chlorine dioxide, hydrate, frozen
9192	167	Fluorine, refrigerated liquid (cryogenic liquid)
9195	135	Metal alkyl, solution, n.o.s.

<b>ID No.</b>	<b>Guide No.</b>	<b>Name of Material</b>
9202	168	Carbon monoxide, refrigerated liquid (cryogenic liquid)
9206	137	Methyl phosphonic dichloride
9260	169	Aluminum, molten
9263	156	Chloropivaloyl chloride
9264	151	3,5-Dichloro-2,4,6-trifluoropyridine
9269	132	Trimethoxysilane
9279	115	Hydrogen absorbed in metal hydride

**Note:** If an entry is highlighted in green in either the yellow-bordered or blue-bordered pages AND THERE IS NO FIRE, go directly to Table 1 - Initial Isolation and Protective Action Distances (green bordered pages) and look up the ID number and name of material to obtain initial isolation and protective action distances. IF THERE IS A FIRE, or IF A FIRE IS INVOLVED, ALSO CONSULT the assigned guide (orange-bordered pages) and apply as appropriate the evacuation information shown under PUBLIC SAFETY. Please remember that, if the name in Table 1 is shown with (when spilled in water), and the material has not been spilled in water, Table 1 does not apply and safety distances can be found within the appropriate guide.

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
AC	117	1051	Acrylamide	153P	2074
Accumulators, pressurized, pneumatic or hydraulic	126	1956	Acrylamide, solid	153P	2074
Acetal	127	1088	Acrylamide, solution	153P	3426
Acetaldehyde	129	1089	Acrylic acid, stabilized	132P	2218
Acetaldehyde ammonia	171	1841	Acrylonitrile, stabilized	131P	1093
Acetaldehyde oxime	129	2332	Adamsite	154	1698
Acetic acid, glacial	132	2789	Adhesives (flammable)	128	1133
Acetic acid, solution, more than 10% but not more than 80% acid	153	2790	Adiponitrile	153	2205
Acetic acid, solution, more than 80% acid	132	2789	Aerosol dispensers	126	1950
Acetic anhydride	137	1715	Aerosols	126	1950
Acetone	127	1090	Air, compressed	122	1002
Acetone cyanohydrin, stabilized	155	1541	Air, refrigerated liquid (cryogenic liquid)	122	1003
Acetone oils	127	1091	Air, refrigerated liquid (cryogenic liquid), non-pressurized	122	1003
Acetonitrile	127	1648	Air bag inflators	171	3268
Acetyl bromide	156	1716	Air bag inflators, compressed gas	126	3353
Acetyl chloride	155	1717	Air bag inflators, pyrotechnic	171	3268
Acetylene	116	1001	Air bag modules	171	3268
Acetylene, dissolved	116	1001	Air bag modules, compressed gas	126	3353
Acetylene, solvent free	116	3374	Air bag modules, pyrotechnic	171	3268
Acetylene, Ethylene and Propylene in mixture, refrigerated liquid containing at least 71.5% Ethylene with not more than 22.5% Acetylene and not more than 6% Propylene	115	3138	Aircraft hydraulic power unit fuel tank	131	3165
Acetylene tetrabromide	159	2504	Alcoholates solution, n.o.s., in alcohol	132	3274
Acetyl iodide	156	1898	Alcoholic beverages	127	3065
Acetyl methyl carbinol	127	2621	Alcohols, flammable, poisonous, n.o.s.	131	1986
Acid, sludge	153	1906	Alcohols, flammable, toxic, n.o.s.	131	1986
Acid butyl phosphate	153	1718	Alcohols, n.o.s.	127	1987
Acridine	153	2713	Alcohols, poisonous, n.o.s.	131	1986
Acrolein, stabilized	131P	1092	Alcohols, toxic, n.o.s.	131	1986
Acrolein dimer, stabilized	129P	2607	Aldehydes, flammable, poisonous, n.o.s.	131	1988

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Aldehydes, flammable, toxic, n.o.s.	131	1988	Alkylamines, n.o.s.	132	2734
Aldehydes, n.o.s.	129	1989	Alkylamines, n.o.s.	153	2735
Aldehydes, poisonous, n.o.s.	131	1988	Alkyl phenols, liquid, n.o.s. (including C2-C12 homologues)	153	3145
Aldehydes, toxic, n.o.s.	131	1988	Alkyl phenols, solid, n.o.s. (including C2-C12 homologues)	153	2430
Aldol	153	2839	Alkyl sulfonic acids, liquid, with more than 5% free Sulfuric acid	153	2584
Aldrin, liquid	131	2762	Alkyl sulfonic acids, liquid, with not more than 5% free Sulfuric acid	153	2586
Aldrin, solid	151	2761	Alkyl sulfonic acids, solid, with more than 5% free Sulfuric acid	153	2583
Alkali metal alcoholates, self-heating, corrosive, n.o.s.	136	3206	Alkyl sulfonic acids, solid, with not more than 5% free Sulfuric acid	153	2585
Alkali metal alloy, liquid, n.o.s.	138	1421	Alkylsulfuric acids	156	2571
Alkali metal amalgam	138	1389	Alkyl sulphonic acids, liquid, with more than 5% free Sulphuric acid	153	2584
Alkali metal amalgam, liquid	138	1389	Alkyl sulphonic acids, liquid, with not more than 5% free Sulphuric acid	153	2586
Alkali metal amalgam, solid	138	1389	Alkyl sulphonic acids, solid, with more than 5% free Sulphuric acid	153	2583
Alkali metal amalgam, solid	138	3401	Alkyl sulphonic acids, solid, with not more than 5% free Sulphuric acid	153	2585
Alkali metal amides	139	1390	Alkyl sulphonic acids, solid, with more than 5% free Sulphuric acid	153	2584
Alkali metal dispersion	138	1391	Alkyl sulphonic acids, solid, with not more than 5% free Sulphuric acid	153	2586
Alkaline earth metal alcoholates, n.o.s.	135	3205	Alkylsulphuric acids	156	2571
Alkaline earth metal alloy, n.o.s.	138	1393	Allyl acetate	131	2333
Alkaline earth metal amalgam	138	1392	Allyl alcohol	131	1098
Alkaline earth metal amalgam, liquid	138	1392	Allylamine	131	2334
Alkaline earth metal amalgam, solid	138	3402	Allyl bromide	131	1099
Alkaline earth metal dispersion	138	1391			
Alkaloids, liquid, n.o.s. (poisonous)	151	3140			
Alkaloids, solid, n.o.s. (poisonous)	151	1544			
Alkaloid salts, liquid, n.o.s. (poisonous)	151	3140			
Alkaloid salts, solid, n.o.s. (poisonous)	151	1544			
Alkylamines, n.o.s.	132	2733			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Allyl chloride	131	1100	Aluminum processing by-products	138	3170
Allyl chlorocarbonate	155	1722	Aluminum remelting by-products	138	3170
Allyl chloroformate	155	1722	Aluminum resinate	133	2715
Allyl ethyl ether	131	2335	Aluminum silicon powder, uncoated	138	1398
Allyl formate	131	2336	Aluminum smelting by-products	138	3170
Allyl glycidyl ether	129	2219	Amines, flammable, corrosive, n.o.s.	132	2733
Allyl iodide	132	1723	Amines, liquid, corrosive, flammable, n.o.s.	132	2734
Allyl isothiocyanate, stabilized	155	1545	Amines, liquid, corrosive, n.o.s.	153	2735
Allyltrichlorosilane, stabilized	155	1724	Amines, solid, corrosive, n.o.s.	154	3259
Aluminum, molten	169	9260	2-Amino-4-chlorophenol	151	2673
Aluminum alkyl halides	135	3052	2-Amino-5-diethylaminopentane	153	2946
Aluminum alkyl halides, liquid	135	3052	2-Amino-4,6-dinitrophenol, wetted with not less than 20% water	113	3317
Aluminum alkyl halides, solid	135	3052	2-(2-Aminoethoxy)ethanol	154	3055
Aluminum alkyl halides, solid	135	3461	N-Aminoethylpiperazine	153	2815
Aluminum alkyl hydrides	138	3076	Aminophenols	152	2512
Aluminum alkyls	135	3051	Aminopyridines	153	2671
Aluminum borohydride	135	2870	Ammonia, anhydrous	125	1005
Aluminum borohydride in devices	135	2870	Ammonia, solution, with more than 10% but not more than 35% Ammonia	154	2672
Aluminum bromide, anhydrous	137	1725	Ammonia, solution, with more than 35% but not more than 50% Ammonia	125	2073
Aluminum bromide, solution	154	2580	Ammonia solution, with more than 50% Ammonia	125	3318
Aluminum carbide	138	1394	Ammonium arsenate	151	1546
Aluminum chloride, anhydrous	137	1726	Ammonium bifluoride, solid	154	1727
Aluminum chloride, solution	154	2581	Ammonium bifluoride, solution	154	2817
Aluminum dross	138	3170	Ammonium dichromate	141	1439
Aluminum ferrosilicon powder	139	1395	Ammonium dinitro-o-cresolate	141	1843
Aluminum hydride	138	2463			
Aluminum nitrate	140	1438			
Aluminum phosphide	139	1397			
Aluminum phosphide pesticide	157	3048			
Aluminum powder, coated	170	1309			
Aluminum powder, pyrophoric	135	1383			
Aluminum powder, uncoated	138	1396			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Ammonium dinitro-o-cresolate, solid	141	1843	Ammonium nitrate fertilizers, with Ammonium sulphate	140	2069
Ammonium dinitro-o-cresolate, solution	141	3424	Ammonium nitrate fertilizers, with Calcium carbonate	140	2068
Ammonium fluoride	154	2505	Ammonium nitrate fertilizers, with Phosphate or Potash	143	2070
Ammonium fluorosilicate	151	2854	Ammonium nitrate-fuel oil mixtures	112	—
Ammonium hydrogendifluoride, solid	154	1727	Ammonium nitrate gel	140	3375
Ammonium hydrogendifluoride, solution	154	2817	Ammonium nitrate mixed fertilizers	140	2069
Ammonium hydrogen fluoride, solid	154	1727	Ammonium nitrate suspension	140	3375
Ammonium hydrogen fluoride, solution	154	2817	Ammonium perchlorate	143	1442
Ammonium hydrogen sulfate	154	2506	Ammonium persulfate	140	1444
Ammonium hydrogen sulphate	154	2506	Ammonium persulphate	140	1444
Ammonium hydroxide	154	2672	Ammonium picrate, wetted with not less than 10% water	113	1310
Ammonium hydroxide, with more than 10% but not more than 35% Ammonia	154	2672	Ammonium polysulfide, solution	154	2818
Ammonium metavanadate	154	2859	Ammonium polysulphide, solution	154	2818
Ammonium nitrate, liquid (hot concentrated solution)	140	2426	Ammonium polyvanadate	151	2861
Ammonium nitrate, with not more than 0.2% combustible substances	140	1942	Ammonium silicofluoride	151	2854
Ammonium nitrate emulsion	140	3375	Ammonium sulfide, solution	132	2683
Ammonium nitrate fertilizer, n.o.s.	140	2072	Ammonium sulphide, solution	132	2683
Ammonium nitrate fertilizer, with not more than 0.4% combustible material	140	2071	Ammunition, poisonous, non-explosive	151	2016
Ammonium nitrate fertilizers	140	2067	Ammunition, tear-producing, non-explosive	159	2017
Ammonium nitrate fertilizers	140	2071	Ammunition, toxic, non-explosive	151	2016
Ammonium nitrate fertilizers	140	2072	Amyl acetates	129	1104
Ammonium nitrate fertilizers, with Ammonium sulfate	140	2069	Amyl acid phosphate	153	2819
			Amyl alcohols	129	1105
			Amylamines	132	1106
			Amyl butyrates	130	2620
			Amyl chloride	129	1107

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
n-Amylene	128	1108	Antimony trichloride, solution	157	1733
Amyl formates	129	1109	Antimony trifluoride, solid	157	1549
Amyl mercaptan	130	1111	Antimony trifluoride, solution	157	1549
n-Amyl methyl ketone	127	1110	Aqua regia	157	1798
Amyl methyl ketone	127	1110	Argon	121	1006
Amyl nitrate	140	1112	Argon, compressed	121	1006
Amyl nitrite	129	1113	Argon, refrigerated liquid (cryogenic liquid)	120	1951
Amyltrimethylsilane	155	1728	Arsenic	152	1558
Anhydrous ammonia	125	1005	Arsenic acid, liquid	154	1553
Aniline	153	1547	Arsenic acid, solid	154	1554
Aniline hydrochloride	153	1548	Arsenical dust	152	1562
Anisidines	153	2431	Arsenical pesticide, liquid, flammable, poisonous	131	2760
Anisidines, liquid	153	2431	Arsenical pesticide, liquid, flammable, toxic	131	2760
Anisidines, solid	153	2431	Arsenical pesticide, liquid, poisonous	151	2994
Anisole	128	2222	Arsenical pesticide, liquid, poisonous, flammable	131	2993
Anisoyl chloride	156	1729	Arsenical pesticide, liquid, toxic	151	2994
Antimony compound, inorganic, liquid, n.o.s.	157	3141	Arsenical pesticide, liquid, toxic, flammable	131	2993
Antimony compound, inorganic, n.o.s.	157	1549	Arsenical pesticide, solid, poisonous	151	2759
Antimony compound, inorganic, solid, n.o.s.	157	1549	Arsenical pesticide, solid, toxic	151	2759
Antimony lactate	151	1550	Arsenic bromide	151	1555
Antimony pentachloride, liquid	157	1730	Arsenic chloride	157	1560
Antimony pentachloride, solution	157	1731	Arsenic compound, liquid, n.o.s.	152	1556
Antimony pentafluoride	157	1732	Arsenic compound, liquid, n.o.s., inorganic	152	1556
Antimony potassium tartrate	151	1551	Arsenic compound, solid, n.o.s.	152	1557
Antimony powder	170	2871	Arsenic compound, solid, n.o.s., inorganic	152	1557
Antimony tribromide, solid	157	1549	Arsenic pentoxide	151	1559
Antimony tribromide, solution	157	1549	Arsenic sulfide	152	1557
Antimony trichloride	157	1733			
Antimony trichloride, liquid	157	1733			
Antimony trichloride, solid	157	1733			

Name of Material	Guide ID No.	ID No.	Name of Material	Guide ID No.	ID No.
Arsenic sulphide	152	1557	Asbestos	171	2212
Arsenic trichloride	157	1560	Asbestos, blue	171	2212
Arsenic trioxide	151	1561	Asbestos, brown	171	2212
Arsenic trisulfide	152	1557	Asbestos, white	171	2590
Arsenic trisulphide	152	1557	Asphalt	130	1999
Arsine	119	2188	Aviation regulated liquid, n.o.s.	171	3334
Articles containing Polychlorinated biphenyls (PCB)	171	2315	Aviation regulated solid, n.o.s.	171	3335
Articles, pressurized, hydraulic (containing non-flammable gas)	126	3164	1-Aziridinyl phosphine oxide (Tris)	152	2501
Articles, pressurized, pneumatic (containing non-flammable gas)	126	3164	Azodicarbonamide	149	3242
Aryl sulfonic acids, liquid, with more than 5% free Sulfuric acid	153	2584	Barium	138	1400
Aryl sulfonic acids, liquid, with not more than 5% free Sulfuric acid	153	2586	Barium alloys, pyrophoric	135	1854
Aryl sulfonic acids, solid, with more than 5% free Sulfuric acid	153	2583	Barium azide, wetted with not less than 50% water	113	1571
Aryl sulfonic acids, solid, with not more than 5% free Sulfuric acid	153	2585	Barium bromate	141	2719
Aryl sulphonic acids, liquid, with more than 5% free Sulphuric acid	153	2584	Barium chlorate	141	1445
Aryl sulphonic acids, liquid, with not more than 5% free Sulphuric acid	153	2586	Barium chlorate, solid	141	1445
Aryl sulphonic acids, solid, with more than 5% free Sulphuric acid	153	2583	Barium chlorate, solution	141	3405
Aryl sulphonic acids, solid, with not more than 5% free Sulphuric acid	153	2585	Barium compound, n.o.s.	154	1564
			Barium cyanide	157	1565
			Barium hypochlorite, with more than 22% available Chlorine	141	2741
			Barium nitrate	141	1446
			Barium oxide	157	1884
			Barium perchlorate	141	1447
			Barium perchlorate, solid	141	1447
			Barium perchlorate, solution	141	3406
			Barium permanganate	141	1448
			Barium peroxide	141	1449
			Batteries, containing Sodium	138	3292
			Batteries, dry, containing Potassium hydroxide solid	154	3028
			Batteries, wet, filled with acid	154	2794
			Batteries, wet, filled with alkali	154	2795



Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Batteries, wet, non-spillable	154	2800	Benzoquinone	153	2587
Battery fluid, acid	157	2796	Benzotrichloride	156	2226
Battery fluid, alkali	154	2797	Benzotrifluoride	127	2338
Battery fluid, alkali, with battery	154	2797	Benzoyl chloride	137	1736
Battery fluid, alkali, with electronic equipment or actuating device	154	2797	Benzyl bromide	156	1737
Battery-powered equipment (wet battery)	154	3171	Benzyl chloride	156	1738
Battery-powered vehicle (wet battery)	154	3171	Benzyl chloroformate	137	1739
Benzaldehyde	129	1990	Benzylidene dimethylamine	132	2619
Benzene	130	1114	Benzylidene chloride	156	1886
Benzene phosphorus dichloride	137	2798	Benzyl iodide	156	2653
Benzene phosphorus thiodichloride	137	2799	Beryllium compound, n.o.s.	154	1566
Benzenesulfonyl chloride	156	2225	Beryllium nitrate	141	2464
Benzenesulphonyl chloride	156	2225	Beryllium powder	134	1567
Benidine	153	1885	Bhusa, wet, damp or contaminated with oil	133	1327
Benzoic derivative pesticide, liquid, flammable, poisonous	131	2770	Bicyclo[2.2.1]hepta-2,5-diene, stabilized	128P	2251
Benzoic derivative pesticide, liquid, flammable, toxic	131	2770	Biological agents	158	—
Benzoic derivative pesticide, liquid, poisonous	151	3004	Biological substance, category B (Bio)Medical waste, n.o.s.	158	3373
Benzoic derivative pesticide, liquid, poisonous, flammable	131	3003	Bipyridilium pesticide, liquid, flammable, poisonous	131	2782
Benzoic derivative pesticide, liquid, toxic	151	3004	Bipyridilium pesticide, liquid, flammable, toxic	131	2782
Benzoic derivative pesticide, liquid, toxic, flammable	131	3003	Bipyridilium pesticide, liquid, poisonous	151	3016
Benzoic derivative pesticide, solid, poisonous	151	2769	Bipyridilium pesticide, liquid, poisonous, flammable	131	3015
Benzoic derivative pesticide, solid, toxic	151	2769	Bipyridilium pesticide, liquid, toxic	151	3016
Benzonitrile	152	2224	Bipyridilium pesticide, liquid, toxic, flammable	131	3015
			Bipyridilium pesticide, liquid, toxic, flammable	151	2781
			Bipyridilium pesticide, solid, poisonous	151	2781
			Bipyridilium pesticide, solid, toxic	151	2781

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Bisulfates, aqueous solution	154	2837	Boron trifluoride propionic acid complex, solid	157	3420
Bisulfites, aqueous solution, n.o.s.	154	2693	Bromates, inorganic, aqueous solution, n.o.s.	140	3213
Bisulfites, inorganic, aqueous solution, n.o.s.	154	2693	Bromates, inorganic, n.o.s.	141	1450
Bisulphates, aqueous solution	154	2837	Bromine	154	1744
Bisulphites, aqueous solution, n.o.s.	154	2693	Bromine, solution	154	1744
Bisulphites, inorganic, aqueous solution, n.o.s.	154	2693	Bromine, solution (Inhalation Hazard Zone A)	154	1744
Blasting agent, n.o.s.	112	—	Bromine, solution (Inhalation Hazard Zone B)	154	1744
Bleaching powder	140	2208	Bromine chloride	124	2901
Blue asbestos	171	2212	Bromine pentafluoride	144	1745
Bombs, smoke, non-explosive, with corrosive liquid, without initiating device	153	2028	Bromine trifluoride	144	1746
Borate and Chlorate mixtures	140	1458	Bromoacetic acid	156	1938
Borneol	133	1312	Bromoacetic acid, solid	156	3425
Boron tribromide	157	2692	Bromoacetic acid, solution	156	1938
Boron trichloride	125	1741	Bromoacetone	131	1569
Boron trifluoride	125	1008	Bromoacetyl bromide	156	2513
Boron trifluoride, compressed	125	1008	Bromobenzene	130	2514
Boron trifluoride, dihydrate	157	2851	Bromobenzyl cyanides	159	1694
Boron trifluoride acetic acid complex	157	1742	Bromobenzyl cyanides, liquid	159	1694
Boron trifluoride acetic acid complex, liquid	157	1742	Bromobenzyl cyanides, solid	159	1694
Boron trifluoride acetic acid complex, solid	157	3419	Bromobenzyl cyanides, solid	159	3449
Boron trifluoride diethyl etherate	132	2604	1-Bromobutane	130	1126
Boron trifluoride dimethyl etherate	139	2965	2-Bromobutane	130	2339
Boron trifluoride propionic acid complex	157	1743	Bromochlorodifluoromethane	126	1974
Boron trifluoride propionic acid complex, liquid	157	1743	Bromochloromethane	160	1887
			1-Bromo-3-chloropropane	159	2688
			2-Bromoethyl ethyl ether	130	2340
			Bromoform	159	2515
			1-Bromo-3-methylbutane	130	2341
			Bromomethylpropanes	130	2342
			2-Bromo-2-nitropropane-1,3-diol	133	3241

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
2-Bromopentane	130	2343	Butyl ethers	128	1149
2-Bromopropane	129	2344	n-Butyl formate	129	1128
Bromopropanes	129	2344	tert-Butyl hypochlorite	135	3255
3-Bromopropyne	130	2345	N,n-Butylimidazole	152	2690
Bromotrifluoroethylene	116	2419	n-Butyl isocyanate	155	2485
Bromotrifluoromethane	126	1009	tert-Butyl isocyanate	155	2484
Brown asbestos	171	2212	Butyl mercaptan	130	2347
Brucine	152	1570	n-Butyl methacrylate, stabilized	130P	2227
Butadienes, stabilized	116P	1010	Butyl methyl ether	127	2350
Butadienes and hydrocarbon mixture, stabilized	116P	1010	Butyl nitrites	129	2351
Butane	115	1011	Butyl propionates	130	1914
Butane	115	1075	Butyltoluenes	152	2667
Butanedione	127	2346	Butyltrichlorosilane	155	1747
Butane mixture	115	1011	5-tert-Butyl-2,4,6-trinitro-m-xylene	149	2956
Butane mixture	115	1075	Butyl vinyl ether, stabilized	127P	2352
Butanols	129	1120	1,4-Butynediol	153	2716
Butoxyl	127	2708	Butyraldehyde	129	1129
Butyl acetates	129	1123	Butyraldoxime	129	2840
Butyl acid phosphate	153	1718	Butyric acid	153	2820
Butyl acrylates, stabilized	129P	2348	Butyric anhydride	156	2739
n-Butylamine	132	1125	Butyronitrile	131	2411
N-Butylaniline	153	2738	Butyryl chloride	132	2353
Butylbenzenes	128	2709	Buzz	153	2810
n-Butyl bromide	130	1126	BZ	153	2810
Butyl chloride	130	1127	CA	159	1694
n-Butyl chloroformate	155	2743	Cacodylic acid	151	1572
sec-Butyl chloroformate	155	2742	Cadmium compound	154	2570
tert-Butylcyclohexyl chloroformate	156	2747	Caesium	138	1407
Butylene	115	1012	Caesium hydroxide	157	2682
Butylene	115	1075	Caesium hydroxide, solution	154	2681
1,2-Butylene oxide, stabilized	127P	3022	Caesium nitrate	140	1451
			Calcium	138	1401

<b>Name of Material</b>	<b>Guide No.</b>	<b>ID No.</b>	<b>Name of Material</b>	<b>Guide No.</b>	<b>ID No.</b>
Calcium, metal and alloys, pyrophoric	135	1855	Calcium hypochlorite mixture, dry, with more than 39% available Chlorine (8.8% available Oxygen)	140	1748
Calcium, pyrophoric	135	1855	Calcium manganese silicon	138	2844
Calcium alloys, pyrophoric	135	1855	Calcium nitrate	140	1454
Calcium arsenate	151	1573	Calcium oxide	157	1910
Calcium arsenate and Calcium arsenite mixture, solid	151	1574	Calcium perchlorate	140	1455
Calcium arsenite, solid	151	1574	Calcium permanganate	140	1456
Calcium arsenite and Calcium arsenate mixture, solid	151	1574	Calcium peroxide	140	1457
Calcium carbide	138	1402	Calcium phosphide	139	1360
Calcium chlorate	140	1452	Calcium resinate	133	1313
Calcium chlorate, aqueous solution	140	2429	Calcium resinate, fused	133	1314
Calcium chlorate, solution	140	2429	Calcium silicide	138	1405
Calcium chlorite	140	1453	Calcium silicon	138	1406
Calcium cyanamide, with more than 0.1% Calcium carbide	138	1403	Camphor	133	2717
Calcium cyanide	157	1575	Camphor, synthetic	133	2717
Calcium dithionite	135	1923	Camphor oil	128	1130
Calcium hydride	138	1404	Caproic acid	153	2829
Calcium hydrosulfite	135	1923	Carbamate pesticide, liquid, flammable, poisonous	131	2758
Calcium hydrosulphite	135	1923	Carbamate pesticide, liquid, flammable, toxic	131	2758
Calcium hypochlorite, dry	140	1748	Carbamate pesticide, liquid, poisonous	151	2992
Calcium hypochlorite, hydrated, with not less than 5.5% but not more than 16% water	140	2880	Carbamate pesticide, liquid, poisonous, flammable	131	2991
Calcium hypochlorite, hydrated mixture, with not less than 5.5% but not more than 16% water	140	2880	Carbamate pesticide, liquid, toxic	151	2992
Calcium hypochlorite mixture, dry, with more than 10% but not more than 39% available Chlorine	140	2208	Carbamate pesticide, liquid, toxic, flammable	131	2991
			Carbamate pesticide, solid, poisonous	151	2757
			Carbamate pesticide, solid, toxic	151	2757
			Carbon, activated	133	1362

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Carbon, animal or vegetable origin	133	1361	Carbon monoxide and Hydrogen mixture	119	2600
Carbon bisulfide	131	1131	Carbon monoxide and Hydrogen mixture, compressed	119	2600
Carbon bisulphide	131	1131	Carbon tetrabromide	151	2516
Carbon dioxide	120	1013	Carbon tetrachloride	151	1846
Carbon dioxide, compressed	120	1013	Carbonyl fluoride	125	2417
Carbon dioxide, refrigerated liquid	120	2187	Carbonyl fluoride, compressed	125	2417
Carbon dioxide, solid	120	1845	Carbonyl sulfide	119	2204
Carbon dioxide and Ethylene oxide mixture, with more than 9% but not more than 87% Ethylene oxide	115	1041	Carbonyl sulphide	119	2204
Carbon dioxide and Ethylene oxide mixture, with more than 87% Ethylene oxide	119P	3300	Castor beans, meal, pomace or flake	171	2969
Carbon dioxide and Ethylene oxide mixtures, with more than 6% Ethylene oxide	115	1041	Caustic alkali liquid, n.o.s.	154	1719
Carbon dioxide and Ethylene oxide mixtures, with not more than 6% Ethylene oxide	126	1952	Caustic potash, dry, solid	154	1813
Carbon dioxide and Ethylene oxide mixtures, with not more than 9% Ethylene oxide	126	1952	Caustic potash, liquid	154	1814
Carbon dioxide and Nitrous oxide mixture	126	1015	Caustic potash, solution	154	1814
Carbon dioxide and Oxygen mixture	122	1014	Caustic soda, bead	154	1823
Carbon dioxide and Oxygen mixture, compressed	122	1014	Caustic soda, flake	154	1823
Carbon disulfide	131	1131	Caustic soda, granular	154	1823
Carbon disulphide	131	1131	Caustic soda, solid	154	1823
Carbon monoxide	119	1016	Caustic soda, solution	154	1824
Carbon monoxide, compressed	119	1016	Cells, containing Sodium	138	3292
Carbon monoxide, refrigerated liquid (cryogenic liquid)	168	9202	Celluloid, in blocks, rods, rolls, sheets, tubes, etc., except scrap	133	2000
			Celluloid, scrap	135	2002
			Cerium, slabs, ingots or rods	170	1333
			Cerium, turnings or gritty powder	138	3078
			Cesium	138	1407
			Cesium hydroxide	157	2682
			Cesium hydroxide, solution	154	2681
			Cesium nitrate	140	1451
			CG	125	1076
			Charcoal	133	1361

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Chemical kit	154	1760	Chloroacetic acid, solid	153	1751
Chemical kit	171	3316	Chloroacetic acid, solution	153	1750
Chemical sample, poisonous	151	3315	Chloroacetone, stabilized	131	1695
Chemical sample, poisonous liquid	151	3315	Chloroacetonitrile	131	2668
Chemical sample, poisonous solid	151	3315	Chloroacetophenone	153	1697
Chemical sample, toxic	151	3315	Chloroacetophenone, liquid	153	1697
Chemical sample, toxic liquid	151	3315	Chloroacetophenone, liquid	153	3416
Chemical sample, toxic solid	151	3315	Chloroacetophenone, solid	153	1697
Chloral, anhydrous, stabilized	153	2075	Chloroacetyl chloride	156	1752
Chlorate and Borate mixtures	140	1458	Chloroanilines, liquid	152	2019
Chlorate and Magnesium chloride mixture	140	1459	Chloroanilines, solid	152	2018
Chlorate and Magnesium chloride mixture, solid	140	1459	Chloroanisidines	152	2233
Chlorate and Magnesium chloride mixture, solution	140	3407	Chlorobenzene	130	1134
Chlorates, inorganic, aqueous solution, n.o.s.	140	3210	Chlorobenzotrifluorides	130	2234
Chlorates, inorganic, n.o.s.	140	1461	Chlorobenzyl chlorides	153	2235
Chloric acid, aqueous solution, with not more than 10% Chloric acid	140	2626	Chlorobenzyl chlorides, liquid	153	2235
Chlorine	124	1017	Chlorobenzyl chlorides, solid	153	3427
Chlorine dioxide, hydrate, frozen	143	9191	1-Chloro-3-bromopropane	159	2688
Chlorine pentafluoride	124	2548	Chlorobutanes	130	1127
Chlorine trifluoride	124	1749	Chlorocresols	152	2669
Chlorite solution	154	1908	Chlorocresols, liquid	152	2669
Chlorite solution, with more than 5% available Chlorine	154	1908	Chlorocresols, solid	152	2669
Chlorites, inorganic, n.o.s.	143	1462	Chlorocresols, solid	152	3437
Chloroacetaldehyde	153	2232	Chlorocresols, solution	152	2669
Chloroacetic acid, liquid	153	1750	Chlorodifluorobromomethane	126	1974
Chloroacetic acid, molten	153	3250	1-Chloro-1,1-difluoroethane	115	2517
			Chlorodifluoroethanes	115	2517
			Chlorodifluoromethane	126	1018
			Chlorodifluoromethane and Chloropentafluoroethane mixture	126	1973
			Chlorodinitrobenzenes	153	1577
			Chlorodinitrobenzenes, liquid	153	1577
			Chlorodinitrobenzenes, solid	153	1577

Name of Material	Guide ID No.	ID No.	Name of Material	Guide ID No.	ID No.
Chlorodinitrobenzenes, solid	153	3441	Chlorophenates, solid	154	2905
1-Chloro-2,3-epoxypropane	131P	2023	Chlorophenolates, liquid	154	2904
2-Chloroethanal	153	2232	Chlorophenolates, solid	154	2905
Chloroform	151	1888	Chlorophenols, liquid	153	2021
Chloroformates, n.o.s.	155	2742	Chlorophenols, solid	153	2020
Chloroformates, poisonous, corrosive, flammable, n.o.s.	155	2742	Chlorophenyltrichlorosilane	156	1753
Chloroformates, poisonous, corrosive, n.o.s.	154	3277	Chloropicrin	154	1580
Chloroformates, toxic, corrosive, flammable, n.o.s.	155	2742	Chloropicrin and Methyl bromide mixture	123	1581
Chloroformates, toxic, corrosive, n.o.s.	154	3277	Chloropicrin and Methyl chloride mixture	119	1582
Chloromethyl chloroformate	157	2745	Chloropicrin mixture, n.o.s.	154	1583
Chloromethyl ethyl ether	131	2354	Chloropivaloyl chloride	156	9263
3-Chloro-4-methylphenyl isocyanate	156	2236	Chloroplatinic acid, solid	154	2507
3-Chloro-4-methylphenyl isocyanate, liquid	156	2236	Chloroprene, stabilized	131P	1991
3-Chloro-4-methylphenyl isocyanate, solid	156	3428	1-Chloropropane	129	1278
Chloronitroanilines	153	2237	2-Chloropropane	129	2356
Chloronitrobenzenes	152	1578	3-Chloropropanol-1	153	2849
Chloronitrobenzenes, liquid	152	1578	2-Chloropropene	130P	2456
Chloronitrobenzenes, liquid	152	3409	2-Chloropropionic acid	153	2511
Chloronitrobenzenes, solid	152	1578	2-Chloropropionic acid, solid	153	2511
Chloronitrotoluenes	152	2433	2-Chloropropionic acid, solution	153	2511
Chloronitrotoluenes, liquid	152	2433	2-Chloropyridine	153	2822
Chloronitrotoluenes, solid	152	2433	Chlorosilanes, corrosive, flammable, n.o.s.	155	2986
Chloronitrotoluenes, solid	152	3457	Chlorosilanes, corrosive, n.o.s.	156	2987
Chloropentafluoroethane	126	1020	Chlorosilanes, flammable, corrosive, n.o.s.	155	2985
Chloropentafluoroethane and Chlorodifluoromethane mixture	126	1973	Chlorosilanes, n.o.s.	155	2985
Chlorophenates, liquid	154	2904	Chlorosilanes, n.o.s.	155	2986
			Chlorosilanes, n.o.s.	156	2987
			Chlorosilanes, n.o.s.	139	2988
			Chlorosilanes, poisonous, corrosive, flammable, n.o.s.	155	3362

Name of Material	Guide ID No.	ID No.	Name of Material	Guide ID No.	ID No.
Chlorosilanes, poisonous, corrosive, n.o.s.	156	3361	Chlorotrifluoromethane and Trifluoromethane azeotropic mixture with approximately 60% Chlorotrifluoromethane	126	2599
Chlorosilanes, toxic, corrosive flammable, n.o.s.	155	3362	Chromic acid, solid	141	1463
Chlorosilanes, toxic, corrosive, n.o.s.	156	3361	Chromic acid, solution	154	1755
Chlorosilanes, water-reactive, flammable, corrosive, n.o.s.	139	2988	Chromic fluoride, solid	154	1756
Chlorosulfonic acid	137	1754	Chromic fluoride, solution	154	1757
Chlorosulfonic acid and Sulfur trioxide mixture	137	1754	Chromium nitrate	141	2720
Chlorosulphonic acid	137	1754	Chromium oxychloride	137	1758
Chlorosulphonic acid and Sulphur trioxide mixture	137	1754	Chromium trioxide, anhydrous	141	1463
1-Chloro-1,2,2,2-tetrafluoroethane	126	1021	Chromosulfuric acid	154	2240
Chlorotetrafluoroethane	126	1021	Chromosulphuric acid	154	2240
Chlorotetrafluoroethane and Ethylene oxide mixture, with not more than 8.8% Ethylene oxide	126	3297	CK	125	1589
Chlorotoluenes	129	2238	Clinical specimens	158	3373
4-Chloro-o-toluidine hydrochloride	153	1579	Clinical waste, unspecified, n.o.s.	158	3291
4-Chloro-o-toluidine hydrochloride, solid	153	1579	CN	153	1697
4-Chloro-o-toluidine hydrochloride, solution	153	3410	Coal gas	119	1023
Chlorotoluidines	153	2239	Coal gas, compressed	119	1023
Chlorotoluidines, liquid	153	2239	Coal tar distillates, flammable	128	1136
Chlorotoluidines, liquid	153	3429	Coating solution	127	1139
Chlorotoluidines, solid	153	2239	Cobalt naphthenates, powder	133	2001
1-Chloro-2,2,2-trifluoroethane	126	1983	Cobalt resinate, precipitated	133	1318
Chlorotrifluoroethane	126	1983	Combustible liquid, n.o.s.	128	1993
Chlorotrifluoromethane	126	1022	Compound, cleaning liquid (corrosive)	154	1760
			Compound, cleaning liquid (flammable)	128	1993
			Compound, tree or weed killing, liquid (corrosive)	154	1760
			Compound, tree or weed killing, liquid (flammable)	128	1993
			Compound, tree or weed killing, liquid (toxic)	153	2810



Name of Material	Guide No.	ID No.
Compressed gas, flammable, n.o.s.	115	1954
Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone A)	119	1953
Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone B)	119	1953
Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone C)	119	1953
Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone D)	119	1953
Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone A)	119	1953
Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone B)	119	1953
Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone C)	119	1953
Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone D)	119	1953
Compressed gas, n.o.s.	126	1956
Compressed gas, oxidizing, n.o.s.	122	3156
Compressed gas, poisonous, corrosive, n.o.s.	123	3304
Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone A)	123	3304
Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone B)	123	3304
Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone C)	123	3304

Name of Material	Guide No.	ID No.
Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone D)	123	3304
Compressed gas, poisonous, flammable, corrosive, n.o.s.	119	3305
Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)	119	3305
Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)	119	3305
Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)	119	3305
Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)	119	3305
Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)	119	1953
Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone B)	119	1953
Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)	119	1953
Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone D)	119	1953
Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)	119	1953
Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone B)	119	1953
Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)	119	1953
Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone D)	119	1953
Compressed gas, poisonous, n.o.s.	123	1955
Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone A)	123	1955
Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone B)	123	1955

Name of Material	Guide No.	ID No.
------------------	-----------	--------

Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone C)	123	1955
--	-----	------

Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone D)	123	1955
--	-----	------

Compressed gas, poisonous, oxidizing, corrosive, n.o.s.	124	3306
---	-----	------

Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)	124	3306
--	-----	------

Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone B)	124	3306
--	-----	------

Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)	124	3306
--	-----	------

Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)	124	3306
--	-----	------

Compressed gas, poisonous, oxidizing, n.o.s.	124	3303
--	-----	------

Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone A)	124	3303
---	-----	------

Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone B)	124	3303
---	-----	------

Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone C)	124	3303
---	-----	------

Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone D)	124	3303
---	-----	------

Compressed gas, toxic, corrosive, n.o.s.	123	3304
--	-----	------

Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone A)	123	3304
---	-----	------

Name of Material	Guide No.	ID No.
------------------	-----------	--------

Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone B)	123	3304
---	-----	------

Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone C)	123	3304
---	-----	------

Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone D)	123	3304
---	-----	------

Compressed gas, toxic, flammable, corrosive, n.o.s.	119	3305
---	-----	------

Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)	119	3305
--	-----	------

Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)	119	3305
--	-----	------

Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)	119	3305
--	-----	------

Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)	119	3305
--	-----	------

Compressed gas, toxic, flammable, n.o.s.	119	1953
--	-----	------

Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone A)	119	1953
---	-----	------

Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone B)	119	1953
---	-----	------

Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone C)	119	1953
---	-----	------

Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone D)	119	1953
---	-----	------

Compressed gas, toxic, n.o.s.	123	1955
-------------------------------	-----	------

Name of Material	Guide No.	ID No.
Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone A)	123	1955
Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone B)	123	1955
Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone C)	123	1955
Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone D)	123	1955
Compressed gas, toxic, oxidizing, corrosive, n.o.s.	124	3306
Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)	124	3306
Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone B)	124	3306
Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)	124	3306
Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)	124	3306
Compressed gas, toxic, oxidizing, n.o.s.	124	3303
Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone A)	124	3303
Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone B)	124	3303
Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone C)	124	3303
Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone D)	124	3303
Consumer commodity	171	8000
Copper acetoarsenite	151	1585

Name of Material	Guide No.	ID No.
Copper arsenite	151	1586
Copper based pesticide, liquid, flammable, poisonous	131	2776
Copper based pesticide, liquid, flammable, toxic	131	2776
Copper based pesticide, liquid, poisonous	151	3010
Copper based pesticide, liquid, poisonous, flammable	131	3009
Copper based pesticide, liquid, toxic	151	3010
Copper based pesticide, liquid, toxic, flammable	131	3009
Copper based pesticide, solid, poisonous	151	2775
Copper based pesticide, solid, toxic	151	2775
Copper chlorate	141	2721
Copper chloride	154	2802
Copper cyanide	151	1587
Copra	135	1363
Corrosive liquid, acidic, inorganic, n.o.s.	154	3264
Corrosive liquid, acidic, organic, n.o.s.	153	3265
Corrosive liquid, basic, inorganic, n.o.s.	154	3266
Corrosive liquid, basic, organic, n.o.s.	153	3267
Corrosive liquid, flammable, n.o.s.	132	2920
Corrosive liquid, n.o.s.	154	1760
Corrosive liquid, oxidizing, n.o.s.	140	3093
Corrosive liquid, poisonous, n.o.s.	154	2922

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Corrosive liquid, self-heating, n.o.s.	136	3301	Coumarin derivative pesticide, liquid, poisonous	151	3026
Corrosive liquid, toxic, n.o.s.	154	2922	Coumarin derivative pesticide, liquid, poisonous, flammable	131	3025
Corrosive liquid, water-reactive, n.o.s.	138	3094	Coumarin derivative pesticide, liquid, toxic	151	3026
Corrosive liquid, which in contact with water emits flammable gases, n.o.s.	138	3094	Coumarin derivative pesticide, liquid, toxic, flammable	131	3025
Corrosive solid, acidic, inorganic, n.o.s.	154	3260	Coumarin derivative pesticide, solid, poisonous	151	3027
Corrosive solid, acidic, organic, n.o.s.	154	3261	Coumarin derivative pesticide, solid, toxic	151	3027
Corrosive solid, basic, inorganic, n.o.s.	154	3262	Cresols	153	2076
Corrosive solid, basic, organic, n.o.s.	154	3263	Cresols, liquid	153	2076
Corrosive solid, flammable, n.o.s.	134	2921	Cresols, solid	153	2076
Corrosive solid, n.o.s.	154	1759	Cresols, solid	153	3455
Corrosive solid, oxidizing, n.o.s.	140	3084	Cresylic acid	153	2022
Corrosive solid, poisonous, n.o.s.	154	2923	Crotonaldehyde	131P	1143
Corrosive solid, self-heating, n.o.s.	136	3095	Crotonaldehyde, stabilized	131P	1143
Corrosive solid, toxic, n.o.s.	154	2923	Crotonic acid	153	2823
Corrosive solid, water-reactive, n.o.s.	138	3096	Crotonic acid, liquid	153	2823
Corrosive solid, which in contact with water emits flammable gases, n.o.s.	138	3096	Crotonic acid, liquid	153	3472
Cotton	133	1365	Crotonic acid, solid	153	2823
Cotton, wet	133	1365	Crotonylene	128	1144
Cotton waste, oily	133	1364	CS	153	2810
Coumarin derivative pesticide, liquid, flammable, poisonous	131	3024	Cumene	130	1918
Coumarin derivative pesticide, liquid, flammable, toxic	131	3024	Cupriethylenediamine, solution	154	1761
			CX	154	2811
			Cyanide solution, n.o.s.	157	1935
			Cyanides, inorganic, n.o.s.	157	1588
			Cyanides, inorganic, solid, n.o.s.	157	1588
			Cyanogen	119	1026
			Cyanogen bromide	157	1889

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Cyanogen chloride, stabilized	125	1589	Decaborane	134	1868
Cyanogen gas	119	1026	Decahydronaphthalene	130	1147
Cyanuric chloride	157	2670	n-Decane	128	2247
Cyclobutane	115	2601	Denatured alcohol	127	1987
Cyclobutyl chloroformate	155	2744	Denatured alcohol (toxic)	131	1986
1,5,9-Cyclododecatriene	153	2518	Desensitized explosive, liquid, n.o.s.	128	3379
Cycloheptane	128	2241	Desensitized explosive, solid, n.o.s.	133	3380
Cycloheptatriene	131	2603	Deuterium	115	1957
Cycloheptene	128	2242	Deuterium, compressed	115	1957
Cyclohexane	128	1145	Devices, small, hydrocarbon gas powered, with release device	115	3150
Cyclohexanethiol	129	3054	Diacetone alcohol	129	1148
Cyclohexanone	127	1915	Diacetyl	127	2346
Cyclohexene	130	2256	Diagnostic specimens	158	3373
Cyclohexenyltrichlorosilane	156	1762	Diallylamine	132	2359
Cyclohexyl acetate	130	2243	Diallyl ether	131P	2360
Cyclohexylamine	132	2357	4,4'-Diaminodiphenylmethane	153	2651
Cyclohexyl isocyanate	155	2488	Di-n-amylamine	131	2841
Cyclohexyl mercaptan	129	3054	Dibenzylidichlorosilane	156	2434
Cyclohexyltrichlorosilane	156	1763	Diborane	119	1911
Cyclooctadiene phosphines	135	2940	Diborane, compressed	119	1911
Cyclooctadienes	130P	2520	Diborane mixtures	119	1911
Cyclooctatetraene	128P	2358	Dibromobenzene	129	2711
Cyclopentane	128	1146	1,2-Dibromobutan-3-one	154	2648
Cyclopentanol	129	2244	Dibromochloropropanes	159	2872
Cyclopentanone	128	2245	Dibromodifluoromethane	171	1941
Cyclopentene	128	2246	Dibromomethane	160	2664
Cyclopropane	115	1027	Di-n-butylamine	132	2248
Cymenes	130	2046	Dibutylaminoethanol	153	2873
DA	151	1699	Dibutyl ethers	128	1149
Dangerous goods in apparatus	171	3363	Dichloroacetic acid	153	1764
Dangerous goods in machinery	171	3363	1,3-Dichloroacetone	153	2649
DC	153	2810			

**Name of Material**                      **Guide ID**  
**No.**   **No.**

Dichloroacetyl chloride	<b>156</b>	1765
Dichloroanilines	<b>153</b>	1590
Dichloroanilines, liquid	<b>153</b>	1590
Dichloroanilines, solid	<b>153</b>	1590
Dichloroanilines, solid	<b>153</b>	3442
o-Dichlorobenzene	<b>152</b>	1591
Dichlorobutene	<b>132</b>	2920
2,2'-Dichlorodiethyl ether	<b>152</b>	1916
Dichlorodifluoromethane	<b>126</b>	1028
Dichlorodifluoromethane and Difluoroethane azeotropic mixture with approximately 74% Dichlorodifluoromethane	<b>126</b>	2602
Dichlorodifluoromethane and Ethylene oxide mixture, with not more than 12.5% Ethylene oxide	<b>126</b>	3070
Dichlorodifluoromethane and Ethylene oxide mixture, with not more than 12% Ethylene oxide	<b>126</b>	3070
Dichlorodimethyl ether, symmetrical	<b>131</b>	2249
1,1-Dichloroethane	<b>130</b>	2362
1,2-Dichloroethylene	<b>130P</b>	1150
Dichloroethylene	<b>130P</b>	1150
Dichloroethyl ether	<b>152</b>	1916
Dichlorofluoromethane	<b>126</b>	1029
Dichloroisocyanuric acid, dry	<b>140</b>	2465
Dichloroisocyanuric acid salts	<b>140</b>	2465
Dichloroisopropyl ether	<b>153</b>	2490
Dichloromethane	<b>160</b>	1593
1,1-Dichloro-1-nitroethane	<b>153</b>	2650
Dichloropentanes	<b>130</b>	1152
Dichlorophenyl isocyanates	<b>156</b>	2250

**Name of Material**                      **Guide ID**  
**No.**   **No.**

Dichlorophenyltrichlorosilane	<b>156</b>	1766
1,2-Dichloropropane	<b>130</b>	1279
Dichloropropane	<b>130</b>	1279
1,3-Dichloropropanol-2	<b>153</b>	2750
Dichloropropenes	<b>129</b>	2047
Dichlorosilane	<b>119</b>	2189
1,2-Dichloro-1,1,2,2-tetrafluoroethane	<b>126</b>	1958
Dichlorotetrafluoroethane	<b>126</b>	1958
3,5-Dichloro-2,4,6-trifluoropyridine	<b>151</b>	9264
Dicyclohexylamine	<b>153</b>	2565
Dicyclohexylammonium nitrite	<b>133</b>	2687
Dicyclopentadiene	<b>130</b>	2048
1,2-Di-(dimethylamino)ethane	<b>129</b>	2372
Didymium nitrate	<b>140</b>	1465
Dieldrin	<b>151</b>	2761
Diesel fuel	<b>128</b>	1202
Diesel fuel	<b>128</b>	1993
Diethoxymethane	<b>127</b>	2373
3,3-Diethoxypropene	<b>127</b>	2374
Diethylamine	<b>132</b>	1154
2-Diethylaminoethanol	<b>132</b>	2686
Diethylaminoethanol	<b>132</b>	2686
3-Diethylaminopropylamine	<b>132</b>	2684
Diethylaminopropylamine	<b>132</b>	2684
N,N-Diethylaniline	<b>153</b>	2432
Diethylbenzene	<b>130</b>	2049
Diethyl carbonate	<b>128</b>	2366
Diethyldichlorosilane	<b>155</b>	1767
Diethylenetriamine	<b>154</b>	2079
Diethyl ether	<b>127</b>	1155
N,N-Diethylethylenediamine	<b>132</b>	2685

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Diethyl ketone	127	1156	2-Dimethylaminoethanol	132	2051
Diethyl sulfate	152	1594	2-Dimethylaminoethyl acrylate	152	3302
Diethyl sulfide	129	2375	2-Dimethylaminoethyl methacrylate	153P	2522
Diethyl sulphate	152	1594	Dimethylaminoethyl methacrylate	153P	2522
Diethyl sulphide	129	2375	N,N-Dimethylaniline	153	2253
Diethylthiophosphoryl chloride	155	2751	2,3-Dimethylbutane	128	2457
Diethylzinc	135	1366	1,3-Dimethylbutylamine	132	2379
Difluorochloroethanes	115	2517	Dimethylcarbamoyl chloride	156	2262
1,1-Difluoroethane	115	1030	Dimethyl carbonate	129	1161
Difluoroethane	115	1030	Dimethylcyclohexanes	128	2263
Difluoroethane and Dichlorodifluoromethane azeotropic mixture with approximately 74% Dichlorodifluoromethane	126	2602	N,N-Dimethylcyclohexylamine	132	2264
1,1-Difluoroethylene	116P	1959	Dimethylcyclohexylamine	132	2264
Difluoromethane	115	3252	Dimethyldichlorosilane	155	1162
Difluorophosphoric acid, anhydrous	154	1768	Dimethyldiethoxysilane	127	2380
2,3-Dihydropyran	127	2376	Dimethyldioxanes	127	2707
Diisobutylamine	132	2361	Dimethyl disulfide	130	2381
Diisobutylene, isomeric compounds	128	2050	Dimethyl disulphide	130	2381
Diisobutyl ketone	128	1157	Dimethylethanolamine	132	2051
Diisooctyl acid phosphate	153	1902	Dimethyl ether	115	1033
Diisopropylamine	132	1158	N,N-Dimethylformamide	129	2265
Diisopropyl ether	127	1159	1,1-Dimethylhydrazine	131	1163
Diketene, stabilized	131P	2521	1,2-Dimethylhydrazine	131	2382
1,1-Dimethoxyethane	127	2377	Dimethylhydrazine, symmetrical	131	2382
1,2-Dimethoxyethane	127	2252	Dimethylhydrazine, unsymmetrical	131	1163
Dimethylamine, anhydrous	118	1032	2,2-Dimethylpropane	115	2044
Dimethylamine, aqueous solution	132	1160	Dimethyl-N-propylamine	132	2266
Dimethylamine, solution	132	1160	Dimethyl sulfate	156	1595
2-Dimethylaminoacetonitrile	131	2378	Dimethyl sulfide	130	1164
			Dimethyl sulphate	156	1595
			Dimethyl sulphide	130	1164
			Dimethyl thiophosphoryl chloride	156	2267

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Dimethylzinc	135	1370	Dipicryl sulfide, wetted with not less than 10% water	113	2852
Dinitroanilines	153	1596	Dipicryl sulphide, wetted with not less than 10% water	113	2852
Dinitrobenzenes	152	1597	Dipropylamine	132	2383
Dinitrobenzenes, liquid	152	1597	Di-n-propyl ether	127	2384
Dinitrobenzenes, solid	152	1597	Dipropyl ether	127	2384
Dinitrobenzenes, solid	152	3443	Dipropyl ketone	128	2710
Dinitrochlorobenzenes	153	1577	Disinfectant, liquid, corrosive, n.o.s.	153	1903
Dinitro-o-cresol	153	1598	Disinfectant, liquid, poisonous, n.o.s.	151	3142
Dinitrogen tetroxide	124	1067	Disinfectant, liquid, toxic, n.o.s.	151	3142
Dinitrogen tetroxide and Nitric oxide mixture	124	1975	Disinfectant, solid, poisonous, n.o.s.	151	1601
Dinitrophenol, solution	153	1599	Disinfectant, solid, toxic, n.o.s.	151	1601
Dinitrophenol, wetted with not less than 15% water	113	1320	Disinfectants, corrosive, liquid, n.o.s.	153	1903
Dinitrophenolates, wetted with not less than 15% water	113	1321	Disinfectants, liquid, n.o.s. (poisonous)	151	3142
Dinitroresorcinol, wetted with not less than 15% water	113	1322	Disinfectants, solid, n.o.s. (poisonous)	151	1601
Dinitrotoluenes	152	2038	Disodium trioxosilicate	154	3253
Dinitrotoluenes, liquid	152	2038	Disodium trioxosilicate, pentahydrate	154	3253
Dinitrotoluenes, molten	152	1600	Dispersant gas, n.o.s.	126	1078
Dinitrotoluenes, solid	152	2038	Dispersant gas, n.o.s. (flammable)	115	1954
Dinitrotoluenes, solid	152	3454	Dithiocarbamate pesticide, liquid, flammable, poisonous	131	2772
Dioxane	127	1165	Dithiocarbamate pesticide, liquid, flammable, toxic	131	2772
Dioxolane	127	1166	Dithiocarbamate pesticide, liquid, poisonous	151	3006
Dipentene	128	2052	Dithiocarbamate pesticide, liquid, poisonous, flammable	131	3005
Diphenylamine chloroarsine	154	1698	Dithiocarbamate pesticide, liquid, toxic	151	3006
Diphenylchloroarsine	151	1699	Diphenyldichlorosilane	156	1769
Diphenylchloroarsine, liquid	151	1699	Diphenylmethyl bromide	153	1770
Diphenylchloroarsine, solid	151	1699	Diphosgene	125	1076
Diphenylchloroarsine, solid	151	3450			



Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Dithiocarbamate pesticide, liquid, toxic, flammable	131	3005	Elevated temperature liquid, flammable, n.o.s., with flash point above 60.5°C (141°F), at or above its flash point	128	3256
Dithiocarbamate pesticide, solid, poisonous	151	2771	Elevated temperature liquid, n.o.s., at or above 100°C (212°F), and below its flash point	128	3257
Dithiocarbamate pesticide, solid, toxic	151	2771	Elevated temperature solid, n.o.s., at or above 240°C (464°F)	171	3258
Divinyl ether, stabilized	128P	1167	Engine starting fluid	115	1960
DM	154	1698	Engines, internal combustion, flammable gas powered	128	3166
Dodecylbenzenesulfonic acid	153	2584	Engines, internal combustion, flammable liquid powered	128	3166
Dodecylbenzenesulphonic acid	153	2584	Engines, internal combustion, including when fitted in machinery or vehicles	128	3166
Dodecyltrichlorosilane	156	1771	Environmentally hazardous substances, liquid, n.o.s.	171	3082
DP	125	1076	Environmentally hazardous substances, solid, n.o.s.	171	3077
Dry ice	120	1845	Epibromohydrin	131	2558
Dye, liquid, corrosive, n.o.s.	154	2801	Epichlorohydrin	131P	2023
Dye, liquid, poisonous, n.o.s.	151	1602	1,2-Epoxy-3-ethoxypropane	127	2752
Dye, liquid, toxic, n.o.s.	151	1602	Esters, n.o.s.	127	3272
Dye, solid, corrosive, n.o.s.	154	3147	Ethane	115	1035
Dye, solid, poisonous, n.o.s.	151	3143	Ethane, compressed	115	1035
Dye, solid, toxic, n.o.s.	151	3143	Ethane, refrigerated liquid	115	1961
Dye intermediate, liquid, corrosive, n.o.s.	154	2801	Ethane-Propane mixture, refrigerated liquid	115	1961
Dye intermediate, liquid, poisonous, n.o.s.	151	1602	Ethanol	127	1170
Dye intermediate, liquid, toxic, n.o.s.	151	1602	Ethanol and gasoline mixture, with more than 10% ethanol	127	3475
Dye intermediate, solid, corrosive, n.o.s.	154	3147	Ethanol and motor spirit mixture, with more than 10% ethanol	127	3475
Dye intermediate, solid, poisonous, n.o.s.	151	3143			
Dye intermediate, solid, toxic, n.o.s.	151	3143			
ED	151	1892			
Elevated temperature liquid, flammable, n.o.s., with flash point above 37.8°C (100°F), at or above its flash point	128	3256			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Ethanol and petrol mixture, with more than 10% ethanol	127	3475	Ethyl chloroacetate	155	1181
Ethanol, solution	127	1170	Ethyl chloroformate	155	1182
Ethanolamine	153	2491	Ethyl 2-chloropropionate	129	2935
Ethanolamine, solution	153	2491	Ethyl chlorothioformate	155	2826
Ethers, n.o.s.	127	3271	Ethyl crotonate	130	1862
Ethyl acetate	129	1173	Ethyl cyanoacetate	156	2666
Ethylacetylene, stabilized	116P	2452	Ethylidichloroarsine	151	1892
Ethyl acrylate, stabilized	129P	1917	Ethylidichlorosilane	139	1183
Ethyl alcohol	127	1170	Ethylene	116P	1962
Ethyl alcohol, solution	127	1170	Ethylene, Acetylene and Propylene in mixture, refrigerated liquid containing at least 71.5% Ethylene with not more than 22.5% Acetylene and not more than 6% Propylene	115	3138
Ethylamine	118	1036	Ethylene, compressed	116P	1962
Ethylamine, aqueous solution, with not less than 50% but not more than 70% Ethylamine	132	2270	Ethylene, refrigerated liquid (cryogenic liquid)	115	1038
Ethyl amyl ketone	128	2271	Ethylene chlorohydrin	131	1135
2-Ethylaniline	153	2273	Ethylenediamine	132	1604
N-Ethylaniline	153	2272	Ethylene dibromide	154	1605
Ethylbenzene	130	1175	Ethylene dibromide and Methyl bromide mixture, liquid	151	1647
N-Ethyl-N-benzylaniline	153	2274	Ethylene dichloride	131	1184
N-Ethylbenzyltoluidines	153	2753	Ethylene glycol diethyl ether	127	1153
N-Ethylbenzyltoluidines, liquid	153	2753	Ethylene glycol monobutyl ether	152	2369
N-Ethylbenzyltoluidines, solid	153	2753	Ethylene glycol monoethyl ether	127	1171
N-Ethylbenzyltoluidines, solid	153	3460	Ethylene glycol monoethyl ether acetate	129	1172
Ethyl borate	129	1176	Ethylene glycol monomethyl ether	127	1188
Ethyl bromide	131	1891	Ethylene glycol monomethyl ether acetate	129	1189
Ethyl bromoacetate	155	1603	Ethyleneimine, stabilized	131P	1185
2-Ethylbutanol	129	2275	Ethylene oxide	119P	1040
2-Ethylbutyl acetate	130	1177			
Ethylbutyl acetate	130	1177			
Ethyl butyl ether	127	1179			
2-Ethylbutyraldehyde	130	1178			
Ethyl butyrate	130	1180			
Ethyl chloride	115	1037			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Ethylene oxide and Carbon dioxide mixture, with more than 9% but not more than 87% Ethylene oxide	115	1041	Ethyl ether	127	1155
Ethylene oxide and Carbon dioxide mixture, with more than 87% Ethylene oxide	119P	3300	Ethyl fluoride	115	2453
Ethylene oxide and Carbon dioxide mixtures, with more than 6 % Ethylene oxide	115	1041	Ethyl formate	129	1190
Ethylene oxide and Carbon dioxide mixtures, with not more than 6% Ethylene oxide	126	1952	Ethylhexaldehydes	129	1191
Ethylene oxide and Carbon dioxide mixtures, with not more than 9% Ethylene oxide	126	1952	2-Ethylhexylamine	132	2276
Ethylene oxide and Chlorotetrafluoroethane mixture, with not more than 8.8% Ethylene oxide	126	3297	2-Ethylhexyl chloroformate	156	2748
Ethylene oxide and Dichlorodifluoromethane mixture, with not more than 12.5% Ethylene oxide	126	3070	Ethyl isobutyrate	129	2385
Ethylene oxide and Dichlorodifluoromethane mixtures, with not more than 12% Ethylene oxide	126	3070	Ethyl isocyanate	155	2481
Ethylene oxide and Pentafluoroethane mixture, with not more than 7.9% Ethylene oxide	126	3298	Ethyl lactate	129	1192
Ethylene oxide and Propylene oxide mixture, with not more than 30% Ethylene oxide	129P	2983	Ethyl mercaptan	129	2363
Ethylene oxide and Tetrafluoroethane mixture, with not more than 5.6% Ethylene oxide	126	3299	Ethyl methacrylate	130P	2277
Ethylene oxide with Nitrogen	119P	1040	Ethyl methacrylate, stabilized	130P	2277
			Ethyl methyl ether	115	1039
			Ethyl methyl ketone	127	1193
			Ethyl nitrite, solution	131	1194
			Ethyl orthoformate	129	2524
			Ethyl oxalate	156	2525
			Ethylphenyldichlorosilane	156	2435
			Ethyl phosphonothioic dichloride, anhydrous	154	2927
			Ethyl phosphonous dichloride, anhydrous	135	2845
			Ethyl phosphorodichloridate	154	2927
			1-Ethylpiperidine	132	2386
			Ethyl propionate	129	1195
			Ethyl propyl ether	127	2615
			Ethyl silicate	129	1292
			Ethylsulfuric acid	156	2571
			Ethylsulphuric acid	156	2571
			N-Ethyltoluidines	153	2754
			Ethyltrichlorosilane	155	1196
			Explosive A	112	—
			Explosive B	112	—

<b>Name of Material</b>	<b>Guide No.</b>	<b>ID No.</b>	<b>Name of Material</b>	<b>Guide No.</b>	<b>ID No.</b>
Explosive C	114	—	Fibres, animal or vegetable, burnt, wet or damp	133	1372
Explosives, division 1.1, 1.2, 1.3, 1.5 or 1.6	112	—	Fibres, animal or vegetable or synthetic, n.o.s. with oil	133	1373
Explosives, division 1.4	114	—	Fibres, vegetable, dry	133	3360
Extracts, aromatic, liquid	127	1169	Fibres impregnated with weakly nitrated Nitrocellulose, n.o.s.	133	1353
Extracts, flavoring, liquid	127	1197	Films, nitrocellulose base	133	1324
Extracts, flavouring, liquid	127	1197	Fire extinguisher charges, corrosive liquid	154	1774
Fabrics, animal or vegetable or synthetic, n.o.s. with oil	133	1373	Fire extinguishers with compressed gas	126	1044
Fabrics impregnated with weakly nitrated Nitrocellulose, n.o.s.	133	1353	Fire extinguishers with liquefied gas	126	1044
Ferric arsenate	151	1606	Firelighters, solid, with flammable liquid	133	2623
Ferric arsenite	151	1607	First aid kit	171	3316
Ferric chloride	157	1773	Fish meal, stabilized	171	2216
Ferric chloride, anhydrous	157	1773	Fish meal, unstabilized	133	1374
Ferric chloride, solution	154	2582	Fish scrap, stabilized	171	2216
Ferric nitrate	140	1466	Fish scrap, unstabilized	133	1374
Ferrocium	170	1323	Flammable liquid, corrosive, n.o.s	132	2924
Ferrosilicon	139	1408	Flammable liquid, n.o.s.	128	1993
Ferrous arsenate	151	1608	Flammable liquid, poisonous, corrosive, n.o.s.	131	3286
Ferrous chloride, solid	154	1759	Flammable liquid, poisonous, n.o.s.	131	1992
Ferrous chloride, solution	154	1760	Flammable liquid, toxic, corrosive, n.o.s.	131	3286
Ferrous metal borings, shavings, turnings or cuttings	170	2793	Flammable liquid, toxic, n.o.s.	131	1992
Fertilizer, ammoniating solution, with free Ammonia	125	1043	Flammable solid, corrosive, inorganic, n.o.s.	134	3180
Fiber, animal or vegetable, n.o.s., burnt, wet or damp	133	1372	Flammable solid, corrosive, n.o.s.	134	2925
Fibers, animal or vegetable or synthetic, n.o.s. with oil	133	1373	Flammable solid, corrosive, organic, n.o.s.	134	2925
Fibers, animal or vegetable, burnt, wet or damp	133	1372			
Fibers, vegetable, dry	133	3360			
Fibers impregnated with weakly nitrated Nitrocellulose, n.o.s.	133	1353			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Flammable solid, inorganic, corrosive, n.o.s.	134	3180	Fluosilicic acid	154	1778
Flammable solid, inorganic, n.o.s.	133	3178	Formaldehyde, solution, flammable	132	1198
Flammable solid, n.o.s.	133	1325	Formaldehyde, solutions (Formalin)	132	1198
Flammable solid, organic, molten, n.o.s.	133	3176	Formaldehyde, solutions (Formalin) (corrosive)	132	2209
Flammable solid, organic, n.o.s.	133	1325	Formic acid	153	1779
Flammable solid, oxidizing, n.o.s.	140	3097	Formic acid, with more than 85% acid	153	1779
Flammable solid, poisonous, inorganic, n.o.s.	134	3179	Formic acid, with not less than 5% but less than 10% acid	153	3412
Flammable solid, poisonous, n.o.s.	134	2926	Formic acid, with not less than 10% but not more than 85% acid	153	3412
Flammable solid, poisonous, organic, n.o.s.	134	2926	Fuel, aviation, turbine engine	128	1863
Flammable solid, toxic, inorganic, n.o.s.	134	3179	Fuel cell cartridges contained in equipment, containing corrosive substances	153	3477
Flammable solid, toxic, organic, n.o.s.	134	2926	Fuel cell cartridges contained in equipment, containing flammable liquids	128	3473
Fluoboric acid	154	1775	Fuel cell cartridges contained in equipment, containing hydrogen in metal hydride	115	3479
Fluorine	124	1045	Fuel cell cartridges contained in equipment, containing liquefied flammable gas	115	3478
Fluorine, compressed	124	1045	Fuel cell cartridges contained in equipment, containing water-reactive substances	138	3476
Fluorine, refrigerated liquid (cryogenic liquid)	167	9192	Fuel cell cartridges, containing corrosive substances	153	3477
Fluoroacetic acid	154	2642	Fuel cell cartridges, containing flammable liquids	128	3473
Fluoroanilines	153	2941	Fuel cell cartridges, containing hydrogen in metal hydride	115	3479
Fluorobenzene	130	2387	Fuel cell cartridges, containing liquefied flammable gas	115	3478
Fluoroboric acid	154	1775			
Fluorophosphoric acid, anhydrous	154	1776			
Fluorosilicates, n.o.s.	151	2856			
Fluorosilicic acid	154	1778			
Fluorosulfonic acid	137	1777			
Fluorosulphonic acid	137	1777			
Fluorotoluenes	130	2388			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Fuel cell cartridges, containing water-reactive substances	138	3476	Gas, refrigerated liquid, oxidizing, n.o.s.	122	3311
Fuel cell cartridges packed with equipment, containing corrosive substances	153	3477	Gas cartridges	115	2037
Fuel cell cartridges packed with equipment, containing flammable liquids	128	3473	Gas generator assemblies	171	8013
Fuel cell cartridges packed with equipment, containing hydrogen in metal hydride	115	3479	Gas identification set	123	9035
Fuel cell cartridges packed with equipment, containing liquefied flammable gas	115	3478	Gasohol	128	1203
Fuel cell cartridges packed with equipment, containing water-reactive substances	138	3476	Gas oil	128	1202
Fuel oil	128	1202	Gasoline	128	1203
Fuel oil	128	1993	Gasoline and ethanol mixture, with more than 10% ethanol	127	3475
Fuel oil, no. 1,2,4,5,6	128	1202	Gas sample, non-pressurized, flammable, n.o.s., not refrigerated liquid	115	3167
Fumaryl chloride	156	1780	Gas sample, non-pressurized, poisonous, flammable, n.o.s., not refrigerated liquid	119	3168
Fumigated unit	171	3359	Gas sample, non-pressurized, poisonous, n.o.s., not refrigerated liquid	123	3169
Furaldehydes	132P	1199	Gas sample, non-pressurized, toxic, flammable, n.o.s., not refrigerated liquid	119	3168
Furan	128	2389	Gas sample, non-pressurized, toxic, n.o.s., not refrigerated liquid	123	3169
Furfural	132P	1199	GB	153	2810
Furfuraldehydes	132P	1199	GD	153	2810
Furfuryl alcohol	153	2874	Genetically modified micro-organisms	171	3245
Furfurylamine	132	2526	Genetically modified organisms	171	3245
Fusee (rail or highway)	133	1325	Germane	119	2192
Fusel oil	127	1201	GF	153	2810
GA	153	2810	Glycerol alpha-monochlorohydrin	153	2689
Gallium	172	2803	Glycidaldehyde	131P	2622
Gas, refrigerated liquid, flammable, n.o.s.	115	3312	Guanidine nitrate	143	1467
Gas, refrigerated liquid, n.o.s.	120	3158			

Name of Material	Guide No.	ID No.
<b>H</b>	<b>153</b>	<b>2810</b>
Hafnium powder, dry	135	2545
Hafnium powder, wetted with not less than 25% water	170	1326
Halogenated irritating liquid, n.o.s.	159	1610
Hay, wet, damp or contaminated with oil	133	1327
Hazardous waste, liquid, n.o.s.	171	3082
Hazardous waste, solid, n.o.s.	171	3077
<b>HD</b>	<b>153</b>	<b>2810</b>
Heating oil, light	128	1202
Heat producing article	171	8038
Helium	121	1046
Helium, compressed	121	1046
Helium, refrigerated liquid (cryogenic liquid)	120	1963
Heptafluoropropane	126	3296
n-Heptaldehyde	129	3056
Heptanes	128	1206
n-Heptene	128	2278
Hexachloroacetone	153	2661
Hexachlorobenzene	152	2729
Hexachlorobutadiene	151	2279
<b>Hexachlorocyclopentadiene</b>	<b>151</b>	<b>2646</b>
Hexachlorophene	151	2875
<b>Hexadecyltrichlorosilane</b>	<b>156</b>	<b>1781</b>
Hexadiene	130	2458
Hexaethyl tetraphosphate	151	1611
Hexaethyl tetraphosphate, liquid	151	1611
Hexaethyl tetraphosphate, solid	151	1611
<b>Hexaethyl tetraphosphate and compressed gas mixture</b>	<b>123</b>	<b>1612</b>
<b>Hexafluoroacetone</b>	<b>125</b>	<b>2420</b>

Name of Material	Guide No.	ID No.
Hexafluoroacetone hydrate	151	2552
Hexafluoroacetone hydrate, liquid	151	2552
Hexafluoroacetone hydrate, solid	151	3436
Hexafluoroethane	126	2193
Hexafluoroethane, compressed	126	2193
Hexafluorophosphoric acid	154	1782
Hexafluoropropylene	126	1858
Hexafluoropropylene oxide	126	1956
Hexaldehyde	130	1207
Hexamethylenediamine, solid	153	2280
Hexamethylenediamine, solution	153	1783
Hexamethylene diisocyanate	156	2281
Hexamethyleneimine	132	2493
Hexamethylenetetramine	133	1328
Hexamine	133	1328
Hexanes	128	1208
Hexanoic acid	153	2829
Hexanols	129	2282
1-Hexene	128	2370
<b>Hexyltrichlorosilane</b>	<b>156</b>	<b>1784</b>
<b>HL</b>	<b>153</b>	<b>2810</b>
<b>HN-1</b>	<b>153</b>	<b>2810</b>
<b>HN-2</b>	<b>153</b>	<b>2810</b>
<b>HN-3</b>	<b>153</b>	<b>2810</b>
Hydrazine, anhydrous	132	2029
Hydrazine, aqueous solution, with more than 37% Hydrazine	153	2030
Hydrazine, aqueous solution, with not less than 37% but not more than 64% Hydrazine	153	2030

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Hydrazine, aqueous solution, with not more than 37% Hydrazine	152	3293	Hydrofluoric acid and Sulphuric acid mixture	157	1786
Hydrazine, aqueous solutions, with more than 64% Hydrazine	132	2029	Hydrofluorosilicic acid	154	1778
Hydrazine hydrate	153	2030	Hydrogen	115	1049
Hydrides, metal, n.o.s.	138	1409	Hydrogen absorbed in metal hydride	115	9279
Hydriodic acid	154	1787	Hydrogen, compressed	115	1049
Hydriodic acid, solution	154	1787	Hydrogen in a metal hydride storage system	115	3468
Hydrobromic acid	154	1788	Hydrogen in a metal hydride storage system contained in equipment	115	3468
Hydrobromic acid, solution	154	1788	Hydrogen in a metal hydride storage system packed with equipment	115	3468
Hydrocarbon gas, compressed, n.o.s.	115	1964	Hydrogen, refrigerated liquid (cryogenic liquid)	115	1966
Hydrocarbon gas, liquefied, n.o.s.	115	1965	Hydrogen and Carbon monoxide mixture	119	2600
Hydrocarbon gas mixture, compressed, n.o.s.	115	1964	Hydrogen and Carbon monoxide mixture, compressed	119	2600
Hydrocarbon gas mixture, liquefied, n.o.s.	115	1965	Hydrogen and Methane mixture, compressed	115	2034
Hydrocarbon gas refills for small devices, with release device	115	3150	Hydrogen bromide, anhydrous	125	1048
Hydrocarbons, liquid, n.o.s.	128	3295	Hydrogen chloride, anhydrous	125	1050
Hydrochloric acid	157	1789	Hydrogen chloride, refrigerated liquid	125	2186
Hydrochloric acid, solution	157	1789	Hydrogen cyanide, anhydrous, stabilized	117	1051
Hydrocyanic acid, aqueous solution, with less than 5% Hydrogen cyanide	154	1613	Hydrogen cyanide, aqueous solution, with not more than 20% Hydrogen cyanide	154	1613
Hydrocyanic acid, aqueous solution, with not more than 20% Hydrogen cyanide	154	1613	Hydrogen cyanide, solution in alcohol, with not more than 45% Hydrogen cyanide	131	3294
Hydrocyanic acid, aqueous solutions, with more than 20% Hydrogen cyanide	117	1051	Hydrogen cyanide, stabilized	117	1051
Hydrofluoric acid	157	1790	Hydrogen cyanide, stabilized (absorbed)	152	1614
Hydrofluoric acid, solution	157	1790			
Hydrofluoric acid and Sulfuric acid mixture	157	1786			



Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Hydrogendifluorides, n.o.s.	154	1740	Hypochlorite solution, with more than 5% available Chlorine	154	1791
Hydrogendifluorides, solid, n.o.s.	154	1740	Hypochlorites, inorganic, n.o.s.	140	3212
Hydrogendifluorides, solution, n.o.s.	154	3471	3,3'-Iminodipropylamine	153	2269
Hydrogen fluoride, anhydrous	125	1052	Infectious substance, affecting animals only	158	2900
Hydrogen iodide, anhydrous	125	2197	Infectious substance, affecting humans	158	2814
Hydrogen peroxide, aqueous solution, stabilized, with more than 60% Hydrogen peroxide	143	2015	Ink, printer's, flammable	129	1210
Hydrogen peroxide, aqueous solution, with not less than 8% but less than 20% Hydrogen peroxide	140	2984	Insecticide gas, flammable, n.o.s.	115	1954
Hydrogen peroxide, aqueous solution, with not less than 20% but not more than 60% Hydrogen peroxide (stabilized as necessary)	140	2014	Insecticide gas, flammable, n.o.s.	115	3354
Hydrogen peroxide, stabilized	143	2015	Insecticide gas, n.o.s.	126	1968
Hydrogen peroxide and Peroxyacetic acid mixture, with acid(s), water and not more than 5% Peroxyacetic acid, stabilized	140	3149	Insecticide gas, poisonous, flammable, n.o.s.	119	3355
Hydrogen selenide, anhydrous	117	2202	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)	119	3355
Hydrogen sulfide	117	1053	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone B)	119	3355
Hydrogen sulphide	117	1053	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)	119	3355
Hydroquinone	153	2662	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone D)	119	3355
Hydroquinone, solid	153	2662	Insecticide gas, poisonous, n.o.s.	123	1967
Hydroquinone, solution	153	3435	Insecticide gas, toxic, flammable, n.o.s.	119	3355
1-Hydroxybenzotriazole, anhydrous, wetted with not less than 20% water	113	3474	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone A)	119	3355
Hydroxylamine sulfate	154	2865	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone B)	119	3355
Hydroxylamine sulphate	154	2865	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone C)	119	3355
Hypochlorite solution	154	1791			

Name of Material	Guide ID No.	ID No.	Name of Material	Guide ID No.	ID No.
Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone D)	119	3355	Isobutyric anhydride	132	2530
Insecticide gas, toxic, n.o.s.	123	1967	Isobutyronitrile	131	2284
Iodine monochloride	157	1792	Isobutryl chloride	132	2395
Iodine pentafluoride	144	2495	Isocyanate solution, flammable, poisonous, n.o.s.	155	2478
2-Iodobutane	129	2390	Isocyanate solution, flammable, toxic, n.o.s.	155	2478
Iodomethylpropanes	129	2391	Isocyanate solution, poisonous, flammable, n.o.s.	155	3080
Iodopropanes	129	2392	Isocyanate solution, poisonous, n.o.s.	155	2206
IPDI	156	2290	Isocyanate solution, toxic, flammable, n.o.s.	155	3080
Iron oxide, spent	135	1376	Isocyanate solution, toxic, n.o.s.	155	2206
Iron pentacarbonyl	131	1994	Isocyanate solutions, n.o.s.	155	2206
Iron sponge, spent	135	1376	Isocyanate solutions, n.o.s.	155	2478
Isobutane	115	1075	Isocyanate solutions, n.o.s.	155	3080
Isobutane	115	1969	Isocyanates, flammable, poisonous, n.o.s.	155	2478
Isobutane mixture	115	1075	Isocyanates, flammable, toxic, n.o.s.	155	2478
Isobutane mixture	115	1969	Isocyanates, n.o.s.	155	2206
Isobutanol	129	1212	Isocyanates, n.o.s.	155	2478
Isobutyl acetate	129	1213	Isocyanates, n.o.s.	155	3080
Isobutyl acrylate, stabilized	129P	2527	Isocyanates, poisonous, flammable, n.o.s.	155	3080
Isobutyl alcohol	129	1212	Isocyanates, poisonous, n.o.s.	155	2206
Isobutyl aldehyde	130	2045	Isocyanates, toxic, flammable, n.o.s.	155	3080
Isobutylamine	132	1214	Isocyanates, toxic, n.o.s.	155	2206
Isobutyl chloroformate	155	2742	Isocyanatobenzotrifluorides	156	2285
Isobutylene	115	1055	Isoheptenes	128	2287
Isobutylene	115	1075	Isohexenes	128	2288
Isobutyl formate	129	2393	Isooctane	128	1262
Isobutyl isobutyrate	130	2528	Isooctenes	128	1216
Isobutyl isocyanate	155	2486			
Isobutyl methacrylate, stabilized	130P	2283			
Isobutyl propionate	129	2394			
Isobutyraldehyde	130	2045			
Isobutyric acid	132	2529			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Isopentane	128	1265	Lead compound, soluble, n.o.s.	151	2291
Isopentenes	128	2371	Lead cyanide	151	1620
Isophoronediamine	153	2289	Lead dioxide	141	1872
Isophorone diisocyanate	156	2290	Lead nitrate	141	1469
Isoprene, stabilized	130P	1218	Lead perchlorate	141	1470
Isopropanol	129	1219	Lead perchlorate, solid	141	1470
Isopropenyl acetate	129P	2403	Lead perchlorate, solution	141	1470
Isopropenylbenzene	128	2303	Lead perchlorate, solution	141	3408
Isopropyl acetate	129	1220	Lead phosphite, dibasic	133	2989
Isopropyl acid phosphate	153	1793	Lead sulfate, with more than 3% free acid	154	1794
Isopropyl alcohol	129	1219	Lead sulphate, with more than 3% free acid	154	1794
Isopropylamine	132	1221	Lewisite	153	2810
Isopropylbenzene	130	1918	Life-saving appliances, not self-inflating	171	3072
Isopropyl butyrate	129	2405	Life-saving appliances, self-inflating	171	2990
Isopropyl chloroacetate	155	2947	Lighter refills (cigarettes) (flammable gas)	115	1057
Isopropyl chloroformate	155	2407	Lighters (cigarettes) (flammable gas)	115	1057
Isopropyl 2-chloropropionate	129	2934	Lighters for cigars, cigarettes (flammable liquid)	128	1226
Isopropyl isobutyrate	127	2406	Liquefied gas, flammable, n.o.s.	115	3161
Isopropyl isocyanate	155	2483	Liquefied gas, n.o.s.	126	3163
Isopropyl nitrate	130	1222	Liquefied gas, oxidizing, n.o.s.	122	3157
Isopropyl propionate	129	2409	Liquefied gas, poisonous, corrosive, n.o.s.	123	3308
Isosorbide dinitrate mixture	133	2907	Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone A)	123	3308
Isosorbide-5-mononitrate	133	3251	Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone B)	123	3308
Kerosene	128	1223	L (Lewisite)	153	2810
Ketones, liquid, n.o.s.	127	1224	Lead acetate	151	1616
Krypton	121	1056	Lead arsenates	151	1617
Krypton, compressed	121	1056	Lead arsenites	151	1618
Krypton, refrigerated liquid (cryogenic liquid)	120	1970			

Name of Material	Guide ID No.	ID No.	Name of Material	Guide ID No.	ID No.
Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone C)	123	3308	Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone C)	123	3162
Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone D)	123	3308	Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone D)	123	3162
Liquefied gas, poisonous, flammable, corrosive, n.o.s.	119	3309	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s.	124	3310
Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)	119	3309	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)	124	3310
Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)	119	3309	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone B)	124	3310
Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)	119	3309	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)	124	3310
Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)	119	3309	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)	124	3310
Liquefied gas, poisonous, flammable, n.o.s.	119	3160	Liquefied gas, poisonous, oxidizing, n.o.s.	124	3307
Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)	119	3160	Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone A)	124	3307
Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone B)	119	3160	Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone B)	124	3307
Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)	119	3160	Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone C)	124	3307
Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone D)	119	3160	Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone D)	124	3307
Liquefied gas, poisonous, n.o.s.	123	3162	Liquefied gas, toxic, corrosive, n.o.s.	123	3308
Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone A)	123	3162	Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone A)	123	3308
Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone B)	123	3162	Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone B)	123	3308

Name of Material	Guide ID No.	ID No.
Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone C)	123	3308
Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone D)	123	3308
Liquefied gas, toxic, flammable, corrosive, n.o.s.	119	3309
Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)	119	3309
Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)	119	3309
Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)	119	3309
Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)	119	3309
Liquefied gas, toxic, flammable, n.o.s.	119	3160
Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone A)	119	3160
Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone B)	119	3160
Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone C)	119	3160
Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone D)	119	3160
Liquefied gas, toxic, n.o.s.	123	3162
Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone A)	123	3162
Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone B)	123	3162

Name of Material	Guide ID No.	ID No.
Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone C)	123	3162
Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone D)	123	3162
Liquefied gas, toxic, oxidizing, corrosive, n.o.s.	124	3310
Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)	124	3310
Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone B)	124	3310
Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)	124	3310
Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)	124	3310
Liquefied gas, toxic, oxidizing, n.o.s.	124	3307
Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone A)	124	3307
Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone B)	124	3307
Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone C)	124	3307
Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone D)	124	3307
Liquefied gases, non-flammable, charged with Nitrogen, Carbon dioxide or Air	120	1058
Liquefied natural gas (cryogenic liquid)	115	1972
Liquefied petroleum gas	115	1075
Lithium	138	1415

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Lithium alkyls	135	2445	Lithium metal batteries	138	3091
Lithium alkyls, liquid	135	2445	contained in equipment (including lithium alloy batteries)		
Lithium alkyls, solid	135	3433	Lithium metal batteries	138	3090
Lithium aluminum hydride	138	1410	(including lithium alloy batteries)		
Lithium aluminum hydride, ethereal	138	1411	Lithium metal batteries packed with equipment (including lithium alloy batteries)	138	3091
Lithium amide	139	1412	Lithium nitrate	140	2722
Lithium batteries	138	3090	Lithium nitride	138	2806
Lithium batteries, liquid or solid cathode	138	3090	Lithium peroxide	143	1472
Lithium batteries contained in equipment	138	3091	Lithium silicon	138	1417
Lithium batteries packed with equipment	138	3091	LNG (cryogenic liquid)	115	1972
Lithium borohydride	138	1413	London purple	151	1621
Lithium ferrosilicon	139	2830	LPG	115	1075
Lithium hydride	138	1414	Magnesium	138	1869
Lithium hydride, fused solid	138	2805	Magnesium, in pellets, turnings or ribbons	138	1869
Lithium hydroxide	154	2680	Magnesium alkyls	135	3053
Lithium hydroxide, monohydrate	154	2680	Magnesium alloys, with more than 50% Magnesium, in pellets, turnings or ribbons	138	1869
Lithium hydroxide, solid	154	2680	Magnesium alloys powder	138	1418
Lithium hydroxide, solution	154	2679	Magnesium aluminum phosphide	139	1419
Lithium hypochlorite, dry	140	1471	Magnesium arsenate	151	1622
Lithium hypochlorite mixture	140	1471	Magnesium bromate	140	1473
Lithium hypochlorite mixtures, dry	140	1471	Magnesium chlorate	140	2723
Lithium ion batteries contained in equipment (including lithium ion polymer batteries)	147	3481	Magnesium chloride and Chlorate mixture	140	1459
Lithium ion batteries (including lithium ion polymer batteries)	147	3480	Magnesium chloride and Chlorate mixture, solid	140	1459
Lithium ion batteries packed with equipment (including lithium ion polymer batteries)	147	3481	Magnesium chloride and Chlorate mixture, solution	140	3407
			Magnesium diamide	135	2004
			Magnesium diphenyl	135	2005

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Magnesium fluorosilicate	151	2853	Medicine, liquid, toxic, n.o.s.	151	1851
Magnesium granules, coated	138	2950	Medicine, solid, poisonous, n.o.s.	151	3249
Magnesium hydride	138	2010	Medicine, solid, toxic, n.o.s.	151	3249
Magnesium nitrate	140	1474	Medicines, corrosive, liquid, n.o.s.	154	1760
Magnesium perchlorate	140	1475	Medicines, corrosive, solid, n.o.s.	154	1759
Magnesium peroxide	140	1476	Medicines, flammable, liquid, n.o.s.	128	1993
Magnesium phosphide	139	2011	Medicines, flammable, solid, n.o.s.	133	1325
Magnesium powder	138	1418	Mercaptan mixture, liquid, flammable, n.o.s.	130	3336
Magnesium silicide	138	2624	Mercaptan mixture, liquid, flammable, poisonous, n.o.s.	131	1228
Magnesium silicofluoride	151	2853	Mercaptan mixture, liquid, flammable, toxic, n.o.s.	131	1228
Magnetized material	171	2807	Mercaptan mixture, liquid, poisonous, flammable, n.o.s.	131	3071
Maleic acid	156	2215	Mercaptan mixture, liquid, toxic, flammable, n.o.s.	131	3071
Maleic anhydride	156	2215	Mercaptans, liquid, flammable, n.o.s.	130	3336
Maleic anhydride, molten	156	2215	Mercaptans, liquid, flammable, poisonous, n.o.s.	131	1228
Malononitrile	153	2647	Mercaptans, liquid, flammable, toxic, n.o.s.	131	1228
Maneb	135	2210	Mercaptans, liquid, toxic, flammable, n.o.s.	131	3071
Maneb, stabilized	135	2968	Mercaptans, liquid, toxic, flammable, n.o.s.	131	3071
Maneb preparation, stabilized	135	2968	Mercaptans, liquid, toxic, flammable, n.o.s.	131	3071
Maneb preparation, with not less than 60% Maneb	135	2210	Mercaptans, liquid, toxic, flammable, n.o.s.	131	3071
Manganese nitrate	140	2724	Mercuric arsenate	151	1623
Manganese resinate	133	1330	Mercuric bromide	154	1634
Matches, fusee	133	2254	Mercuric chloride	154	1624
Matches, safety	133	1944	Mercuric cyanide	154	1636
Matches, "strike anywhere"	133	1331	Mercuric nitrate	141	1625
Matches, wax "vesta"	133	1945			
MD	152	1556			
Medical waste, n.o.s.	158	3291			
Medicine, liquid, flammable, poisonous, n.o.s.	131	3248			
Medicine, liquid, flammable, toxic, n.o.s.	131	3248			
Medicine, liquid, poisonous, n.o.s.	151	1851			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Mercuric oxycyanide	151	1642	Mercury oxide	151	1641
Mercuric potassium cyanide	157	1626	Mercury oxycyanide, desensitized	151	1642
Mercuric sulfate	151	1645	Mercury potassium iodide	151	1643
Mercuric sulphate	151	1645	Mercury salicylate	151	1644
Mercurous bromide	154	1634	Mercury sulfate	151	1645
Mercurous nitrate	141	1627	Mercury sulphate	151	1645
Mercury	172	2809	Mercury thiocyanate	151	1646
Mercury acetate	151	1629	Mesityl oxide	129	1229
Mercury ammonium chloride	151	1630	Metal alkyl, solution, n.o.s.	135	9195
Mercury based pesticide, liquid, flammable, poisonous	131	2778	Metal alkyl halides, n.o.s.	138	3049
Mercury based pesticide, liquid, flammable, toxic	131	2778	Metal alkyl halides, water-reactive, n.o.s.	138	3049
Mercury based pesticide, liquid, poisonous	151	3012	Metal alkyl hydrides, n.o.s.	138	3050
Mercury based pesticide, liquid, poisonous, flammable	131	3011	Metal alkyl hydrides, water-reactive, n.o.s.	138	3050
Mercury based pesticide, liquid, toxic	151	3012	Metal alkyls, n.o.s.	135	2003
Mercury based pesticide, liquid, toxic, flammable	131	3011	Metal alkyls, water-reactive, n.o.s.	135	2003
Mercury based pesticide, solid, poisonous	151	2777	Metal aryl halides, n.o.s.	138	3049
Mercury based pesticide, solid, toxic	151	2777	Metal aryl halides, water-reactive, n.o.s.	138	3049
Mercury benzoate	154	1631	Metal aryl hydrides, n.o.s.	138	3050
Mercury bromides	154	1634	Metal aryl hydrides, water-reactive, n.o.s.	138	3050
Mercury compound, liquid, n.o.s.	151	2024	Metal aryls, n.o.s.	135	2003
Mercury compound, solid, n.o.s.	151	2025	Metal aryls, water-reactive, n.o.s.	135	2003
Mercury cyanide	154	1636	Metal carbonyls, liquid, n.o.s.	151	3281
Mercury gluconate	151	1637	Metal carbonyls, n.o.s.	151	3281
Mercury iodide	151	1638	Metal carbonyls, solid, n.o.s.	151	3466
Mercury metal	172	2809	Metal catalyst, dry	135	2881
Mercury nucleate	151	1639	Metal catalyst, wetted	170	1378
Mercury oleate	151	1640	Metaldehyde	133	1332
			Metal hydrides, flammable, n.o.s.	170	3182



Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Metal hydrides, water-reactive, n.o.s.	138	1409	Methylamine, anhydrous	118	1061
Metallic substance, water-reactive, n.o.s.	138	3208	Methylamine, aqueous solution	132	1235
Metallic substance, water-reactive, self-heating, n.o.s.	138	3209	Methylamyl acetate	130	1233
Metal powder, flammable, n.o.s.	170	3089	Methylamyl alcohol	129	2053
Metal powder, self-heating, n.o.s.	135	3189	Methyl amyl ketone	127	1110
Metal salts of organic compounds, flammable, n.o.s.	133	3181	N-Methylaniline	153	2294
Methacrylaldehyde, stabilized	131P	2396	Methyl benzoate	152	2938
Methacrylic acid, stabilized	153P	2531	alpha-Methylbenzyl alcohol	153	2937
Methacrylonitrile, stabilized	131P	3079	alpha-Methylbenzyl alcohol, liquid	153	2937
Methallyl alcohol	129	2614	alpha-Methylbenzyl alcohol, solid	153	3438
Methane	115	1971	Methylbenzyl alcohol (alpha)	153	2937
Methane, compressed	115	1971	Methyl bromide	123	1062
Methane, refrigerated liquid (cryogenic liquid)	115	1972	Methyl bromide and Chloropicrin mixture	123	1581
Methane and Hydrogen mixture, compressed	115	2034	Methyl bromide and Ethylene dibromide mixture, liquid	151	1647
Methanesulfonyl chloride	156	3246	Methyl bromoacetate	155	2643
Methanesulphonyl chloride	156	3246	2-Methylbutanal	129	3371
Methanol	131	1230	3-Methylbutan-2-one	127	2397
Methoxymethyl isocyanate	155	2605	2-Methyl-1-butene	128	2459
4-Methoxy-4-methyl-pentan-2-one	128	2293	2-Methyl-2-butene	128	2460
1-Methoxy-2-propanol	129	3092	3-Methyl-1-butene	128	2561
Methyl acetate	129	1231	N-Methylbutylamine	132	2945
Methylacetylene and Propadiene mixture, stabilized	116P	1060	Methyl tert-butyl ether	127	2398
Methyl acrylate, stabilized	129P	1919	Methyl butyrate	129	1237
Methylal	127	1234	Methyl chloride	115	1063
Methyl alcohol	131	1230	Methyl chloride and Chloropicrin mixture	119	1582
Methylallyl chloride	130P	2554	Methyl chloride and Methylene chloride mixture	115	1912
			Methyl chloroacetate	155	2295
			Methyl chloroformate	155	1238

Name of Material	Guide No.	ID No.
Methyl chloromethyl ether	131	1239
Methyl 2-chloropropionate	129	2933
Methylchlorosilane	119	2534
Methyl cyanide	127	1648
Methylcyclohexane	128	2296
Methylcyclohexanols	129	2617
Methylcyclohexanone	128	2297
Methylcyclopentane	128	2298
Methyl dichloroacetate	155	2299
Methyldichloroarsine	152	1556
Methyldichlorosilane	139	1242
Methylene chloride	160	1593
Methylene chloride and Methyl chloride mixture	115	1912
Methyl ethyl ether	115	1039
Methyl ethyl ketone	127	1193
2-Methyl-5-ethylpyridine	153	2300
Methyl fluoride	115	2454
Methyl formate	129	1243
2-Methylfuran	128	2301
2-Methyl-2-heptanethiol	131	3023
5-Methylhexan-2-one	127	2302
Methylhydrazine	131	1244
Methyl iodide	151	2644
Methyl isobutyl carbinol	129	2053
Methyl isobutyl ketone	127	1245
Methyl isocyanate	155	2480
Methyl isopropenyl ketone, stabilized	127P	1246
Methyl isothiocyanate	131	2477
Methyl isovalerate	130	2400
Methyl magnesium bromide in Ethyl ether	135	1928

Name of Material	Guide No.	ID No.
Methyl mercaptan	117	1064
Methyl methacrylate monomer, stabilized	129P	1247
4-Methylmorpholine	132	2535
N-Methylmorpholine	132	2535
Methylmorpholine	132	2535
Methyl nitrite	116	2455
Methyl orthosilicate	155	2606
Methyl parathion, liquid	152	3018
Methyl parathion, solid	152	2783
Methylpentadiene	128	2461
2-Methylpentan-2-ol	129	2560
Methylphenyldichlorosilane	156	2437
Methyl phosphonic dichloride	137	9206
Methyl phosphonous dichloride	135	2845
1-Methylpiperidine	132	2399
Methyl propionate	129	1248
Methyl propyl ether	127	2612
Methyl propyl ketone	127	1249
Methyltetrahydrofuran	127	2536
Methyl trichloroacetate	156	2533
Methyltrichlorosilane	155	1250
alpha-Methylvaleraldehyde	130	2367
Methyl valeraldehyde (alpha)	130	2367
Methyl vinyl ketone, stabilized	131P	1251
M.I.B.C.	129	2053
Molybdenum pentachloride	156	2508
Monoethanolamine	153	2491
Mononitrotoluidines	153	2660
Monopropylamine	132	1277
Morpholine	132	2054
Motor fuel anti-knock mixture	131	1649
Motor spirit	128	1203

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Motor spirit and ethanol mixture, with more than 10% ethanol	127	3475	Nicotine compound, liquid, n.o.s.	151	3144
Muriatic acid	157	1789	Nicotine compound, solid, n.o.s.	151	1655
Musk xylene	149	2956	Nicotine hydrochloride	151	1656
Mustard	153	2810	Nicotine hydrochloride, liquid	151	1656
Mustard Lewisite	153	2810	Nicotine hydrochloride, solid	151	1656
Naphthalene, crude	133	1334	Nicotine hydrochloride, solid	151	3444
Naphthalene, molten	133	2304	Nicotine hydrochloride, solution	151	1656
Naphthalene, refined	133	1334	Nicotine preparation, liquid, n.o.s.	151	3144
alpha-Naphthylamine	153	2077	Nicotine preparation, solid, n.o.s.	151	1655
Naphthylamine (alpha)	153	2077	Nicotine salicylate	151	1657
beta-Naphthylamine	153	1650	Nicotine sulfate, solid	151	1658
beta-Naphthylamine, solid	153	1650	Nicotine sulfate, solid	151	3445
beta-Naphthylamine, solution	153	3411	Nicotine sulfate, solution	151	1658
Naphthylamine (beta)	153	1650	Nicotine sulphate, solid	151	1658
Naphthylamine (beta), solid	153	1650	Nicotine sulphate, solid	151	3445
Naphthylamine (beta), solution	153	3411	Nicotine sulphate, solution	151	1658
Naphthylthiourea	153	1651	Nicotine tartrate	151	1659
Naphthylurea	153	1652	Nitrates, inorganic, aqueous solution, n.o.s.	140	3218
Natural gas, compressed	115	1971	Nitrates, inorganic, n.o.s.	140	1477
Natural gas, refrigerated liquid (cryogenic liquid)	115	1972	Nitrating acid mixture	157	1796
Neohexane	128	1208	Nitrating acid mixture, spent	157	1826
Neon	121	1065	Nitric acid, fuming	157	2032
Neon, compressed	121	1065	Nitric acid, other than red fuming	157	2031
Neon, refrigerated liquid (cryogenic liquid)	120	1913	Nitric acid, red fuming	157	2032
Nickel carbonyl	131	1259	Nitric oxide	124	1660
Nickel catalyst, dry	135	2881	Nitric oxide, compressed	124	1660
Nickel cyanide	151	1653	Nitric oxide and Dinitrogen tetroxide mixture	124	1975
Nickel nitrate	140	2725	Nitric oxide and Nitrogen dioxide mixture	124	1975
Nickel nitrite	140	2726			
Nicotine	151	1654			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Nitric oxide and Nitrogen tetroxide mixture	124	1975	Nitrocellulose mixture, without pigment	133	2557
Nitriles, flammable, poisonous, n.o.s.	131	3273	Nitrocellulose mixture, without plasticizer	133	2557
Nitriles, flammable, toxic, n.o.s.	131	3273	Nitrocellulose mixture, with pigment	133	2557
Nitriles, poisonous, flammable, n.o.s.	131	3275	Nitrocellulose mixture, with pigment and plasticizer	133	2557
Nitriles, poisonous, liquid, n.o.s.	151	3276	Nitrocellulose mixture, with plasticizer	133	2557
Nitriles, poisonous, n.o.s.	151	3276	Nitrocellulose, solution, flammable	127	2059
Nitriles, poisonous, solid, n.o.s.	151	3439	Nitrocellulose, solution, in a flammable liquid	127	2059
Nitriles, toxic, flammable, n.o.s.	131	3275	Nitrocellulose with alcohol	113	2556
Nitriles, toxic, liquid, n.o.s.	151	3276	Nitrocellulose with not less than 25% alcohol	113	2556
Nitriles, toxic, n.o.s.	151	3276	Nitrocellulose with water, not less than 25% water	113	2555
Nitriles, toxic, solid, n.o.s.	151	3439	3-Nitro-4-chlorobenzotrifluoride	152	2307
Nitrites, inorganic, aqueous solution, n.o.s.	140	3219	Nitrocresols	153	2446
Nitrites, inorganic, n.o.s.	140	2627	Nitrocresols, liquid	153	3434
Nitroanilines	153	1661	Nitrocresols, solid	153	2446
Nitroanisoles	152	2730	Nitroethane	129	2842
Nitroanisoles, liquid	152	2730	Nitrogen	121	1066
Nitroanisoles, solid	152	2730	Nitrogen, compressed	121	1066
Nitroanisoles, solid	152	3458	Nitrogen, refrigerated liquid (cryogenic liquid)	120	1977
Nitrobenzene	152	1662	Nitrogen and Rare gases mixture	121	1981
Nitrobenzenesulfonic acid	153	2305	Nitrogen and Rare gases mixture, compressed	121	1981
Nitrobenzenesulphonic acid	153	2305	Nitrogen dioxide	124	1067
Nitrobenzotrifluorides	152	2306	Nitrogen dioxide and Nitric oxide mixture	124	1975
Nitrobenzotrifluorides, liquid	152	2306	Nitrogen tetroxide and Nitric oxide mixture	124	1975
Nitrobenzotrifluorides, solid	152	3431			
Nitrobromobenzenes	152	2732			
Nitrobromobenzenes, liquid	152	2732			
Nitrobromobenzenes, solid	152	2732			
Nitrobromobenzenes, solid	152	3459			
Nitrocellulose	133	2557			
Nitrocellulose membrane filters	133	3270			

Name of Material	Guide ID No.	ID No.	Name of Material	Guide ID No.	ID No.
Nitrogen trifluoride	122	2451	Nitrostarch, wetted with not less than 20% water	113	1337
Nitrogen trifluoride, compressed	122	2451	Nitrostarch, wetted with not less than 30% solvent	113	1337
Nitrogen trioxide	124	2421	Nitrosyl chloride	125	1069
Nitroglycerin, solution in alcohol, with more than 1% but not more than 5% Nitroglycerin	127	3064	Nitrosylsulfuric acid	157	2308
Nitroglycerin, solution in alcohol, with not more than 1% Nitroglycerin	127	1204	Nitrosylsulfuric acid, liquid	157	2308
Nitroglycerin mixture, desensitized, liquid, flammable, n.o.s., with not more than 30% Nitroglycerin	113	3343	Nitrosylsulfuric acid, solid	157	2308
Nitroglycerin mixture, desensitized, liquid, n.o.s., with not more than 30% Nitroglycerin	113	3357	Nitrosylsulfuric acid, solid	157	3456
Nitroglycerin mixture, desensitized, solid, n.o.s., with more than 2% but not more than 10% Nitroglycerin	113	3319	Nitrosylsulphuric acid	157	2308
Nitroglycerin mixture with more than 2% but not more than 10% Nitroglycerin, desensitized	113	3319	Nitrosylsulphuric acid, liquid	157	2308
Nitroguanidine (Picrite), wetted with not less than 20% water	113	1336	Nitrosylsulphuric acid, solid	157	2308
Nitroguanidine, wetted with not less than 20% water	113	1336	Nitrotoluenes	152	1664
Nitrohydrochloric acid	157	1798	Nitrotoluenes, liquid	152	1664
Nitromethane	129	1261	Nitrotoluenes, solid	152	1664
Nitronaphthalene	133	2538	Nitrotoluenes, solid	152	3446
Nitrophenols	153	1663	Nitrotoluidines (mono)	153	2660
4-Nitrophenylhydrazine, with not less than 30% water	113	3376	Nitrous oxide	122	1070
Nitropropanes	129	2608	Nitrous oxide, compressed	122	1070
p-Nitrosodimethylaniline	135	1369	Nitrous oxide, refrigerated liquid	122	2201
			Nitrous oxide and Carbon dioxide mixture	126	1015
			Nitroxylenes	152	1665
			Nitroxylenes, liquid	152	1665
			Nitroxylenes, solid	152	1665
			Nitroxylenes, solid	152	3447
			Nonanes	128	1920
			Nonyltrichlorosilane	156	1799
			2,5-Norbornadiene, stabilized	128P	2251
			Octadecyltrichlorosilane	156	1800
			Octadiene	128P	2309
			Octafluorobut-2-ene	126	2422

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Octafluorocyclobutane	126	1976	Organic peroxide type F, liquid, temperature controlled	148	3119
Octafluoropropane	126	2424	Organic peroxide type F, solid	145	3110
Octanes	128	1262	Organic peroxide type F, solid, temperature controlled	148	3120
Octyl aldehydes	129	1191	Organic phosphate compound mixed with compressed gas	123	1955
tert-Octyl mercaptan	131	3023	Organic phosphate mixed with compressed gas	123	1955
Octyltrichlorosilane	156	1801	Organic phosphorus compound mixed with compressed gas	123	1955
Oil, petroleum	128	1270	Organic pigments, self-heating	135	3313
Oil gas	119	1071	Organoarsenic compound, liquid, n.o.s.	151	3280
Oil gas, compressed	119	1071	Organoarsenic compound, n.o.s.	151	3280
Organic peroxide type B, liquid	146	3101	Organic peroxide type B, liquid, temperature controlled	148	3111
Organic peroxide type B, liquid, temperature controlled	148	3111	Organic peroxide type B, solid	146	3102
Organic peroxide type B, solid	146	3102	Organic peroxide type B, solid, temperature controlled	148	3112
Organic peroxide type B, solid, temperature controlled	148	3112	Organic peroxide type C, liquid	146	3103
Organic peroxide type C, liquid	146	3103	Organic peroxide type C, liquid, temperature controlled	148	3113
Organic peroxide type C, liquid, temperature controlled	148	3113	Organic peroxide type C, solid	146	3104
Organic peroxide type C, solid	146	3104	Organic peroxide type C, solid, temperature controlled	148	3114
Organic peroxide type C, solid, temperature controlled	148	3114	Organic peroxide type D, liquid	145	3105
Organic peroxide type D, liquid	145	3105	Organic peroxide type D, liquid, temperature controlled	148	3115
Organic peroxide type D, liquid, temperature controlled	148	3115	Organic peroxide type D, solid	145	3106
Organic peroxide type D, solid	145	3106	Organic peroxide type D, solid, temperature controlled	148	3116
Organic peroxide type D, solid, temperature controlled	148	3116	Organic peroxide type E, liquid	145	3107
Organic peroxide type E, liquid	145	3107	Organic peroxide type E, liquid, temperature controlled	148	3117
Organic peroxide type E, liquid, temperature controlled	148	3117	Organic peroxide type E, solid	145	3108
Organic peroxide type E, solid	145	3108	Organic peroxide type E, solid, temperature controlled	148	3118
Organic peroxide type E, solid, temperature controlled	148	3118	Organic peroxide type F, liquid	145	3109
Organic peroxide type F, liquid	145	3109	Organic peroxide type F, liquid, temperature controlled	148	3109
			Organic peroxide type F, solid	145	3110
			Organic peroxide type F, solid, temperature controlled	148	3120
			Organic phosphate compound mixed with compressed gas	123	1955
			Organic phosphate mixed with compressed gas	123	1955
			Organic phosphorus compound mixed with compressed gas	123	1955
			Organic pigments, self-heating	135	3313
			Organoarsenic compound, liquid, n.o.s.	151	3280
			Organoarsenic compound, n.o.s.	151	3280
			Organoarsenic compound, solid, n.o.s.	151	3465
			Organochlorine pesticide, liquid, flammable, poisonous	131	2762
			Organochlorine pesticide, liquid, flammable, toxic	131	2762
			Organochlorine pesticide, liquid, poisonous	151	2996
			Organochlorine pesticide, liquid, poisonous, flammable	131	2995
			Organochlorine pesticide, liquid, toxic	151	2996
			Organochlorine pesticide, liquid, toxic, flammable	131	2995
			Organochlorine pesticide, solid, poisonous	151	2761
			Organochlorine pesticide, solid, toxic	151	2761
			Organometallic compound, poisonous, liquid, n.o.s.	151	3282
			Organometallic compound, poisonous, n.o.s.	151	3282

Name of Material	Guide ID No.	ID No.	Name of Material	Guide ID No.	ID No.
Organometallic compound, poisonous, solid, n.o.s.	151	3467	Organometallic substance, solid, water-reactive, flammable	138	3396
Organometallic compound, solid water-reactive, flammable, n.o.s.	138	3372	Organometallic substance, solid, water-reactive, self-heating	138	3397
Organometallic compound, toxic, liquid, n.o.s.	151	3282	Organophosphorus compound, poisonous, flammable, n.o.s.	131	3279
Organometallic compound, toxic, n.o.s.	151	3282	Organophosphorus compound, poisonous, liquid, n.o.s.	151	3278
Organometallic compound, toxic, solid, n.o.s.	151	3467	Organophosphorus compound, poisonous, n.o.s.	151	3278
Organometallic compound, water-reactive, flammable, n.o.s.	138	3207	Organophosphorus compound, poisonous, solid, n.o.s.	151	3464
Organometallic compound dispersion, water-reactive, flammable, n.o.s.	138	3207	Organophosphorus compound, toxic, flammable, n.o.s.	131	3279
Organometallic compound solution, water-reactive, flammable, n.o.s.	138	3207	Organophosphorus compound, toxic, liquid, n.o.s.	151	3278
Organometallic substance, liquid, pyrophoric	135	3392	Organophosphorus compound, toxic, n.o.s.	151	3278
Organometallic substance, liquid, pyrophoric, water-reactive	135	3394	Organophosphorus compound, toxic, solid, n.o.s.	151	3464
Organometallic substance, liquid, water-reactive	135	3398	Organophosphorus pesticide, liquid, flammable, poisonous	131	2784
Organometallic substance, liquid, water-reactive, flammable	138	3399	Organophosphorus pesticide, liquid, flammable, toxic	131	2784
Organometallic substance, solid, pyrophoric	135	3391	Organophosphorus pesticide, liquid, poisonous	152	3018
Organometallic substance, solid, pyrophoric, water-reactive	135	3393	Organophosphorus pesticide, liquid, poisonous, flammable	131	3017
Organometallic substance, solid, self-heating	138	3400	Organophosphorus pesticide, liquid, toxic	152	3018
Organometallic substance, solid, water-reactive	135	3395	Organophosphorus pesticide, liquid, toxic, flammable	131	3017
			Organophosphorus pesticide, solid, poisonous	152	2783
			Organophosphorus pesticide, solid, toxic	152	2783

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Organotin compound, liquid, n.o.s.	153	2788	Oxidizing solid, toxic, n.o.s.	141	3087
Organotin compound, solid, n.o.s.	153	3146	Oxidizing solid, water-reactive, n.o.s.	144	3121
Organotin pesticide, liquid, flammable, poisonous	131	2787	Oxygen	122	1072
Organotin pesticide, liquid, flammable, toxic	131	2787	Oxygen, compressed	122	1072
Organotin pesticide, liquid, poisonous	153	3020	Oxygen, refrigerated liquid (cryogenic liquid)	122	1073
Organotin pesticide, liquid, poisonous, flammable	131	3019	Oxygen and Carbon dioxide mixture	122	1014
Organotin pesticide, liquid, toxic	153	3020	Oxygen and Carbon dioxide mixture, compressed	122	1014
Organotin pesticide, liquid, toxic, flammable	131	3019	Oxygen and Rare gases mixture	121	1980
Organotin pesticide, solid, poisonous	153	2786	Oxygen and Rare gases mixture, compressed	121	1980
Organotin pesticide, solid, toxic	153	2786	Oxygen difluoride	124	2190
Osmium tetroxide	154	2471	Oxygen difluoride, compressed	124	2190
Other regulated substances, liquid, n.o.s.	171	3082	Oxygen generator, chemical	140	3356
Other regulated substances, solid, n.o.s.	171	3077	Oxygen generator, chemical, spent	140	3356
Oxidizing liquid, corrosive, n.o.s.	140	3098	Paint (corrosive)	153	3066
Oxidizing liquid, n.o.s.	140	3139	Paint, corrosive, flammable	132	3470
Oxidizing liquid, poisonous, n.o.s.	142	3099	Paint (flammable)	128	1263
Oxidizing liquid, toxic, n.o.s.	142	3099	Paint, flammable, corrosive	132	3469
Oxidizing solid, corrosive, n.o.s.	140	3085	Paint related material (corrosive)	153	3066
Oxidizing solid, flammable, n.o.s.	140	3137	Paint related material, corrosive, flammable	132	3470
Oxidizing solid, n.o.s.	140	1479	Paint related material (flammable)	128	1263
Oxidizing solid, poisonous, n.o.s.	141	3087	Paint related material, flammable, corrosive	132	3469
Oxidizing solid, self-heating, n.o.s.	135	3100	Paper, unsaturated oil treated	133	1379
			Paraformaldehyde	133	2213
			Paraldehyde	129	1264
			Parathion	152	2783



Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Parathion and compressed gas mixture	123	1967	Perchloric acid, with not more than 50% acid	140	1802
PCB	171	2315	Perchloroethylene	160	1897
PD	152	1556	Perchloromethyl mercaptan	157	1670
Pentaborane	135	1380	Perchloryl fluoride	124	3083
Pentachloroethane	151	1669	Perfluoroethyl vinyl ether	115	3154
Pentachlorophenol	154	3155	Perfluoro(ethyl vinyl ether)	115	3154
Pentaerythrite tetranitrate mixture, desensitized, solid, n.o.s., with more than 10% but not more than 20% PETN	113	3344	Perfluoromethyl vinyl ether	115	3153
Pentaerythritol tetranitrate mixture, desensitized, solid, n.o.s., with more than 10% but not more than 20% PETN	113	3344	Perfluoro(methyl vinyl ether)	115	3153
Pentafluoroethane	126	3220	Perfumery products, with flammable solvents	127	1266
Pentafluoroethane and Ethylene oxide mixture, with not more than 7.9% Ethylene oxide	126	3298	Permanganates, inorganic, aqueous solution, n.o.s.	140	3214
Pentamethylheptane	128	2286	Permanganates, inorganic, n.o.s.	140	1482
Pentan-2,4-dione	131	2310	Peroxides, inorganic, n.o.s.	140	1483
n-Pentane	128	1265	Persulfates, inorganic, aqueous solution, n.o.s.	140	3216
2,4-Pentanedione	131	2310	Persulfates, inorganic, n.o.s.	140	3215
Pentane-2,4-dione	131	2310	Persulphates, inorganic, aqueous solution, n.o.s.	140	3216
Pentanes	128	1265	Persulphates, inorganic, n.o.s.	140	3215
Pentanol	129	1105	Pesticide, liquid, flammable, poisonous, n.o.s.	131	3021
1-Pentene	128	1108	Pesticide, liquid, flammable, toxic, n.o.s.	131	3021
1-Pentol	153P	2705	Pesticide, liquid, poisonous, flammable, n.o.s.	131	2903
Percarbonates, inorganic, n.o.s.	140	3217	Pesticide, liquid, poisonous, n.o.s.	151	2902
Perchlorates, inorganic, aqueous solution, n.o.s.	140	3211	Pesticide, liquid, toxic, flammable, n.o.s.	131	2903
Perchlorates, inorganic, n.o.s.	140	1481	Pesticide, liquid, toxic, n.o.s.	151	2902
Perchloric acid, with more than 50% but not more than 72% acid	143	1873	Pesticide, solid, poisonous	151	2588
			Pesticide, solid, poisonous, n.o.s.	151	2588

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Pesticide, solid, toxic, n.o.s.	151	2588	Phenoxyacetic acid derivative pesticide, liquid, toxic, flammable	131	3347
PETN mixture, desensitized, solid, n.o.s., with more than 10% but not more than 20% PETN	113	3344	Phenoxyacetic acid derivative pesticide, solid, poisonous	153	3345
Petrol	128	1203	Phenoxyacetic acid derivative pesticide, solid, toxic	153	3345
Petrol and ethanol mixture, with more than 10% ethanol	127	347	Phenoxy pesticide, liquid, flammable, poisonous	131	2766
Petroleum crude oil	128	1267	Phenoxy pesticide, liquid, flammable, toxic	131	2766
Petroleum distillates, n.o.s.	128	1268	Phenoxy pesticide, liquid, poisonous	152	3000
Petroleum gases, liquefied	115	1075	Phenoxy pesticide, liquid, poisonous, flammable	131	2999
Petroleum oil	128	1270	Phenoxy pesticide, liquid, toxic	152	3000
Petroleum products, n.o.s.	128	1268	Phenoxy pesticide, liquid, toxic, flammable	131	2999
Phenacyl bromide	153	2645	Phenoxy pesticide, solid, poisonous	152	2765
Phenetidines	153	2311	Phenoxy pesticide, solid, toxic	152	2765
Phenol, molten	153	2312	Phenylacetoneitrile, liquid	152	2470
Phenol, solid	153	1671	Phenylacetyl chloride	156	2577
Phenol solution	153	2821	Phenylcarbylamine chloride	151	1672
Phenolates, liquid	154	2904	Phenyl chloroformate	156	2746
Phenolates, solid	154	2905	Phenylenediamines	153	1673
Phenolsulfonic acid, liquid	153	1803	Phenylhydrazine	153	2572
Phenolsulphonic acid, liquid	153	1803	Phenyl isocyanate	155	2487
Phenoxyacetic acid derivative pesticide, liquid, flammable, poisonous	131	3346	Phenyl mercaptan	131	2337
Phenoxyacetic acid derivative pesticide, liquid, flammable, toxic	131	3346	Phenylmercuric acetate	151	1674
Phenoxyacetic acid derivative pesticide, liquid, poisonous	153	3348	Phenylmercuric compound, n.o.s.	151	2026
Phenoxyacetic acid derivative pesticide, liquid, poisonous, flammable	131	3347	Phenylmercuric hydroxide	151	1894
Phenoxyacetic acid derivative pesticide, liquid, toxic	153	3348	Phenylmercuric nitrate	151	1895
			Phenylphosphorus dichloride	137	2798

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Phenylphosphorus thiodichloride	137	2799	Phosphorus heptasulfide, free from yellow and white Phosphorus	139	1339
Phenyltrichlorosilane	156	1804	Phosphorus heptasulphide, free from yellow and white Phosphorus	139	1339
Phenyl urea pesticide, liquid, flammable, poisonous	131	2768	Phosphorus oxybromide	137	1939
Phenyl urea pesticide, liquid, flammable, toxic	131	2768	Phosphorus oxybromide, molten	137	2576
Phenyl urea pesticide, liquid, poisonous	151	3002	Phosphorus oxybromide, solid	137	1939
Phenyl urea pesticide, liquid, poisonous, flammable	131	3001	Phosphorus oxychloride	137	1810
Phenyl urea pesticide, liquid, toxic	151	3002	Phosphorus pentabromide	137	2691
Phenyl urea pesticide, liquid, toxic, flammable	131	3001	Phosphorus pentachloride	137	1806
Phenyl urea pesticide, solid, poisonous	151	2767	Phosphorus pentafluoride	125	2198
Phenyl urea pesticide, solid, toxic	151	2767	Phosphorus pentafluoride, compressed	125	2198
Phosgene	125	1076	Phosphorus pentasulfide, free from yellow and white Phosphorus	139	1340
9-Phosphabicyclononanes	135	2940	Phosphorus pentasulphide, free from yellow and white Phosphorus	139	1340
Phosphine	119	2199	Phosphorus pentoxide	137	1807
Phosphoric acid	154	1805	Phosphorus sesquisulfide, free from yellow and white Phosphorus	139	1341
Phosphoric acid, liquid	154	1805	Phosphorus sesquisulphide, free from yellow and white Phosphorus	139	1341
Phosphoric acid, solid	154	1805	Phosphorus tribromide	137	1808
Phosphoric acid, solid	154	3453	Phosphorus trichloride	137	1809
Phosphoric acid, solution	154	1805	Phosphorus trioxide	157	2578
Phosphorous acid	154	2834	Phosphorus trisulfide, free from yellow and white Phosphorus	139	1343
Phosphorous acid, ortho	154	2834	Phosphorus trisulphide, free from yellow and white Phosphorus	139	1343
Phosphorus, amorphous	133	1338	Phthalic anhydride	156	2214
Phosphorus, amorphous, red	133	1338			
Phosphorus, white, dry or under water or in solution	136	1381			
Phosphorus, white, molten	136	2447			
Phosphorus, yellow, dry or under water or in solution	136	1381			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Phthalimide derivative pesticide, liquid, flammable, poisonous	131	2774	Plastic, nitrocellulose-based, spontaneously combustible, n.o.s.	135	2006
Phthalimide derivative pesticide, liquid, flammable, toxic	131	2774	Plastics moulding compound	171	3314
Phthalimide derivative pesticide, liquid, poisonous	151	3008	Plastics, nitrocellulose-based, self-heating, n.o.s.	135	2006
Phthalimide derivative pesticide, liquid, poisonous, flammable	131	3007	Poison B, liquid, n.o.s.	153	2810
Phthalimide derivative pesticide, liquid, toxic	151	3008	Poisonous by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)	154	3389
Phthalimide derivative pesticide, liquid, toxic, flammable	131	3007	Poisonous by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)	154	3390
Phthalimide derivative pesticide, solid, poisonous	151	2773	Poisonous by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone A)	131	3383
Phthalimide derivative pesticide, solid, toxic	151	2773	Poisonous by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone B)	131	3384
Picolines	129	2313	Poisonous by inhalation liquid, n.o.s. (Inhalation Hazard Zone A)	151	3381
Picric acid, wet, with not less than 10% water	113	1344	Poisonous by inhalation liquid, n.o.s. (Inhalation Hazard Zone B)	151	3382
Picric acid, wetted with not less than 10% water	113	3364	Poisonous by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)	142	3387
Picrite, wetted	113	1336	Poisonous by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)	142	3388
Picryl chloride, wetted with not less than 10% water	113	3365	Poisonous by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)	139	3385
Picric acid, wetted with not less than 30% water	113	1344	Poisonous by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)	139	3386
alpha-Pinene	128	2368	Poisonous liquid, corrosive, inorganic, n.o.s.	154	3289
Pinene (alpha)	128	2368			
Pine oil	129	1272			
Piperazine	153	2579			
Piperidine	132	2401			
Plastic molding compound	171	3314			

Name of Material	Guide ID No.	Guide ID No.
Poisonous liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone A)	154	3289
Poisonous liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone B)	154	3289
Poisonous liquid, corrosive, n.o.s.	154	2927
Poisonous liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)	154	2927
Poisonous liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)	154	2927
Poisonous liquid, corrosive, organic, n.o.s.	154	2927
Poisonous liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone A)	154	2927
Poisonous liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone B)	154	2927
Poisonous liquid, flammable, n.o.s.	131	2929
Poisonous liquid, flammable, n.o.s. (Inhalation Hazard Zone A)	131	2929
Poisonous liquid, flammable, n.o.s. (Inhalation Hazard Zone B)	131	2929
Poisonous liquid, flammable, organic, n.o.s.	131	2929
Poisonous liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone A)	131	2929
Poisonous liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone B)	131	2929
Poisonous liquid, inorganic, n.o.s.	151	3287

Name of Material	Guide ID No.	Guide ID No.
Poisonous liquid, inorganic, n.o.s. (Inhalation Hazard Zone A)	151	3287
Poisonous liquid, inorganic, n.o.s. (Inhalation Hazard Zone B)	151	3287
Poisonous liquid, n.o.s.	153	2810
Poisonous liquid, n.o.s. (Inhalation Hazard Zone A)	153	2810
Poisonous liquid, n.o.s. (Inhalation Hazard Zone B)	153	2810
Poisonous liquid, organic, n.o.s.	153	2810
Poisonous liquid, organic, n.o.s. (Inhalation Hazard Zone A)	153	2810
Poisonous liquid, organic, n.o.s. (Inhalation Hazard Zone B)	153	2810
Poisonous liquid, oxidizing, n.o.s.	142	3122
Poisonous liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)	142	3122
Poisonous liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)	142	3122
Poisonous liquid, water-reactive, n.o.s.	139	3123
Poisonous liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)	139	3123
Poisonous liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)	139	3123
Poisonous liquid, which in contact with water emits flammable gases, n.o.s.	139	3123
Poisonous liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone A)	139	3123

Name of Material	Guide ID No.	ID No.	Name of Material	Guide ID No.	ID No.
Poisonous liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone B)	139	3123	Polychlorinated biphenyls, solid	171	2315
Poisonous solid, corrosive, inorganic, n.o.s.	154	3290	Polychlorinated biphenyls, solid	171	3432
Poisonous solid, corrosive, n.o.s.	154	2928	Polyester resin kit	128	3269
Poisonous solid, flammable, n.o.s.	134	2930	Polyhalogenated biphenyls, liquid	171	3151
Poisonous solid, flammable, organic, n.o.s.	134	2930	Polyhalogenated biphenyls, solid	171	3152
Poisonous solid, inorganic, n.o.s.	151	3288	Polyhalogenated terphenyls, liquid	171	3151
Poisonous solid, organic, n.o.s.	154	2811	Polyhalogenated terphenyls, solid	171	3152
Poisonous solid, oxidizing, n.o.s.	141	3086	Polymeric beads, expandable	133	2211
Poisonous solid, self-heating, n.o.s.	136	3124	Polystyrene beads, expandable	133	2211
Poisonous solid, water-reactive, n.o.s.	139	3125	Potassium	138	2257
Poisonous solid, which in contact with water emits flammable gases, n.o.s.	139	3125	Potassium, metal	138	2257
Polyalkylamines, n.o.s.	132	2733	Potassium, metal alloys	138	1420
Polyalkylamines, n.o.s.	132	2734	Potassium, metal alloys, liquid	138	1420
Polyalkylamines, n.o.s.	153	2735	Potassium, metal alloys, solid	138	3403
Polyamines, flammable, corrosive, n.o.s.	132	2733	Potassium arsenate	151	1677
Polyamines, liquid, corrosive, flammable, n.o.s.	132	2734	Potassium arsenite	154	1678
Polyamines, liquid, corrosive, n.o.s.	153	2735	Potassium borohydride	138	1870
Polyamines, solid, corrosive, n.o.s.	154	3259	Potassium bromate	140	1484
Polychlorinated biphenyls	171	2315	Potassium chlorate	140	1485
Polychlorinated biphenyls, liquid	171	2315	Potassium chlorate, aqueous solution	140	2427
			Potassium chlorate, solution	140	2427
			Potassium cuprocyanide	157	1679
			Potassium cyanide	157	1680
			Potassium cyanide, solid	157	1680
			Potassium cyanide, solution	157	3413
			Potassium dithionite	135	1929
			Potassium fluoride	154	1812
			Potassium fluoride, solid	154	1812
			Potassium fluoride, solution	154	3422

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Potassium fluoroacetate	151	2628	Potassium sulfide, hydrated, with not less than 30% water of crystallization	153	1847
Potassium fluorosilicate	151	2655	Potassium sulfide, hydrated, with not less than 30% water of hydration	153	1847
Potassium hydrogendifluoride	154	1811	Potassium sulfide, with less than 30% water of crystallization	135	1382
Potassium hydrogen difluoride, solid	154	1811	Potassium sulfide, with less than 30% water of hydration	135	1382
Potassium hydrogen difluoride, solution	154	3421	Potassium sulphide, anhydrous	135	1382
Potassium hydrogen sulfate	154	2509	Potassium sulphide, hydrated, with not less than 30% water of crystallization	153	1847
Potassium hydrogen sulphate	154	2509	Potassium sulphide, hydrated, with not less than 30% water of hydration	153	1847
Potassium hydrosulfite	135	1929	Potassium sulphide, with less than 30% water of crystallization	135	1382
Potassium hydrosulphite	135	1929	Potassium sulphide, with less than 30% water of hydration	135	1382
Potassium hydroxide, dry, solid	154	1813	Potassium superoxide	143	2466
Potassium hydroxide, flake	154	1813	Printing ink, flammable	129	1210
Potassium hydroxide, solid	154	1813	Printing ink related material	129	1210
Potassium hydroxide, solution	154	1814	Propadiene, stabilized	116P	2200
Potassium metavanadate	151	2864	Propadiene and Methylacetylene mixture, stabilized	116P	1060
Potassium monoxide	154	2033	Propane	115	1075
Potassium nitrate	140	1486	Propane	115	1978
Potassium nitrate and Sodium nitrate mixture	140	1499	Propane-Ethane mixture, refrigerated liquid	115	1961
Potassium nitrate and Sodium nitrite mixture	140	1487	Propane mixture	115	1075
Potassium nitrite	140	1488	Propane mixture	115	1978
Potassium perchlorate	140	1489	Propanethiols	130	2402
Potassium permanganate	140	1490	n-Propanol	129	1274
Potassium peroxide	144	1491			
Potassium persulfate	140	1492			
Potassium persulphate	140	1492			
Potassium phosphide	139	2012			
Potassium silicofluoride	151	2655			
Potassium sodium alloys	138	1422			
Potassium sodium alloys, liquid	138	1422			
Potassium sodium alloys, solid	138	3404			
Potassium sulfide, anhydrous	135	1382			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Propargyl alcohol	131	1986	Propylene tetramer	128	2850
Propionaldehyde	129	1275	Propyl formates	129	1281
Propionic acid	132	1848	n-Propyl isocyanate	155	2482
Propionic acid, with not less than 10% and less than 90% acid	132	1848	n-Propyl nitrate	131	1865
Propionic acid, with not less than 90% acid	132	3463	Propyltrichlorosilane	155	1816
Propionic anhydride	156	2496	Pyrethroid pesticide, liquid, flammable, poisonous	131	3350
Propionitrile	131	2404	Pyrethroid pesticide, liquid, flammable, toxic	131	3350
Propionyl chloride	132	1815	Pyrethroid pesticide, liquid, poisonous	151	3352
n-Propyl acetate	129	1276	Pyrethroid pesticide, liquid, poisonous, flammable	131	3351
normal Propyl alcohol	129	1274	Pyrethroid pesticide, liquid, toxic	151	3352
Propyl alcohol, normal	129	1274	Pyrethroid pesticide, liquid, toxic, flammable	131	3351
Propylamine	132	1277	Pyrethroid pesticide, solid, poisonous	151	3349
n-Propyl benzene	128	2364	Pyrethroid pesticide, solid, toxic	151	3349
Propyl chloride	129	1278	Pyridine	129	1282
n-Propyl chloroformate	155	2740	Pyrophoric alloy, n.o.s.	135	1383
Propylene	115	1075	Pyrophoric liquid, inorganic, n.o.s.	135	3194
Propylene	115	1077	Pyrophoric liquid, n.o.s.	135	2845
Propylene, Ethylene and Acetylene in mixture, refrigerated liquid containing at least 71.5% Ethylene with not more than 22.5% Acetylene and not more than 6% Propylene	115	3138	Pyrophoric liquid, organic, n.o.s.	135	2845
Propylene chlorohydrin	131	2611	Pyrophoric metal, n.o.s.	135	1383
1,2-Propylenediamine	132	2258	Pyrophoric organometallic compound, n.o.s.	135	3203
1,3-Propylenediamine	132	2258	Pyrophoric organometallic compound, water-reactive, n.o.s.	135	3203
Propylene dichloride	130	1279	Pyrophoric solid, inorganic, n.o.s.	135	3200
Propyleneimine, stabilized	131P	1921	Pyrophoric solid, n.o.s.	135	2846
Propylene oxide	127P	1280	Pyrophoric solid, organic, n.o.s.	135	2846
Propylene oxide and Ethylene oxide mixture, with not more than 30% Ethylene oxide	129P	2983			



Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Pyrosulfuryl chloride	137	1817	Radioactive material, low specific activity (LSA-I) non fissile or fissile-excepted	162	2912
Pyrosulphuryl chloride	137	1817			
Pyrrolidine	132	1922	Radioactive material, low specific activity (LSA-II), fissile	165	3324
Quinoline	154	2656			
Radioactive material, excepted package, articles manufactured from depleted Uranium	161	2909	Radioactive material, low specific activity (LSA-II), non fissile or fissile-excepted	162	3321
Radioactive material, excepted package, articles manufactured from depleted Uranium	161	2910	Radioactive material, low specific activity (LSA-III), fissile	165	3325
Radioactive material, excepted package, articles manufactured from natural Thorium	161	2909	Radioactive material, low specific activity (LSA-III), non fissile or fissile-excepted	162	3322
Radioactive material, excepted package, articles manufactured from natural Thorium	161	2910	Radioactive material, n.o.s.	163	2982
Radioactive material, excepted package, articles manufactured from natural Uranium	161	2909	Radioactive material, special form, n.o.s.	164	2974
Radioactive material, excepted package, articles manufactured from natural Uranium	161	2910	Radioactive material, surface contaminated objects (SCO)	162	2913
Radioactive material, excepted package, articles manufactured from natural Uranium	161	2908	Radioactive material, surface contaminated objects (SCO-I), fissile	165	3326
Radioactive material, excepted package, empty packaging	161	2910	Radioactive material, surface contaminated objects (SCO-I) non fissile or fissile-excepted	162	2913
Radioactive material, excepted package, empty packaging	161	2910	Radioactive material, surface contaminated objects (SCO-II), fissile	165	3326
Radioactive material, excepted package, instruments or articles	161	2910	Radioactive material, surface contaminated objects (SCO-II) non fissile or fissile-excepted	162	2913
Radioactive material, excepted package, instruments or articles	161	2911	Radioactive material, transported under special arrangement, fissile	165	3331
Radioactive material, excepted package, limited quantity of material	161	2910	Radioactive material, transported under special arrangement non fissile or fissile-excepted	163	2919
Radioactive material, fissile, n.o.s.	165	2918			
Radioactive material, low specific activity (LSA), n.o.s.	162	2912	Radioactive material, Type A package, fissile, non-special form	165	3327

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Radioactive material, Type A package non-special form, non fissile or fissile-excepted	163	2915	Red phosphorus	133	1338
Radioactive material, Type A package, special form, fissile	165	3333	Red phosphorus, amorphous	133	1338
Radioactive material, Type A package, special form, non fissile or fissile-excepted	164	3332	Refrigerant gas, n.o.s.	126	1078
Radioactive material, Type B(M) package, fissile	165	3329	Refrigerant gas, n.o.s. (flammable)	115	1954
Radioactive material, Type B(M) package non fissile or fissile-excepted	163	2917	Refrigerant gas R-12	126	1028
Radioactive material, Type B(U) package, fissile	165	3328	Refrigerant gas R-12 and Refrigerant gas R-152a azeotropic mixture with 74% Refrigerant gas R-12	126	2602
Radioactive material, Type B(U) package non fissile or fissile-excepted	163	2916	Refrigerant gas R-12B1	126	1974
Radioactive material, Type C package	163	3323	Refrigerant gas R-13	126	1022
Radioactive material, Type C package, fissile	165	3330	Refrigerant gas R-13 and Refrigerant gas R-23 azeotropic mixture with 60% Refrigerant gas R-13	126	2599
Radioactive material, Uranium hexafluoride	166	2978	Refrigerant gas R-13B1	126	1009
Radioactive material, Uranium hexafluoride, fissile	166	2977	Refrigerant gas R-14	126	1982
Rags, oily	133	1856	Refrigerant gas R-14, compressed	126	1982
Rare gases and Nitrogen mixture	121	1981	Refrigerant gas R-21	126	1029
Rare gases and Nitrogen mixture, compressed	121	1981	Refrigerant gas R-22	126	1018
Rare gases and Oxygen mixture	121	1980	Refrigerant gas R-23	126	1984
Rare gases and Oxygen mixture, compressed	121	1980	Refrigerant gas R-23 and Refrigerant gas R-13 azeotropic mixture with 60% Refrigerant gas R-13	126	2599
Rare gases mixture	121	1979	Refrigerant gas R-32	115	3252
Rare gases mixture, compressed	121	1979	Refrigerant gas R-40	115	1063
Receptacles, small, containing gas	115	2037	Refrigerant gas R-41	115	2454
			Refrigerant gas R-114	126	1958
			Refrigerant gas R-115	126	1020
			Refrigerant gas R-116	126	2193
			Refrigerant gas R-116, compressed	126	2193
			Refrigerant gas R-124	126	1021

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Refrigerant gas R-125	126	3220	Refrigerating machines, containing Ammonia solutions (UN2672)	126	2857
Refrigerant gas R-133a	126	1983	Refrigerating machines, containing flammable, non-poisonous, non-corrosive, liquefied gas	115	1954
Refrigerant gas R-134a	126	3159	Refrigerating machines, containing flammable, non-poisonous, liquefied gases	115	3358
Refrigerant gas R-142b	115	2517	Refrigerating machines, containing flammable, non-toxic, liquefied gases	115	3358
Refrigerant gas R-143a	115	2035	Refrigerating machines, containing non-flammable, non-poisonous gases	126	2857
Refrigerant gas R-152a	115	1030	Refrigerating machines, containing non-flammable, non-toxic gases	126	2857
Refrigerant gas R-152a and Refrigerant gas R-12 azeotropic mixture with 74% Refrigerant gas R-12	126	2602	Regulated medical waste, n.o.s.	158	3291
Refrigerant gas R-161	115	2453	Resin solution	127	1866
Refrigerant gas R-218	126	2424	Resorcinol	153	2876
Refrigerant gas R-227	126	3296	Rosin oil	127	1286
Refrigerant gas R-404A	126	3337	Rubber scrap, powdered or granulated	133	1345
Refrigerant gas R-407A	126	3338	Rubber shoddy, powdered or granulated	133	1345
Refrigerant gas R-407B	126	3339	Rubber solution	127	1287
Refrigerant gas R-407C	126	3340	Rubidium	138	1423
Refrigerant gas R-500 (azeotropic mixture of Refrigerant gas R-12 and Refrigerant gas R-152a with approximately 74% Refrigerant gas R-12)	126	2602	Rubidium hydroxide	154	2678
Refrigerant gas R-502	126	1973	Rubidium hydroxide, solid	154	2678
Refrigerant gas R-503 (azeotropic mixture of Refrigerant gas R-13 and Refrigerant gas R-23 with approximately 60% Refrigerant gas R-13)	126	2599	Rubidium hydroxide, solution	154	2677
Refrigerant gas R-1132a	116P	1959	Rubidium metal	138	1423
Refrigerant gas R-1216	126	1858	SA	119	2188
Refrigerant gas R-1318	126	2422	Sarin	153	2810
Refrigerant gas RC-318	126	1976	Seat-belt modules	171	3268
Refrigerating machine	128	1993	Seat-belt pre-tensioners	171	3268

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Seat-belt pre-tensioners, compressed gas	126	3353	Self-heating liquid, poisonous, organic, n.o.s.	136	3184
Seat-belt pre-tensioners, pyrotechnic	171	3268	Self-heating liquid, toxic, inorganic, n.o.s.	136	3187
Seed cake, with more than 1.5% oil and not more than 11% moisture	135	1386	Self-heating liquid, toxic, organic, n.o.s.	136	3184
Seed cake, with not more than 1.5% oil and not more than 11% moisture	135	2217	Self-heating metal powders, n.o.s.	135	3189
Selenates	151	2630	Self-heating solid, corrosive, inorganic, n.o.s.	136	3192
Selenic acid	154	1905	Self-heating solid, corrosive, organic, n.o.s.	136	3126
Selenites	151	2630	Self-heating solid, inorganic, n.o.s.	135	3190
Selenium compound, liquid, n.o.s.	151	3440	Self-heating solid, inorganic, poisonous, n.o.s.	136	3191
Selenium compound, n.o.s.	151	3283	Self-heating solid, inorganic, toxic, n.o.s.	136	3191
Selenium compound, solid, n.o.s.	151	3283	Self-heating solid, organic, n.o.s.	135	3088
Selenium disulfide	153	2657	Self-heating solid, oxidizing, n.o.s.	135	3127
Selenium disulphide	153	2657	Self-heating solid, poisonous, inorganic, n.o.s.	136	3191
Selenium hexafluoride	125	2194	Self-heating solid, poisonous, organic, n.o.s.	136	3128
Selenium oxide	154	2811	Self-heating solid, toxic, inorganic, n.o.s.	136	3191
Selenium oxychloride	157	2879	Self-heating solid, toxic, organic, n.o.s.	136	3128
Selenium powder	152	2658	Self-heating solid, toxic, inorganic, n.o.s.	136	3191
Self-defense spray, non-pressurized	171	3334	Self-heating solid, toxic, organic, n.o.s.	136	3128
Self-heating liquid, corrosive, inorganic, n.o.s.	136	3188	Self-reactive liquid type B	149	3221
Self-heating liquid, corrosive, organic, n.o.s.	136	3185	Self-reactive liquid type B, temperature controlled	150	3231
Self-heating liquid, inorganic, n.o.s.	135	3186	Self-reactive liquid type C	149	3223
Self-heating liquid, organic, n.o.s.	135	3183	Self-reactive liquid type C, temperature controlled	150	3233
Self-heating liquid, poisonous, inorganic, n.o.s.	136	3187	Self-reactive liquid type D	149	3225

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Self-reactive liquid type D, temperature controlled	150	3235	Silver picrate, wetted with not less than 30% water	113	1347
Self-reactive liquid type E	149	3227	Sludge acid	153	1906
Self-reactive liquid type E, temperature controlled	150	3237	Smokeless powder for small arms	133	3178
Self-reactive liquid type F	149	3229	Soda lime, with more than 4% Sodium hydroxide	154	1907
Self-reactive liquid type F, temperature controlled	150	3239	Sodium	138	1428
Self-reactive solid type B	149	3222	Sodium aluminate, solid	154	2812
Self-reactive solid type B, temperature controlled	150	3232	Sodium aluminate, solution	154	1819
Self-reactive solid type C	149	3224	Sodium aluminum hydride	138	2835
Self-reactive solid type C, temperature controlled	150	3234	Sodium ammonium vanadate	154	2863
Self-reactive solid type D	149	3226	Sodium arsanilate	154	2473
Self-reactive solid type D, temperature controlled	150	3236	Sodium arsenate	151	1685
Self-reactive solid type E	149	3228	Sodium arsenite, aqueous solution	154	1686
Self-reactive solid type E, temperature controlled	150	3238	Sodium arsenite, solid	151	2027
Self-reactive solid type F	149	3230	Sodium azide	153	1687
Self-reactive solid type F, temperature controlled	150	3240	Sodium bisulfate, solution	154	2837
Shale oil	128	1288	Sodium bisulphate, solution	154	2837
Silane	116	2203	Sodium borohydride	138	1426
Silicofluorides, n.o.s.	151	2856	Sodium borohydride and Sodium hydroxide solution, with not more than 12% Sodium borohydride and not more than 40% Sodium hydroxide	157	3320
Silane, compressed	116	2203	Sodium bromate	141	1494
Silicon powder, amorphous	170	1346	Sodium cacodylate	152	1688
Silicon tetrachloride	157	1818	Sodium carbonate peroxyhydrate	140	3378
Silicon tetrafluoride	125	1859	Sodium chlorate	140	1495
Silicon tetrafluoride, compressed	125	1859	Sodium chlorate, aqueous solution	140	2428
Silver arsenite	151	1683	Sodium chlorite	143	1496
Silver cyanide	151	1684	Sodium chlorite, solution, with more than 5% available Chlorine	154	1908
Silver nitrate	140	1493			

Name of Material	Guide ID No.	ID No.	Name of Material	Guide ID No.	ID No.
Sodium chloroacetate	151	2659	Sodium hydrosulfide, with not less than 25% water of crystallization	154	2949
Sodium cuprocyanide, solid	157	2316	Sodium hydrosulfite	135	1384
Sodium cuprocyanide, solution	157	2317	Sodium hydrosulphide, solid, with less than 25% water of crystallization	135	2318
Sodium cyanide	157	1689	Sodium hydrosulphide, solution	154	2922
Sodium cyanide, solid	157	1689	Sodium hydrosulphide, with less than 25% water of crystallization	135	2318
Sodium cyanide, solution	157	3414	Sodium hydrosulphide, with not less than 25% water of crystallization	154	2949
Sodium dichloroisocyanurate	140	2465	Sodium hydrosulphite	135	1384
Sodium dichloro-s-triazinetrione	140	2465	Sodium hydroxide, bead	154	1823
Sodium dinitro-o-cresolate, wetted with not less than 10% water	113	3369	Sodium hydroxide, dry	154	1823
Sodium dinitro-o-cresolate, wetted with not less than 15% water	113	1348	Sodium hydroxide, flake	154	1823
Sodium dinitro-ortho-cresolate, wetted	113	1348	Sodium hydroxide, granular	154	1823
Sodium dithionite	135	1384	Sodium hydroxide, solid	154	1823
Sodium fluoride	154	1690	Sodium hydroxide, solution	154	1824
Sodium fluoride, solid	154	1690	Sodium methylate	138	1431
Sodium fluoride, solution	154	3415	Sodium methylate, dry	138	1431
Sodium fluoroacetate	151	2629	Sodium methylate, solution in alcohol	132	1289
Sodium fluorosilicate	154	2674	Sodium monoxide	157	1825
Sodium hydride	138	1427	Sodium nitrate	140	1498
Sodium hydrogendifluoride	154	2439	Sodium nitrate and Potassium nitrate mixture	140	1499
Sodium hydrogen sulfate, solution	154	2837	Sodium nitrite	140	1500
Sodium hydrogen sulphate, solution	154	2837	Sodium nitrite and Potassium nitrate mixture	140	1487
Sodium hydrosulfide, solid, with less than 25% water of crystallization	135	2318	Sodium pentachlorophenate	154	2567
Sodium hydrosulfide, solution	154	2922	Sodium perborate monohydrate	140	3377
Sodium hydrosulfide, with less than 25% water of crystallization	135	2318			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Sodium percarbonates	140	2467	Stannic chloride, anhydrous	137	1827
Sodium perchlorate	140	1502	Stannic chloride, pentahydrate	154	2440
Sodium permanganate	140	1503	Stannic phosphides	139	1433
Sodium peroxide	144	1504	<b>Stibine</b>	<b>119</b>	<b>2676</b>
Sodium peroxoborate, anhydrous	140	3247	Straw, wet, damp or contaminated with oil	133	1327
Sodium persulfate	140	1505	Strontium arsenite	151	1691
Sodium persulphate	140	1505	Strontium chlorate	143	1506
<b>Sodium phosphide</b>	<b>139</b>	<b>1432</b>	Strontium chlorate, solid	143	1506
Sodium picramate, wetted with not less than 20% water	113	1349	Strontium chlorate, solution	143	1506
Sodium potassium alloys	138	1422	Strontium nitrate	140	1507
Sodium potassium alloys, liquid	138	1422	Strontium perchlorate	140	1508
Sodium potassium alloys, solid	138	3404	Strontium peroxide	143	1509
Sodium selenite	151	2630	<b>Strontium phosphide</b>	<b>139</b>	<b>2013</b>
Sodium silicofluoride	154	2674	Strychnine	151	1692
Sodium sulfide, anhydrous	135	1385	Strychnine salts	151	1692
Sodium sulfide, hydrated, with not less than 30% water	153	1849	Styrene monomer, stabilized	128P	2055
Sodium sulfide, with less than 30% water of crystallization	135	1385	Substituted nitrophenol pesticide, liquid, flammable, poisonous	131	2780
Sodium sulphide, anhydrous	135	1385	Substituted nitrophenol pesticide, liquid, flammable, toxic	131	2780
Sodium sulphide, hydrated, with not less than 30% water	153	1849	Substituted nitrophenol pesticide, liquid, poisonous	153	3014
Sodium sulphide, with less than 30% water of crystallization	135	1385	Substituted nitrophenol pesticide, liquid, poisonous, flammable	131	3013
Sodium superoxide	143	2547	Substituted nitrophenol pesticide, liquid, toxic	153	3014
Solids containing corrosive liquid, n.o.s.	154	3244	Substituted nitrophenol pesticide, liquid, toxic, flammable	131	3013
Solids containing flammable liquid, n.o.s.	133	3175	Substituted nitrophenol pesticide, solid, poisonous	153	2779
Solids containing poisonous liquid, n.o.s.	151	3243			
Solids containing toxic liquid, n.o.s.	151	3243			
<b>Soman</b>	<b>153</b>	<b>2810</b>			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Substituted nitrophenol pesticide, solid, toxic	153	2779	Sulphur dioxide	125	1079
Sulfamic acid	154	2967	Sulphur hexafluoride	126	1080
Sulfur	133	1350	Sulphuric acid	137	1830
Sulfur, molten	133	2448	Sulphuric acid, fuming	137	1831
Sulfur chlorides	137	1828	Sulphuric acid, fuming, with less than 30% free Sulphur trioxide	137	1831
Sulfur dioxide	125	1079	Sulphuric acid, fuming, with not less than 30% free Sulphur trioxide	137	1831
Sulfur hexafluoride	126	1080	Sulphuric acid, spent	137	1832
Sulfuric acid	137	1830	Sulphuric acid, with more than 51% acid	137	1830
Sulfuric acid, fuming	137	1831	Sulphuric acid, with not more than 51% acid	157	2796
Sulfuric acid, fuming, with less than 30% free Sulfur trioxide	137	1831	Sulphuric acid and Hydrofluoric acid mixture	157	1786
Sulfuric acid, fuming, with not less than 30% free Sulfur trioxide	137	1831	Sulphurous acid	154	1833
Sulfuric acid, spent	137	1832	Sulphur tetrafluoride	125	2418
Sulfuric acid, with more than 51% acid	137	1830	Sulphur trioxide, inhibited	137	1829
Sulfuric acid, with not more than 51% acid	157	2796	Sulphur trioxide, stabilized	137	1829
Sulfuric acid and Hydrofluoric acid mixture	157	1786	Sulphur trioxide, uninhibited	137	1829
Sulfurous acid	154	1833	Sulphur trioxide and Chlorosulphonic acid mixture	137	1754
Sulfur tetrafluoride	125	2418	Sulphuryl chloride	137	1834
Sulfur trioxide, inhibited	137	1829	Sulphuryl fluoride	123	2191
Sulfur trioxide, stabilized	137	1829	Tabun	153	2810
Sulfur trioxide, uninhibited	137	1829	Tars, liquid	130	1999
Sulfur trioxide and Chlorosulfonic acid mixture	137	1754	Tear gas candles	159	1700
Sulfuryl chloride	137	1834	Tear gas devices	159	1693
Sulfuryl fluoride	123	2191	Tear gas grenades	159	1700
Sulphamic acid	154	2967	Tear gas substance, liquid, n.o.s.	159	1693
Sulphur	133	1350	Tear gas substance, solid, n.o.s.	159	1693
Sulphur, molten	133	2448	Tear gas substance, solid, n.o.s.	159	3448
Sulphur chlorides	137	1828			



Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Tellurium compound, n.o.s.	151	3284	Tetramethylammonium hydroxide, solid	153	3423
<b>Tellurium hexafluoride</b>	<b>125</b>	<b>2195</b>	Tetramethylammonium hydroxide, solution	153	1835
Terpene hydrocarbons, n.o.s.	128	2319	Tetramethylsilane	130	2749
Terpinolene	128	2541	<b>Tetranitromethane</b>	<b>143</b>	<b>1510</b>
Tetrabromoethane	159	2504	Tetrapropyl orthotitanate	128	2413
1,1,2,2-Tetrachloroethane	151	1702	Textile waste, wet	133	1857
Tetrachloroethane	151	1702	Thallium chlorate	141	2573
Tetrachloroethylene	160	1897	Thallium compound, n.o.s.	151	1707
Tetraethyl dithiopyrophosphate	153	1704	Thallium nitrate	141	2727
Tetraethyl dithiopyrophosphate, mixture, dry or liquid	153	1704	Thallium sulfate, solid	151	1707
Tetraethylenepentamine	153	2320	Thallium sulphate, solid	151	1707
Tetraethyl lead, liquid	131	1649	4-Thiapentanal	152	2785
Tetraethyl pyrophosphate, liquid	152	3018	Thia-4-pentanal	152	2785
Tetraethyl pyrophosphate, solid	152	2783	<b>Thickened GD</b>	<b>153</b>	<b>2810</b>
Tetraethyl silicate	129	1292	Thioacetic acid	129	2436
1,1,1,2-Tetrafluoroethane	126	3159	Thiocarbamate pesticide, liquid, flammable, poisonous	131	2772
Tetrafluoroethane and Ethylene oxide mixture, with not more than 5.6% Ethylene oxide	126	3299	Thiocarbamate pesticide, liquid, flammable, toxic	131	2772
Tetrafluoroethylene, stabilized	116P	1081	Thiocarbamate pesticide, liquid, poisonous	151	3006
Tetrafluoromethane	126	1982	Thiocarbamate pesticide, liquid, poisonous, flammable	131	3005
Tetrafluoromethane, compressed	126	1982	Thiocarbamate pesticide, liquid, toxic	151	3006
1,2,3,6-Tetrahydrobenzaldehyde	129	2498	Thiocarbamate pesticide, liquid, toxic, flammable	131	3005
Tetrahydrofuran	127	2056	Thiocarbamate pesticide, solid, poisonous	151	2771
Tetrahydrofurfurylamine	129	2943	Thiocarbamate pesticide, solid, toxic	151	2771
Tetrahydrophthalic anhydrides	156	2698	Thioglycol	153	2966
1,2,3,6-Tetrahydropyridine	129	2410	Thioglycolic acid	153	1940
1,2,5,6-Tetrahydropyridine	129	2410			
Tetrahydrothiophene	130	2412			
Tetramethylammonium hydroxide	153	1835			

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Thiolactic acid	153	2936	Toluene diisocyanate	156	2078
Thionyl chloride	137	1836	Toluidines	153	1708
Thiophene	130	2414	Toluidines, liquid	153	1708
Thiophosgene	157	2474	Toluidines, solid	153	1708
Thiophosphoryl chloride	157	1837	Toluidines, solid	153	3451
Thiourea dioxide	135	3341	2,4-Toluylenediamine	151	1709
Thorium metal, pyrophoric	162	2975	2,4-Toluylenediamine, solid	151	1709
Thorium nitrate, solid	162	2976	2,4-Toluylenediamine, solution	151	3418
Tinctures, medicinal	127	1293	Toxic by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)	154	3389
Tin tetrachloride	137	1827	Toxic by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)	154	3390
Tin tetrachloride, pentahydrate	154	2440	Toxic by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone A)	131	3383
Titanium disulfide	135	3174	Toxic by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone B)	131	3384
Titanium disulphide	135	3174	Toxic by inhalation liquid, n.o.s. (Inhalation Hazard Zone A)	151	3381
Titanium hydride	170	1871	Toxic by inhalation liquid, n.o.s. (Inhalation Hazard Zone B)	151	3382
Titanium powder, dry	135	2546	Toxic by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)	142	3387
Titanium powder, wetted with not less than 25% water	170	1352	Toxic by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)	142	3388
Titanium sponge granules	170	2878	Toxic by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)	139	3385
Titanium sponge powders	170	2878	Toxic by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)	139	3386
Titanium sulfate, solution	154	1760	Toluene	130	1294
Titanium sulphate, solution	154	1760	2,4-Toluenediamine	151	1709
Titanium tetrachloride	137	1838	Toxic liquid, corrosive, inorganic, n.o.s.	154	3289
Titanium trichloride, pyrophoric	135	2441			
Titanium trichloride mixture	157	2869			
Titanium trichloride mixture, pyrophoric	135	2441			
TNT, wetted with not less than 10% water	113	3366			
TNT, wetted with not less than 30% water	113	1356			
Toe puffs, nitrocellulose base	133	1353			

Name of Material	Guide ID No.	ID No.
Toxic liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone A)	154	3289
Toxic liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone B)	154	3289
Toxic liquid, corrosive, n.o.s.	154	2927
Toxic liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)	154	2927
Toxic liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)	154	2927
Toxic liquid, corrosive, organic, n.o.s.	154	2927
Toxic liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone A)	154	2927
Toxic liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone B)	154	2927
Toxic liquid, flammable, n.o.s.	131	2929
Toxic liquid, flammable, n.o.s. (Inhalation Hazard Zone A)	131	2929
Toxic liquid, flammable, n.o.s. (Inhalation Hazard Zone B)	131	2929
Toxic liquid, flammable, organic, n.o.s.	131	2929
Toxic liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone A)	131	2929
Toxic liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone B)	131	2929
Toxic liquid, inorganic, n.o.s.	151	3287
Toxic liquid, inorganic, n.o.s. (Inhalation Hazard Zone A)	151	3287
Toxic liquid, inorganic, n.o.s. (Inhalation Hazard Zone B)	151	3287

Name of Material	Guide ID No.	ID No.
Toxic liquid, n.o.s.	153	2810
Toxic liquid, n.o.s. (Inhalation Hazard Zone A)	153	2810
Toxic liquid, n.o.s. (Inhalation Hazard Zone B)	153	2810
Toxic liquid, organic, n.o.s.	153	2810
Toxic liquid, organic, n.o.s. (Inhalation Hazard Zone A)	153	2810
Toxic liquid, organic, n.o.s. (Inhalation Hazard Zone B)	153	2810
Toxic liquid, oxidizing, n.o.s.	142	3122
Toxic liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)	142	3122
Toxic liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)	142	3122
Toxic liquid, water-reactive, n.o.s.	139	3123
Toxic liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)	139	3123
Toxic liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)	139	3123
Toxic liquid, which in contact with water emits flammable gases, n.o.s.	139	3123
Toxic liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone A)	139	3123
Toxic liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone B)	139	3123
Toxic solid, corrosive, inorganic, n.o.s.	154	3290
Toxic solid, corrosive, organic, n.o.s.	154	2928
Toxic solid, flammable, n.o.s.	134	2930

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Toxic solid, flammable, organic, n.o.s.	134	2930	Tri-(1-aziridinyl)phosphine oxide, solution	152	2501
Toxic solid, inorganic, n.o.s.	151	3288	Tributylamine	153	2542
Toxic solid, organic, n.o.s.	154	2811	Tributylphosphane	135	3254
Toxic solid, oxidizing, n.o.s.	141	3086	Tributylphosphine	135	3254
Toxic solid, self-heating, n.o.s.	136	3124	Trichloroacetic acid	153	1839
Toxic solid, water-reactive, n.o.s.	139	3125	Trichloroacetic acid, solution	153	2564
Toxic solid, which in contact with water emits flammable gases, n.o.s.	139	3125	Trichloroacetyl chloride	156	2442
Toxins	153	—	Trichlorobenzenes, liquid	153	2321
Toxins, extracted from living sources, liquid, n.o.s.	153	3172	Trichlorobutene	152	2322
Toxins, extracted from living sources, n.o.s.	153	3172	1,1,1-Trichloroethane	160	2831
Toxins, extracted from living sources, solid, n.o.s.	153	3172	Trichloroethylene	160	1710
Toxins, extracted from living sources, solid, n.o.s.	153	3462	Trichloroisocyanuric acid, dry	140	2468
Triallylamine	132	2610	Trichlorosilane	139	1295
Triallyl borate	156	2609	(mono)-(Trichloro)-tetra-(monopotassium dichloro)-penta-s-triazinetrione, dry	140	2468
Triazine pesticide, liquid, flammable, poisonous	131	2764	Tricresyl phosphate	151	2574
Triazine pesticide, liquid, flammable, toxic	131	2764	Triethylamine	132	1296
Triazine pesticide, liquid, poisonous	151	2998	Triethylenetetramine	153	2259
Triazine pesticide, liquid, poisonous, flammable	131	2997	Triethyl phosphite	130	2323
Triazine pesticide, liquid, toxic	151	2998	Trifluoroacetic acid	154	2699
Triazine pesticide, liquid, toxic, flammable	131	2997	Trifluoroacetyl chloride	125	3057
Triazine pesticide, solid, poisonous	151	2763	Trifluorochloroethylene, stabilized	119P	1082
Triazine pesticide, solid, toxic	151	2763	1,1,1-Trifluoroethane	115	2035
			Trifluoroethane, compressed	115	2035
			Trifluoromethane	126	1984
			Trifluoromethane, refrigerated liquid	120	3136
			Trifluoromethane and Chlorotrifluoromethane azeotropic mixture with approximately 60% Chlorotrifluoromethane	126	2599

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
2-Trifluoromethylaniline	153	2942	Tripropylene	128	2057
3-Trifluoromethylaniline	153	2948	Tris-(1-aziridinyl)phosphine oxide, solution	152	2501
Triisobutylene	128	2324	<b>Tungsten hexafluoride</b>	<b>125</b>	<b>2196</b>
Triisopropyl borate	129	2616	Turpentine	128	1299
<b>Trimethoxysilane</b>	<b>132</b>	<b>9269</b>	Turpentine substitute	128	1300
<b>Trimethylacetyl chloride</b>	<b>132</b>	<b>2438</b>	Undecane	128	2330
Trimethylamine, anhydrous	118	1083	<b>Uranium hexafluoride</b>	<b>166</b>	<b>2978</b>
Trimethylamine, aqueous solution	132	1297	<b>Uranium hexafluoride, fissile containing more than 1% Uranium-235</b>	<b>166</b>	<b>2977</b>
1,3,5-Trimethylbenzene	129	2325	<b>Uranium hexafluoride, non fissile or fissile-excepted</b>	<b>166</b>	<b>2978</b>
Trimethyl borate	129	2416	Uranium metal, pyrophoric	162	2979
<b>Trimethylchlorosilane</b>	<b>155</b>	<b>1298</b>	Uranyl nitrate, hexahydrate, solution	162	2980
Trimethylcyclohexylamine	153	2326	Uranyl nitrate, solid	162	2981
Trimethylhexamethylenediamines	153	2327	Urea hydrogen peroxide	140	1511
Trimethylhexamethylene diisocyanate	156	2328	Urea nitrate, wetted with not less than 10% water	113	3370
Trimethyl phosphite	130	2329	Urea nitrate, wetted with not less than 20% water	113	1357
Trinitrobenzene, wetted with not less than 10% water	113	3367	Valeraldehyde	129	2058
Trinitrobenzene, wetted with not less than 30% water	113	1354	Valeryl chloride	132	2502
Trinitrobenzoic acid, wetted with not less than 10% water	113	3368	Vanadium compound, n.o.s.	151	3285
Trinitrobenzoic acid, wetted with not less than 30% water	113	1355	Vanadium oxytrichloride	137	2443
Trinitrochlorobenzene, wetted with not less than 10% water	113	3365	Vanadium pentoxide	151	2862
Trinitrophenol, wetted with not less than 10% water	113	3364	Vanadium tetrachloride	137	2444
Trinitrophenol, wetted with not less than 30% water	113	1344	Vanadium trichloride	157	2475
Trinitrotoluene, wetted with not less than 10% water	113	3366	Vanadyl sulfate	151	2931
Trinitrotoluene, wetted with not less than 30% water	113	1356	Vanadyl sulphate	151	2931
Tripropylamine	132	2260	Vehicle, flammable gas powered	128	3166
			Vehicle, flammable liquid powered	128	3166
			Vinyl acetate, stabilized	129P	1301

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Vinyl bromide, stabilized	116P	1085	White asbestos	171	2590
Vinyl butyrate, stabilized	129P	2838	White phosphorus, dry	136	1381
Vinyl chloride, stabilized	116P	1086	White phosphorus, in solution	136	1381
Vinyl chloroacetate	155	2589	White phosphorus, molten	136	2447
Vinyl ethyl ether, stabilized	127P	1302	White phosphorus, under water	136	1381
Vinyl fluoride, stabilized	116P	1860	Wood preservatives, liquid	129	1306
Vinylidene chloride, stabilized	130P	1303	Wool waste, wet	133	1387
Vinyl isobutyl ether, stabilized	127P	1304	Xanthates	135	3342
Vinyl methyl ether, stabilized	116P	1087	Xenon	121	2036
Vinylpyridines, stabilized	131P	3073	Xenon, compressed	121	2036
Vinyltoluenes, stabilized	130P	2618	Xenon, refrigerated liquid (cryogenic liquid)	120	2591
Vinyltrichlorosilane	155P	1305	Xylenes	130	1307
Vinyltrichlorosilane, stabilized	155P	1305	Xylenols	153	2261
VX	153	2810	Xylenols, liquid	153	3430
Water-reactive liquid, corrosive, n.o.s.	138	3129	Xylenols, solid	153	2261
Water-reactive liquid, n.o.s.	138	3148	Xylidines	153	1711
Water-reactive liquid, poisonous, n.o.s.	139	3130	Xylidines, liquid	153	1711
Water-reactive liquid, toxic, n.o.s.	139	3130	Xylidines, solid	153	1711
Water-reactive solid, corrosive, n.o.s.	138	3131	Xylidines, solid	153	3452
Water-reactive solid, flammable, n.o.s.	138	3132	Xylyl bromide	152	1701
Water-reactive solid, n.o.s.	138	2813	Xylyl bromide, liquid	152	1701
Water-reactive solid, oxidizing, n.o.s.	138	3133	Xylyl bromide, solid	152	3417
Water-reactive solid, poisonous, n.o.s.	139	3134	Yellow phosphorus, dry	136	1381
Water-reactive solid, self- heating, n.o.s.	138	3135	Yellow phosphorus, in solution	136	1381
Water-reactive solid, toxic, n.o.s.	139	3134	Yellow phosphorus, molten	136	2447
Wheelchair, electric, with batteries	154	3171	Yellow phosphorus, under water	136	1381
			Zinc ammonium nitrite	140	1512
			Zinc arsenate	151	1712
			Zinc arsenate and Zinc arsenite mixture	151	1712
			Zinc arsenite	151	1712
			Zinc arsenite and Zinc arsenate mixture	151	1712

Name of Material	Guide No.	ID No.	Name of Material	Guide No.	ID No.
Zinc ashes	138	1435	Zirconium powder, wetted with not less than 25% water	170	1358
Zinc bromate	140	2469	Zirconium scrap	135	1932
Zinc chlorate	140	1513	Zirconium sulfate	171	9163
Zinc chloride, anhydrous	154	2331	Zirconium sulphate	171	9163
Zinc chloride, solution	154	1840	Zirconium suspended in a flammable liquid	170	1308
Zinc cyanide	151	1713	Zirconium suspended in a liquid (flammable)	170	1308
Zinc dithionite	171	1931	Zirconium tetrachloride	137	2503
Zinc dross	138	1435			
Zinc dust	138	1436			
Zinc fluorosilicate	151	2855			
Zinc hydrosulfite	171	1931			
Zinc hydrosulphite	171	1931			
Zinc nitrate	140	1514			
Zinc permanganate	140	1515			
Zinc peroxide	143	1516			
Zinc phosphide	139	1714			
Zinc powder	138	1436			
Zinc residue	138	1435			
Zinc resinate	133	2714			
Zinc silicofluoride	151	2855			
Zinc skimmings	138	1435			
Zirconium, dry, coiled wire, finished metal sheets or strips	170	2858			
Zirconium, dry, finished sheets, strips or coiled wire	135	2009			
Zirconium hydride	138	1437			
Zirconium metal, liquid suspension	170	1308			
Zirconium metal, powder, wet	170	1358			
Zirconium nitrate	140	2728			
Zirconium picramate, wetted with not less than 20% water	113	1517			
Zirconium powder, dry	135	2008			

## NOTES



# GUIDES

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- May explode from heat, shock, friction or contamination.
- May react violently or explosively on contact with air, water or foam.
- May be ignited by heat, sparks or flames.
- Vapors may travel to source of ignition and flash back.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**HEALTH**

- Inhalation, ingestion or contact with substance may cause severe injury, infection, disease or death.
- High concentration of gas may cause asphyxiation without warning.
- Contact may cause burns to skin and eyes.
- Fire or contact with water may produce irritating, toxic and/or corrosive gases.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it may not be effective in spill situations.

**EVACUATION****Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

**CAUTION:** Material may react with extinguishing agent.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks**

- Cool containers with flooding quantities of water until well after fire is out.
- Do not get water inside containers.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Prevent entry into waterways, sewers, basements or confined areas.

**Small Spill** • Take up with sand or other non-combustible absorbent material and place into containers for later disposal.

**Large Spill** • Dike far ahead of liquid spill for later disposal.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Shower and wash with soap and water.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- MAY EXPLODE AND THROW FRAGMENTS 1600 meters (1 MILE) OR MORE IF FIRE REACHES CARGO.
- For information on "Compatibility Group" letters, refer to Glossary section.

**HEALTH**

- Fire may produce irritating, corrosive and/or toxic gases.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- Isolate spill or leak area immediately for at least 500 meters (1/3 mile) in all directions.
- Move people out of line of sight of the scene and away from windows.
- Keep unauthorized personnel away.
- Stay upwind.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- **Consider initial evacuation for 800 meters (1/2 mile) in all directions.**

**Fire**

- If rail car or trailer is involved in a fire and heavily encased explosives such as bombs or artillery projectiles are suspected, ISOLATE for 1600 meters (1 mile) in all directions; also, initiate evacuation including emergency responders for 1600 meters (1 mile) in all directions.
- When heavily encased explosives are not involved, evacuate the area for 800 meters (1/2 mile) in all directions.

**\* For information on "Compatibility Group" letters, refer to the Glossary section.**

**EMERGENCY RESPONSE****FIRE****CARGO Fire**

- **DO NOT fight fire when fire reaches cargo! Cargo may EXPLODE!**
- Stop all traffic and clear the area for at least 1600 meters (1 mile) in all directions and let burn.
- **Do not move cargo or vehicle if cargo has been exposed to heat.**

**TIRE or VEHICLE Fire**

- **Use plenty of water - FLOOD it! If water is not available, use CO<sub>2</sub>, dry chemical or dirt.**
- If possible, and WITHOUT RISK, use unmanned hose holders or monitor nozzles from maximum distance to prevent fire from spreading to cargo area.
- Pay special attention to tire fires as re-ignition may occur. Stand by with extinguisher ready.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material.
- DO NOT OPERATE RADIO TRANSMITTERS WITHIN 100 meters (330 feet) OF ELECTRIC DETONATORS.
- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**\* For information on "Compatibility Group" letters, refer to the Glossary section.**

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Flammable/combustible material.
- May be ignited by heat, sparks or flames.
- **DRIED OUT material may explode if exposed to heat, flame, friction or shock; Treat as an explosive (GUIDE 112).**
- **Keep material wet with water or treat as an explosive (GUIDE 112).**
- Runoff to sewer may create fire or explosion hazard.

**HEALTH**

- Some are toxic and may be fatal if inhaled, swallowed or absorbed through skin.
- Contact may cause burns to skin and eyes.
- Fire may produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- Isolate spill or leak area immediately for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- **Consider initial evacuation for 500 meters (1/3 mile) in all directions.**

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****CARGO Fire**

- **DO NOT fight fire when fire reaches cargo! Cargo may EXPLODE!**
- Stop all traffic and clear the area for at least 800 meters (1/2 mile) in all directions and let burn.
- **Do not move cargo or vehicle if cargo has been exposed to heat.**

**TIRE or VEHICLE Fire**

- **Use plenty of water - FLOOD it! If water is not available, use CO<sub>2</sub>, dry chemical or dirt.**
- If possible, and WITHOUT RISK, use unmanned hose holders or monitor nozzles from maximum distance to prevent fire from spreading to cargo area.
- Pay special attention to tire fires as re-ignition may occur. Stand by with extinguisher ready.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material.

**Small Spill**

- Flush area with flooding quantities of water.

**Large Spill**

- Wet down with water and dike for later disposal.
- **KEEP "WETTED" PRODUCT WET BY SLOWLY ADDING FLOODING QUANTITIES OF WATER.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- **MAY EXPLODE AND THROW FRAGMENTS 500 meters (1/3 MILE) OR MORE IF FIRE REACHES CARGO.**
- For information on "Compatibility Group" letters, refer to Glossary section.

**HEALTH**

- Fire may produce irritating, corrosive and/or toxic gases.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- Isolate spill or leak area immediately for at least 100 meters (330 feet) in all directions.
- Move people out of line of sight of the scene and away from windows.
- Keep unauthorized personnel away.
- Stay upwind.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- **Consider initial evacuation for 250 meters (800 feet) in all directions.**

**Fire**

- If rail car or trailer is involved in a fire, ISOLATE for 500 meters (1/3 mile) in all directions; also initiate evacuation including emergency responders for 500 meters (1/3 mile) in all directions.

**\* For information on "Compatibility Group" letters, refer to the Glossary section.**



**EMERGENCY RESPONSE****FIRE****CARGO Fire**

- **DO NOT fight fire when fire reaches cargo! Cargo may EXPLODE!**
- Stop all traffic and clear the area for at least 500 meters (1/3 mile) in all directions and let burn.
- **Do not move cargo or vehicle if cargo has been exposed to heat.**

**TIRE or VEHICLE Fire**

- **Use plenty of water - FLOOD it! If water is not available, use CO<sub>2</sub>, dry chemical or dirt.**
- If possible, and WITHOUT RISK, use unmanned hose holders or monitor nozzles from maximum distance to prevent fire from spreading to cargo area.
- Pay special attention to tire fires as re-ignition may occur. Stand by with extinguisher ready.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material.
- DO NOT OPERATE RADIO TRANSMITTERS WITHIN 100 meters (330 feet) OF ELECTRIC DETONATORS.
- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**SUPPLEMENTAL INFORMATION**

- Packages bearing the 1.4S label or packages containing material classified as 1.4S are designed or packaged in such a manner that when involved in a fire, may burn vigorously with localized detonations and projection of fragments.
- Effects are usually confined to immediate vicinity of packages.
- If fire threatens cargo area containing packages bearing the 1.4S label or packages containing material classified as 1.4S, consider isolating at least 15 meters (50 feet) in all directions. Fight fire with normal precautions from a reasonable distance.

**\* For information on "Compatibility Group" letters, refer to the Glossary section.**

**POTENTIAL HAZARDS****FIRE OR EXPLOSION****• EXTREMELY FLAMMABLE.**

- Will be easily ignited by heat, sparks or flames.
- Will form explosive mixtures with air.
- Vapors from liquefied gas are initially heavier than air and spread along ground.

**CAUTION:Hydrogen (UN1049), Deuterium (UN1957), Hydrogen, refrigerated liquid (UN1966) and Methane (UN1971) are lighter than air and will rise. Hydrogen and Deuterium fires are difficult to detect since they burn with an invisible flame. Use an alternate method of detection (thermal camera, broom handle, etc.)**

- Vapors may travel to source of ignition and flash back.
- Cylinders exposed to fire may vent and release flammable gas through pressure relief devices.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**HEALTH**

- Vapors may cause dizziness or asphyxiation without warning.
- Some may be irritating if inhaled at high concentrations.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire may produce irritating and/or toxic gases.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.
- Always wear thermal protective clothing when handling refrigerated/cryogenic liquids.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 800 meters (1/2 mile).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

**CAUTION:** Hydrogen (UN1049), Deuterium (UN1957) and Hydrogen, refrigerated liquid (UN1966) burn with an invisible flame. Hydrogen and Methane mixture, compressed (UN2034) may burn with an invisible flame.

**Small Fire**

- Dry chemical or CO<sub>2</sub>.

**Large Fire**

- Water spray or fog.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Do not direct water at spill or source of leak.
- Prevent spreading of vapors through sewers, ventilation systems and confined areas.
- Isolate area until gas has dispersed.

**CAUTION:** When in contact with refrigerated/cryogenic liquids, many materials become brittle and are likely to break without warning.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Clothing frozen to the skin should be thawed before being removed.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. • Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION****• EXTREMELY FLAMMABLE.**

- Will be easily ignited by heat, sparks or flames.
- Will form explosive mixtures with air.
- Silane will ignite spontaneously in air.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Vapors may travel to source of ignition and flash back.
- Cylinders exposed to fire may vent and release flammable gas through pressure relief devices.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**HEALTH**

- Vapors may cause dizziness or asphyxiation without warning.
- Some may be toxic if inhaled at high concentrations.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire may produce irritating and/or toxic gases.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 800 meters (1/2 mile).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- **DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.**

**Small Fire**

- Dry chemical or CO<sub>2</sub>.

**Large Fire**

- Water spray or fog.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Stop leak if you can do it without risk.
- Do not touch or walk through spilled material.
- Do not direct water at spill or source of leak.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Isolate area until gas has dispersed.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH****• TOXIC; Extremely Hazardous.**

- May be fatal if inhaled or absorbed through skin.
- Initial odor may be irritating or foul and may deaden your sense of smell.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control may cause pollution.

**FIRE OR EXPLOSION**

- These materials are extremely flammable.
- May form explosive mixtures with air.
- May be ignited by heat, sparks or flames.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Vapors may travel to source of ignition and flash back.
- Runoff may create fire or explosion hazard.
- Cylinders exposed to fire may vent and release toxic and flammable gas through pressure relief devices.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances.

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- **DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.**

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.
- Damaged cylinders should be handled only by specialists.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
  - Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
  - Do not direct water at spill or source of leak.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Isolate area until gas has dispersed.
- Consider igniting spill or leak to eliminate toxic gas concerns.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Keep victim warm and quiet. • Keep victim under observation.
- Effects of contact or inhalation may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION****• EXTREMELY FLAMMABLE.**

- May be ignited by heat, sparks or flames.
- May form explosive mixtures with air.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Vapors may travel to source of ignition and flash back.
- Some of these materials may react violently with water.
- Cylinders exposed to fire may vent and release flammable gas through pressure relief devices.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**HEALTH**

- May cause toxic effects if inhaled.
- Vapors are extremely irritating.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas. • Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 800 meters (1/2 mile).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.



**EMERGENCY RESPONSE****FIRE**

- **DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.**

**Small Fire**

- Dry chemical or CO<sub>2</sub>.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.
- Damaged cylinders should be handled only by specialists.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Do not direct water at spill or source of leak.
- Isolate area until gas has dispersed.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Keep victim warm and quiet. • Keep victim under observation.
- Effects of contact or inhalation may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC; may be fatal if inhaled or absorbed through skin.**
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control may cause pollution.

**FIRE OR EXPLOSION**

- Flammable; may be ignited by heat, sparks or flames.
- May form explosive mixtures with air.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Vapors may travel to source of ignition and flash back.
- Some of these materials may react violently with water.
- Cylinders exposed to fire may vent and release toxic and flammable gas through pressure relief devices.
- Containers may explode when heated.
- Ruptured cylinders may rocket.
- Runoff may create fire or explosion hazard.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away. • Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas. • Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- **DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.**

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Large Fire**

- Water spray, fog or alcohol-resistant foam.
- **FOR CHLOROSILANES, DO NOT USE WATER**; use AFFF alcohol-resistant medium expansion foam.
  - Move containers from fire area if you can do it without risk.
- Damaged cylinders should be handled only by specialists.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
  - ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Do not direct water at spill or source of leak.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- **FOR CHLOROSILANES**, use AFFF alcohol-resistant medium expansion foam to reduce vapors.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Isolate area until gas has dispersed.

**FIRST AID**

- Move victim to fresh air.
  - Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Keep victim warm and quiet.
  - Keep victim under observation.
- Effects of contact or inhalation may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- Vapors may cause dizziness or asphyxiation without warning.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.

**FIRE OR EXPLOSION**

- **Non-flammable gases.**
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.
- Always wear thermal protective clothing when handling refrigerated/cryogenic liquids or solids.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- Use extinguishing agent suitable for type of surrounding fire.
- Move containers from fire area if you can do it without risk.
- Damaged cylinders should be handled only by specialists.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Do not direct water at spill or source of leak.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Allow substance to evaporate.
- Ventilate the area.

**CAUTION: When in contact with refrigerated/cryogenic liquids, many materials become brittle and are likely to break without warning.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Clothing frozen to the skin should be thawed before being removed.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- Vapors may cause dizziness or asphyxiation without warning.
- Vapors from liquefied gas are initially heavier than air and spread along ground.

**FIRE OR EXPLOSION**

- **Non-flammable gases.**
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- Use extinguishing agent suitable for type of surrounding fire.
- Move containers from fire area if you can do it without risk.
- Damaged cylinders should be handled only by specialists.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Do not direct water at spill or source of leak.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Allow substance to evaporate.
- Ventilate the area.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Substance does not burn but will support combustion.
- Some may react explosively with fuels.
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Runoff may create fire or explosion hazard.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**HEALTH**

- Vapors may cause dizziness or asphyxiation without warning.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire may produce irritating and/or toxic gases.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
- Always wear thermal protective clothing when handling refrigerated/cryogenic liquids.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 500 meters (1/3 mile).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



**EMERGENCY RESPONSE****FIRE**

- Use extinguishing agent suitable for type of surrounding fire.

**Small Fire**

- Dry chemical or CO<sub>2</sub>.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.
- Damaged cylinders should be handled only by specialists.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Do not direct water at spill or source of leak.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Prevent entry into waterways, sewers, basements or confined areas.
- Allow substance to evaporate.
- Isolate area until gas has dispersed.

**CAUTION: When in contact with refrigerated/cryogenic liquids, many materials become brittle and are likely to break without warning.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Clothing frozen to the skin should be thawed before being removed.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC; may be fatal if inhaled or absorbed through skin.**
- Vapors may be irritating.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control may cause pollution.

**FIRE OR EXPLOSION**

- Some may burn but none ignite readily.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Cylinders exposed to fire may vent and release toxic and/or corrosive gas through pressure relief devices.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical or CO<sub>2</sub>.

**Large Fire**

- Water spray, fog or regular foam.
- Do not get water inside containers.
- Move containers from fire area if you can do it without risk.
- Damaged cylinders should be handled only by specialists.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Do not direct water at spill or source of leak.
- Isolate area until gas has dispersed.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet. • Keep victim under observation.
- Effects of contact or inhalation may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC; may be fatal if inhaled or absorbed through skin.**
- Fire will produce irritating, corrosive and/or toxic gases.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Runoff from fire control may cause pollution.

**FIRE OR EXPLOSION**

- Substance does not burn but will support combustion.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- These are strong oxidizers and will react vigorously or explosively with many materials including fuels.
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- Some will react violently with air, moist air and/or water.
- Cylinders exposed to fire may vent and release toxic and/or corrosive gas through pressure relief devices.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances.

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

**Small Fire: Water only; no dry chemical, CO<sub>2</sub> or Halon®.**

- Contain fire and let burn. If fire must be fought, water spray or fog is recommended.
- Do not get water inside containers.
- Move containers from fire area if you can do it without risk.
- Damaged cylinders should be handled only by specialists.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- Do not touch or walk through spilled material.
- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Do not direct water at spill or source of leak.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Isolate area until gas has dispersed.
- Ventilate the area.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Clothing frozen to the skin should be thawed before being removed.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet. • Keep victim under observation.
- Effects of contact or inhalation may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC; may be fatal if inhaled, ingested or absorbed through skin.**
- Vapors are extremely irritating and corrosive.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control may cause pollution.

**FIRE OR EXPLOSION**

- Some may burn but none ignite readily.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Some of these materials may react violently with water.
- Cylinders exposed to fire may vent and release toxic and/or corrosive gas through pressure relief devices.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical or CO<sub>2</sub>.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.
- Do not get water inside containers.
- Damaged cylinders should be handled only by specialists.

**Fire Involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. • ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Do not direct water at spill or source of leak.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. • Isolate area until gas has dispersed.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- **In case of contact with Hydrogen fluoride, anhydrous (UN1052),** flush skin and eyes with water for 5 minutes; then, for skin exposures rub on a calcium/jelly combination; for eyes flush with a water/calcium solution for 15 minutes.
- Keep victim warm and quiet. • Keep victim under observation.
- Effects of contact or inhalation may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Some may burn but none ignite readily.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**HEALTH**

- Vapors may cause dizziness or asphyxiation without warning.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire may produce irritating, corrosive and/or toxic gases.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 500 meters (1/3 mile).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



**EMERGENCY RESPONSE****FIRE**

- Use extinguishing agent suitable for type of surrounding fire.

**Small Fire**

- Dry chemical or CO<sub>2</sub>.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.
- Damaged cylinders should be handled only by specialists.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- Some of these materials, if spilled, may evaporate leaving a flammable residue.

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Do not direct water at spill or source of leak.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Allow substance to evaporate.
- Ventilate the area.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- **HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.**
- Vapors may form explosive mixtures with air.
- Vapors may travel to source of ignition and flash back.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapor explosion hazard indoors, outdoors or in sewers.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Runoff to sewer may create fire or explosion hazard.
- Containers may explode when heated.
- Many liquids are lighter than water.

**HEALTH**

- Inhalation or contact with material may irritate or burn skin and eyes.
- Fire may produce irritating, corrosive and/or toxic gases.
- Vapors may cause dizziness or suffocation.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 300 meters (1000 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

**CAUTION:** All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Large Fire**

- Water spray, fog or alcohol-resistant foam.
- Use water spray or fog; do not use straight streams.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- A vapor suppressing foam may be used to reduce vapors.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- Use clean non-sparking tools to collect absorbed material.

**Large Spill**

- Dike far ahead of liquid spill for later disposal.
- Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. • Wash skin with soap and water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- **HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.**
- Vapors may form explosive mixtures with air.
- Vapors may travel to source of ignition and flash back.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapor explosion hazard indoors, outdoors or in sewers.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Runoff to sewer may create fire or explosion hazard.
- Containers may explode when heated.
- Many liquids are lighter than water.
- Substance may be transported hot.
- **If molten aluminum is involved, refer to GUIDE 169.**

**HEALTH**

- Inhalation or contact with material may irritate or burn skin and eyes.
- Fire may produce irritating, corrosive and/or toxic gases.
- Vapors may cause dizziness or suffocation.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 300 meters (1000 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

**CAUTION:** All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.

**CAUTION:** For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog or regular foam.
- Use water spray or fog; do not use straight streams.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material. • Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- A vapor suppressing foam may be used to reduce vapors.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. • Use clean non-sparking tools to collect absorbed material.

**Large Spill**

- Dike far ahead of liquid spill for later disposal.
- Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Wash skin with soap and water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. • Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- **HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.**
- Vapors may form explosive mixtures with air.
- Vapors may travel to source of ignition and flash back.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapor explosion hazard indoors, outdoors or in sewers.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Runoff to sewer may create fire or explosion hazard.
- Containers may explode when heated.
- Many liquids are lighter than water.

**HEALTH**

- May cause toxic effects if inhaled or absorbed through skin.
- Inhalation or contact with material may irritate or burn skin and eyes.
- Fire will produce irritating, corrosive and/or toxic gases.
- Vapors may cause dizziness or suffocation.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 300 meters (1000 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

**CAUTION:** All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.

**Small Fire** • Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

- **Do not use dry chemical extinguishers to control fires involving nitromethane or nitroethane.**

**Large Fire**

- Water spray, fog or alcohol-resistant foam.
- **Do not use straight streams.**
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material. • Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- A vapor suppressing foam may be used to reduce vapors.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- Use clean non-sparking tools to collect absorbed material.

**Large Spill** • Dike far ahead of liquid spill for later disposal.

- Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Wash skin with soap and water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. • Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- **HIGHLY FLAMMABLE:** Will be easily ignited by heat, sparks or flames.
- Vapors may form explosive mixtures with air.
- Vapors may travel to source of ignition and flash back.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapor explosion hazard indoors, outdoors or in sewers.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Runoff to sewer may create fire or explosion hazard.
- Containers may explode when heated.
- Many liquids are lighter than water.

**HEALTH**

- May cause toxic effects if inhaled or absorbed through skin.
- Inhalation or contact with material may irritate or burn skin and eyes.
- Fire will produce irritating, corrosive and/or toxic gases.
- Vapors may cause dizziness or suffocation.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 300 meters (1000 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



**EMERGENCY RESPONSE****FIRE**

**CAUTION:** All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog or regular foam.
- **Do not use straight streams.**
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- A vapor suppressing foam may be used to reduce vapors.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- Use clean non-sparking tools to collect absorbed material.

**Large Spill** • Dike far ahead of liquid spill for later disposal.

- Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Wash skin with soap and water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. • Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC; may be fatal if inhaled, ingested or absorbed through skin.**
- Inhalation or contact with some of these materials will irritate or burn skin and eyes.
- Fire will produce irritating, corrosive and/or toxic gases.
- Vapors may cause dizziness or suffocation.
- Runoff from fire control or dilution water may cause pollution.

**FIRE OR EXPLOSION**

- **HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.**
- Vapors may form explosive mixtures with air.
- Vapors may travel to source of ignition and flash back.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapor explosion and poison hazard indoors, outdoors or in sewers.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Runoff to sewer may create fire or explosion hazard.
- Containers may explode when heated.
- Many liquids are lighter than water.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind. • Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

**CAUTION:** All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.

**Small Fire** • Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Large Fire**

- Water spray, fog or alcohol-resistant foam.
- Move containers from fire area if you can do it without risk.
- Dike fire-control water for later disposal; do not scatter the material.
- Use water spray or fog; do not use straight streams.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material. • Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- A vapor suppressing foam may be used to reduce vapors.

**Small Spill** • Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

- Use clean non-sparking tools to collect absorbed material.

**Large Spill** • Dike far ahead of liquid spill for later disposal.

- Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Wash skin with soap and water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. • Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Flammable/combustible material.
- May be ignited by heat, sparks or flames.
- Vapors may form explosive mixtures with air.
- Vapors may travel to source of ignition and flash back.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapor explosion hazard indoors, outdoors or in sewers.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Runoff to sewer may create fire or explosion hazard.
- Containers may explode when heated.
- Many liquids are lighter than water.

**HEALTH**

- May cause toxic effects if inhaled or ingested/swallowed.
- Contact with substance may cause severe burns to skin and eyes.
- Fire will produce irritating, corrosive and/or toxic gases.
- Vapors may cause dizziness or suffocation.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Large Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- **Some of these materials may react violently with water.**

**Small Fire** • Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Large Fire** • Water spray, fog or alcohol-resistant foam.

- Move containers from fire area if you can do it without risk.
- Dike fire-control water for later disposal; do not scatter the material.
- Do not get water inside containers.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material. • Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- A vapor suppressing foam may be used to reduce vapors.
- Absorb with earth, sand or other non-combustible material and transfer to containers (except for Hydrazine).
- Use clean non-sparking tools to collect absorbed material.

**Large Spill** • Dike far ahead of liquid spill for later disposal.

- Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Flammable/combustible material.
- May be ignited by friction, heat, sparks or flames.
- Some may burn rapidly with flare burning effect.
- Powders, dusts, shavings, borings, turnings or cuttings may explode or burn with explosive violence.
- Substance may be transported in a molten form at a temperature that may be above its flash point.
- May re-ignite after fire is extinguished.

**HEALTH**

- Fire may produce irritating and/or toxic gases.
- Contact may cause burns to skin and eyes.
- Contact with molten substance may cause severe burns to skin and eyes.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub>, sand, earth, water spray or regular foam.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.

**Fire Involving Metal Pigments or Pastes (e.g. "Aluminum Paste")**

- Aluminum Paste fires should be treated as a combustible metal fire. Use DRY sand, graphite powder, dry sodium chloride based extinguishers, G-1® or Met-L-X® powder. Also, see GUIDE 170.

**Fire involving Tanks or Car/Trailer Loads**

- Cool containers with flooding quantities of water until well after fire is out.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch or walk through spilled material.

**Small Dry Spill**

- With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.

**Large Spill**

- Wet down with water and dike for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Removal of solidified molten material from skin requires medical assistance.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Flammable/combustible material.
- May be ignited by heat, sparks or flames.
- When heated, vapors may form explosive mixtures with air: indoors, outdoors and sewers explosion hazards.
- Contact with metals may evolve flammable hydrogen gas.
- Containers may explode when heated.

**HEALTH**

- **TOXIC**; inhalation, ingestion or skin contact with material may cause severe injury or death.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions.
- Stay upwind.
- Keep unauthorized personnel away.
- Keep out of low areas.
- Ventilate enclosed areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Large Fire**

- Water spray, fog or alcohol-resistant foam.
- Move containers from fire area if you can do it without risk.
- Use water spray or fog; do not use straight streams.
- Do not get water inside containers.
- Dike fire-control water for later disposal; do not scatter the material.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Stop leak if you can do it without risk.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Prevent entry into waterways, sewers, basements or confined areas.
- Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Flammable/combustible material.
- May ignite on contact with moist air or moisture.
- May burn rapidly with flare-burning effect.
- Some react vigorously or explosively on contact with water.
- Some may decompose explosively when heated or involved in a fire.
- May re-ignite after fire is extinguished.
- Runoff may create fire or explosion hazard.
- Containers may explode when heated.

**HEALTH**

- Fire will produce irritating, corrosive and/or toxic gases.
- Inhalation of decomposition products may cause severe injury or death.
- Contact with substance may cause severe burns to skin and eyes.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Stay upwind.
- Keep unauthorized personnel away.
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

• **DO NOT USE WATER, CO<sub>2</sub> OR FOAM ON MATERIAL ITSELF.**

- Some of these materials may react violently with water.

**EXCEPTION: For Xanthates, UN3342 and for Dithionite (Hydrosulfite/ Hydrosulphite) UN1384, UN1923 and UN1929, USE FLOODING AMOUNTS OF WATER for SMALL AND LARGE fires to stop the reaction. Smothering will not work for these materials, they do not need air to burn.**

**Small Fire**

- Dry chemical, soda ash, lime or DRY sand, **EXCEPT for UN1384, UN1923 and UN1929.**

**Large Fire**

- DRY sand, dry chemical, soda ash or lime, **EXCEPT for UN1384, UN1923 and UN1929**, or withdraw from area and let fire burn.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers or in contact with substance.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch or walk through spilled material. • Stop leak if you can do it without risk.

**Small Spill**

**EXCEPTION: For spills of Xanthates, UN3342 and for Dithionite (Hydrosulfite/ Hydrosulphite), UN1384, UN1923 and UN1929, dissolve in 5 parts water and collect for proper disposal.**

- Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
- Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. • Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Extremely flammable; will ignite itself if exposed to air.
- Burns rapidly, releasing dense, white, irritating fumes.
- Substance may be transported in a molten form.
- May re-ignite after fire is extinguished.
- Corrosive substances in contact with metals may produce flammable hydrogen gas.
- Containers may explode when heated.

**HEALTH**

- Fire will produce irritating, corrosive and/or toxic gases.
- TOXIC; ingestion of substance or inhalation of decomposition products will cause severe injury or death.
- Contact with substance may cause severe burns to skin and eyes.
- Some effects may be experienced due to skin absorption.
- Runoff from fire control may be corrosive and/or toxic and cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Stay upwind.
- Keep unauthorized personnel away.
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
- **For Phosphorus (UN1381): Special aluminized protective clothing should be worn when direct contact with the substance is possible.**

**EVACUATION****Spill**

- Consider initial downwind evacuation for at least 300 meters (1000 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Water spray, wet sand or wet earth.

**Large Fire**

- Water spray or fog.
- **Do not scatter spilled material with high pressure water streams.**
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch or walk through spilled material.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.

**Small Spill**

- Cover with water, sand or earth. Shovel into metal container and keep material under water.

**Large Spill**

- Dike for later disposal and cover with wet sand or earth.
- Prevent entry into waterways, sewers, basements or confined areas.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- In case of contact with substance, keep exposed skin areas immersed in water or covered with wet bandages until medical attention is received.
- Removal of solidified molten material from skin requires medical assistance.
- Remove and isolate contaminated clothing and shoes at the site and place in metal container filled with water. Fire hazard if allowed to dry.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- CORROSIVE and/or TOXIC; inhalation, ingestion or contact (skin, eyes) with vapors, dusts or substance may cause severe injury, burns or death.
- Fire will produce irritating, corrosive and/or toxic gases.
- Reaction with water may generate much heat that will increase the concentration of fumes in the air.
- Contact with molten substance may cause severe burns to skin and eyes.
- Runoff from fire control or dilution water may cause pollution.

**FIRE OR EXPLOSION**

- **EXCEPT FOR ACETIC ANHYDRIDE (UN1715), THAT IS FLAMMABLE**, some of these materials may burn, but none ignite readily.
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- Substance will react with water (some violently), releasing corrosive and/or toxic gases and runoff.
- Flammable/toxic gases may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.).
- Contact with metals may evolve flammable hydrogen gas.
- Containers may explode when heated or if contaminated with water.
- Substance may be transported in a molten form.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind. • Keep out of low areas. • Ventilate enclosed areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- **When material is not involved in fire, do not use water on material itself.**

**Small Fire**

- Dry chemical or CO<sub>2</sub>.
- Move containers from fire area if you can do it without risk.

**Large Fire**

- Flood fire area with large quantities of water, while knocking down vapors with water fog. If insufficient water supply: knock down vapors only.

**Fire involving Tanks or Car/Trailer Loads**

- Cool containers with flooding quantities of water until well after fire is out.
- Do not get water inside containers.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container.
- Keep combustibles (wood, paper, oil, etc.) away from spilled material.

**Small Spill** • Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.

- Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Removal of solidified molten material from skin requires medical assistance.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Produce flammable gases on contact with water.
- May ignite on contact with water or moist air.
- Some react vigorously or explosively on contact with water.
- May be ignited by heat, sparks or flames.
- May re-ignite after fire is extinguished.
- Some are transported in highly flammable liquids.
- Runoff may create fire or explosion hazard.

**HEALTH**

- Inhalation or contact with vapors, substance or decomposition products may cause severe injury or death.
- May produce corrosive solutions on contact with water.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate the area before entry.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Large Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



**EMERGENCY RESPONSE****FIRE**

- **DO NOT USE WATER OR FOAM.**

**Small Fire**

- Dry chemical, soda ash, lime or sand.

**Large Fire**

- DRY sand, dry chemical, soda ash or lime or withdraw from area and let fire burn.
- Move containers from fire area if you can do it without risk.

**Fire Involving Metals or Powders (Aluminum, Lithium, Magnesium, etc.)**

- Use dry chemical, DRY sand, sodium chloride powder, graphite powder or Met-L-X® powder; in addition, for Lithium you may use Lith-X® powder or copper powder. Also, see GUIDE 170.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- **DO NOT GET WATER on spilled substance or inside containers.**

**Small Spill** • Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.

- Dike for later disposal; do not apply water unless directed to do so.

**Powder Spill** • Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry.

- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, wipe from skin immediately; flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Produce flammable and toxic gases on contact with water.
- May ignite on contact with water or moist air.
- Some react vigorously or explosively on contact with water.
- May be ignited by heat, sparks or flames.
- May re-ignite after fire is extinguished.
- Some are transported in highly flammable liquids.
- Containers may explode when heated.
- Runoff may create fire or explosion hazard.

**HEALTH**

- Highly toxic: contact with water produces toxic gas, may be fatal if inhaled.
- Inhalation or contact with vapors, substance or decomposition products may cause severe injury or death.
- May produce corrosive solutions on contact with water.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate the area before entry.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Large Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

## EMERGENCY RESPONSE

## FIRE

**DO NOT USE WATER OR FOAM. (FOAM MAY BE USED FOR CHLOROSILANES, SEE BELOW)**

**Small Fire**

- Dry chemical, soda ash, lime or sand.

**Large Fire**

- DRY sand, dry chemical, soda ash or lime or withdraw from area and let fire burn.
- **FOR CHLOROSILANES, DO NOT USE WATER;** use AFFF alcohol-resistant medium expansion foam; **DO NOT USE** dry chemicals, soda ash or lime on chlorosilane fires (large or small) as they may release large quantities of hydrogen gas that may explode.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not get water inside containers.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- **ALWAYS** stay away from tanks engulfed in fire.

## SPILL OR LEAK

- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- **ELIMINATE** all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- **DO NOT GET WATER on spilled substance or inside containers.**
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- **FOR CHLOROSILANES,** use AFFF alcohol-resistant medium expansion foam to reduce vapors.

**Small Spill** • Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.

- Dike for later disposal; do not apply water unless directed to do so.

**Powder Spill** • Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry.

- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

## FIRST AID

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, wipe from skin immediately; flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- These substances will accelerate burning when involved in a fire.
- Some may decompose explosively when heated or involved in a fire.
- May explode from heat or contamination.
- Some will react explosively with hydrocarbons (fuels).
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- Containers may explode when heated.
- Runoff may create fire or explosion hazard.

**HEALTH**

- Inhalation, ingestion or contact (skin, eyes) with vapors or substance may cause severe injury, burns or death.
- Fire may produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Use water. Do not use dry chemicals or foams. CO<sub>2</sub> or Halon® may provide limited control.

**Large Fire**

- Flood fire area with water from a distance.
- Do not move cargo or vehicle if cargo has been exposed to heat.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- Do not get water inside containers.

**Small Dry Spill**

- With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.

**Small Liquid Spill**

- Use a non-combustible material like vermiculite or sand to soak up the product and place into a container for later disposal.

**Large Spill**

- Dike far ahead of liquid spill for later disposal.
- **Following product recovery, flush area with water.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Contaminated clothing may be a fire risk when dry.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- These substances will accelerate burning when involved in a fire.
- May explode from heat or contamination.
- Some may burn rapidly.
- Some will react explosively with hydrocarbons (fuels).
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- Containers may explode when heated.
- Runoff may create fire or explosion hazard.

**HEALTH**

- Toxic by ingestion.
- Inhalation of dust is toxic.
- Fire may produce irritating, corrosive and/or toxic gases.
- Contact with substance may cause severe burns to skin and eyes.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Use water. Do not use dry chemicals or foams. CO<sub>2</sub> or Halon® may provide limited control.

**Large Fire**

- Flood fire area with water from a distance.
- Do not move cargo or vehicle if cargo has been exposed to heat.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.

**Small Dry Spill**

- With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.

**Large Spill**

- Dike far ahead of spill for later disposal.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Contaminated clothing may be a fire risk when dry.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- These substances will accelerate burning when involved in a fire.
- May explode from heat or contamination.
- Some will react explosively with hydrocarbons (fuels).
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- Containers may explode when heated.
- Runoff may create fire or explosion hazard.

**HEALTH**

- **TOXIC**; inhalation, ingestion or contact (skin, eyes) with vapors or substance may cause severe injury, burns or death.
- Fire may produce irritating, corrosive and/or toxic gases.
- Toxic/flammable fumes may accumulate in confined areas (basement, tanks, tank cars, etc.).
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations **ONLY**; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



**EMERGENCY RESPONSE****FIRE****Small Fire**

- Use water. Do not use dry chemicals or foams. CO<sub>2</sub> or Halon® may provide limited control.

**Large Fire**

- Flood fire area with water from a distance.
- Do not move cargo or vehicle if cargo has been exposed to heat.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors or divert vapor cloud drift.
- Do not get water inside containers.

**Small Liquid Spill**

- Use a non-combustible material like vermiculite or sand to soak up the product and place into a container for later disposal.

**Large Spill**

- Dike far ahead of liquid spill for later disposal.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Contaminated clothing may be a fire risk when dry.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- May explode from friction, heat or contamination.
- These substances will accelerate burning when involved in a fire.
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- Some will react explosively with hydrocarbons (fuels).
- Containers may explode when heated.
- Runoff may create fire or explosion hazard.

**HEALTH**

- **TOXIC**; inhalation, ingestion or contact (skin, eyes) with vapors, dusts or substance may cause severe injury, burns or death.
- Fire may produce irritating and/or toxic gases.
- Toxic fumes or dust may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.).
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Use water. Do not use dry chemicals or foams. CO<sub>2</sub> or Halon® may provide limited control.

**Large Fire**

- Flood fire area with water from a distance.
- Do not move cargo or vehicle if cargo has been exposed to heat.
- Move containers from fire area if you can do it without risk.
- Do not get water inside containers: a violent reaction may occur.

**Fire involving Tanks or Car/Trailer Loads**

- Cool containers with flooding quantities of water until well after fire is out.
- Dike fire-control water for later disposal.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Use water spray to reduce vapors or divert vapor cloud drift.
- Prevent entry into waterways, sewers, basements or confined areas.

**Small Spill**

- Flush area with flooding quantities of water.

**Large Spill**

- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Contaminated clothing may be a fire risk when dry.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- May ignite combustibles (wood, paper, oil, clothing, etc.).
- React vigorously and/or explosively with water.
- Produce toxic and/or corrosive substances on contact with water.
- Flammable/toxic gases may accumulate in tanks and hopper cars.
- Some may produce flammable hydrogen gas upon contact with metals.
- Containers may explode when heated.
- Runoff may create fire or explosion hazard.

**HEALTH**

- **TOXIC**; inhalation or contact with vapor, substance, or decomposition products may cause severe injury or death.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations **ONLY**; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- **DO NOT USE WATER OR FOAM.**

**Small Fire**

- Dry chemical, soda ash or lime.

**Large Fire**

- DRY sand, dry chemical, soda ash or lime or withdraw from area and let fire burn.
- Do not move cargo or vehicle if cargo has been exposed to heat.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- **DO NOT GET WATER on spilled substance or inside containers.**

**Small Spill**

- Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.

**Large Spill**

- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Contaminated clothing may be a fire risk when dry.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet. • Keep victim under observation.
- Effects of contact or inhalation may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- May explode from heat or contamination.
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- May be ignited by heat, sparks or flames.
- May burn rapidly with flare-burning effect.
- Containers may explode when heated.
- Runoff may create fire or explosion hazard.

**HEALTH**

- Fire may produce irritating, corrosive and/or toxic gases.
- Ingestion or contact (skin, eyes) with substance may cause severe injury or burns.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial evacuation for at least 250 meters (800 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Water spray or fog is preferred; if water not available use dry chemical, CO<sub>2</sub> or regular foam.

**Large Fire**

- Flood fire area with water from a distance.
- Use water spray or fog; do not use straight streams.
- Do not move cargo or vehicle if cargo has been exposed to heat.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Keep substance wet using water spray.
- Stop leak if you can do it without risk.

**Small Spill**

- Take up with inert, damp, non-combustible material using clean non-sparking tools and place into loosely covered plastic containers for later disposal.

**Large Spill**

- Wet down with water and dike for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.
- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Contaminated clothing may be a fire risk when dry.
- Remove material from skin immediately.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- May explode from heat, shock, friction or contamination.
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- May be ignited by heat, sparks or flames.
- May burn rapidly with flare-burning effect.
- Containers may explode when heated.
- Runoff may create fire or explosion hazard.

**HEALTH**

- Fire may produce irritating, corrosive and/or toxic gases.
- Ingestion or contact (skin, eyes) with substance may cause severe injury or burns.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial evacuation for at least 250 meters (800 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



**EMERGENCY RESPONSE****FIRE****Small Fire**

- Water spray or fog is preferred; if water not available use dry chemical, CO<sub>2</sub> or regular foam.

**Large Fire**

- Flood fire area with water from a distance.
- Use water spray or fog; do not use straight streams.
- Do not move cargo or vehicle if cargo has been exposed to heat.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Keep substance wet using water spray.
- Stop leak if you can do it without risk.

**Small Spill**

- Take up with inert, damp, non-combustible material using clean non-sparking tools and place into loosely covered plastic containers for later disposal.

**Large Spill**

- Wet down with water and dike for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.
- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Contaminated clothing may be a fire risk when dry.
- Remove material from skin immediately.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Lithium ion batteries contain flammable liquid electrolyte that may vent, ignite and produce sparks when subjected to high temperatures (> 150 °C (302 °F)), when damaged or abused (e.g., mechanical damage or electrical overcharging).
- May burn rapidly with flare-burning effect.
- May ignite other batteries in close proximity.

**HEALTH**

- Contact with battery electrolyte may be irritating to skin, eyes and mucous membranes.
- Fire will produce irritating, corrosive and/or toxic gases.
- Burning batteries may produce toxic hydrogen fluoride gas (see GUIDE 125).
- Fumes may cause dizziness or suffocation.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- If rail car or trailer is involved in a fire, ISOLATE for 500 meters (1/3 mile) in all directions; also initiate evacuation including emergency responders for 500 meters (1/3 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.

---

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch or walk through spilled material.
- Absorb with earth, sand or other non-combustible material.
- Leaking batteries and contaminated absorbent material should be placed in metal containers.

---

**FIRST AID**

- Move victim to fresh air.
- Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- May explode from heat, contamination or loss of temperature control.
- These materials are particularly sensitive to temperature rises. Above a given "Control Temperature" they decompose violently and catch fire.
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- May ignite spontaneously if exposed to air.
- May be ignited by heat, sparks or flames.
- May burn rapidly with flare-burning effect.
- Containers may explode when heated.
- Runoff may create fire or explosion hazard.

**HEALTH**

- Fire may produce irritating, corrosive and/or toxic gases.
- Ingestion or contact (skin, eyes) with substance may cause severe injury or burns.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- **DO NOT allow the substance to warm up. Obtain liquid nitrogen, dry ice or ice for cooling. If none can be obtained, evacuate the area immediately.**

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial evacuation for at least 250 meters (800 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- The temperature of the substance must be maintained at or below the "Control Temperature" at all times.

**Small Fire**

- Water spray or fog is preferred; if water not available use dry chemical, CO<sub>2</sub> or regular foam.

**Large Fire**

- Flood fire area with water from a distance.
- Use water spray or fog; do not use straight streams.
- Do not move cargo or vehicle if cargo has been exposed to heat.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- **BEWARE OF POSSIBLE CONTAINER EXPLOSION.**
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.

**Small Spill**

- Take up with inert, damp, non-combustible material using clean non-sparking tools and place into loosely covered plastic containers for later disposal.

**Large Spill**

- Dike far ahead of liquid spill for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.
- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Contaminated clothing may be a fire risk when dry.
- Remove material from skin immediately.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- **Self-decomposition or self-ignition may be triggered by heat, chemical reaction, friction or impact.**
- May be ignited by heat, sparks or flames.
- Some may decompose explosively when heated or involved in a fire.
- May burn violently. Decomposition may be self-accelerating and produce large amounts of gases.
- Vapors or dust may form explosive mixtures with air.

**HEALTH**

- Inhalation or contact with vapors, substance or decomposition products may cause severe injury or death.
- May produce irritating, toxic and/or corrosive gases.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 250 meters (800 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Flood fire area with water from a distance.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- **BEWARE OF POSSIBLE CONTAINER EXPLOSION.**
- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.

**Small Spill**

- Take up with inert, damp, non-combustible material using clean non-sparking tools and place into loosely covered plastic containers for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- **Self-decomposition or self-ignition may be triggered by heat, chemical reaction, friction or impact.**
- Self-accelerating decomposition may occur if the specific control temperature is not maintained.
- These materials are particularly sensitive to temperature rises. Above a given "Control Temperature" they decompose violently and catch fire.
- May be ignited by heat, sparks or flames.
- Some may decompose explosively when heated or involved in a fire.
- May burn violently. Decomposition may be self-accelerating and produce large amounts of gases.
- Vapors or dust may form explosive mixtures with air.

**HEALTH**

- Inhalation or contact with vapors, substance or decomposition products may cause severe injury or death.
- May produce irritating, toxic and/or corrosive gases.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- **DO NOT allow the substance to warm up. Obtain liquid nitrogen, dry ice or ice for cooling. If none can be obtained, evacuate the area immediately.**

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 250 meters (800 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



**EMERGENCY RESPONSE****FIRE**

- The temperature of the substance must be maintained at or below the "Control Temperature" at all times.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Flood fire area with water from a distance.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- **BEWARE OF POSSIBLE CONTAINER EXPLOSION.**
- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.

**Small Spill**

- Take up with inert, damp, non-combustible material using clean non-sparking tools and place into loosely covered plastic containers for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.
- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **Highly toxic**, may be fatal if inhaled, swallowed or absorbed through skin.
- Avoid any skin contact.
- Effects of contact or inhalation may be delayed.
- Fire may produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution.

**FIRE OR EXPLOSION**

- Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive and/or toxic fumes.
- Containers may explode when heated.
- Runoff may pollute waterways.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub> or water spray.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.
- Dike fire-control water for later disposal; do not scatter the material.
- Use water spray or fog; do not use straight streams.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- Cover with plastic sheet to prevent spreading.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- DO NOT GET WATER INSIDE CONTAINERS.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **Highly toxic**, may be fatal if inhaled, swallowed or absorbed through skin.
- Contact with molten substance may cause severe burns to skin and eyes.
- Avoid any skin contact.
- Effects of contact or inhalation may be delayed.
- Fire may produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution.

**FIRE OR EXPLOSION**

- Combustible material: may burn but does not ignite readily.
- Containers may explode when heated.
- Runoff may pollute waterways.
- Substance may be transported in a molten form.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations **ONLY**; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub> or water spray.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.
- Dike fire-control water for later disposal; do not scatter the material.
- Use water spray or fog; do not use straight streams.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- Cover with plastic sheet to prevent spreading.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- DO NOT GET WATER INSIDE CONTAINERS.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC**; inhalation, ingestion or skin contact with material may cause severe injury or death.
- Contact with molten substance may cause severe burns to skin and eyes.
- Avoid any skin contact.
- Effects of contact or inhalation may be delayed.
- Fire may produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution.

**FIRE OR EXPLOSION**

- Combustible material: may burn but does not ignite readily.
- When heated, vapors may form explosive mixtures with air: indoors, outdoors and sewers explosion hazards.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Contact with metals may evolve flammable hydrogen gas.
- Containers may explode when heated.
- Runoff may pollute waterways.
- Substance may be transported in a molten form.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind. • Keep out of low areas. • Ventilate enclosed areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub> or water spray.

**Large Fire**

- Dry chemical, CO<sub>2</sub>, alcohol-resistant foam or water spray.
- Move containers from fire area if you can do it without risk.
- Dike fire-control water for later disposal; do not scatter the material.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- DO NOT GET WATER INSIDE CONTAINERS.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC**; inhalation, ingestion or skin contact with material may cause severe injury or death.
- Contact with molten substance may cause severe burns to skin and eyes.
- Avoid any skin contact.
- Effects of contact or inhalation may be delayed.
- Fire may produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution.

**FIRE OR EXPLOSION**

- Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive and/or toxic fumes.
- Some are oxidizers and may ignite combustibles (wood, paper, oil, clothing, etc.).
- Contact with metals may evolve flammable hydrogen gas.
- Containers may explode when heated.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate enclosed areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



## EMERGENCY RESPONSE

**FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub> or water spray.

**Large Fire**

- Dry chemical, CO<sub>2</sub>, alcohol-resistant foam or water spray.
- Move containers from fire area if you can do it without risk.
- Dike fire-control water for later disposal; do not scatter the material.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- DO NOT GET WATER INSIDE CONTAINERS.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- **HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.**
- Vapors form explosive mixtures with air: indoors, outdoors and sewers explosion hazards.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapors may travel to source of ignition and flash back.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Substance will react with water (some violently) releasing flammable, toxic or corrosive gases and runoff.
- Contact with metals may evolve flammable hydrogen gas.
- Containers may explode when heated or if contaminated with water.

**HEALTH**

- **TOXIC;** inhalation, ingestion or contact (skin, eyes) with vapors, dusts or substance may cause severe injury, burns or death.
- **Bromoacetates and chloroacetates are extremely irritating/lachrymators.**
- Reaction with water or moist air will release toxic, corrosive or flammable gases.
- Reaction with water may generate much heat that will increase the concentration of fumes in the air.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind. • Keep out of low areas. • Ventilate enclosed areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

## EMERGENCY RESPONSE

## FIRE

- Note: Most foams will react with the material and release corrosive/toxic gases.

**CAUTION: For Acetyl chloride (UN1717), use CO<sub>2</sub> or dry chemical only.**

**Small Fire** • CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam.

**Large Fire**

- Water spray, fog or alcohol-resistant foam.
- **FOR CHLOROSILANES, DO NOT USE WATER;** use AFFF alcohol-resistant medium expansion foam.
- Move containers from fire area if you can do it without risk.
- Use water spray or fog; do not use straight streams.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

## SPILL OR LEAK

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- A vapor suppressing foam may be used to reduce vapors.
- **FOR CHLOROSILANES,** use AFFF alcohol-resistant medium expansion foam to reduce vapors.
- **DO NOT GET WATER on spilled substance or inside containers.**
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Prevent entry into waterways, sewers, basements or confined areas.

**Small Spill** • Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.

- Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal.

## FIRST AID

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Combustible material: may burn but does not ignite readily.
- Substance will react with water (some violently) releasing flammable, toxic or corrosive gases and runoff.
- When heated, vapors may form explosive mixtures with air: indoors, outdoors and sewers explosion hazards.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapors may travel to source of ignition and flash back.
- Contact with metals may evolve flammable hydrogen gas.
- Containers may explode when heated or if contaminated with water.

**HEALTH**

- **TOXIC**; inhalation, ingestion or contact (skin, eyes) with vapors, dusts or substance may cause severe injury, burns or death.
- Contact with molten substance may cause severe burns to skin and eyes.
- Reaction with water or moist air will release toxic, corrosive or flammable gases.
- Reaction with water may generate much heat that will increase the concentration of fumes in the air.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind. • Keep out of low areas. • Ventilate enclosed areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- Note: Most foams will react with the material and release corrosive/toxic gases.

**Small Fire** • CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam.

**Large Fire**

- Water spray, fog or alcohol-resistant foam.
- **FOR CHLOROSILANES, DO NOT USE WATER**; use AFFF alcohol-resistant medium expansion foam.
- Move containers from fire area if you can do it without risk.
- Use water spray or fog; do not use straight streams.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- A vapor suppressing foam may be used to reduce vapors.
- **FOR CHLOROSILANES**, use AFFF alcohol-resistant medium expansion foam to reduce vapors.
- **DO NOT GET WATER on spilled substance or inside containers.**
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Prevent entry into waterways, sewers, basements or confined areas.

**Small Spill** • Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.

- Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC**; inhalation, ingestion or contact (skin, eyes) with vapors, dusts or substance may cause severe injury, burns or death.
- Reaction with water or moist air will release toxic, corrosive or flammable gases.
- Reaction with water may generate much heat that will increase the concentration of fumes in the air.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution.

**FIRE OR EXPLOSION**

- Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive and/or toxic fumes.
- Vapors may accumulate in confined areas (basement, tanks, hopper/tank cars etc.).
- Substance will react with water (some violently), releasing corrosive and/or toxic gases and runoff.
- Contact with metals may evolve flammable hydrogen gas.
- Containers may explode when heated or if contaminated with water.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate enclosed areas.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

## EMERGENCY RESPONSE

## FIRE

- Note: Most foams will react with the material and release corrosive/toxic gases.

**Small Fire** • CO<sub>2</sub> (except for Cyanides), dry chemical, dry sand, alcohol-resistant foam.

**Large Fire**

- Water spray, fog or alcohol-resistant foam.
- Move containers from fire area if you can do it without risk.
- Use water spray or fog; do not use straight streams.
- Dike fire-control water for later disposal; do not scatter the material.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

## SPILL OR LEAK

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- A vapor suppressing foam may be used to reduce vapors.
- DO NOT GET WATER INSIDE CONTAINERS.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Prevent entry into waterways, sewers, basements or confined areas.

**Small Spill** • Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.

- Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal.

## FIRST AID

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Keep victim warm and quiet.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- Inhalation or contact with substance may cause infection, disease or death.
- Runoff from fire control may cause pollution.
- **Note: Damaged packages containing solid CO<sub>2</sub> as a refrigerant may produce water or frost from condensation of air. Do not touch this liquid as it could be contaminated by the contents of the parcel.**

**FIRE OR EXPLOSION**

- Some of these materials may burn, but none ignite readily.
- Some may be transported in flammable liquids.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Obtain identity of substance involved.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.



**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, soda ash, lime or sand.

**Large Fire**

- Use extinguishing agent suitable for type of surrounding fire.
- Do not scatter spilled material with high pressure water streams.
- Move containers from fire area if you can do it without risk.

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Absorb with earth, sand or other non-combustible material.
- Cover damaged package or spilled material with damp towel or rag and keep wet with liquid bleach or other disinfectant.
- **DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.**

**FIRST AID**

- Move victim to a safe isolated area.

**CAUTION: Victim may be a source of contamination.**

- Call 911 or emergency medical service.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- **For further assistance, contact your local Poison Control Center.**
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- Inhalation of vapors or dust is extremely irritating.
- May cause burning of eyes and flow of tears.
- May cause coughing, difficult breathing and nausea.
- Brief exposure effects last only a few minutes.
- Exposure in an enclosed area may be very harmful.
- Fire will produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may cause pollution.

**FIRE OR EXPLOSION**

- Some of these materials may burn, but none ignite readily.
- Containers may explode when heated.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Large Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.
- Dike fire-control water for later disposal; do not scatter the material.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Do not get water inside containers.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.

**Small Spill**

- Take up with sand or other non-combustible absorbent material and place into containers for later disposal.

**Large Spill**

- Dike far ahead of liquid spill for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- **Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.**
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Keep victim warm and quiet.
- Effects should disappear after individual has been exposed to fresh air for approximately 10 minutes.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- Toxic by ingestion.
- Vapors may cause dizziness or suffocation.
- Exposure in an enclosed area may be very harmful.
- Contact may irritate or burn skin and eyes.
- Fire may produce irritating and/or toxic gases.
- Runoff from fire control or dilution water may cause pollution.

**FIRE OR EXPLOSION**

- Some of these materials may burn, but none ignite readily.
- Most vapors are heavier than air.
- Air/vapor mixtures may explode when ignited.
- Container may explode in heat of fire.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer.
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub> or water spray.

**Large Fire**

- Dry chemical, CO<sub>2</sub>, alcohol-resistant foam or water spray.
- Move containers from fire area if you can do it without risk.
- Dike fire-control water for later disposal; do not scatter the material.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Stop leak if you can do it without risk.

**Small Liquid Spill**

- Take up with sand, earth or other non-combustible absorbent material.

**Large Spill**

- Dike far ahead of liquid spill for later disposal.
- Prevent entry into waterways, sewers, basements or confined areas.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- For minor skin contact, avoid spreading material on unaffected skin.
- Wash skin with soap and water.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- Radiation presents minimal risk to transport workers, emergency response personnel and the public during transportation accidents. Packaging durability increases as potential hazard of radioactive content increases.
- Very low levels of contained radioactive materials and low radiation levels outside packages result in low risks to people. Damaged packages may release measurable amounts of radioactive material, but the resulting risks are expected to be low.
- Some radioactive materials cannot be detected by commonly available instruments.
- Packages do not have RADIOACTIVE I, II, or III labels. Some may have EMPTY labels or may have the word "Radioactive" in the package marking.

**FIRE OR EXPLOSION**

- Some of these materials may burn, but most do not ignite readily.
- Many have cardboard outer packaging; content (physically large or small) can be of many different physical forms.
- Radioactivity does not change flammability or other properties of materials.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- **Priorities for rescue, life-saving, first aid, fire control and other hazards are higher than the priority for measuring radiation levels.**
- Radiation Authority must be notified of accident conditions. Radiation Authority is usually responsible for decisions about radiological consequences and closure of emergencies.
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions.
- Stay upwind.
- Keep unauthorized personnel away.
- Detain or isolate uninjured persons or equipment suspected to be contaminated; delay decontamination and cleanup until instructions are received from Radiation Authority.

**PROTECTIVE CLOTHING**

- Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide adequate protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- When a large quantity of this material is involved in a major fire, consider an initial evacuation distance of 300 meters (1000 feet) in all directions.

**EMERGENCY RESPONSE****FIRE**

- Presence of radioactive material will not influence the fire control processes and should not influence selection of techniques.
- Move containers from fire area if you can do it without risk.
- Do not move damaged packages; move undamaged packages out of fire zone.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog (flooding amounts).

**SPILL OR LEAK**

- Do not touch damaged packages or spilled material.
- Cover liquid spill with sand, earth or other non-combustible absorbent material.
- Cover powder spill with plastic sheet or tarp to minimize spreading.

**FIRST AID**

- Call 911 or emergency medical service.
- Medical problems take priority over radiological concerns.
- Use first aid treatment according to the nature of the injury.
- Do not delay care and transport of a seriously injured person.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Injured persons contaminated by contact with released material are not a serious hazard to health care personnel, equipment or facilities.
- Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**POTENTIAL HAZARDS****HEALTH**

- Radiation presents minimal risk to transport workers, emergency response personnel and the public during transportation accidents. Packaging durability increases as potential hazard of radioactive content increases.
- Undamaged packages are safe. Contents of damaged packages may cause higher external radiation exposure, or both external and internal radiation exposure if contents are released.
- Low radiation hazard when material is inside container. If material is released from package or bulk container, hazard will vary from low to moderate. Level of hazard will depend on the type and amount of radioactivity, the kind of material it is in, and/or the surfaces it is on.
- Some material may be released from packages during accidents of moderate severity but risks to people are not great.
- Released radioactive materials or contaminated objects usually will be visible if packaging fails.
- Some exclusive use shipments of bulk and packaged materials will not have "RADIOACTIVE" labels. Placards, markings and shipping papers provide identification.
- Some packages may have a "RADIOACTIVE" label and a second hazard label. The second hazard is usually greater than the radiation hazard; so follow this GUIDE as well as the response GUIDE for the second hazard class label.
- Some radioactive materials cannot be detected by commonly available instruments.
- Runoff from control of cargo fire may cause low-level pollution.

**FIRE OR EXPLOSION**

- Some of these materials may burn, but most do not ignite readily.
- Uranium and Thorium metal cuttings may ignite spontaneously if exposed to air (see GUIDE 136).
- Nitrates are oxidizers and may ignite other combustibles (see GUIDE 141).

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- **Priorities for rescue, life-saving, first aid, fire control and other hazards are higher than the priority for measuring radiation levels.**
- Radiation Authority must be notified of accident conditions. Radiation Authority is usually responsible for decisions about radiological consequences and closure of emergencies.
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. • Stay upwind. • Keep unauthorized personnel away.
- Detain or isolate uninjured persons or equipment suspected to be contaminated; delay decontamination and cleanup until instructions are received from Radiation Authority.

**PROTECTIVE CLOTHING**

- Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide adequate protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- When a large quantity of this material is involved in a major fire, consider an initial evacuation distance of 300 meters (1000 feet) in all directions.



**EMERGENCY RESPONSE****FIRE**

- Presence of radioactive material will not influence the fire control processes and should not influence selection of techniques.
- Move containers from fire area if you can do it without risk.
- Do not move damaged packages; move undamaged packages out of fire zone.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog (flooding amounts).
- Dike fire-control water for later disposal.

**SPILL OR LEAK**

- Do not touch damaged packages or spilled material.
- Cover liquid spill with sand, earth or other non-combustible absorbent material.
- Dike to collect large liquid spills.
- Cover powder spill with plastic sheet or tarp to minimize spreading.

**FIRST AID**

- Call 911 or emergency medical service.
- Medical problems take priority over radiological concerns.
- Use first aid treatment according to the nature of the injury.
- Do not delay care and transport of a seriously injured person.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- In case of contact with substance, wipe from skin immediately; flush skin or eyes with running water for at least 20 minutes.
- Injured persons contaminated by contact with released material are not a serious hazard to health care personnel, equipment or facilities.
- Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**POTENTIAL HAZARDS****HEALTH**

- Radiation presents minimal risk to transport workers, emergency response personnel and the public during transportation accidents. Packaging durability increases as potential hazard of radioactive content increases.
- Undamaged packages are safe. Contents of damaged packages may cause higher external radiation exposure, or both external and internal radiation exposure if contents are released.
- Type A packages (cartons, boxes, drums, articles, etc.) identified as "Type A" by marking on packages or by shipping papers contain non-life endangering amounts. Partial releases might be expected if "Type A" packages are damaged in moderately severe accidents.
- Type B packages, and the rarely occurring Type C packages, (large and small, usually metal) contain the most hazardous amounts. They can be identified by package markings or by shipping papers. Life threatening conditions may exist only if contents are released or package shielding fails. Because of design, evaluation and testing of packages, these conditions would be expected only for accidents of utmost severity.
- The rarely occurring "Special Arrangement" shipments may be of Type A, Type B or Type C packages. Package type will be marked on packages, and shipment details will be on shipping papers.
- Radioactive White-I labels indicate radiation levels outside single, isolated, undamaged packages are very low (less than 0.005 mSv/h (0.5 mrem/h)).
- Radioactive Yellow-II and Yellow-III labeled packages have higher radiation levels. The transport index (TI) on the label identifies the maximum radiation level in mrem/h one meter from a single, isolated, undamaged package.
- Some radioactive materials cannot be detected by commonly available instruments.
- Water from cargo fire control may cause pollution.

**FIRE OR EXPLOSION**

- Some of these materials may burn, but most do not ignite readily.
- Radioactivity does not change flammability or other properties of materials.
- Type B packages are designed and evaluated to withstand total engulfment in flames at temperatures of 800°C (1475°F) for a period of 30 minutes.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- **Priorities for rescue, life-saving, first aid, fire control and other hazards are higher than the priority for measuring radiation levels.**
- Radiation Authority must be notified of accident conditions. Radiation Authority is usually responsible for decisions about radiological consequences and closure of emergencies.
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. • Stay upwind. • Keep unauthorized personnel away.
- Detain or isolate uninjured persons or equipment suspected to be contaminated; delay decontamination and cleanup until instructions are received from Radiation Authority.

**PROTECTIVE CLOTHING**

- Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide adequate protection against internal radiation exposure, but not external radiation exposure.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- When a large quantity of this material is involved in a major fire, consider an initial evacuation distance of 300 meters (1000 feet) in all directions.

**EMERGENCY RESPONSE****FIRE**

- Presence of radioactive material will not influence the fire control processes and should not influence selection of techniques.
- Move containers from fire area if you can do it without risk.
- Do not move damaged packages; move undamaged packages out of fire zone.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog (flooding amounts).
- Dike fire-control water for later disposal.

**SPILL OR LEAK**

- Do not touch damaged packages or spilled material.
- Damp surfaces on undamaged or slightly damaged packages are seldom an indication of packaging failure. Most packaging for liquid content have inner containers and/or inner absorbent materials.
- Cover liquid spill with sand, earth or other non-combustible absorbent material.

**FIRST AID**

- Call 911 or emergency medical service.
- Medical problems take priority over radiological concerns.
- Use first aid treatment according to the nature of the injury.
- Do not delay care and transport of a seriously injured person.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Injured persons contaminated by contact with released material are not a serious hazard to health care personnel, equipment or facilities.
- Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**POTENTIAL HAZARDS****HEALTH**

- Radiation presents minimal risk to transport workers, emergency response personnel and the public during transportation accidents. Packaging durability increases as potential hazard of radioactive content increases.
- Undamaged packages are safe; contents of damaged packages may cause external radiation exposure, and much higher external exposure if contents (source capsules) are released.
- Contamination and internal radiation hazards are not expected, but not impossible.
- Type A packages (cartons, boxes, drums, articles, etc.) identified as "Type A" by marking on packages or by shipping papers contain non-life endangering amounts. Radioactive sources may be released if "Type A" packages are damaged in moderately severe accidents.
- Type B packages, and the rarely occurring Type C packages, (large and small, usually metal) contain the most hazardous amounts. They can be identified by package markings or by shipping papers. Life threatening conditions may exist only if contents are released or package shielding fails. Because of design, evaluation and testing of packages, these conditions would be expected only for accidents of utmost severity.
- Radioactive White-I labels indicate radiation levels outside single, isolated, undamaged packages are very low (less than 0.005 mSv/h (0.5 mrem/h)).
- Radioactive Yellow-II and Yellow-III labeled packages have higher radiation levels. The transport index (TI) on the label identifies the maximum radiation level in mrem/h one meter from a single, isolated, undamaged package.
- Radiation from the package contents, usually in durable metal capsules, can be detected by most radiation instruments.
- Water from cargo fire control is not expected to cause pollution.

**FIRE OR EXPLOSION**

- Packagings can burn completely without risk of content loss from sealed source capsule.
- Radioactivity does not change flammability or other properties of materials.
- Radioactive source capsules and Type B packages are designed and evaluated to withstand total engulfment in flames at temperatures of 800°C (1475°F) for a period of 30 minutes.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- **Priorities for rescue, life-saving, first aid, fire control and other hazards are higher than the priority for measuring radiation levels.**
- Radiation Authority must be notified of accident conditions. Radiation Authority is usually responsible for decisions about radiological consequences and closure of emergencies.
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions.
- Stay upwind. • Keep unauthorized personnel away.
- Delay final cleanup until instructions or advice is received from Radiation Authority.

**PROTECTIVE CLOTHING**

- Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide adequate protection against internal radiation exposure, but not external radiation exposure.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- When a large quantity of this material is involved in a major fire, consider an initial evacuation distance of 300 meters (1000 feet) in all directions.

**EMERGENCY RESPONSE****FIRE**

- Presence of radioactive material will not influence the fire control processes and should not influence selection of techniques.
- Move containers from fire area if you can do it without risk.
- Do not move damaged packages; move undamaged packages out of fire zone.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog (flooding amounts).

**SPILL OR LEAK**

- Do not touch damaged packages or spilled material.
- Damp surfaces on undamaged or slightly damaged packages are seldom an indication of packaging failure. Contents are seldom liquid. Content is usually a metal capsule, easily seen if released from package.
- If source capsule is identified as being out of package, **DO NOT TOUCH**. Stay away and await advice from Radiation Authority.

**FIRST AID**

- Call 911 or emergency medical service.
- Medical problems take priority over radiological concerns.
- Use first aid treatment according to the nature of the injury.
- Do not delay care and transport of a seriously injured person.
- Persons exposed to special form sources are not likely to be contaminated with radioactive material.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Injured persons contaminated by contact with released material are not a serious hazard to health care personnel, equipment or facilities.
- Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**POTENTIAL HAZARDS****HEALTH**

- Radiation presents minimal risk to transport workers, emergency response personnel and the public during transportation accidents. Packaging durability increases as potential radiation and criticality hazards of the content increase.
- Undamaged packages are safe. Contents of damaged packages may cause higher external radiation exposure, or both external and internal radiation exposure if contents are released.
- Type AF or IF packages, identified by package markings, do not contain life-threatening amounts of material. External radiation levels are low and packages are designed, evaluated and tested to control releases and to prevent a fission chain reaction under severe transport conditions.
- Type B(U)F, B(M)F and CF packages (identified by markings on packages or shipping papers) contain potentially life endangering amounts. Because of design, evaluation and testing of packages, fission chain reactions are prevented and releases are not expected to be life endangering for all accidents except those of utmost severity.
- The rarely occurring "Special Arrangement" shipments may be of Type AF, BF or CF packages. Package type will be marked on packages, and shipment details will be on shipping papers.
- The transport index (TI) shown on labels or a shipping paper might not indicate the radiation level at one meter from a single, isolated, undamaged package; instead, it might relate to controls needed during transport because of the fissile properties of the materials. Alternatively, the fissile nature of the contents may be indicated by a criticality safety index (CSI) on a special FISSILE label or on the shipping paper.
- Some radioactive materials cannot be detected by commonly available instruments.
- Water from cargo fire control is not expected to cause pollution.

**FIRE OR EXPLOSION**

- These materials are seldom flammable. Packages are designed to withstand fires without damage to contents.
- Radioactivity does not change flammability or other properties of materials.
- Type AF, IF, B(U)F, B(M)F and CF packages are designed and evaluated to withstand total engulfment in flames at temperatures of 800°C (1475°F) for a period of 30 minutes.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- **Priorities for rescue, life-saving, first aid, fire control and other hazards are higher than the priority for measuring radiation levels.**
- Radiation Authority must be notified of accident conditions. Radiation Authority is usually responsible for decisions about radiological consequences and closure of emergencies.
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. • Stay upwind. • Keep unauthorized personnel away.
- Detain or isolate uninjured persons or equipment suspected to be contaminated; delay decontamination and cleanup until instructions are received from Radiation Authority.

**PROTECTIVE CLOTHING**

- Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide adequate protection against internal radiation exposure, but not external radiation exposure.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- When a large quantity of this material is involved in a major fire, consider an initial evacuation distance of 300 meters (1000 feet) in all directions.

**EMERGENCY RESPONSE****FIRE**

- Presence of radioactive material will not influence the fire control processes and should not influence selection of techniques.
- Move containers from fire area if you can do it without risk.
- Do not move damaged packages; move undamaged packages out of fire zone.

**Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog (flooding amounts).

**SPILL OR LEAK**

- Do not touch damaged packages or spilled material.
- Damp surfaces on undamaged or slightly damaged packages are seldom an indication of packaging failure. Most packaging for liquid content have inner containers and/or inner absorbent materials.

**Liquid Spill**

- Package contents are seldom liquid. If any radioactive contamination resulting from a liquid release is present, it probably will be low-level.

**FIRST AID**

- Call 911 or emergency medical service.
- Medical problems take priority over radiological concerns.
- Use first aid treatment according to the nature of the injury.
- Do not delay care and transport of a seriously injured person.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Injured persons contaminated by contact with released material are not a serious hazard to health care personnel, equipment or facilities.
- Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**POTENTIAL HAZARDS****HEALTH**

- Radiation presents minimal risk to transport workers, emergency response personnel and the public during transportation accidents. Packaging durability increases as potential radiation and criticality hazards of the content increase.
- Chemical hazard greatly exceeds radiation hazard.
- Substance reacts with water and water vapor in air to form toxic and corrosive hydrogen fluoride gas and an extremely irritating and corrosive, white-colored, water-soluble residue.
- If inhaled, may be fatal.
- Direct contact causes burns to skin, eyes, and respiratory tract.
- Low-level radioactive material; very low radiation hazard to people.
- Runoff from control of cargo fire may cause low-level pollution.

**FIRE OR EXPLOSION**

- Substance does not burn. • The material may react violently with fuels.
- Containers in protective overpacks (horizontal cylindrical shape with short legs for tie-downs), are identified with "AF", "B(U)F" or "H(U)" on shipping papers or by markings on the overpacks. They are designed and evaluated to withstand severe conditions including total engulfment in flames at temperatures of 800°C (1475°F) for a period of 30 minutes.
- Bare filled cylinders, identified with UN2978 as part of the marking (may also be marked H(U) or H(M)), may rupture in heat of engulfing fire; bare empty (except for residue) cylinders will not rupture in fires.
- Radioactivity does not change flammability or other properties of materials.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- **Priorities for rescue, life-saving, first aid, fire control and other hazards are higher than the priority for measuring radiation levels.**
- Radiation Authority must be notified of accident conditions. Radiation Authority is usually responsible for decisions about radiological consequences and closure of emergencies.
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. • Stay upwind. • Keep unauthorized personnel away.
- Detain or isolate uninjured persons or equipment suspected to be contaminated; delay decontamination and cleanup until instructions are received from Radiation Authority.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**EVACUATION****Large Spill**

- See Table 1 - Initial Isolation and Protective Action Distances.

**Fire**

- When a large quantity of this material is involved in a major fire, consider an initial evacuation distance of 300 meters (1000 feet) in all directions.



**EMERGENCY RESPONSE****FIRE**

- DO NOT USE WATER OR FOAM ON MATERIAL ITSELF.
- Move containers from fire area if you can do it without risk.

**Small Fire**

- Dry chemical or CO<sub>2</sub>.

**Large Fire**

- Water spray, fog or regular foam.
- Cool containers with flooding quantities of water until well after fire is out.
- If this is impossible, withdraw from area and let fire burn.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Do not touch damaged packages or spilled material.
- Without fire or smoke, leak will be evident by visible and irritating vapors and residue forming at the point of release.
- Use fine water spray to reduce vapors; do not put water directly on point of material release from container.
- Residue buildup may self-seal small leaks.
- Dike far ahead of spill to collect runoff water.

**FIRST AID**

- Call 911 or emergency medical service.
- Medical problems take priority over radiological concerns.
- Use first aid treatment according to the nature of the injury.
- Do not delay care and transport of a seriously injured person.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.
- Injured persons contaminated by contact with released material are not a serious hazard to health care personnel, equipment or facilities.
- Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC; may be fatal if inhaled.**
- Vapors are extremely irritating.
- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Runoff from fire control may cause pollution.

**FIRE OR EXPLOSION**

- Substance does not burn but will support combustion.
- This is a strong oxidizer and will react vigorously or explosively with many materials including fuels.
- May ignite combustibles (wood, paper, oil, clothing, etc.).
- Vapor explosion and poison hazard indoors, outdoors or in sewers.
- Containers may explode when heated.
- Ruptured cylinders may rocket.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
- Always wear thermal protective clothing when handling refrigerated/cryogenic liquids.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances.

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, soda ash, lime or sand.

**Large Fire**

- Water spray, fog (flooding amounts).
- Do not get water inside containers.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- If you have not donned special protective clothing approved for this material, do not expose yourself to any risk of this material touching you.
- **Do not direct water at spill or source of leak.**
- A fine water spray remotely directed to the edge of the spill pool can be used to direct and maintain a hot flare fire that will burn the spilled material in a controlled manner.
- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Isolate area until gas has dispersed.
- Ventilate the area.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Clothing frozen to the skin should be thawed before being removed.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet. • Keep victim under observation.
- Effects of contact or inhalation may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- **TOXIC; Extremely Hazardous.**
- Inhalation extremely dangerous; may be fatal.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Odorless, will not be detected by sense of smell.

**FIRE OR EXPLOSION**

- **EXTREMELY FLAMMABLE.**
- May be ignited by heat, sparks or flames.
- Flame may be invisible.
- Containers may explode when heated.
- Vapor explosion and poison hazard indoors, outdoors or in sewers.
- Vapors from liquefied gas are initially heavier than air and spread along ground.
- Vapors may travel to source of ignition and flash back.
- Runoff may create fire or explosion hazard.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Keep out of low areas.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.
- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
- Always wear thermal protective clothing when handling refrigerated/cryogenic liquids.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances.

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- **DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.**

**Small Fire**

- Dry chemical, CO<sub>2</sub> or water spray.

**Large Fire**

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Do not direct water at spill or source of leak.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Prevent entry into waterways, sewers, basements or confined areas.
- Isolate area until gas has dispersed.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- Keep victim warm and quiet. • Keep victim under observation.
- Effects of contact or inhalation may be delayed.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Substance is transported in molten form at a temperature above 705°C (1300°F).
- Violent reaction with water; contact may cause an explosion or may produce a flammable gas.
- Will ignite combustible materials (wood, paper, oil, debris, etc.).
- Contact with nitrates or other oxidizers may cause an explosion.
- Contact with containers or other materials, including cold, wet or dirty tools, may cause an explosion.
- Contact with concrete will cause spalling and small pops.

**HEALTH**

- Contact causes severe burns to skin and eyes.
- Fire may produce irritating and/or toxic gases.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Keep unauthorized personnel away.
- Ventilate closed spaces before entering.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear flame retardant structural firefighters' protective clothing, including faceshield, helmet and gloves, this will provide limited thermal protection.

**EMERGENCY RESPONSE****FIRE**

- Do Not Use Water, except in life threatening situations and then only in a fine spray.
- Do not use halogenated extinguishing agents or foam.
- Move combustibles out of path of advancing pool if you can do so without risk.
- Extinguish fires started by molten material by using appropriate method for the burning material; keep water, halogenated extinguishing agents and foam away from the molten material.

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- Do not attempt to stop leak, due to danger of explosion.
- Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- Substance is very fluid, spreads quickly, and may splash. Do not try to stop it with shovels or other objects.
- Dike far ahead of spill; use dry sand to contain the flow of material.
- Where possible allow molten material to solidify naturally.
- Avoid contact even after material solidifies. Molten, heated and cold aluminum look alike; do not touch unless you know it is cold.
- Clean up under the supervision of an expert after material has solidified.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- For severe burns, immediate medical attention is required.
- Removal of solidified molten material from skin requires medical assistance.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- May react violently or explosively on contact with water.
- Some are transported in flammable liquids.
- May be ignited by friction, heat, sparks or flames.
- Some of these materials will burn with intense heat.
- Dusts or fumes may form explosive mixtures in air.
- Containers may explode when heated.
- May re-ignite after fire is extinguished.

**HEALTH**

- Oxides from metallic fires are a severe health hazard.
- Inhalation or contact with substance or decomposition products may cause severe injury or death.
- Fire may produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Stay upwind.
- Keep unauthorized personnel away.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 50 meters (160 feet).

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



**EMERGENCY RESPONSE****FIRE****• DO NOT USE WATER, FOAM OR CO<sub>2</sub>.**

- Dousing metallic fires with water will generate hydrogen gas, an extremely dangerous explosion hazard, particularly if fire is in a confined environment (i.e., building, cargo hold, etc.).
- Use DRY sand, graphite powder, dry sodium chloride based extinguishers, G-1® or Met-L-X® powder.
- Confining and smothering metal fires is preferable rather than applying water.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- If impossible to extinguish, protect surroundings and allow fire to burn itself out.

**SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****FIRE OR EXPLOSION**

- Some may burn but none ignite readily.
- Containers may explode when heated.
- Some may be transported hot.

**HEALTH**

- Inhalation of material may be harmful.
- Contact may cause burns to skin and eyes.
- Inhalation of Asbestos dust may have a damaging effect on the lungs.
- Fire may produce irritating, corrosive and/or toxic gases.
- Some liquids produce vapors that may cause dizziness or suffocation.
- Runoff from fire control may cause pollution.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
- Keep unauthorized personnel away.
- Stay upwind.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Spill**

- See Table 1 - Initial Isolation and Protective Action Distances for highlighted materials. For non-highlighted materials, increase, in the downwind direction, as necessary, the isolation distance shown under "PUBLIC SAFETY".

**Fire**

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

**EMERGENCY RESPONSE****FIRE****Small Fire**

- Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Large Fire**

- Water spray, fog or regular foam.
- Do not scatter spilled material with high pressure water streams.
- Move containers from fire area if you can do it without risk.
- Dike fire-control water for later disposal.

**Fire involving Tanks**

- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Prevent dust cloud.
- Avoid inhalation of asbestos dust.

**Small Dry Spill**

- With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.

**Small Spill**

- Take up with sand or other non-combustible absorbent material and place into containers for later disposal.

**Large Spill**

- Dike far ahead of liquid spill for later disposal.
- Cover powder spill with plastic sheet or tarp to minimize spreading.
- Prevent entry into waterways, sewers, basements or confined areas.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**POTENTIAL HAZARDS****HEALTH**

- Inhalation of vapors or contact with substance will result in contamination and potential harmful effects.
- Fire will produce irritating, corrosive and/or toxic gases.

**FIRE OR EXPLOSION**

- Non-combustible, substance itself does not burn but may react upon heating to produce corrosive and/or toxic fumes.
- Runoff may pollute waterways.

**PUBLIC SAFETY**

- **CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- Stay upwind.
- Keep unauthorized personnel away.

**PROTECTIVE CLOTHING**

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

**EVACUATION****Large Spill**

- Consider initial downwind evacuation for at least 100 meters (330 feet).

**Fire**

- When any large container is involved in a fire, consider initial evacuation for 500 meters (1/3 mile) in all directions.

**EMERGENCY RESPONSE****FIRE**

- Use extinguishing agent suitable for type of surrounding fire.
- **Do not direct water at the heated metal.**

**SPILL OR LEAK**

- Do not touch or walk through spilled material.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- Do not use steel or aluminum tools or equipment.
- Cover with earth, sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
- For mercury, use a mercury spill kit.
- Mercury spill areas may be subsequently treated with calcium sulphide/calcium sulfide or with sodium thiosulphate/sodium thiosulfate wash to neutralize any residual mercury.

**FIRST AID**

- Move victim to fresh air. • Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.



## NOTES

## INTRODUCTION TO TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES

Table 1 - Initial Isolation and Protective Action Distances suggests distances useful to protect people from vapors resulting from spills involving dangerous goods that are considered toxic by inhalation (TIH), including certain chemical warfare agents, or which produce toxic gases upon contact with water. Table 1 provides first responders with initial guidance until technically qualified emergency response personnel are available. **Distances show areas likely to be affected during the first 30 minutes after materials are spilled and could increase with time.**

The **Initial Isolation Zone** defines an area SURROUNDING the incident in which persons may be exposed to dangerous (upwind) and life threatening (downwind) concentrations of material. The **Protective Action Zone** defines an area DOWNWIND from the incident in which persons may become incapacitated and unable to take protective action and/or incur serious or irreversible health effects. Table 1 provides specific guidance for small and large spills occurring day or night.

Adjusting distances for a specific incident involves many interdependent variables and should be made only by personnel technically qualified to make such adjustments. For this reason, no precise guidance can be provided in this document to aid in adjusting the table distances; however, general guidance follows.

### **Factors That May Change the Protective Action Distances**

**The GUIDE for a material** (orange-bordered pages) clearly indicates under the section EVACUATION – Fire, the evacuation distance required to protect against fragmentation hazard of a large container. If the material becomes involved in a **FIRE**, the toxic hazard may become less important than the fire or explosion hazard.

If more than one tank car, cargo tank, portable tank, or large cylinder involved in the incident is leaking, LARGE SPILL distances may need to be increased.

For a material with a protective action distance of 11.0+ km (7.0+ miles), the actual distance can be larger in certain atmospheric conditions. If the dangerous goods vapor plume is channeled in a valley or between many tall buildings, distances may be larger than shown in Table 1 due to less mixing of the plume with the atmosphere. Daytime spills in regions with known strong inversions or snow cover, or occurring near sunset, may require an increase of the protective action distance because airborne contaminants mix and disperse more slowly and may travel much farther downwind. In such cases, the nighttime protective action distance may be more appropriate. In addition, protective action distances may be larger for liquid spills when either the material or outdoor temperature exceeds 30°C (86°F).

Materials which react with water to produce large amounts of toxic gases are included in Table 1 - Initial Isolation and Protective Action Distances. Note that some



water-reactive materials (WRM) which are also TIH (e.g., Bromine trifluoride (1746), Thionyl chloride (1836), etc.) produce additional TIH materials when spilled in water. For these materials, two entries are provided in Table 1 - Initial Isolation and Protective Action Distances (i.e., for spills on land and for spills in water). If it is not clear whether the spill is on land or in water, or in cases where the spill occurs both on land and in water, choose the larger Protective Action Distance. Following Table 1, Table 2 – Materials which produce large amounts of Toxic Inhalation Hazard gases (TIH) when spilled in water lists the toxic gases that are produced when these water-reactive materials (WRM) are spilled in water.

When a water-reactive TIH producing material is spilled into a river or stream, the source of the toxic gas may move with the current and stretch from the spill point downstream for a substantial distance.

Initial isolation and protective action distances in this guidebook are derived from historical data on transportation incidents and the use of statistical models. For worst case scenarios involving the instantaneous release of the entire contents of a package (e.g., as a result of terrorism, sabotage or catastrophic accident) the distances may increase substantially. For such events, doubling of the initial isolation and protective action distances is appropriate in absence of other information.

## **PROTECTIVE ACTION DECISION FACTORS TO CONSIDER**

The choice of protective actions for a given situation depends on a number of factors. For some cases, evacuation may be the best option; in others, sheltering in-place may be the best course. Sometimes, these two actions may be used in combination. In any emergency, officials need to quickly give the public instructions. The public will need continuing information and instructions while being evacuated or sheltered in-place.

Proper evaluation of the factors listed below will determine the effectiveness of evacuation or in-place protection. The importance of these factors can vary with emergency conditions. In specific emergencies, other factors may need to be identified and considered as well. This list indicates what kind of information may be needed to make the initial decision.

### **The Dangerous Goods**

- Degree of health hazard
- Chemical and physical properties
- Amount involved
- Containment/control of release
- Rate of vapor movement

### **The Population Threatened**

- Location
- Number of people
- Time available to evacuate or shelter in-place
- Ability to control evacuation or shelter in-place
- Building types and availability
- Special institutions or populations, e.g., nursing homes, hospitals, prisons

### **Weather Conditions**

- Effect on vapor and cloud movement
- Potential for change
- Effect on evacuation or protection in-place

## PROTECTIVE ACTIONS

**Protective Actions** are those steps taken to preserve the health and safety of emergency responders and the public during an incident involving releases of dangerous goods. Table 1 - Initial Isolation and Protective Action Distances (green-bordered pages) predicts the size of downwind areas which could be affected by a cloud of toxic gas. People in this area should be evacuated and/or sheltered in-place inside buildings.

**Isolate Hazard Area and Deny Entry** means keep everybody away from the area if they are not directly involved in emergency response operations. Unprotected emergency responders should not be allowed to enter the isolation zone. This “isolation” task is done first to establish control over the area of operations. This is the first step for any protective actions that may follow. See Table 1 - Isolation and Protective Action Distances (green-bordered pages) for more detailed information on specific materials.

**Evacuate** means move all people from a threatened area to a safer place. To perform an evacuation, there must be enough time for people to be warned, to get ready, and to leave an area. If there is enough time, evacuation is the best protective action. Begin evacuating people nearby and those outdoors in direct view of the scene. When additional help arrives, expand the area to be evacuated downwind and crosswind to at least the extent recommended in this guidebook. Even after people move to the distances recommended, they may not be completely safe from harm. They should not be permitted to congregate at such distances. Send evacuees to a definite place, by a specific route, far enough away so they will not have to be moved again if the wind shifts.

**Shelter In-Place** means people should seek shelter inside a building and remain inside until the danger passes. **Sheltering in-place is used when evacuating the public would cause greater risk than staying where they are, or when an evacuation cannot be performed.** Direct the people inside to **close all doors and windows** and to **shut off all ventilating, heating and cooling systems.** In-place protection may not be the best option if (a) the vapors are flammable; (b) if it will take a long time for the gas to clear the area; or (c) if buildings cannot be closed tightly. Vehicles can offer some protection for a short period if the windows are closed and the ventilating systems are shut off. Vehicles are not as effective as buildings for in-place protection.

**It is vital to maintain communications with competent persons inside the building** so that they are advised about changing conditions. **Persons protected-in-place should be warned to stay far from windows** because of the danger from glass and projected metal fragments in a fire and/or explosion.

Every dangerous goods incident is different. Each will have special problems and concerns. Action to protect the public must be selected carefully. These pages can help with **initial** decisions on how to protect the public. Officials must continue to gather information and monitor the situation until the threat is removed.

## **BACKGROUND ON TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

Initial Isolation and Protective Action Distances in this guidebook were determined for small and large spills occurring during day or night. The overall analysis was statistical in nature and utilized state-of-the-art emission rate and dispersion models; statistical release data from the U.S. DOT HMIS (Hazardous Materials Incident Reporting System) database; meteorological observations from over 120 locations in United States, Canada and Mexico; and the most current toxicological exposure guidelines.

For each chemical, thousands of hypothetical releases were modeled to account for the statistical variation in both release amount and atmospheric conditions. Based on this statistical sample, the 90% percentile Protective Action Distance for each chemical and category was selected to appear in the Table. A brief description of the analysis is provided below. A detailed report outlining the methodology and data used in the generation of the Initial Isolation and Protective Action Distances may be obtained from the U.S. Department of Transportation, Pipeline and Hazardous Materials Safety Administration.

**Release amounts and emission rates** into the atmosphere were statistically modeled based on (1) data from the U.S. DOT HMIS database; (2) container types and sizes authorized for transport as specified in 49 CFR §172.101 and Part 173; (3) physical properties of the individual materials, and (4) atmospheric data from a historical database. The emission model calculated the release of vapor due to evaporation of pools on the ground, direct release of vapors from the container, or a combination of both, as would occur for liquefied gases which can flash to form both a vapor/aerosol mixture and an evaporating pool. In addition, the emission model also calculated the emission of toxic vapor by-products generated from spilling water-reactive materials in water. Spills that involve releases of approximately 200 liters (300 kg for solids) or less are considered Small Spills, while spills that involve quantities greater than 200 liters (300 kg for solids) are considered Large Spills. An exception to this is certain chemical warfare agents where Small Spills include releases up to 2 kg, and Large Spills include releases up to 25 kg. These agents are BZ, CX, GA, GB, GD, GF, HD, HL, HN1, HN2, HN3, L and VX.

**Downwind dispersion** of the vapor was estimated for each case modeled. Atmospheric parameters affecting the dispersion, and the emission rate, were selected in a statistical fashion from a database containing hourly meteorological data from 120 cities in the United States, Canada and Mexico. The dispersion calculation accounted for the time dependent emission rate from the source as well as the density of the vapor plume (i.e., heavy gas effects). Since atmospheric mixing is less effective at dispersing vapor plumes during nighttime, day and night were separated in the analysis. In Table 1, "Day" refers to time periods after sunrise and before sunset, while "Night" includes all hours between sunset and sunrise.

**Toxicological short-term exposure guidelines** for the materials were applied to determine the downwind distance to which persons may become incapacitated and unable to take protective action or may incur serious health effects. When available, toxicological exposure guidelines were chosen from AEGL-2 or ERPG-2 emergency response guidelines, with AEGL-2 values being the first choice. For materials that do not have AEGL-2 or ERPG-2 values, emergency response guidelines estimated from lethal concentration limits derived from animal studies were used, as recommended by an independent panel of toxicological experts from industry and academia.




## HOW TO USE TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES

- (1) The responder should already have:
  - Identified the material by its ID Number and Name; (if an ID Number cannot be found, use the Name of Material index in the blue-bordered pages to locate that number.)
  - Found the three-digit guide for that material in order to consult the emergency actions recommended jointly with this table;
  - **Noted the wind direction.**
- (2) Look in Table 1 (the green-bordered pages) for the ID Number and Name of the Material involved in the incident. Some ID Numbers have more than one shipping name listed—look for the specific name of the material. (If the shipping name is not known and Table 1 lists more than one name for the same ID Number, use the entry with the largest protective action distances.)
- (3) Determine if the incident involves a SMALL or LARGE spill and if DAY or NIGHT. Generally, a SMALL SPILL is one which involves a single, small package (e.g., a drum containing up to approximately 200 liters), a small cylinder, or a small leak from a large package. A LARGE SPILL is one which involves a spill from a large package, or multiple spills from many small packages. DAY is any time after sunrise and before sunset. NIGHT is any time between sunset and sunrise.

- (4) Look up the INITIAL ISOLATION DISTANCE.


Direct all persons to move, in a crosswind direction, away from the spill to the distance specified—in meters and feet.



- (5) Look up the initial PROTECTIVE ACTION DISTANCE shown in Table 1. For a given material, spill size, and whether day or night, Table 1 gives the downwind distance—in kilometers and miles—for which protective actions should be considered. For practical purposes, the Protective Action Zone (i.e., the area in which people are at risk of harmful exposure) is a square, whose length and width are the same as the downwind distance shown in Table 1.

- (6) Initiate Protective Actions to the extent possible, beginning with those closest to the spill site and working away from the site in the downwind direction. When a water-reactive TIH producing material is spilled into a river or stream, the source of the toxic gas may move with the current or stretch from the spill point downstream for a substantial distance.

The shape of the area in which protective actions should be taken (the Protective Action Zone) is shown in this figure. The spill is located at the center of the small circle. The larger circle represents the INITIAL ISOLATION zone around the spill.



**NOTE 1:** See "Introduction To Table 1 - Initial Isolation And Protective Action Distances" for factors which may increase or decrease Protective Action Distances.

**NOTE 2:** See Table 2 – Water-Reactive Materials which Produce Toxic Gases for the list of gases produced when these materials are spilled in water.

Call the emergency response telephone number listed on the shipping paper, or the appropriate response agency as soon as possible for additional information on the material, safety precautions, and mitigation procedures.

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
1005	Ammonia, anhydrous	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	150 m (500 ft)	0.8 km (0.5 mi)	2.3 km (1.4 mi)
1005	Anhydrous ammonia								
1008	Boron trifluoride	30 m (100 ft)	0.1 km (0.1 mi)	0.6 km (0.4 mi)	0.1 mi	0.6 km (0.4 mi)	300 m (1000 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)
1008	Boron trifluoride, compressed								
1016	Carbon monoxide	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 mi	0.1 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
1016	Carbon monoxide, compressed								
1017	Chlorine	60 m (200 ft)	0.4 km (0.3 mi)	1.6 km (1.0 mi)	0.4 mi	1.6 km (1.0 mi)	600 m (2000 ft)	3.5 km (2.2 mi)	8.0 km (5.0 mi)
1023	Coal gas	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 mi	0.1 km (0.1 mi)	60 m (200 ft)	0.3 km (0.2 mi)	0.4 km (0.3 mi)
1023	Coal gas, compressed								
1026	Cyanogen	30 m (100 ft)	0.2 km (0.1 mi)	0.9 km (0.5 mi)	0.2 mi	0.9 km (0.5 mi)	150 m (500 ft)	1.0 km (0.7 mi)	3.5 km (2.2 mi)
1026	Cyanogen gas								
1040	Ethylene oxide	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	150 m (500 ft)	0.8 km (0.5 mi)	2.5 km (1.6 mi)
1040	Ethylene oxide with Nitrogen								
1045	Fluorine	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.1 mi	0.3 km (0.2 mi)	150 m (500 ft)	0.8 km (0.5 mi)	3.1 km (1.9 mi)
1045	Fluorine, compressed								
1048	Hydrogen bromide, anhydrous	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	0.1 mi	0.4 km (0.3 mi)	300 m (1000 ft)	1.5 km (1.0 mi)	4.5 km (2.8 mi)
1050	Hydrogen chloride, anhydrous	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	0.1 mi	0.4 km (0.2 mi)	60 m (200 ft)	0.3 km (0.2 mi)	1.4 km (0.9 mi)
1051	AC (when used as a weapon)	100 m (300 ft)	0.3 km (0.2 mi)	1.1 km (0.7 mi)	0.3 mi	1.1 km (0.7 mi)	1000 m (3000 ft)	3.8 km (2.4 mi)	7.2 km (4.5 mi)
1051	Hydrocyanic acid, aqueous solutions, with more than 20% Hydrogen cyanide	60 m (200 ft)	0.2 km (0.1 mi)	0.6 km (0.4 mi)	0.2 mi	0.6 km (0.4 mi)	400 m (1250 ft)	1.6 km (1.0 mi)	4.1 km (2.5 mi)
1051	Hydrogen cyanide, anhydrous, stabilized								
1051	Hydrogen cyanide, stabilized								
1052	Hydrogen fluoride, anhydrous	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	0.1 mi	0.5 km (0.3 mi)	300 m (1000 ft)	1.7 km (1.1 mi)	3.6 km (2.2 mi)



1053	Hydrogen sulfide	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	300 m (1000 ft)	2.0 km (1.3 mi)	6.2 km (3.9 mi)
1053	Hydrogen sulphide	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	300 m (1000 ft)	2.0 km (1.3 mi)	6.2 km (3.9 mi)
1062	Methyl bromide	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.4 mi)	2.2 km (1.4 mi)
1064	Methyl mercaptan	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	200 m (600 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
1067	Dinitrogen tetroxide	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	400 m (1250 ft)	1.1 km (0.7 mi)	3.0 km (1.9 mi)
1067	Nitrogen dioxide	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	400 m (1250 ft)	1.1 km (0.7 mi)	3.0 km (1.9 mi)
1069	Nitrosyl chloride	30 m (100 ft)	0.2 km (0.2 mi)	1.1 km (0.7 mi)	800 m (2500 ft)	4.2 km (2.6 mi)	11.0+ km (7.0+ mi)
1071	Oil gas	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	60 m (200 ft)	0.3 km (0.2 mi)	0.4 km (0.3 mi)
1071	Oil gas, compressed	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	60 m (200 ft)	0.3 km (0.2 mi)	0.4 km (0.3 mi)
1076	CG (when used as a weapon)	200 m (600 ft)	1.1 km (0.7 mi)	4.0 km (2.5 mi)	1000 m (3000 ft)	7.5 km (4.7 mi)	11.0+ km (7.0+ mi)
1076	Diphosgene	30 m (100 ft)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	30 m (100 ft)	0.4 km (0.2 mi)	0.5 km (0.3 mi)
1076	DP (when used as a weapon)	30 m (100 ft)	0.2 km (0.2 mi)	0.7 km (0.5 mi)	200 m (600 ft)	1.1 km (0.7 mi)	2.5 km (1.6 mi)
1076	Phosgene	100 m (300 ft)	0.7 km (0.4 mi)	2.6 km (1.6 mi)	500 m (1500 ft)	3.3 km (2.0 mi)	9.7 km (6.1 mi)
1079	Sulfur dioxide	60 m (200 ft)	0.3 km (0.2 mi)	1.2 km (0.7 mi)	400 m (1250 ft)	2.1 km (1.3 mi)	5.7 km (3.6 mi)
1079	Sulphur dioxide	60 m (200 ft)	0.3 km (0.2 mi)	1.2 km (0.7 mi)	400 m (1250 ft)	2.1 km (1.3 mi)	5.7 km (3.6 mi)
1082	Trifluorochloroethylene, stabilized	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.4 km (0.3 mi)	1.0 km (0.6 mi)
1092	Acrolein, stabilized	100 m (300 ft)	1.1 km (0.7 mi)	3.3 km (2.0 mi)	1000 m (3000 ft)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)
1098	Allyl alcohol	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.1 km (0.7 mi)
1135	Ethylene chlorohydrin	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.7 km (0.5 mi)	1.2 km (0.7 mi)
1143	Crotonaldehyde	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	60 m (200 ft)	0.4 km (0.3 mi)	0.7 km (0.5 mi)
1143	Crotonaldehyde, stabilized	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	60 m (200 ft)	0.4 km (0.3 mi)	0.7 km (0.5 mi)
1162	Dimethylchlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	2.0 km (1.3 mi)
1163	1,1-Dimethylhydrazine	30 m (100 ft)	0.2 km (0.1 mi)	0.5 km (0.4 mi)	100 m (300 ft)	1.3 km (0.8 mi)	2.4 km (1.5 mi)
1163	Dimethylhydrazine, unsymmetrical	30 m (100 ft)	0.2 km (0.1 mi)	0.5 km (0.4 mi)	100 m (300 ft)	1.3 km (0.8 mi)	2.4 km (1.5 mi)
1182	Ethyl chloroformate	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.4 km (0.3 mi)	0.7 km (0.4 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
1183	Ethylchlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.7 km (0.4 mi)	2.2 km (1.4 mi)		
1185	Ethyleneimine, stabilized	30 m (100 ft)	0.2 km (0.1 mi)	0.5 km (0.3 mi)	100 m (300 ft)	1.1 km (0.7 mi)	2.2 km (1.4 mi)		
1196	Ethyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	0.8 km (0.5 mi)	2.7 km (1.7 mi)		
1238	Methyl chloroformate	30 m (100 ft)	0.2 km (0.2 mi)	0.6 km (0.4 mi)	150 m (500 ft)	1.2 km (0.8 mi)	2.5 km (1.6 mi)		
1239	Methyl chloromethyl ether	30 m (100 ft)	0.3 km (0.2 mi)	1.1 km (0.7 mi)	200 m (600 ft)	2.5 km (1.5 mi)	5.1 km (3.2 mi)		
1242	Methylchlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.8 km (0.5 mi)	2.5 km (1.6 mi)		
1244	Methylhydrazine	30 m (100 ft)	0.3 km (0.2 mi)	0.7 km (0.4 mi)	150 m (500 ft)	1.5 km (1.0 mi)	2.5 km (1.5 mi)		
1250	Methyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	2.0 km (1.3 mi)		
1251	Methyl vinyl ketone, stabilized	150 m (500 ft)	1.6 km (1.0 mi)	3.6 km (2.3 mi)	1000 m (3000 ft)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)		
1259	Nickel carbonyl	150 m (500 ft)	1.4 km (0.9 mi)	4.9 km (3.1 mi)	1000 m (3000 ft)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)		
1295	Trichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.7 km (0.5 mi)	2.3 km (1.4 mi)		
1298	Trimethylchlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.4 km (0.3 mi)	1.2 km (0.7 mi)		
1305	Vinyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	2.0 km (1.3 mi)		
1305	Vinyltrichlorosilane, stabilized (when spilled in water)								

1340	Phosphorus pentasulfide, free from yellow and white Phosphorus <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.4 km (0.2 mi)	1.5 km (0.9 mi)
1340	Phosphorus pentasulphide, free from yellow and white Phosphorus <b>(when spilled in water)</b>	60 m (200 ft)	0.4 km (0.2 mi)	1.5 km (0.9 mi)	500 m (1500 ft)	4.4 km (2.8 mi)	11.0+ km (7.0+ mi)
1380	Pentaborane	60 m (200 ft)	0.7 km (0.4 mi)	2.3 km (1.4 mi)	400 m (1250 ft)	4.6 km (2.9 mi)	8.9 km (5.5 mi)
1384	Sodium dithionite <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.2 km (0.7 mi)
1384	Sodium hydrosulfite <b>(when spilled in water)</b>						
1384	Sodium hydrosulphite <b>(when spilled in water)</b>						
1397	Aluminum phosphide <b>(when spilled in water)</b>	60 m (200 ft)	0.5 km (0.3 mi)	1.9 km (1.2 mi)	600 m (2000 ft)	5.7 km (3.6 mi)	11.0+ km (7.0+ mi)
1412	Lithium amide <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.0 km (0.6 mi)
1419	Magnesium aluminum phosphide <b>(when spilled in water)</b>	60 m (200 ft)	0.4 km (0.3 mi)	1.7 km (1.1 mi)	600 m (2000 ft)	5.3 km (3.3 mi)	11.0+ km (7.0+ mi)
1432	Sodium phosphide <b>(when spilled in water)</b>	30 m (100 ft)	0.3 km (0.2 mi)	1.2 km (0.8 mi)	400 m (1250 ft)	3.5 km (2.2 mi)	10.6 km (6.6 mi)
1510	Tetranitromethane	30 m (100 ft)	0.2 km (0.2 mi)	0.4 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.0 km (0.6 mi)
1541	Acetone cyanohydrin, stabilized <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	100 m (300 ft)	0.3 km (0.2 mi)	1.0 km (0.7 mi)
1556	MD <b>(when used as a weapon)</b>	30 m (100 ft)	0.2 km (0.1 mi)	0.5 km (0.4 mi)	150 m (500 ft)	0.7 km (0.4 mi)	2.2 km (1.4 mi)
1556	Methylchloroarsine	30 m (100 ft)	0.2 km (0.1 mi)	0.2 km (0.2 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
1556	PD <b>(when used as a weapon)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.1 mi)	0.2 km (0.1 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT Then persons Downwind during-		ISOLATE in all Directions		PROTECT Then persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
1560	Arsenic chloride	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	100 m (300 ft)	1.1 km (0.7 mi)	1.1 km (0.7 mi)	1.8 km (1.1 mi)	
1560	Arsenic trichloride	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	100 m (300 ft)	1.1 km (0.7 mi)	1.1 km (0.7 mi)	1.8 km (1.1 mi)	
1569	Bromoacetone	30 m (100 ft)	0.2 km (0.2 mi)	0.8 km (0.5 mi)	100 m (300 ft)	1.1 km (0.7 mi)	1.1 km (0.7 mi)	2.3 km (1.5 mi)	
1580	Chloropicrin	30 m (100 ft)	0.4 km (0.3 mi)	1.0 km (0.6 mi)	150 m (500 ft)	1.9 km (1.2 mi)	1.9 km (1.2 mi)	3.3 km (2.1 mi)	
1581	Chloropicrin and Methyl bromide mixture	30 m (100 ft)	0.1 km (0.1 mi)	0.6 km (0.4 mi)	300 m (1000 ft)	2.1 km (1.3 mi)	2.1 km (1.3 mi)	5.9 km (3.7 mi)	
1581	Methyl bromide and Chloropicrin mixture	30 m (100 ft)	0.1 km (0.1 mi)	0.6 km (0.4 mi)	300 m (1000 ft)	2.1 km (1.3 mi)	2.1 km (1.3 mi)	5.9 km (3.7 mi)	
1582	Chloropicrin and Methyl chloride mixture	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	60 m (200 ft)	0.4 km (0.2 mi)	0.4 km (0.2 mi)	1.7 km (1.1 mi)	
1582	Methyl chloride and Chloropicrin mixture	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	60 m (200 ft)	0.4 km (0.2 mi)	0.4 km (0.2 mi)	1.7 km (1.1 mi)	
1583	Chloropicrin mixture, n.o.s.	30 m (100 ft)	0.4 km (0.3 mi)	1.0 km (0.6 mi)	150 m (500 ft)	1.9 km (1.2 mi)	1.9 km (1.2 mi)	3.3 km (2.1 mi)	
1589	CK (when used as a weapon)	60 m (200 ft)	0.4 km (0.3 mi)	1.5 km (1.0 mi)	600 m (2000 ft)	4.1 km (2.5 mi)	4.1 km (2.5 mi)	8.0 km (5.0 mi)	
1589	Cyanogen chloride, stabilized	100 m (300 ft)	0.4 km (0.3 mi)	1.5 km (0.9 mi)	400 m (1250 ft)	3.1 km (2.0 mi)	3.1 km (2.0 mi)	6.8 km (4.3 mi)	
1595	Dimethyl sulfate	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.5 km (0.3 mi)	0.7 km (0.5 mi)	
1595	Dimethyl sulphate	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.5 km (0.3 mi)	0.7 km (0.5 mi)	
1605	Ethylene dibromide	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.3 km (0.2 mi)	0.5 km (0.3 mi)	
1612	Hexaethyl tetraphosphate and compressed gas mixture	100 m (300 ft)	0.8 km (0.5 mi)	2.7 km (1.7 mi)	400 m (1250 ft)	3.5 km (2.2 mi)	3.5 km (2.2 mi)	8.1 km (5.1 mi)	
1613	Hydrocyanic acid, aqueous solution, with not more than 20% Hydrogen cyanide	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	0.5 km (0.3 mi)	1.1 km (0.7 mi)	
1613	Hydrogen cyanide, aqueous solution, with not more than 20% Hydrogen cyanide	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	0.5 km (0.3 mi)	1.1 km (0.7 mi)	

1614	Hydrogen cyanide, stabilized (absorbed)	60 m (200 ft)	0.2 km (0.1 mi)	0.6 km (0.4 mi)	150 m (500 ft)	0.6 km (0.4 mi)	1.7 km (1.1 mi)
1647	Ethylene dibromide and Methyl bromide mixture, liquid	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.4 mi)	2.2 km (1.4 mi)
1647	Methyl bromide and Ethylene dibromide mixture, liquid	30 m (100 ft)	0.1 km (0.1 mi)	0.6 km (0.4 mi)	100 m (300 ft)	0.6 km (0.4 mi)	2.2 km (1.4 mi)
1660	Nitric oxide	30 m (100 ft)	0.2 km (0.2 mi)	0.4 km (0.2 mi)	100 m (300 ft)	0.8 km (0.5 mi)	1.4 km (0.9 mi)
1660	Nitric oxide, compressed	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.3 km (0.2 mi)	1.2 km (0.8 mi)
1670	Perchloromethyl mercaptan	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.4 km (0.3 mi)	1.4 km (0.9 mi)
1680	Potassium cyanide (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.4 km (0.3 mi)	1.4 km (0.9 mi)
1680	Potassium cyanide, solid (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.4 km (0.3 mi)	1.4 km (0.9 mi)
1689	Sodium cyanide (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.4 km (0.3 mi)	1.4 km (0.9 mi)
1689	Sodium cyanide, solid (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.4 km (0.3 mi)	1.4 km (0.9 mi)
1694	CA (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	100 m (300 ft)	0.6 km (0.4 mi)	2.7 km (1.7 mi)
1695	Chloroacetone, stabilized	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.1 km (0.7 mi)
1697	CN (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.3 km (0.2 mi)	1.4 km (0.9 mi)
1698	Adamsite (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.3 km (0.2 mi)	1.4 km (0.9 mi)
1698	DM (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.3 km (0.2 mi)	1.4 km (0.9 mi)
1699	DA (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.6 km (0.4 mi)	200 m (600 ft)	1.0 km (0.6 mi)	3.8 km (2.4 mi)
1716	Acetyl bromide (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.7 km (1.1 mi)
1717	Acetyl chloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	100 m (300 ft)	0.9 km (0.6 mi)	2.8 km (1.8 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-			
			DAY Kilometers (Miles)	NIGHT Kilometers (Miles)		DAY Kilometers (Miles)	NIGHT Kilometers (Miles)		
1722	Allyl chloroacetate	100 m (300 ft)	1.2 km (0.8 mi)	2.8 km (1.8 mi)	600 m (2000 ft)	7.8 km (4.9 mi)	11.0+ km (7.0+ mi)		
1722	Allyl chloroformate	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.9 km (1.2 mi)		
1724	Allyltrichlorosilane, stabilized (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	30 m (100 ft)	0.4 km (0.2 mi)	1.2 km (0.8 mi)		
1725	Aluminum bromide, anhydrous (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	2.1 km (1.3 mi)		
1726	Aluminum chloride, anhydrous (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.9 km (1.2 mi)		
1728	Amyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	150 m (500 ft)	1.2 km (0.8 mi)	4.0 km (2.5 mi)		
1732	Antimony pentafluoride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	100 m (300 ft)	0.6 km (0.4 mi)	1.5 km (1.0 mi)		
1741	Boron trichloride (when spilled on land)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	100 m (300 ft)	1.3 km (0.8 mi)	3.9 km (2.4 mi)		
1741	Boron trichloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	3.1 km (1.9 mi)	6.6 km (4.1 mi)		
1744	Bromine	60 m (200 ft)	0.6 km (0.4 mi)	1.1 km (0.7 mi)	150 m (500 ft)	1.9 km (1.2 mi)	3.4 km (2.1 mi)		
1744	Bromine, solution								
1744	Bromine, solution (Inhalation Hazard Zone A)	30 m (100 ft)	0.5 km (0.3 mi)	0.9 km (0.6 mi)	150 m (500 ft)	1.5 km (0.9 mi)	3.2 km (2.0 mi)		
1744	Bromine, solution (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.4 mi)	150 m (500 ft)	1.3 km (0.8 mi)	4.2 km (2.6 mi)		
1745	Bromine pentafluoride (when spilled on land)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.4 mi)	150 m (500 ft)	1.3 km (0.8 mi)	4.2 km (2.6 mi)		
1745	Bromine pentafluoride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.4 mi)	150 m (500 ft)	1.3 km (0.8 mi)	4.2 km (2.6 mi)		

1746	Bromine trifluoride (when spilled on land)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.5 km (0.3 mi)
1746	Bromine trifluoride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	100 m (300 ft)	1.1 km (0.7 mi)	3.9 km (2.4 mi)
1747	Butylchlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.4 km (0.2 mi)	1.2 km (0.7 mi)
1749	Chlorine trifluoride	60 m (200 ft)	0.4 km (0.3 mi)	0.4 km (0.3 mi)	1.8 km (1.1 mi)	400 m (1250 ft)	2.7 km (1.7 mi)	7.2 km (4.5 mi)
1752	Chloroacetyl chloride (when spilled on land)	30 m (100 ft)	0.3 km (0.2 mi)	0.3 km (0.2 mi)	0.7 km (0.4 mi)	150 m (500 ft)	1.4 km (0.9 mi)	2.3 km (1.5 mi)
1752	Chloroacetyl chloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.9 km (0.5 mi)
1753	Chlorophenyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.0 km (0.7 mi)
1754	Chlorosulfonic acid (when spilled on land)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.4 km (0.3 mi)
1754	Chlorosulfonic acid (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	60 m (200 ft)	1.0 km (0.6 mi)	2.9 km (1.8 mi)
1754	Chlorosulfonic acid and Sulfur trioxide mixture (when spilled on land)	60 m (200 ft)	0.4 km (0.2 mi)	0.4 km (0.2 mi)	1.0 km (0.6 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
1754	Chlorosulfonic acid and Sulfur trioxide mixture (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	60 m (200 ft)	1.0 km (0.6 mi)	2.9 km (1.8 mi)
1754	Chlorosulphonic acid (when spilled on land)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.4 km (0.3 mi)
1754	Chlorosulphonic acid (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	60 m (200 ft)	1.0 km (0.6 mi)	2.9 km (1.8 mi)
1754	Chlorosulphonic acid and Sulphur trioxide mixture (when spilled on land)	60 m (200 ft)	0.4 km (0.2 mi)	0.4 km (0.2 mi)	1.0 km (0.6 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)			LARGE SPILLS (From a large package or from many small packages)		
		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-	
			DAY Kilometers (Miles)	NIGHT Kilometers (Miles)		DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
1754	Chlorosulfonic acid and Sulphur trioxide mixture (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	60 m (200 ft)	1.0 km (0.6 mi)	2.9 km (1.8 mi)
1754	Sulfur trioxide and Chlorosulfonic acid mixture (when spilled on land)	60 m (200 ft)	0.4 km (0.2 mi)	1.0 km (0.6 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
1754	Sulfur trioxide and Chlorosulfonic acid mixture (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	60 m (200 ft)	1.0 km (0.6 mi)	2.9 km (1.8 mi)
1754	Sulphur trioxide and Chlorosulfonic acid mixture (when spilled on land)	60 m (200 ft)	0.4 km (0.2 mi)	1.0 km (0.6 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
1754	Sulphur trioxide and Chlorosulfonic acid mixture (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	60 m (200 ft)	1.0 km (0.6 mi)	2.9 km (1.8 mi)
1758	Chromium oxychloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.2 mi)	0.8 km (0.5 mi)
1762	Cyclohexenylnchlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	30 m (100 ft)	0.4 km (0.3 mi)	1.4 km (0.9 mi)
1763	Cyclohexyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	30 m (100 ft)	0.4 km (0.3 mi)	1.4 km (0.9 mi)
1765	Dichloroacetyl chloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.0 km (0.6 mi)
1766	Dichlorophenyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	60 m (200 ft)	0.7 km (0.4 mi)	2.2 km (1.4 mi)
1767	Diethylchlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.4 km (0.2 mi)	1.1 km (0.7 mi)
1769	Diphenyldichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.2 mi)	0.6 km (0.4 mi)



1771	Dodecyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	1.4 km (0.9 mi)
1777	Fluorosulfonic acid (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.2 mi)	0.8 km (0.5 mi)
1777	Fluorosulphonic acid (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.2 mi)	0.8 km (0.5 mi)
1781	Hexadecyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.2 mi)	0.7 km (0.4 mi)
1784	Hexyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	1.5 km (0.9 mi)
1799	Nonyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)
1800	Octadecyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	30 m (100 ft)	0.4 km (0.3 mi)	1.4 km (0.9 mi)
1801	Octyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)
1804	Phenyltrichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)
1806	Phosphorus pentachloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	30 m (100 ft)	0.4 km (0.3 mi)	1.6 km (1.0 mi)
1808	Phosphorus tribromide (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	2.0 km (1.2 mi)
1809	Phosphorus trichloride (when spilled on land)	30 m (100 ft)	0.2 km (0.2 mi)	0.7 km (0.4 mi)	150 m (500 ft)	1.5 km (0.9 mi)	3.0 km (1.9 mi)
1809	Phosphorus trichloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	60 m (200 ft)	0.8 km (0.5 mi)	2.8 km (1.7 mi)
1810	Phosphorus oxychloride (when spilled on land)	30 m (100 ft)	0.3 km (0.2 mi)	0.5 km (0.4 mi)	100 m (300 ft)	1.1 km (0.7 mi)	2.0 km (1.3 mi)
1810	Phosphorus oxychloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.7 km (0.5 mi)	2.3 km (1.4 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
1815	Propionyl chloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.8 km (0.5 mi)	
1816	Propylchlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	0.2 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	2.0 km (1.3 mi)	
1818	Silicon tetrachloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.3 km (0.2 mi)	100 m (300 ft)	0.9 km (0.6 mi)	2.9 km (1.8 mi)	
1828	Sulfur chlorides (when spilled on land)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.7 km (0.5 mi)	1.2 km (0.8 mi)	
1828	Sulfur chlorides (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	30 m (100 ft)	0.4 km (0.2 mi)	1.2 km (0.8 mi)	
1828	Sulphur chlorides (when spilled on land)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.7 km (0.5 mi)	1.2 km (0.8 mi)	
1828	Sulphur chlorides (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	30 m (100 ft)	0.4 km (0.2 mi)	1.2 km (0.8 mi)	
1829	Sulfur trioxide, inhibited								
1829	Sulfur trioxide, stabilized	60 m (200 ft)	0.4 km (0.2 mi)	1.0 km (0.6 mi)	1.0 km (0.6 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)	
1829	Sulfur trioxide, uninhibited								
1829	Sulphur trioxide, inhibited								
1829	Sulphur trioxide, stabilized								
1829	Sulphur trioxide, uninhibited								
1831	Sulfuric acid, fuming								
1831	Sulfuric acid, fuming, with not less than 30% free Sulfur trioxide	60 m (200 ft)	0.4 km (0.2 mi)	1.0 km (0.6 mi)	1.0 km (0.6 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)	
1831	Sulphuric acid, fuming								
1831	Sulphuric acid, fuming, with not less than 30% free Sulphur trioxide								

1834	Sulfonyl chloride (when spilled on land)	30 m (100 ft)	0.2 km (0.1 mi)	0.5 km (0.4 mi)	100 m (300 ft)	1.0 km (0.6 mi)	2.1 km (1.3 mi)
1834	Sulfonyl chloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	1.8 km (1.2 mi)
1834	Sulphonyl chloride (when spilled on land)	30 m (100 ft)	0.2 km (0.1 mi)	0.5 km (0.4 mi)	100 m (300 ft)	1.0 km (0.6 mi)	2.1 km (1.3 mi)
1834	Sulphonyl chloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	1.8 km (1.2 mi)
1836	Thionyl chloride (when spilled on land)	30 m (100 ft)	0.3 km (0.2 mi)	0.7 km (0.5 mi)	100 m (300 ft)	0.9 km (0.6 mi)	1.9 km (1.2 mi)
1836	Thionyl chloride (when spilled in water)	30 m (100 ft)	0.3 km (0.2 mi)	1.4 km (0.9 mi)	300 m (1000 ft)	3.3 km (2.1 mi)	7.5 km (4.7 mi)
1838	Titanium tetrachloride (when spilled on land)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
1838	Titanium tetrachloride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.9 km (1.2 mi)
1859	Silicon tetrafluoride	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.9 km (1.2 mi)
1859	Silicon tetrafluoride, compressed	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	150 m (500 ft)	0.8 km (0.5 mi)	1.9 km (1.2 mi)
1892	ED (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	0.9 km (0.6 mi)
1892	Ethylchloroarsine	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.5 km (0.3 mi)	1.4 km (0.9 mi)
1898	Acetyl iodide (when spilled in water)	30 m (100 ft)	0.3 km (0.2 mi)	1.2 km (0.8 mi)	300 m (1000 ft)	1.7 km (1.1 mi)	4.3 km (2.7 mi)
1911	Diborane	60 m (200 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.2 km (0.8 mi)
1911	Diborane, compressed	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.2 km (0.8 mi)
1923	Calcium dithionite (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.2 km (0.8 mi)
1923	Calcium hydrosulfite (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.2 km (0.8 mi)
1923	Calcium hydrosulphite (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.2 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.2 km (0.8 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
1929	Potassium dithionite (when spilled in water)	30 m (100 ft)	0.1 mi (0.1 mi)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.1 km (0.7 mi)	
1929	Potassium hydrosulfite								
1929	Potassium hydrosulphite (when spilled in water)								
1931	Zinc dithionite (when spilled in water)	30 m (100 ft)	0.1 mi (0.1 mi)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.1 km (0.7 mi)	
1931	Zinc hydrosulfite								
1931	Zinc hydrosulphite (when spilled in water)								
1953	Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone A)	100 m (300 ft)	0.6 km (0.4 mi)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)	
1953	Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)	
1953	Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)	
1953	Compressed gas, flammable, poisonous, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)	
1953	Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone A)	100 m (300 ft)	0.6 km (0.4 mi)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)	

1953	Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)
1953	Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
1953	Compressed gas, flammable, toxic, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
1953	Compressed gas, poisonous, flammable, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
1953	Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
1953	Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)
1953	Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
1953	Compressed gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
1953	Compressed gas, toxic, flammable, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
1953	Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone A)	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
1953	Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)			LARGE SPILLS (From a large package or from many small packages)		
		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-	
			DAY Kilometers (Miles)	NIGHT Kilometers (Miles)		DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
1953	Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
1953	Compressed gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
1955	Compressed gas, poisonous, n.o.s.	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
1955	Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)
1955	Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	200 m (600 ft)	1.0 km (0.6 mi)	3.2 km (2.0 mi)
1955	Compressed gas, poisonous, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
1955	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone A)	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
1955	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)
1955	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	200 m (600 ft)	1.0 km (0.6 mi)	3.2 km (2.0 mi)
1955	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
1955	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	200 m (600 ft)	1.0 km (0.6 mi)	3.2 km (2.0 mi)
1955	Compressed gas, toxic, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)

1955	Organic phosphate compound mixed with compressed gas	100 m (300 ft)	1.0 km (0.7 mi)	3.4 km (2.1 mi)	500 m (1500 ft)	4.4 km (2.7 mi)	9.6 km (6.0 mi)
1955	Organic phosphate mixed with compressed gas						
1955	Organic phosphorus compound mixed with compressed gas						
1967	Insecticide gas, poisonous, n.o.s.	100 m (300 ft)	1.0 km (0.7 mi)	3.4 km (2.1 mi)	500 m (1500 ft)	4.4 km (2.7 mi)	9.6 km (6.0 mi)
1967	Organic phosphate mixed with compressed gas						
1967	Parathion and compressed gas mixture						
1975	Dinitrogen tetroxide and Nitric oxide mixture	30 m (100 ft)	0.1 km (0.1 mi)	0.6 km (0.4 mi)	100 m (300 ft)	0.6 km (0.4 mi)	2.2 km (1.4 mi)
1975	Nitric oxide and Dinitrogen tetroxide mixture						
1975	Nitric oxide and Nitrogen dioxide mixture						
1975	Nitric oxide and Nitrogen tetroxide mixture						
1975	Nitrogen dioxide and Nitric oxide mixture						
1975	Nitrogen tetroxide and Nitric oxide mixture						
1994	Iron pentacarbonyl	100 m (300 ft)	0.9 km (0.6 mi)	2.1 km (1.3 mi)	500 m (1500 ft)	5.5 km (3.5 mi)	8.9 km (5.5 mi)
2004	Magnesium diamide (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	2.3 km (1.5 mi)
2011	Magnesium phosphide (when spilled in water)	60 m (200 ft)	0.4 km (0.3 mi)	1.6 km (1.0 mi)	500 m (1500 ft)	4.8 km (3.0 mi)	11.0+ km (7.0+ mi)
2012	Potassium phosphide (when spilled in water)	30 m (100 ft)	0.3 km (0.2 mi)	1.2 km (0.7 mi)	400 m (1250 ft)	3.1 km (2.0 mi)	9.4 km (5.9 mi)
2013	Strontium phosphide (when spilled in water)	30 m (100 ft)	0.3 km (0.2 mi)	1.1 km (0.7 mi)	400 m (1250 ft)	3.0 km (1.9 mi)	9.4 km (5.9 mi)
2032	Nitric acid, fuming	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	150 m (500 ft)	0.6 km (0.4 mi)	1.1 km (0.7 mi)
2032	Nitric acid, red fuming						

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
2186	Hydrogen chloride, refrigerated liquid	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	500 m (1500 ft)	2.8 km (1.7 mi)	10.2 km (6.3 mi)		
2188	Arsine	200 m (600 ft)	1.1 km (0.7 mi)	4.0 km (2.5 mi)	1000 m (3000 ft)	7.0 km (4.4 mi)	11.0+ km (7.0+ mi)		
2188	SA (when used as a weapon)	400 m (1250 ft)	2.0 km (1.3 mi)	5.5 km (3.4 mi)	1000 m (3000 ft)	9.2 km (5.7 mi)	11.0+ km (7.0+ mi)		
2189	Dichlorosilane	30 m (100 ft)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	800 m (2500 ft)	4.2 km (2.6 mi)	10.3 km (6.4 mi)		
2190	Oxygen difluoride	800 m (2500 ft)	5.3 km (3.3 mi)	11.0+ km (7.0+ mi)	1000 m (3000 ft)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)		
2190	Oxygen difluoride, compressed								
2191	Sulphury fluoride	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	300 m (1000 ft)	1.7 km (1.1 mi)	4.9 km (3.1 mi)		
2191	Sulphuryl fluoride								
2192	Germane	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	150 m (500 ft)	0.9 km (0.5 mi)	2.8 km (1.8 mi)		
2194	Selenium hexafluoride	60 m (200 ft)	0.4 km (0.3 mi)	1.9 km (1.2 mi)	500 m (1500 ft)	2.9 km (1.8 mi)	6.4 km (4.0 mi)		
2195	Tellurium hexafluoride	200 m (600 ft)	1.2 km (0.8 mi)	4.3 km (2.7 mi)	1000 m (3000 ft)	9.4 km (5.9 mi)	11.0+ km (7.0+ mi)		
2196	Tungsten hexafluoride	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	150 m (500 ft)	1.0 km (0.6 mi)	2.9 km (1.8 mi)		
2197	Hydrogen iodide, anhydrous	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	150 m (500 ft)	1.0 km (0.6 mi)	3.2 km (2.0 mi)		
2198	Phosphorus pentafluoride	30 m (100 ft)	0.2 km (0.2 mi)	1.1 km (0.7 mi)	200 m (600 ft)	1.3 km (0.8 mi)	3.8 km (2.4 mi)		
2198	Phosphorus pentafluoride, compressed								
2199	Phosphine	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)		
2202	Hydrogen selenide, anhydrous	200 m (600 ft)	1.3 km (0.8 mi)	4.6 km (2.9 mi)	1000 m (3000 ft)	8.7 km (5.4 mi)	11.0+ km (7.0+ mi)		
2204	Carbonyl sulfide	30 m (100 ft)	0.2 km (0.1 mi)	0.7 km (0.4 mi)	500 m (1500 ft)	3.3 km (2.1 mi)	8.7 km (5.4 mi)		
2204	Carbonyl sulphide								
2232	Chloroacetaldehyde	30 m (100 ft)	0.2 km (0.1 mi)	0.4 km (0.3 mi)	100 m (300 ft)	0.9 km (0.5 mi)	1.5 km (0.9 mi)		
2232	2-Chloroethanal								



2308	Nitrosylsulfuric acid <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	300 m (1000 ft)	0.8 km (0.5 mi)	2.5 km (1.6 mi)
2308	Nitrosylsulfuric acid, liquid <b>(when spilled in water)</b>						
2308	Nitrosylsulfuric acid, solid <b>(when spilled in water)</b>						
2308	Nitrosylsulfuric acid <b>(when spilled in water)</b>						
2308	Nitrosylsulfuric acid, liquid <b>(when spilled in water)</b>						
2308	Nitrosylsulfuric acid, solid <b>(when spilled in water)</b>						
2334	Allylamine	30 m (100 ft)	0.2 km (0.1 mi)	0.6 km (0.4 mi)	150 m (500 ft)	1.7 km (1.1 mi)	3.0 km (1.9 mi)
2337	Phenyl mercaptan	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.5 km (0.3 mi)
2353	Butyl chloride <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	1.0 km (0.6 mi)
2382	1,2-Dimethylhydrazine	30 m (100 ft)	0.2 km (0.1 mi)	0.4 km (0.3 mi)	100 m (300 ft)	1.0 km (0.6 mi)	1.7 km (1.1 mi)
2382	Dimethylhydrazine, symmetrical						
2395	Isobutyl chloride <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.2 mi)	0.6 km (0.4 mi)
2407	Isopropyl chloroformate	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.7 km (0.5 mi)	1.4 km (0.9 mi)
2417	Carbonyl fluoride	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	150 m (500 ft)	0.9 km (0.5 mi)	3.0 km (1.9 mi)
2417	Carbonyl fluoride, compressed						
2418	Sulfur tetrafluoride	100 m (300 ft)	0.6 km (0.4 mi)	2.6 km (1.6 mi)	800 m (2500 ft)	4.7 km (2.9 mi)	10.3 km (6.4 mi)
2418	Sulphur tetrafluoride						
2420	Hexafluoroacetone	60 m (200 ft)	0.3 km (0.2 mi)	1.5 km (0.9 mi)	1000 m (3000 ft)	8.4 km (5.2 mi)	11.0+ km (7.0+ mi)
2421	Nitrogen trioxide	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	100 m (300 ft)	0.3 km (0.2 mi)	1.2 km (0.8 mi)
2434	Dibenzodichlorosilane <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.1 mi)	0.6 km (0.4 mi)
2435	Ethylphenylchlorosilane <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.4 km (0.2 mi)	1.1 km (0.7 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
2437	Methylphenyldichlorosilane (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.1 mi)	0.6 km (0.4 mi)	
2438	Trimethylacetyl chloride	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.1 km (0.7 mi)	
2442	Trichloroacetyl chloride	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.7 km (0.5 mi)	1.3 km (0.8 mi)	
2474	Thiophosgene	60 m (200 ft)	0.7 km (0.4 mi)	2.0 km (1.3 mi)	2.0 km (1.3 mi)	300 m (1000 ft)	3.1 km (1.9 mi)	5.9 km (3.3 mi)	
2477	Methyl isothiocyanate	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)	
2480	Methyl isocyanate	150 m (500 ft)	1.8 km (1.1 mi)	5.3 km (3.3 mi)	5.3 km (3.3 mi)	1000 m (3000 ft)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)	
2481	Ethyl isocyanate	150 m (500 ft)	1.5 km (1.0 mi)	3.8 km (2.4 mi)	3.8 km (2.4 mi)	1000 m (3000 ft)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)	
2482	n-Propyl isocyanate	100 m (300 ft)	1.2 km (0.8 mi)	2.8 km (1.7 mi)	2.8 km (1.7 mi)	800 m (2500 ft)	9.6 km (6.0 mi)	11.0+ km (7.0+ mi)	
2483	Isopropyl isocyanate	100 m (300 ft)	1.3 km (0.8 mi)	3.0 km (1.9 mi)	3.0 km (1.9 mi)	1000 m (3000 ft)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)	
2484	tert-Butyl isocyanate	100 m (300 ft)	1.1 km (0.7 mi)	2.6 km (1.6 mi)	2.6 km (1.6 mi)	800 m (2500 ft)	9.3 km (5.8 mi)	11.0+ km (7.0+ mi)	
2485	n-Butyl isocyanate	60 m (200 ft)	0.8 km (0.5 mi)	1.7 km (1.1 mi)	1.7 km (1.1 mi)	400 m (1250 ft)	4.8 km (3.0 mi)	6.9 km (4.3 mi)	
2486	Isobutyl isocyanate	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	1.8 km (1.1 mi)	400 m (1250 ft)	4.8 km (3.0 mi)	7.4 km (4.6 mi)	
2487	Phenyl isocyanate	30 m (100 ft)	0.4 km (0.3 mi)	0.6 km (0.4 mi)	0.6 km (0.4 mi)	150 m (500 ft)	1.6 km (1.0 mi)	2.5 km (1.6 mi)	
2488	Cyclohexyl isocyanate	30 m (100 ft)	0.3 km (0.2 mi)	0.4 km (0.2 mi)	0.4 km (0.2 mi)	100 m (300 ft)	1.0 km (0.6 mi)	1.4 km (0.9 mi)	
2495	Iodine pentafluoride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.4 mi)	0.5 km (0.4 mi)	150 m (500 ft)	1.2 km (0.8 mi)	4.2 km (2.6 mi)	
2521	Diketene, stabilized	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.5 km (0.3 mi)	
2534	Methylchlorosilane	30 m (100 ft)	0.2 km (0.1 mi)	0.7 km (0.4 mi)	0.7 km (0.4 mi)	300 m (1000 ft)	1.6 km (1.0 mi)	4.9 km (2.7 mi)	
2548	Chlorine pentafluoride	60 m (200 ft)	0.3 km (0.2 mi)	1.4 km (0.9 mi)	1.4 km (0.9 mi)	400 m (1250 ft)	2.3 km (1.4 mi)	6.5 km (4.1 mi)	

2600	Carbon monoxide and Hydrogen mixture	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
2600	Carbon monoxide and Hydrogen mixture, compressed						
2600	Hydrogen and Carbon monoxide mixture						
2600	Hydrogen and Carbon monoxide mixture, compressed						
2605	Methoxymethyl isocyanate	30 m (100 ft)	0.4 km (0.3 mi)	0.6 km (0.4 mi)	150 m (500 ft)	1.6 km (1.0 mi)	2.5 km (1.6 mi)
2606	Methyl orthosilicate	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.5 km (0.3 mi)
2644	Methyl iodide	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.3 km (0.2 mi)	0.8 km (0.5 mi)
2646	Hexachlorocyclopentadiene	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.4 km (0.3 mi)	0.5 km (0.3 mi)
2668	Chloroacetonitrile	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.5 km (0.3 mi)
2676	Stibine	60 m (200 ft)	0.4 km (0.2 mi)	1.7 km (1.1 mi)	500 m (1500 ft)	2.8 km (1.7 mi)	7.2 km (4.5 mi)
2691	Phosphorus pentabromide (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	30 m (100 ft)	0.4 km (0.3 mi)	1.5 km (1.0 mi)
2692	Boron tribromide (when spilled on land)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	60 m (200 ft)	0.5 km (0.3 mi)	1.0 km (0.6 mi)
2692	Boron tribromide (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.6 km (0.4 mi)	100 m (300 ft)	1.0 km (0.6 mi)	3.0 km (1.9 mi)
2740	n-Propyl chloroformate	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.7 km (0.5 mi)	1.3 km (0.8 mi)
2742	sec-Butyl chloroformate	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.4 km (0.2 mi)	0.6 km (0.4 mi)
2742	Isobutyl chloroformate	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.5 km (0.3 mi)
2743	n-Butyl chloroformate	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.5 km (0.3 mi)
2806	Lithium nitride (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	2.2 km (1.4 mi)
2810	Buzz (when used as a weapon)						
2810	BZ (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
2810	CS (when used as a weapon)	30 m (100 ft)	0.2 km (0.1 mi)	0.7 km (0.4 mi)	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)		
2810	DC (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.6 km (0.4 mi)	100 m (300 ft)	0.5 km (0.3 mi)	2.0 km (1.3 mi)		
2810	GA (when used as a weapon)	30 m (100 ft)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.6 km (0.4 mi)	0.7 km (0.4 mi)		
2810	GB (when used as a weapon)	60 m (200 ft)	0.4 km (0.3 mi)	1.2 km (0.8 mi)	800 m (2500 ft)	2.3 km (1.4 mi)	4.5 km (2.8 mi)		
2810	GD (when used as a weapon)	60 m (200 ft)	0.4 km (0.3 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.7 km (1.1 mi)	2.4 km (1.5 mi)		
2810	GF (when used as a weapon)	60 m (200 ft)	0.2 km (0.2 mi)	0.3 km (0.2 mi)	150 m (500 ft)	0.9 km (0.6 mi)	1.1 km (0.7 mi)		
2810 HD	H (when used as a weapon) HD (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	60 m (200 ft)	0.4 km (0.2 mi)	0.4 km (0.3 mi)		
2810	HL (when used as a weapon)	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.0 km (0.7 mi)		
2810	HN-1 (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	60 m (200 ft)	0.4 km (0.2 mi)	0.5 km (0.4 mi)		
2810	HN-2 (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	60 m (200 ft)	0.3 km (0.2 mi)	0.5 km (0.3 mi)		
2810	HN-3 (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)		
2810	L (Lewisite) (when used as a weapon)	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.0 km (0.7 mi)		
2810	Lewisite (when used as a weapon)	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.0 km (0.7 mi)		
2810	Mustard (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	60 m (200 ft)	0.4 km (0.2 mi)	0.4 km (0.3 mi)		
2810	Mustard Lewisite (when used as a weapon)	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.0 km (0.7 mi)		
2810	Poisonous liquid, n.o.s. Poisonous liquid, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)		
2810	Poisonous liquid, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)		

2810	Poisonous liquid, organic, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	400 m (1250 ft)	4.8 km (3.0 mi)	7.4 km (4.6 mi)
2810	Poisonous liquid, organic, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
2810	Poisonous liquid, organic, n.o.s. (Inhalation Hazard Zone B)	60 m (200 ft)	0.4 km (0.3 mi)	1.2 km (0.8 mi)	800 m (2500 ft)	2.3 km (1.4 mi)	4.5 km (2.8 mi)
2810	Sarin (when used as a weapon)	60 m (200 ft)	0.4 km (0.3 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.7 km (1.1 mi)	2.4 km (1.5 mi)
2810	Soman (when used as a weapon)	30 m (100 ft)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.6 km (0.4 mi)	0.7 km (0.4 mi)
2810	Tabun (when used as a weapon)	60 m (200 ft)	0.4 km (0.3 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.7 km (1.1 mi)	2.4 km (1.5 mi)
2810	Thickened GD (when used as a weapon)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
2810	Toxic liquid, n.o.s.	60 m (200 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
2810	Toxic liquid, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	400 m (1250 ft)	4.8 km (3.0 mi)	7.4 km (4.6 mi)
2810	Toxic liquid, n.o.s. (Inhalation Hazard Zone B)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	400 m (1250 ft)	4.8 km (3.0 mi)	7.4 km (4.6 mi)
2810	Toxic liquid, organic, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
2810	Toxic liquid, organic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	60 m (200 ft)	0.4 km (0.2 mi)	0.4 km (0.3 mi)
2811	CX (when used as a weapon)	30 m (100 ft)	0.1 km (0.1 mi)	0.7 km (0.4 mi)	100 m (300 ft)	0.5 km (0.3 mi)	2.3 km (1.4 mi)
2826	Ethyl chloroformate	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.7 km (0.5 mi)
2845	Ethyl phosphonous dichloride, anhydrous	30 m (100 ft)	0.3 km (0.2 mi)	0.8 km (0.5 mi)	150 m (500 ft)	1.6 km (1.0 mi)	2.9 km (1.8 mi)
2845	Methyl phosphonous dichloride	30 m (100 ft)	0.4 km (0.3 mi)	1.2 km (0.8 mi)	200 m (600 ft)	2.6 km (1.6 mi)	4.5 km (2.8 mi)
2901	Bromine chloride	30 m (100 ft)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	400 m (1250 ft)	2.4 km (1.5 mi)	6.5 km (4.0 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
2927	Ethyl phosphonothioic dichloride, anhydrous	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.1 mi)	0.2 km (0.2 mi)	0.2 km (0.2 mi)
2927	Ethyl phosphorodichloridate	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.2 mi)	0.3 km (0.2 mi)	0.3 km (0.2 mi)
2927	Poisonous liquid, corrosive, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)	5.7 km (3.6 mi)
2927	Poisonous liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)	0.8 km (0.5 mi)
2927	Poisonous liquid, corrosive, organic, n.o.s.	100 m (300 ft)	1.2 km (0.8 mi)	2.8 km (1.8 mi)	2.8 km (1.8 mi)	600 m (2000 ft)	7.8 km (4.9 mi)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)
2927	Poisonous liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)	0.8 km (0.5 mi)
2927	Poisonous liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone B)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)	5.7 km (3.6 mi)
2927	Toxic liquid, corrosive, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)	0.8 km (0.5 mi)
2927	Toxic liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)	100 m (300 ft)	1.2 km (0.8 mi)	2.8 km (1.8 mi)	2.8 km (1.8 mi)	600 m (2000 ft)	7.8 km (4.9 mi)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)
2927	Toxic liquid, corrosive, organic, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)	0.8 km (0.5 mi)
2927	Toxic liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)	0.8 km (0.5 mi)
2927	Toxic liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone B)	100 m (300 ft)	1.2 km (0.8 mi)	2.8 km (1.8 mi)	2.8 km (1.8 mi)	600 m (2000 ft)	7.8 km (4.9 mi)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)
2927	Toxic liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)	0.8 km (0.5 mi)
2927	Toxic liquid, corrosive, organic, n.o.s. (Inhalation Hazard Zone B)	100 m (300 ft)	1.2 km (0.8 mi)	2.8 km (1.8 mi)	2.8 km (1.8 mi)	600 m (2000 ft)	7.8 km (4.9 mi)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)

2929	Poisonous liquid, flammable, n.o.s.	60 m (200 ft)	0.7 km (0.4 mi)	2.3 km (1.4 mi)	400 m (1250 ft)	4.6 km (2.9 mi)	8.9 km (5.5 mi)
2929	Poisonous liquid, flammable, n.o.s. (Inhalation Hazard Zone A)						
2929	Poisonous liquid, flammable, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
2929	Poisonous liquid, flammable, organic, n.o.s.	100 m (300 ft)	1.1 km (0.7 mi)	2.6 km (1.6 mi)	600 m (2000 ft)	7.8 km (4.9 mi)	11.0+ km (7.0+ mi)
2929	Poisonous liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone A)						
2929	Poisonous liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
2929	Toxic liquid, flammable, n.o.s.	60 m (200 ft)	0.7 km (0.4 mi)	2.3 km (1.4 mi)	400 m (1250 ft)	4.6 km (2.9 mi)	8.9 km (5.5 mi)
2929	Toxic liquid, flammable, n.o.s. (Inhalation Hazard Zone A)						
2929	Toxic liquid, flammable, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
2929	Toxic liquid, flammable, organic, n.o.s.	100 m (300 ft)	1.1 km (0.7 mi)	2.6 km (1.6 mi)	600 m (2000 ft)	7.8 km (4.9 mi)	11.0+ km (7.0+ mi)
2929	Toxic liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone A)						
2929	Toxic liquid, flammable, organic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
2977	Radioactive material, Uranium hexafluoride, fissile (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	60 m (200 ft)	0.5 km (0.3 mi)	2.3 km (1.4 mi)
2977	Uranium hexafluoride, fissile containing more than 1% Uranium-235 (when spilled in water)						

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY	NIGHT	Meters (Feet)	Kilometers (Miles)	DAY	NIGHT
2978	Radioactive material, Uranium hexafluoride <b>(when spilled in water)</b>	30 m (100 ft)	0.1 mi (0.1 mi)	0.4 km (0.2 mi)	60 m (200 ft)	0.5 km (0.3 mi)	2.2 km (1.4 mi)		
2978	Uranium hexafluoride <b>(when spilled in water)</b>								
2978	Uranium hexafluoride, non-fissile <b>(when spilled in water)</b>								
2985	Chlorosilanes, flammable, corrosive, n.o.s. <b>(when spilled in water)</b>	30 m (100 ft)	0.1 mi (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)		
2985	Chlorosilanes, n.o.s. <b>(when spilled in water)</b>								
2986	Chlorosilanes, corrosive, flammable, n.o.s. <b>(when spilled in water)</b>	30 m (100 ft)	0.1 mi (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)		
2986	Chlorosilanes, n.o.s. <b>(when spilled in water)</b>								
2987	Chlorosilanes, corrosive, n.o.s. <b>(when spilled in water)</b>	30 m (100 ft)	0.1 mi (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)		
2987	Chlorosilanes, n.o.s. <b>(when spilled in water)</b>								
2988	Chlorosilanes, n.o.s. <b>(when spilled in water)</b>	30 m (100 ft)	0.1 mi (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)		
2988	Chlorosilanes, water-reactive, flammable, corrosive, n.o.s. <b>(when spilled in water)</b>								
3023	2-Methyl-2-heptanethiol	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.7 km (0.5 mi)		
3023	tert-Octyl mercaptan								
3048	Aluminum phosphide pesticide <b>(when spilled in water)</b>	60 m (200 ft)	0.5 km (0.3 mi)	1.9 km (1.2 mi)	600 m (2000 ft)	5.8 km (3.6 mi)	11.0+ km (7.0+ mi)		



3049	Metal alkyl halides, n.o.s. <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.4 km (0.3 mi)	1.3 km (0.8 mi)
3049	Metal alkyl halides, water-reactive, n.o.s. <b>(when spilled in water)</b>						
3049	Metal aryl halides, n.o.s. <b>(when spilled in water)</b>						
3049	Metal aryl halides, water-reactive, n.o.s. <b>(when spilled in water)</b>						
3052	Aluminum alkyl halides <b>(when spilled in water)</b>	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.4 km (0.3 mi)	1.3 km (0.8 mi)
3052	Aluminum alkyl halides, liquid <b>(when spilled in water)</b>						
3052	Aluminum alkyl halides, solid <b>(when spilled in water)</b>						
3057	Trifluoroacetyl chloride	30 m (100 ft)	0.2 km (0.2 mi)	1.0 km (0.7 mi)	800 m (2500 ft)	4.6 km (2.9 mi)	11.0+ km (7.0+ mi)
3079	Methacrylonitrile, stabilized	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.9 km (0.5 mi)
3083	Perchloryl fluoride	30 m (100 ft)	0.2 km (0.1 mi)	0.7 km (0.4 mi)	500 m (1500 ft)	3.1 km (2.0 mi)	8.4 km (5.2 mi)
3122	Poisonous liquid, oxidizing, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3122	Poisonous liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)						
3122	Poisonous liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.0 km (0.6 mi)
3122	Toxic liquid, oxidizing, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3122	Toxic liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)						
3122	Toxic liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.0 km (0.6 mi)
3123	Poisonous liquid, water-reactive, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3123	Poisonous liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)						

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)			LARGE SPILLS (From a large package or from many small packages)		
		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-	
			DAY Kilometers (Miles)	NIGHT Kilometers (Miles)		DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
3123	Poisonous liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
3123	Poisonous liquid, which in contact with water emits flammable gases, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3123	Poisonous liquid, which in contact with water emits flammable gases, with water emits flammable gases, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
3123	Toxic liquid, water-reactive, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3123	Toxic liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
3123	Toxic liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3123	Toxic liquid, which in contact with water emits flammable gases, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
3123	Toxic liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3123	Toxic liquid, which in contact with water emits flammable gases, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)

3160	Liquefied gas, poisonous, flammable, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3160	Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)
3160	Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3160	Liquefied gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3160	Liquefied gas, toxic, flammable, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3160	Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)
3160	Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3160	Liquefied gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3162	Liquefied gas, poisonous, n.o.s.	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3162	Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)
3162	Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	200 m (600 ft)	1.0 km (0.6 mi)	3.2 km (2.0 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
3162	Liquefied gas, poisonous, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3162	Liquefied gas, toxic, n.o.s.	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	0.5 mi	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3162	Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	0.2 mi	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)
3162	Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.2 mi)	0.1 mi	0.4 km (0.2 mi)	200 m (600 ft)	1.0 km (0.6 mi)	3.2 km (2.0 mi)
3162	Liquefied gas, toxic, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3246	Methanesulfonyl chloride (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 mi	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.1 mi)	0.2 km (0.2 mi)
3246	Methanesulphonyl chloride	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.9 km (0.5 mi)
3275	Nitrites; poisonous, flammable, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.9 km (0.5 mi)
3275	Nitrites; toxic, flammable, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.9 km (0.5 mi)
3276	Nitrites; poisonous, liquid, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.9 km (0.5 mi)
3276	Nitrites; poisonous, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.9 km (0.5 mi)
3276	Nitrites; toxic, liquid, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.9 km (0.5 mi)
3276	Nitrites; toxic, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 mi	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.9 km (0.5 mi)
3278	Organophosphorus compound, poisonous, liquid, n.o.s.	30 m (100 ft)	0.4 km (0.3 mi)	1.2 km (0.8 mi)	0.4 mi	1.2 km (0.8 mi)	200 m (600 ft)	2.6 km (1.6 mi)	4.5 km (2.8 mi)
3278	Organophosphorus compound, poisonous, n.o.s.	30 m (100 ft)	0.4 km (0.3 mi)	1.2 km (0.8 mi)	0.4 mi	1.2 km (0.8 mi)	200 m (600 ft)	2.6 km (1.6 mi)	4.5 km (2.8 mi)
3278	Organophosphorus compound, poisonous, n.o.s.	30 m (100 ft)	0.4 km (0.3 mi)	1.2 km (0.8 mi)	0.4 mi	1.2 km (0.8 mi)	200 m (600 ft)	2.6 km (1.6 mi)	4.5 km (2.8 mi)
3278	Organophosphorus compound, toxic, liquid, n.o.s.	30 m (100 ft)	0.4 km (0.3 mi)	1.2 km (0.8 mi)	0.4 mi	1.2 km (0.8 mi)	200 m (600 ft)	2.6 km (1.6 mi)	4.5 km (2.8 mi)
3278	Organophosphorus compound, toxic, n.o.s.	30 m (100 ft)	0.4 km (0.3 mi)	1.2 km (0.8 mi)	0.4 mi	1.2 km (0.8 mi)	200 m (600 ft)	2.6 km (1.6 mi)	4.5 km (2.8 mi)

3279	Organophosphorus compound, poisonous, flammable, n.o.s. Organophosphorus compound, toxic, flammable, n.o.s.	30 m (100 ft)	0.4 km (0.3 mi)	1.2 km (0.8 mi)	200 m (600 ft)	2.6 km (1.6 mi)	4.5 km (2.8 mi)
3279							
3280	Organocarbon compound, liquid, n.o.s.	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	150 m (500 ft)	2.0 km (1.3 mi)	4.8 km (3.0 mi)
3280	Organocarbon compound, n.o.s.						
3281	Metal carbonyls, liquid, n.o.s.	150 m (500 ft)	1.4 km (0.9 mi)	4.9 km (3.1 mi)	1000 m (3000 ft)	11.0+ km (7.0+ mi)	11.0+ km (7.0+ mi)
3281	Metal carbonyls, n.o.s.						
3287	Poisonous liquid, inorganic, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3287	Poisonous liquid, inorganic, n.o.s. (Inhalation Hazard Zone A)						
3287	Poisonous liquid, inorganic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	150 m (500 ft)	0.6 km (0.4 mi)	1.1 km (0.7 mi)
3287	Toxic liquid, inorganic, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3287	Toxic liquid, inorganic, n.o.s. (Inhalation Hazard Zone A)						
3287	Toxic liquid, inorganic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	150 m (500 ft)	0.6 km (0.4 mi)	1.1 km (0.7 mi)
3289	Poisonous liquid, corrosive, inorganic, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3289	Poisonous liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone A)						
3289	Poisonous liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.7 km (0.5 mi)	1.2 km (0.8 mi)
3289	Toxic liquid, corrosive, inorganic, n.o.s.	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3289	Toxic liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone A)						

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)			LARGE SPILLS (From a large package or from many small packages)		
		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-	
			DAY Kilometers (Miles)	NIGHT Kilometers (Miles)		DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
3289	Toxic liquid, corrosive, inorganic, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.7 km (0.5 mi)	1.2 km (0.8 mi)
3294	Hydrogen cyanide, solution in alcohol, with not more than 45% Hydrogen cyanide	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	200 m (600 ft)	0.5 km (0.3 mi)	1.9 km (1.2 mi)
3300	Carbon dioxide and Ethylene oxide mixture, with more than 87% Ethylene oxide	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.8 km (0.5 mi)	2.5 km (1.6 mi)
3300	Ethylene oxide and Carbon dioxide mixture, with more than 87% Ethylene oxide	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.8 km (0.5 mi)	2.5 km (1.6 mi)
3303	Compressed gas, poisonous, oxidizing, n.o.s.	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3303	Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone A)	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3303	Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone B)	60 m (200 ft)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	500 m (1500 ft)	2.7 km (1.7 mi)	7.2 km (4.5 mi)
3303	Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3303	Compressed gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)

3303	Compressed gas, toxic, oxidizing, n.o.s.	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3303	Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone A)						
3303	Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone B)	60 m (200 ft)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	500 m (1500 ft)	2.7 km (1.7 mi)	7.2 km (4.5 mi)
3303	Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3303	Compressed gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3304	Compressed gas, poisonous, corrosive, n.o.s.	150 m (500 ft)	0.7 km (0.4 mi)	2.5 km (1.6 mi)	800 m (2500 ft)	4.7 km (2.9 mi)	10.3 km (6.4 mi)
3304	Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone A)						
3304	Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	400 m (1250 ft)	2.4 km (1.5 mi)	6.5 km (4.0 mi)
3304	Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	300 m (1000 ft)	1.7 km (1.1 mi)	3.6 km (2.2 mi)
3304	Compressed gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3304	Compressed gas, toxic, corrosive, n.o.s.	150 m (500 ft)	0.7 km (0.4 mi)	2.5 km (1.6 mi)	800 m (2500 ft)	4.7 km (2.9 mi)	10.3 km (6.4 mi)
3304	Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone A)						

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)			LARGE SPILLS (From a large package or from many small packages)		
		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-		ISOLATE in all Directions Meters (Feet)	PROTECT Then persons Downwind during-	
			DAY Kilometers (Miles)	NIGHT Kilometers (Miles)		DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
3304	Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	400 m (1250 ft)	2.4 km (1.5 mi)	6.5 km (4.0 mi)
3304	Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	300 m (1000 ft)	1.7 km (1.1 mi)	3.6 km (2.2 mi)
3304	Compressed gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3305	Compressed gas, poisonous, flammable, corrosive, n.o.s.	100 m (300 ft)	0.7 km (0.4 mi)	2.5 km (1.6 mi)	800 m (2500 ft)	4.7 km (2.9 mi)	10.3 km (6.4 mi)
3305	Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	800 m (2500 ft)	4.2 km (2.6 mi)	10.3 km (6.4 mi)
3305	Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3305	Compressed gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3305	Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)	100 m (300 ft)	0.7 km (0.4 mi)	2.5 km (1.6 mi)	800 m (2500 ft)	4.7 km (2.9 mi)	10.3 km (6.4 mi)
3305	Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)



3305	Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	800 m (2500 ft)	4.2 km (2.6 mi)	10.3 km (6.4 mi)
3305	Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3305	Compressed gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3306	Compressed gas, poisonous, oxidizing, corrosive, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3306	Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	500 m (1500 ft)	2.7 km (1.7 mi)	7.2 km (4.5 mi)
3306	Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3306	Compressed gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3306	Compressed gas, toxic, oxidizing, corrosive, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3306	Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	500 m (1500 ft)	2.7 km (1.7 mi)	7.2 km (4.5 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
3306	Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3306	Compressed gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3307	Liquefied gas, poisonous, oxidizing, n.o.s.	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3307	Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone A)	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3307	Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone B)	60 m (200 ft)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	500 m (1500 ft)	2.7 km (1.7 mi)	7.2 km (4.5 mi)
3307	Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3307	Liquefied gas, poisonous, oxidizing, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3307	Liquefied gas, toxic, oxidizing, n.o.s.	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3307	Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone A)	100 m (300 ft)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	0.5 km (0.3 mi)	2.1 km (1.3 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3307	Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone B)	60 m (200 ft)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	500 m (1500 ft)	2.7 km (1.7 mi)	7.2 km (4.5 mi)
3307	Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3307	Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)

3307	Liquefied gas, toxic, oxidizing, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3308	Liquefied gas, poisonous, corrosive, n.o.s.	150 m (500 ft)	0.7 km (0.4 mi)	2.5 km (1.6 mi)	800 m (2500 ft)	4.7 km (2.9 mi)	10.3 km (6.4 mi)
3308	Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	400 m (1250 ft)	2.4 km (1.5 mi)	6.5 km (4.0 mi)
3308	Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	300 m (1000 ft)	1.7 km (1.1 mi)	3.6 km (2.2 mi)
3308	Liquefied gas, poisonous, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3308	Liquefied gas, toxic, corrosive, n.o.s.	150 m (500 ft)	0.7 km (0.4 mi)	2.5 km (1.6 mi)	800 m (2500 ft)	4.7 km (2.9 mi)	10.3 km (6.4 mi)
3308	Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	400 m (1250 ft)	2.4 km (1.5 mi)	6.5 km (4.0 mi)
3308	Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	300 m (1000 ft)	1.7 km (1.1 mi)	3.6 km (2.2 mi)
3308	Liquefied gas, toxic, corrosive, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3309	Liquefied gas, poisonous, flammable, corrosive, n.o.s.	100 m (300 ft)	0.7 km (0.4 mi)	2.5 km (1.6 mi)	800 m (2500 ft)	4.7 km (2.9 mi)	10.3 km (6.4 mi)
3309	Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	400 m (1250 ft)	2.4 km (1.5 mi)	6.5 km (4.0 mi)
3309	Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.4 km (0.3 mi)	300 m (1000 ft)	1.7 km (1.1 mi)	3.6 km (2.2 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
3309	Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3309	Liquefied gas, poisonous, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3309	Liquefied gas, toxic, flammable, corrosive, n.o.s.	100 m (300 ft)	0.7 km (0.4 mi)	2.5 km (1.6 mi)	0.7 km (0.4 mi)	2.5 km (1.6 mi)	800 m (2500 ft)	4.7 km (2.9 mi)	10.3 km (6.4 mi)
3309	Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	0.2 km (0.1 mi)	1.0 km (0.6 mi)	800 m (2500 ft)	4.2 km (2.6 mi)	10.3 km (6.4 mi)
3309	Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3309	Liquefied gas, toxic, flammable, corrosive, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3310	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3310	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	500 m (1500 ft)	2.7 km (1.7 mi)	7.2 km (4.5 mi)

3310	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3310	Liquefied gas, poisonous, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3310	Liquefied gas, toxic, oxidizing, corrosive, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3310	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.2 km (0.2 mi)	1.0 km (0.6 mi)	500 m (1500 ft)	2.7 km (1.7 mi)	7.2 km (4.5 mi)
3310	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)
3310	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
3318	Ammonia solution, with more than 50% Ammonia	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.8 km (0.5 mi)	2.3 km (1.4 mi)
3355	Insecticide gas, poisonous, flammable, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)
3355	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	
3355	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)		
3355	Insecticide gas, poisonous, flammable, n.o.s. (Inhalation Hazard Zone D)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)		
3355	Insecticide gas, toxic, flammable, n.o.s.	100 m (300 ft)	0.6 km (0.4 mi)	2.5 km (1.5 mi)	800 m (2500 ft)	4.4 km (2.7 mi)	8.9 km (5.6 mi)		
3355	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.2 km (0.1 mi)	0.8 km (0.5 mi)	400 m (1250 ft)	1.9 km (1.2 mi)	4.8 km (3.0 mi)		
3355	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	300 m (1000 ft)	1.3 km (0.8 mi)	4.1 km (2.6 mi)		
3355	Insecticide gas, toxic, flammable, n.o.s. (Inhalation Hazard Zone C)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)		
3361	Chlorosilanes, poisonous, corrosive, n.o.s. (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)		
3361	Chlorosilanes, toxic, corrosive, n.o.s. (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)		
3362	Chlorosilanes, poisonous, corrosive, flammable, n.o.s.	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)		
3362	Chlorosilanes, toxic, corrosive, flammable, n.o.s. (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	100 m (300 ft)	0.5 km (0.3 mi)	1.6 km (1.0 mi)		

3381	Poisonous by inhalation liquid, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3381	Toxic by inhalation liquid, n.o.s. (Inhalation Hazard Zone A)						
3382	Poisonous by inhalation liquid, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
3382	Toxic by inhalation liquid, n.o.s. (Inhalation Hazard Zone B)						
3383	Poisonous by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.7 km (0.4 mi)	2.3 km (1.4 mi)	400 m (1250 ft)	4.6 km (2.9 mi)	8.9 km (5.5 mi)
3383	Toxic by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone A)						
3384	Poisonous by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
3384	Toxic by inhalation liquid, flammable, n.o.s. (Inhalation Hazard Zone B)						
3385	Poisonous by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)
3385	Toxic by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone A)						
3386	Poisonous by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)
3386	Toxic by inhalation liquid, water-reactive, n.o.s. (Inhalation Hazard Zone B)						

**TABLE 1 - INITIAL ISOLATION AND PROTECTIVE ACTION DISTANCES**

ID No.	NAME OF MATERIAL	SMALL SPILLS (From a small package or small leak from a large package)				LARGE SPILLS (From a large package or from many small packages)			
		ISOLATE in all Directions		PROTECT persons Downwind during-		ISOLATE in all Directions		PROTECT persons Downwind during-	
		Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)	Meters (Feet)	Kilometers (Miles)	DAY Kilometers (Miles)	NIGHT Kilometers (Miles)
3387	Poisonous by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)	5.7 km (3.6 mi)
3387	Toxic by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.0 km (0.6 mi)	1.0 km (0.6 mi)
3388	Poisonous by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)	5.7 km (3.6 mi)
3388	Toxic by inhalation liquid, oxidizing, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	0.3 km (0.2 mi)	60 m (200 ft)	0.6 km (0.4 mi)	1.0 km (0.6 mi)	1.0 km (0.6 mi)
3389	Poisonous by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)	60 m (200 ft)	0.8 km (0.5 mi)	1.8 km (1.1 mi)	1.8 km (1.1 mi)	300 m (1000 ft)	2.9 km (1.8 mi)	5.7 km (3.6 mi)	5.7 km (3.6 mi)
3389	Toxic by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone A)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)	0.8 km (0.5 mi)
3390	Poisonous by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	0.5 km (0.3 mi)	200 m (600 ft)	0.7 km (0.5 mi)	2.5 km (1.6 mi)	2.5 km (1.6 mi)
3390	Toxic by inhalation liquid, corrosive, n.o.s. (Inhalation Hazard Zone B)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.8 km (0.5 mi)	0.8 km (0.5 mi)
3456	Nitrosylsulfuric acid, solid (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.5 km (0.3 mi)	0.5 km (0.3 mi)	200 m (600 ft)	0.7 km (0.5 mi)	2.5 km (1.6 mi)	2.5 km (1.6 mi)
3456	Nitrosylsulfuric acid, solid (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.4 km (0.3 mi)	1.3 km (0.8 mi)	1.3 km (0.8 mi)
3461	Aluminum alkyl halides, solid (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.4 km (0.3 mi)	1.3 km (0.8 mi)	1.3 km (0.8 mi)
9191	Chlorine dioxide, hydrate, frozen (when spilled in water)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.2 km (0.2 mi)	0.6 km (0.4 mi)	0.6 km (0.4 mi)



9192	Fluorine, refrigerated liquid (cyrogenic liquid)	30 m (100 ft)	0.1 km (0.1 mi)	0.3 km (0.2 mi)	150 m (500 ft)	0.8 km (0.5 mi)	3.1 km (1.9 mi)
9202	Carbon monoxide, refrigerated liquid (cyrogenic liquid)	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	150 m (500 ft)	0.7 km (0.5 mi)	2.7 km (1.7 mi)
9206	Methyl phosphonic dichloride	30 m (100 ft)	0.1 km (0.1 mi)	0.2 km (0.1 mi)	60 m (200 ft)	0.5 km (0.3 mi)	0.7 km (0.4 mi)
9263	Chloropivaloyl chloride	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.4 km (0.2 mi)
9264	3,5-Dichloro-2,4,6-trifluoropyridine	30 m (100 ft)	0.1 km (0.1 mi)	0.1 km (0.1 mi)	30 m (100 ft)	0.3 km (0.2 mi)	0.3 km (0.2 mi)
9269	Trimethoxysilane	30 m (100 ft)	0.2 km (0.1 mi)	0.5 km (0.3 mi)	150 m (500 ft)	1.0 km (0.7 mi)	2.0 km (1.3 mi)

**See Next Page for Table of Water-Reactive Materials Which Produce Toxic Gases**

## TABLE 2 - WATER-REACTIVE MATERIALS WHICH PRODUCE TOXIC GASES

### Materials Which Produce Large Amounts of Toxic-by-Inhalation (TIH) Gas(es) When Spilled in Water

ID No.	Guide No.	Name of Material	TIH Gas(es) Produced
1162	155	Dimethyldichlorosilane	HCl
1183	139	Ethyldichlorosilane	HCl
1196	155	Ethyltrichlorosilane	HCl
1242	139	Methyldichlorosilane	HCl
1250	155	Methyltrichlorosilane	HCl
1295	139	Trichlorosilane	HCl
1298	155	Trimethylchlorosilane	HCl
1305	155P	Vinyltrichlorosilane	HCl
1305	155P	Vinyltrichlorosilane, stabilized	HCl
1340	139	Phosphorus pentasulfide, free from yellow and white Phosphorus	H <sub>2</sub> S
1340	139	Phosphorus pentasulphide, free from yellow and white Phosphorus	H <sub>2</sub> S
1360	139	Calcium phosphide	PH <sub>3</sub>
1384	135	Sodium dithionite	H <sub>2</sub> S SO <sub>2</sub>
1384	135	Sodium hydrosulfite	H <sub>2</sub> S SO <sub>2</sub>
1384	135	Sodium hydrosulphite	H <sub>2</sub> S SO <sub>2</sub>
1397	139	Aluminum phosphide	PH <sub>3</sub>
1412	139	Lithium amide	NH <sub>3</sub>
1419	139	Magnesium aluminum phosphide	PH <sub>3</sub>
1432	139	Sodium phosphide	PH <sub>3</sub>
1541	155	Acetone cyanohydrin, stabilized	HCN
1680	157	Potassium cyanide	HCN
1680	157	Potassium cyanide, solid	HCN
1689	157	Sodium cyanide	HCN
1689	157	Sodium cyanide, solid	HCN

#### Chemical Symbols for TIH Gases:

Br <sub>2</sub>	Bromine	HF	Hydrogen fluoride	PH <sub>3</sub>	Phosphine
Cl <sub>2</sub>	Chlorine	HI	Hydrogen iodide	NO <sub>2</sub>	Nitrogen dioxide
HBr	Hydrogen bromide	H <sub>2</sub> S	Hydrogen sulfide	SO <sub>2</sub>	Sulfur dioxide
HCl	Hydrogen chloride	H <sub>2</sub> S	Hydrogen sulphide	SO <sub>2</sub>	Sulphur dioxide
HCN	Hydrogen cyanide	NH <sub>3</sub>	Ammonia		

## TABLE 2 - WATER-REACTIVE MATERIALS WHICH PRODUCE TOXIC GASES

### Materials Which Produce Large Amounts of Toxic-by-Inhalation (TIH) Gas(es) When Spilled in Water

ID No.	Guide No.	Name of Material	TIH Gas(es) Produced
1716	156	Acetyl bromide	HBr
1717	155	Acetyl chloride	HCl
1724	155	Allyltrichlorosilane, stabilized	HCl
1725	137	Aluminum bromide, anhydrous	HBr
1726	137	Aluminum chloride, anhydrous	HCl
1728	155	Amyltrichlorosilane	HCl
1732	157	Antimony pentafluoride	HF
1741	125	Boron trichloride	HCl
1745	144	Bromine pentafluoride	HF Br <sub>2</sub>
1746	144	Bromine trifluoride	HF Br <sub>2</sub>
1747	155	Butyltrichlorosilane	HCl
1752	156	Chloroacetyl chloride	HCl
1753	156	Chlorophenyltrichlorosilane	HCl
1754	137	Chlorosulfonic acid	HCl
1754	137	Chlorosulfonic acid and Sulfur trioxide mixture	HCl
1754	137	Chlorosulphonic acid	HCl
1754	137	Chlorosulphonic acid and Sulphur trioxide mixture	HCl
1754	137	Sulfur trioxide and Chlorosulfonic acid	HCl
1754	137	Sulphur trioxide and Chlorosulphonic acid	HCl
1758	137	Chromium oxychloride	HCl
1762	156	Cyclohexenyltrichlorosilane	HCl
1763	156	Cyclohexyltrichlorosilane	HCl
1765	156	Dichloroacetyl chloride	HCl
1766	156	Dichlorophenyltrichlorosilane	HCl

#### Chemical Symbols for TIH Gases:

Br <sub>2</sub>	Bromine	HF	Hydrogen fluoride	PH <sub>3</sub>	Phosphine
Cl <sub>2</sub>	Chlorine	HI	Hydrogen iodide	NO <sub>2</sub>	Nitrogen dioxide
HBr	Hydrogen bromide	H <sub>2</sub> S	Hydrogen sulfide	SO <sub>2</sub>	Sulfur dioxide
HCl	Hydrogen chloride	H <sub>2</sub> S	Hydrogen sulphide	SO <sub>2</sub>	Sulphur dioxide
HCN	Hydrogen cyanide	NH <sub>3</sub>	Ammonia		

## TABLE 2 - WATER-REACTIVE MATERIALS WHICH PRODUCE TOXIC GASES

### Materials Which Produce Large Amounts of Toxic-by-Inhalation (TIH) Gas(es) When Spilled in Water

ID No.	Guide No.	Name of Material	TIH Gas(es) Produced
1767	155	Diethyldichlorosilane	HCl
1769	156	Diphenyldichlorosilane	HCl
1771	156	Dodecyltrichlorosilane	HCl
1777	137	Fluorosulfonic acid	HF
1777	137	Fluorosulphonic acid	HF
1781	156	Hexadecyltrichlorosilane	HCl
1784	156	Hexyltrichlorosilane	HCl
1799	156	Nonyltrichlorosilane	HCl
1800	156	Octadecyltrichlorosilane	HCl
1801	156	Octyltrichlorosilane	HCl
1804	156	Phenyltrichlorosilane	HCl
1806	137	Phosphorus pentachloride	HCl
1808	137	Phosphorus tribromide	HBr
1809	137	Phosphorus trichloride	HCl
1810	137	Phosphorus oxychloride	HCl
1815	132	Propionyl chloride	HCl
1816	155	Propyltrichlorosilane	HCl
1818	157	Silicon tetrachloride	HCl
1828	137	Sulfur chlorides	HCl SO <sub>2</sub> H <sub>2</sub> S
1828	137	Sulphur chlorides	HCl SO <sub>2</sub> H <sub>2</sub> S
1834	137	Sulfuryl chloride	HCl
1834	137	Sulphuryl chloride	HCl
1836	137	Thionyl chloride	HCl SO <sub>2</sub>
1838	137	Titanium tetrachloride	HCl

#### Chemical Symbols for TIH Gases:

Br <sub>2</sub>	Bromine	HF	Hydrogen fluoride	PH <sub>3</sub>	Phosphine
Cl <sub>2</sub>	Chlorine	HI	Hydrogen iodide	NO <sub>2</sub>	Nitrogen dioxide
HBr	Hydrogen bromide	H <sub>2</sub> S	Hydrogen sulfide	SO <sub>2</sub>	Sulfur dioxide
HCl	Hydrogen chloride	H <sub>2</sub> S	Hydrogen sulphide	SO <sub>2</sub>	Sulphur dioxide
HCN	Hydrogen cyanide	NH <sub>3</sub>	Ammonia		

## TABLE 2 - WATER-REACTIVE MATERIALS WHICH PRODUCE TOXIC GASES

### Materials Which Produce Large Amounts of Toxic-by-Inhalation (TIH) Gas(es) When Spilled in Water

ID No.	Guide No.	Name of Material	TIH Gas(es) Produced
1898	156	Acetyl iodide	HI
1923	135	Calcium dithionite	H <sub>2</sub> S SO <sub>2</sub>
1923	135	Calcium hydrosulfite	H <sub>2</sub> S SO <sub>2</sub>
1923	135	Calcium hydrosulphite	H <sub>2</sub> S SO <sub>2</sub>
1929	135	Potassium dithionite	H <sub>2</sub> S SO <sub>2</sub>
1929	135	Potassium hydrosulfite	H <sub>2</sub> S SO <sub>2</sub>
1929	135	Potassium hydrosulphite	H <sub>2</sub> S SO <sub>2</sub>
1931	171	Zinc dithionite	H <sub>2</sub> S SO <sub>2</sub>
1931	171	Zinc hydrosulfite	H <sub>2</sub> S SO <sub>2</sub>
1931	171	Zinc hydrosulphite	H <sub>2</sub> S SO <sub>2</sub>
2004	135	Magnesium diamide	NH <sub>3</sub>
2011	139	Magnesium phosphide	PH <sub>3</sub>
2012	139	Potassium phosphide	PH <sub>3</sub>
2013	139	Strontium phosphide	PH <sub>3</sub>
2308	157	Nitrosylsulfuric acid	NO <sub>2</sub>
2308	157	Nitrosylsulfuric acid, liquid	NO <sub>2</sub>
2308	157	Nitrosylsulfuric acid, solid	NO <sub>2</sub>
2308	157	Nitrosylsulphuric acid	NO <sub>2</sub>
2308	157	Nitrosylsulphuric acid, liquid	NO <sub>2</sub>
2308	157	Nitrosylsulphuric acid, solid	NO <sub>2</sub>
2353	132	Butyryl chloride	HCl
2395	132	Isobutyryl chloride	HCl
2434	156	Dibenzylchlorosilane	HCl
2435	156	Ethylphenylchlorosilane	HCl

#### Chemical Symbols for TIH Gases:

Br <sub>2</sub>	Bromine	HF	Hydrogen fluoride	PH <sub>3</sub>	Phosphine
Cl <sub>2</sub>	Chlorine	HI	Hydrogen iodide	NO <sub>2</sub>	Nitrogen dioxide
HBr	Hydrogen bromide	H <sub>2</sub> S	Hydrogen sulfide	SO <sub>2</sub>	Sulfur dioxide
HCl	Hydrogen chloride	H <sub>2</sub> S	Hydrogen sulphide	SO <sub>2</sub>	Sulphur dioxide
HCN	Hydrogen cyanide	NH <sub>3</sub>	Ammonia		

## TABLE 2 - WATER-REACTIVE MATERIALS WHICH PRODUCE TOXIC GASES

### Materials Which Produce Large Amounts of Toxic-by-Inhalation (TIH) Gas(es) When Spilled in Water

ID No.	Guide No.	Name of Material	TIH Gas(es) Produced
2437	156	Methylphenyldichlorosilane	HCl
2495	144	Iodine pentafluoride	HF
2691	137	Phosphorus pentabromide	HBr
2692	157	Boron tribromide	HBr
2806	138	Lithium nitride	NH <sub>3</sub>
2977	166	Radioactive material, Uranium hexafluoride, fissile	HF
2977	166	Uranium hexafluoride, fissile containing more than 1% Uranium-235	HF
2978	166	Radioactive material, Uranium hexafluoride	HF
2978	166	Uranium hexafluoride	HF
2978	166	Uranium hexafluoride non fissile or fissile-excepted	HF
2985	155	Chlorosilanes, flammable, corrosive, n.o.s.	HCl
2985	155	Chlorosilanes, n.o.s.	HCl
2986	155	Chlorosilanes, corrosive, flammable, n.o.s.	HCl
2986	155	Chlorosilanes, n.o.s.	HCl
2987	156	Chlorosilanes, corrosive, n.o.s.	HCl
2987	156	Chlorosilanes, n.o.s.	HCl
2988	139	Chlorosilanes, n.o.s.	HCl
2988	139	Chlorosilanes, water-reactive, flammable, corrosive, n.o.s.	HCl
3048	157	Aluminum phosphide pesticide	PH <sub>3</sub>
3049	138	Metal alkyl halides, n.o.s.	HCl
3049	138	Metal alkyl halides, water-reactive, n.o.s.	HCl
3049	138	Metal aryl halides, n.o.s.	HCl
3049	138	Metal aryl halides, water-reactive, n.o.s.	HCl

#### Chemical Symbols for TIH Gases:

Br <sub>2</sub>	Bromine	HF	Hydrogen fluoride	PH <sub>3</sub>	Phosphine
Cl <sub>2</sub>	Chlorine	HI	Hydrogen iodide	NO <sub>2</sub>	Nitrogen dioxide
HBr	Hydrogen bromide	H <sub>2</sub> S	Hydrogen sulfide	SO <sub>2</sub>	Sulfur dioxide
HCl	Hydrogen chloride	H <sub>2</sub> S	Hydrogen sulphide	SO <sub>2</sub>	Sulphur dioxide
HCN	Hydrogen cyanide	NH <sub>3</sub>	Ammonia		

## TABLE 2 - WATER-REACTIVE MATERIALS WHICH PRODUCE TOXIC GASES

### Materials Which Produce Large Amounts of Toxic-by-Inhalation (TIH) Gas(es) When Spilled in Water

ID No.	Guide No.	Name of Material	TIH Gas(es) Produced
3052	135	Aluminum alkyl halides	HCl
3052	135	Aluminum alkyl halides, liquid	HCl
3052	135	Aluminum alkyl halides, solid	HCl
3361	156	Chlorosilanes, poisonous, corrosive, n.o.s.	HCl
3361	156	Chlorosilanes, toxic, corrosive, n.o.s.	HCl
3362	155	Chlorosilanes, poisonous, corrosive, flammable, n.o.s.	HCl
3362	155	Chlorosilanes, toxic, corrosive, flammable, n.o.s.	HCl
3456	157	Nitrosylsulfuric acid, solid	NO <sub>2</sub>
3456	157	Nitrosylsulphuric acid, solid	NO <sub>2</sub>
3461	135	Aluminum alkyl halides, solid	HCl
9191	143	Chlorine dioxide, hydrate, frozen	Cl <sub>2</sub>

#### Chemical Symbols for TIH Gases:

Br <sub>2</sub>	Bromine	HF	Hydrogen fluoride	PH <sub>3</sub>	Phosphine
Cl <sub>2</sub>	Chlorine	HI	Hydrogen iodide	NO <sub>2</sub>	Nitrogen dioxide
HBr	Hydrogen bromide	H <sub>2</sub> S	Hydrogen sulfide	SO <sub>2</sub>	Sulfur dioxide
HCl	Hydrogen chloride	H <sub>2</sub> S	Hydrogen sulphide	SO <sub>2</sub>	Sulphur dioxide
HCN	Hydrogen cyanide	NH <sub>3</sub>	Ammonia		

## PROTECTIVE CLOTHING

**Street Clothing and Work Uniforms.** These garments, such as uniforms worn by police and emergency medical services personnel, provide almost no protection from the harmful effects of dangerous goods.

**Structural Fire Fighters' Protective Clothing (SFPC).** This category of clothing, often called turnout or bunker gear, means the protective clothing normally worn by fire fighters during structural fire fighting operations. It includes a helmet, coat, pants, boots, gloves and a hood to cover parts of the head not protected by the helmet and facepiece. This clothing must be used with full-facepiece positive pressure self-contained breathing apparatus (SCBA). This protective clothing should, at a minimum, meet the OSHA Fire Brigades Standard (29 CFR 1910.156). Structural fire fighters' protective clothing provides limited protection from heat and cold, but may not provide adequate protection from the harmful vapors or liquids that are encountered during dangerous goods incidents. Each guide includes a statement about the use of SFPC in incidents involving those materials referenced by that guide. Some guides state that SFPC provides limited protection. In those cases, the responder wearing SFPC and SCBA may be able to perform an expedient, that is quick "in-and-out", operation. However, this type of operation can place the responder at risk of exposure, injury or death. The incident commander makes the decision to perform this operation only if an overriding benefit can be gained (i.e., perform an immediate rescue, turn off a valve to control a leak, etc.). The coverall-type protective clothing customarily worn to fight fires in forests or wildlands is **not** SFPC and is not recommended nor referred to elsewhere in this guidebook.

**Positive Pressure Self-Contained Breathing Apparatus (SCBA).** This apparatus provides a constant, positive pressure flow of air within the facepiece, even if one inhales deeply while doing heavy work. Use apparatus certified by NIOSH and the Department of Labor/Mine Safety and Health Administration in accordance with 42 CFR Part 84. Use it in accordance with the requirements for respiratory protection specified in OSHA 29 CFR 1910.134 (Respiratory Protection) and/or 29 CFR 1910.156 (f) (Fire Brigades Standard). Chemical-cartridge respirators or other filtering masks are not acceptable substitutes for positive pressure self-contained breathing apparatus. Demand-type SCBA does not meet the OSHA 29 CFR 1910.156 (f)(1)(i) of the Fire Brigades Standard. If it is suspected that a Chemical Warfare Agent (CW) is involved, the use of NIOSH-certified respirators with CBRN protection are highly recommended.

**Chemical Protective Clothing and Equipment.** Safe use of this type of protective clothing and equipment requires specific skills developed through training and experience. It is generally not available to, or used by, first responders. This type of special clothing may protect against one chemical, yet be readily permeated by chemicals for which it was not designed. Therefore, protective clothing should not be used unless it is compatible with the released material. This type of special clothing offers little or no protection against heat and/or cold. Examples of this type of equipment have been described as (1) Vapor Protective



Suits (NFPA 1991), also known as Totally-Encapsulating Chemical Protective (TECP) Suits or Level A\* protection (OSHA 29 CFR 1910.120, Appendix A & B), and (2) Liquid-Splash Protective Suits (NFPA 1992 & 1993), also known as Level B\* or C\* protection (OSHA 29 CFR 1910.120, Appendix A & B) or suits for chemical/biological terrorism incidents (NFPA 1994), class 1, 2 or 3 Ensembles. No single protective clothing material will protect you from all dangerous goods. Do not assume any protective clothing is resistant to cold and/or heat or flame exposure unless it is so certified by the manufacturer. (NFPA 1991 5-3 Flammability Resistance Test and 5-6 Cold Temperature Performance Test)

\* Consult glossary for additional protection levels under the heading "Protective Clothing".

## FIRE AND SPILL CONTROL

### FIRE CONTROL

Water is the most common and generally most available fire extinguishing agent. Exercise caution in selecting a fire extinguishing method since there are many factors to be considered in an incident. Water may be ineffective in fighting fires involving some materials; its effectiveness depends greatly on the method of application.

Fires involving a spill of flammable liquids are generally controlled by applying a fire fighting foam to the surface of the burning material. Fighting flammable liquid fires requires foam concentrate which is chemically compatible with the burning material, correct mixing of the foam concentrate with water and air, and careful application and maintenance of the foam blanket. There are two general types of fire fighting foam: regular and alcohol-resistant. Examples of regular foam are protein-base, fluoroprotein, and aqueous film forming foam (AFFF). Some flammable liquids, including many petroleum products, can be controlled by applying regular foam. Other flammable liquids, including polar solvents (flammable liquids which are water soluble) such as alcohols and ketones, have different chemical properties. A fire involving these materials cannot be easily controlled with regular foam and requires application of alcohol-resistant foam. Polar-solvent fires may be difficult to control and require a higher foam application rate than other flammable liquid fires (see NFPA/ANSI Standards 11 and 11A for further information). Refer to the appropriate guide to determine which type of foam is recommended. Although it is impossible to make specific recommendations for flammable liquids which have subsidiary corrosive or toxic hazards, alcohol-resistant foam may be effective for many of these materials. The emergency response telephone number on the shipping document, or the appropriate emergency response agency, should be contacted as soon as possible for guidance on the proper fire extinguishing agent to use. The final selection of the agent and method depends on many factors such as incident location, exposure hazards, size of the fire, environmental concerns, as well as the availability of extinguishing agents and equipment at the scene.

### WATER REACTIVE MATERIALS

Water is sometimes used to flush spills and to reduce or direct vapors in spill situations. Some of the materials covered by the guidebook can react violently or even explosively with water. In these cases, consider letting the fire burn or leaving the spill alone (except to prevent its spreading by diking) until additional technical advice can be obtained. The applicable guides clearly warn you of these potentially dangerous reactions. These materials require technical advice since

- (1) water getting inside a ruptured or leaking container may cause an explosion;
- (2) water may be needed to cool adjoining containers to prevent their rupturing (exploding) or further spread of the fires;
- (3) water may be effective in mitigating an incident involving a water-reactive material only if it can be applied at a sufficient flooding rate for an extended period; and

- (4) the products from the reaction with water may be more toxic, corrosive, or otherwise more undesirable than the product of the fire without water applied.

When responding to an incident involving water-reactive materials, take into account the existing conditions such as wind, precipitation, location and accessibility to the incident, as well as the availability of the agents to control the fire or spill. Because there are variables to consider, the decision to use water on fires or spills involving water-reactive materials should be based on information from an authoritative source; for example, a producer of the material, who can be contacted through the emergency response telephone number or the appropriate emergency response agency.

## **VAPOR CONTROL**

Limiting the amount of vapor released from a pool of flammable or corrosive liquids is an operational concern. It requires the use of proper protective clothing, specialized equipment, appropriate chemical agents, and skilled personnel. Before engaging in vapor control, get advice from an authoritative source as to the proper tactics.

There are several ways to minimize the amount of vapors escaping from pools of spilled liquids, such as special foams, adsorbing agents, absorbing agents, and neutralizing agents. To be effective, these vapor control methods must be selected for the specific material involved and performed in a manner that will mitigate, not worsen, the incident.

Where specific materials are known, such as at manufacturing or storage facilities, it is desirable for the dangerous goods response team to prearrange with the facility operators to select and stockpile these control agents in advance of a spill. In the field, first responders may not have the most effective vapor control agent for the material available. They are likely to have only water and only one type of fire fighting foam on their vehicles. If the available foam is inappropriate for use, they are likely to use water spray. Because the water is being used to form a vapor seal, care must be taken not to churn or further spread the spill during application. Vapors that do not react with water may be directed away from the site using the air currents surrounding the water spray. Before using water spray or other methods to safely control vapor emission or to suppress ignition, obtain technical advice, based on specific chemical name identification.

## **CRIMINAL/TERRORIST USE OF CHEMICAL/BIOLOGICAL/RADIOLOGICAL AGENTS**

The following is intended to supply information to first responders for use in making a preliminary assessment of a situation that they suspect involves criminal/terrorist use of chemical, biological agents and/or radioactive materials (CBRN). To aid in the assessment, a list of observable indicators of the use and/or presence of a CB agent or radioactive material is provided in the following paragraphs.

### **DIFFERENCES BETWEEN A CHEMICAL, BIOLOGICAL AND RADIOLOGICAL AGENT**

Chemical and biological agents as well as radioactive materials can be dispersed in the air we breathe, the water we drink, or on surfaces we physically contact. Dispersion methods may be as simple as opening a container, using conventional (garden) spray devices, or as elaborate as detonating an improvised explosive device.

**Chemical Incidents** are characterized by the rapid onset of medical symptoms (minutes to hours) and easily observed signatures (colored residue, dead foliage, pungent odor, dead insects and animals).

**Biological Incidents** are characterized by the onset of symptoms in hours to days. Typically, there will be no characteristic signatures because biological agents are usually odorless and colorless. Because of the delayed onset of symptoms in a biological incident, the area affected may be greater due to the movement of infected individuals.

**Radiological Incidents** are characterized by the onset of symptoms, if any, in days to weeks or longer. Typically, there will be no characteristic signatures because radioactive materials are usually odorless and colorless. Specialized equipment is required to determine the size of the affected area, and whether the level of radioactivity presents an immediate or long-term health hazard. Because radioactivity is not detectable without special equipment, the affected area may be greater due to the migration of contaminated individuals.

At the levels created by most probable sources, not enough radiation would be generated to kill people or cause severe illness. In a radiological incident generated by a “dirty bomb”, or Radiological Dispersal Device (RDD), in which a conventional explosive is detonated to spread radioactive contamination, the primary hazard is from the explosion. However, certain radioactive materials dispersed in the air could contaminate up to several city blocks, creating fear and possibly panic, and requiring potentially costly cleanup.

### **INDICATORS OF A POSSIBLE CHEMICAL INCIDENT**

#### **Dead animals/birds/fish**

Not just an occasional road kill, but numerous animals (wild and domestic, small and large), birds, and fish in the same area.

## INDICATORS OF A POSSIBLE CHEMICAL INCIDENT (Continued)

<b>Lack of insect life</b>	If normal insect activity (ground, air, and/or water) is missing, check the ground/water surface/shore line for dead insects. If near water, check for dead fish/aquatic birds.
<b>Unexplained odors</b>	Smells may range from fruity to flowery to sharp/pungent to garlic/ horseradish-like to bitter almonds/peach kernels to new mown hay. It is important to note that the particular odor is completely out of character with its surroundings.
<b>Unusual numbers of dying or sick people (mass casualties)</b>	Health problems including nausea, disorientation, difficulty in breathing, convulsions, localized sweating, conjunctivitis (reddening of eyes/nerve agent symptoms), erythema (reddening of skin/vesicant symptoms) and death.
<b>Pattern of casualties</b>	Casualties will likely be distributed downwind, or if indoors, by the air ventilation system.
<b>Blisters/rashes</b>	Numerous individuals experiencing unexplained water-like blisters, weals (like bee stings), and/or rashes.
<b>Illness in confined area</b>	Different casualty rates for people working indoors versus outdoors dependent on where the agent was released.
<b>Unusual liquid droplets</b>	Numerous surfaces exhibit oily droplets/film; numerous water surfaces have an oily film. (No recent rain.)
<b>Different looking areas</b>	Not just a patch of dead weeds, but trees, shrubs, bushes, food crops, and/or lawns that are dead, discolored, or withered. (No current drought.)
<b>Low-lying clouds</b>	Low-lying cloud/fog-like condition that is not consistent with its surroundings.
<b>Unusual metal debris</b>	Unexplained bomb/munitions-like material, especially if it contains a liquid.

## INDICATORS OF A POSSIBLE BIOLOGICAL INCIDENT

<b>Unusual numbers of sick or dying people or animals</b>	Any number of symptoms may occur. Casualties may occur hours to days after an incident has occurred. The time required before symptoms are observed is dependent on the agent used.
<b>Unscheduled and unusual spray being disseminated</b>	Especially if outdoors during periods of darkness.
<b>Abandoned spray devices</b>	Devices may not have distinct odors.

## INDICATORS OF A POSSIBLE RADIOLOGICAL INCIDENT

<b>Radiation Symbols</b>	Containers may display a “propeller” radiation symbol.
<b>Unusual metal debris</b>	Unexplained bomb/munitions-like material.
<b>Heat-emitting material</b>	Material that is hot or seems to emit heat without any sign of an external heat source.
<b>Glowing material</b>	Strongly radioactive material may emit or cause radioluminescence.
<b>Sick people/animals</b>	In very improbable scenarios there may be unusual numbers of sick or dying people or animals. Casualties may occur hours to days or weeks after an incident has occurred. The time required before symptoms are observed is dependent on the radioactive material used, and the dose received. Possible symptoms include skin reddening or vomiting.

## PERSONAL SAFETY CONSIDERATIONS

When approaching a scene that may involve CB agents or radioactive materials, the most critical consideration is the safety of oneself and other responders. Protective clothing and respiratory protection of appropriate level of safety must be used. In incidents where it is suspected that CBRN materials have been used as weapons, NIOSH-certified respirators with CBRN protection are highly recommended. Be aware that the presence and identification of CB agents or radioactive materials may not be verifiable, especially in the case of biological or radiological agents. The following actions/measures to be considered are applicable to either a chemical, biological or radiological incident. The guidance is general in nature, not all encompassing, and its applicability should be evaluated on a case-by-case basis.

**Approach and response strategies.** Protect yourself and use a safe approach (minimize any exposure time, maximize the distance between you and the item that is likely to harm you, use cover as protection and wear appropriate personal protective equipment and respiratory protection). Identify and estimate the hazard by using indicators as provided above. Isolate the area and secure the scene; potentially contaminated people should be isolated and decontaminated as soon as possible. To the extent possible, take measures to limit the spread of contamination. In the event of a chemical incident, the fading of chemical odors is not necessarily an indication of reduced vapor concentrations. Some chemicals deaden the senses giving the false perception that the chemical is no longer present.

If there is any indication that an area may be contaminated with radioactive materials, including the site of any non-accidental explosion, responder personnel should be equipped with radiation detection equipment that would alert them if they are entering a radiologically

compromised environment, and should have received adequate training in its use. This equipment should be designed in such a way that it can also alert the responders when an unacceptable ambient dose rate or ambient dose has been reached.

**Initial actions** to consider in a potential CBRN/Hazmat Terrorism Event:

- Avoid using cell phones, radios, etc. within 100 meters (300 feet) of a suspect device.
- NOTIFY your local police by calling 911.
- Set up Incident command upwind and uphill of the area.
- Do NOT touch or move suspicious packages/containers.
- Be cautious regarding potential presence of secondary devices (e.g. Improvised Explosive Devices, IEDs).
- Avoid contamination.
- Limit access to only those responsible for rescue of victims or assessment of unknown materials or devices.
- Evacuate and isolate individuals potentially exposed to dangerous goods/hazardous materials.
- Isolate contaminated areas and secure the scene for analysis of material.

**Decontamination measures.** Emergency responders should follow standard decontamination procedures (flush-strip-flush). Mass casualty decontamination should begin as soon as possible by stripping (all clothing) and flushing (soap and water). If biological agents are involved or suspected, careful washing and use of a brush are more effective. If chemical agents are suspected, the most important and effective decontamination will be that done within the first one or two minutes. If possible, further decontamination should be performed using a 0.5% hypochlorite solution (1 part household bleach mixed with 9 parts water). If biological agents are suspected, a contact time of 10 to 15 minutes should be allowed before rinsing. The solution can be used on soft tissue wounds, but must not be used in eyes or open wounds of the abdomen, chest, head, or spine. For further information contact the agencies listed in this guidebook.

For persons contaminated with radioactive material, remove them to a low radiation area if necessary. Remove their clothing and place it in a clearly marked sealed receptacle, such as a plastic bag, for later testing. Use decontamination methods described above, but avoid breaking the skin, e.g., from shaving, or overly vigorous brushing. External radiological contamination on intact skin surface rarely causes a high enough dose to be a hazard to either the contaminated person or the first responders. For this reason, except in very unusual circumstances, an injured person who is also radiologically contaminated should be medically stabilized, taking care to minimize the spread of the contamination to the extent possible, before decontamination measures are initiated.

**NOTE:** The above information was developed in part by the Department of National Defence (Canada), the U.S. Department of the Army, Aberdeen Proving Ground and the Federal Bureau of Investigation (FBI).

## Glossary

- AEGL(s)** Acute Exposure Guideline Level(s), AEGLs represent threshold exposure limits for the general public and are applicable to emergency exposure periods ranging from 10 minutes to 8 hours. Three levels AEGL-1, AEGL-2 and AEGL-3 are developed for each of five exposure periods (10 and 30 minutes, 1 hour, 4 hours, and 8 hours) and are distinguished by varying degrees of severity of toxic effects; see AEGL-1, AEGL-2 and AEGL-3.
- AEGL-1** AEGL-1 is the airborne concentration (expressed as parts per million or milligrams per cubic meter [ppm or mg/m<sup>3</sup>]) of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic, non-sensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.
- AEGL-2** AEGL-2 is the airborne concentration (expressed as ppm or mg/m<sup>3</sup>) of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.
- AEGL-3** AEGL-3 is the airborne concentration (expressed as ppm or mg/m<sup>3</sup>) of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.
- Alcohol resistant foam** A foam that is resistant to “polar” chemicals such as ketones and esters which may break down other types of foam.
- Biological agents** Living organisms that cause disease, sickness and mortality in humans. Anthrax and Ebola are examples of biological agents.  
**Refer to GUIDE 158.**
- Blister agents (vesicants)** Substances that cause blistering of the skin. Exposure is through liquid or vapor contact with any exposed tissue (eyes, skin, lungs). Mustard (H), Distilled Mustard (HD), Nitrogen Mustard (HN) and Lewisite (L) are blister agents.  
**Symptoms:** Red eyes, skin irritation, burning of skin, blisters, upper respiratory damage, cough, hoarseness.



## Glossary

<b>Blood agents</b>	<p>Substances that injure a person by interfering with cell respiration (the exchange of oxygen and carbon dioxide between blood and tissues). Hydrogen cyanide (AC) and Cyanogen chloride (CK) are blood agents.</p> <p><b>Symptoms:</b> Respiratory distress, headache, unresponsiveness, seizures, coma.</p>
<b>Burn</b>	<p>Refers to either a chemical or thermal burn, the former may be caused by corrosive substances and the latter by liquefied cryogenic gases, hot molten substances, or flames.</p>
<b>CBRN</b>	<p>Chemical, biological, radiological or nuclear warfare agent.</p>
<b>Choking agents</b>	<p>Substances that cause physical injury to the lungs. Exposure is through inhalation. In extreme cases, membranes swell and lungs become filled with liquid (pulmonary edema). Death results from lack of oxygen; hence, the victim is “choked”. Phosgene (CG) is a choking agent.</p> <p><b>Symptoms:</b> Irritation to eyes/nose/throat, respiratory distress, nausea and vomiting, burning of exposed skin.</p>
<b>CO<sub>2</sub></b>	<p>Carbon dioxide gas.</p>
<b>Cold zone</b>	<p>Area where the command post and support functions that are necessary to control the incident are located. This is also referred to as the clean zone, green zone or support zone in other documents. (EPA Standard Operating Safety Guidelines, OSHA 29 CFR 1910.120, NFPA 472)</p>
<b>Combustible liquid</b>	<p>Liquids which have a flash point greater than 60.5°C (141°F) and below 93°C (200°F). U.S. regulations permit a flammable liquid with a flash point between 38°C (100°F) and 60.5°C (141°F) to be reclassified as a combustible liquid.</p>
<b>Compatibility Group</b>	<p>Letters identify explosives that are deemed to be compatible. Class 1 materials are considered to be “compatible” if they can be transported together without significantly increasing either the probability of an incident or, for a given quantity, the magnitude of the effects of such an incident.</p> <p>A Substances which are expected to mass detonate very soon after fire reaches them.</p>

## Glossary

- B Articles which are expected to mass detonate very soon after fire reaches them.
- C Substances or articles which may be readily ignited and burn violently without necessarily exploding.
- D Substances or articles which may mass detonate (with blast and/or fragment hazard) when exposed to fire.
- E&F Articles which may mass detonate in a fire.
- G Substances and articles which may mass explode and give off smoke or toxic gases.
- H Articles which in a fire may eject hazardous projectiles and dense white smoke.
- J Articles which may mass explode.
- K Articles which in a fire may eject hazardous projectiles and toxic gases.
- L Substances and articles which present a special risk and could be activated by exposure to air or water.
- N Articles which contain only extremely insensitive detonating substances and demonstrate a negligible probability of accidental ignition or propagation.
- S Packaged substances or articles which, if accidentally initiated, produce effects that are usually confined to the immediate vicinity.

### **Control zones**

Designated areas at dangerous goods incidents, based on safety and the degree of hazard. Many terms are used to describe control zones; however, in this guidebook, these zones are defined as the hot/exclusion/red/restricted zone, warm/contamination reduction/yellow/limited access zone, and cold/support/green/clean zone. (EPA Standard Operating Safety Guidelines, OSHA 29 CFR 1910.120, NFPA 472)

### **Cryogenic liquid**

A refrigerated, liquefied gas that has a boiling point colder than -90°C (-130°F) at atmospheric pressure.

### **Dangerous Water Reactive Material**

Produces significant toxic gas when it comes in contact with water.

## Glossary

<b>Decomposition products</b>	Products of a chemical or thermal break-down of a substance.
<b>Decontamination</b>	The removal of dangerous goods from personnel and equipment to the extent necessary to prevent potential adverse health effects. Always avoid direct or indirect contact with dangerous goods; however, if contact occurs, personnel should be decontaminated as soon as possible. Since the methods used to decontaminate personnel and equipment differ from one chemical to another, contact the chemical manufacturer, through the agencies listed on the inside back cover, to determine the appropriate procedure. Contaminated clothing and equipment should be removed after use and stored in a controlled area (warm/contamination reduction/limited access zone) until cleanup procedures can be initiated. In some cases, protective clothing and equipment cannot be decontaminated and must be disposed of in a proper manner.
<b>Dry chemical</b>	A preparation designed for fighting fires involving flammable liquids, pyrophoric substances and electrical equipment. Common types contain sodium bicarbonate or potassium bicarbonate.
<b>Edema</b>	The accumulation of an excessive amount of watery fluid in cells and tissues. Pulmonary edema is an excessive buildup of water in the lungs, for instance, after inhalation of a gas that is corrosive to lung tissue.
<b>ERPG(s)</b>	Emergency Response Planning Guideline(s). Values intended to provide estimates of concentration ranges above which one could reasonably anticipate observing adverse health effects; see ERPG-1, ERPG-2 and ERPG-3.
<b>ERPG-1</b>	The maximum airborne concentration below which it is believed nearly all individuals could be exposed for up to 1 hour without experiencing more than mild, transient adverse health effects or without perceiving a clearly defined objectionable odor.
<b>ERPG-2</b>	The maximum airborne concentration below which it is believed nearly all individuals could be exposed for up to 1 hour without experiencing or developing irreversible or other serious health effects or symptoms that could impair an individual's ability to take protective action.

## Glossary

<b>ERPG-3</b>	The maximum airborne concentration below which it is believed nearly all individuals could be exposed for up to 1 hour without experiencing or developing life-threatening health effects.
<b>Flammable liquid</b>	A liquid that has a flash point of 60.5°C (141°F) or lower.
<b>Flash point</b>	Lowest temperature at which a liquid or solid gives off vapor in such a concentration that, when the vapor combines with air near the surface of the liquid or solid, a flammable mixture is formed. Hence, the lower the flash point, the more flammable the material.
<b>Hazard zones (Inhalation Hazard Zones)</b>	<p><b>HAZARD ZONE A:</b> Gases: LC50 of less than or equal to 200 ppm, Liquids: V equal to or greater than 500 LC50 and LC50 less than or equal to 200 ppm,</p> <p><b>HAZARD ZONE B:</b> Gases: LC50 greater than 200 ppm and less than or equal to 1000 ppm, Liquids: V equal to or greater than 10 LC50; LC50 less than or equal to 1000 ppm and criteria for Hazard Zone A are not met.</p> <p><b>HAZARD ZONE C:</b> LC50 greater than 1000 ppm and less than or equal to 3000 ppm,</p> <p><b>HAZARD ZONE D:</b> LC50 greater than 3000 ppm and less than or equal to 5000 ppm.</p>
<b>Hot zone</b>	Area immediately surrounding a dangerous goods incident which extends far enough to prevent adverse effects from released dangerous goods to personnel outside the zone. This zone is also referred to as exclusion zone, red zone or restricted zone in other documents. (EPA Standard Operating Safety Guidelines, OSHA 29 CFR 1910.120, NFPA 472)
<b>IED</b>	See “Improvised Explosive Device”.
<b>Immiscible</b>	In this guidebook, means that a material does not mix readily with water.
<b>Improvised Explosive Device</b>	A bomb that is manufactured from commercial, military or homemade explosives.
<b>Large spill</b>	A spill that involves quantities that are greater than 200 liters for liquids and greater than 300 kilograms for solids.

## Glossary

<b>LC50</b>	Lethal concentration 50. The concentration of a material administered by inhalation that is expected to cause the death of 50% of an experimental animal population within a specified time. (Concentration is reported in either ppm or mg/m <sup>3</sup> )
<b>Mass explosion</b>	Explosion which affects almost the entire load virtually instantaneously.
<b>mg/m<sup>3</sup></b>	Milligrams of a material per cubic meter of air.
<b>Miscible</b>	In this guidebook, means that a material mixes readily with water.
<b>mL/m<sup>3</sup></b>	Milliliters of a material per cubic meter of air. (1 mL/m <sup>3</sup> equals 1 ppm)
<b>Nerve agents</b>	<p>Substances that interfere with the central nervous system. Exposure is primarily through contact with the liquid (via skin and eyes) and secondarily through inhalation of the vapor. Tabun (GA), Sarin (GB), Soman (GD) and VX are nerve agents.</p> <p><b>Symptoms:</b> Pinpoint pupils, extreme headache, severe tightness in the chest, dyspnea, runny nose, coughing, salivation, unresponsiveness, seizures.</p>
<b>Non-polar</b>	See "Immiscible".
<b>n.o.s.</b>	These letters refer to "not otherwise specified". The entries which use this description are generic names such as "Corrosive liquid, n.o.s." This means that the actual chemical name for that corrosive liquid is not listed in the regulations; therefore, a generic name must be used to describe it on shipping papers.
<b>Noxious</b>	In this guidebook, means that a material may be harmful or injurious to health or physical well-being.
<b>Oxidizer</b>	A chemical which supplies its own oxygen and which helps other combustible material burn more readily.
<b>P</b>	The letter "P" following a guide number in the yellow-bordered and blue-bordered pages identifies a material which may polymerize violently under high temperature conditions or contamination with other products. This polymerization will produce heat and high pressure buildup in containers which may explode or rupture. (See polymerization below)

## Glossary

<b>Packing Group</b>	The Packing Group (PG) is assigned based on the degree of danger presented by the hazardous material:  PG I : Great danger PG II : Medium danger PG III : Minor danger
<b>PG</b>	See Packing Group
<b>pH</b>	pH is a value that represents the acidity or alkalinity of a water solution. Pure water has a pH of 7. A pH value below 7 indicates an acid solution (a pH of 1 is extremely acidic). A pH above 7 indicates an alkaline solution (a pH of 14 is extremely alkaline). Acids and alkalies (bases) are commonly referred to as corrosive materials.
<b>PIH</b>	Poison Inhalation Hazard. Term used to describe gases and volatile liquids that are toxic when inhaled. (Same as TIH)
<b>Polar</b>	See "Miscible".
<b>Polymerization</b>	This term describes a chemical reaction which is generally associated with the production of plastic substances. Basically, the individual molecules of the chemical (liquid or gas) react with each other to produce what can be described as a long chain. These chains can be formed in many useful applications. A well known example is the styrofoam (polystyrene) coffee cup which is formed when liquid molecules of styrene react with each other or polymerize forming a solid, therefore changing the name from styrene to polystyrene (poly means many).
<b>ppm</b>	Parts per million. (1 ppm equals 1 mL/m <sup>3</sup> )
<b>Protective clothing</b>	Includes both respiratory and physical protection. One cannot assign a level of protection to clothing or respiratory devices separately. These levels were accepted and defined by response organizations such as U.S. Coast Guard, NIOSH, and U.S. EPA. Level A: SCBA plus totally encapsulating chemical resistant clothing (permeation resistant). Level B: SCBA plus hooded chemical resistant clothing (splash suit). Level C: Full or half-face respirator plus hooded chemical resistant clothing (splash suit). Level D: Coverall with no respiratory protection.

## Glossary

<b>Pyrophoric</b>	A material which ignites spontaneously upon exposure to air (or oxygen).
<b>Radiation Authority</b>	As referred to in GUIDES 161 through 166 for radioactive materials, the Radiation Authority is either a Federal, state/provincial agency or state/province designated official. The responsibilities of this authority include evaluating radiological hazard conditions during normal operations and during emergencies. If the identity and telephone number of the authority are not known by emergency responders, or included in the local response plan, the information can be obtained from the agencies listed on the inside back cover. They maintain a periodically updated list of radiation authorities.
<b>Radioactivity</b>	The property of some substances to emit invisible and potentially harmful radiation.
<b>Refrigerated liquid</b>	See “Cryogenic liquid”.
<b>Small spill</b>	A spill that involves quantities that are less than 200 liters for liquids and less than 300 kilograms for solids.
<b>Straight (solid) stream</b>	Method used to apply or distribute water from the end of a hose. The water is delivered under pressure for penetration. In an efficient straight (solid) stream, approximately 90% of the water passes through an imaginary circle 38 cm (15 inches) in diameter at the breaking point. Hose (solid or straight) streams are frequently used to cool tanks and other equipment exposed to flammable liquid fires, or for washing burning spills away from danger points. However, straight streams will cause a spill fire to spread if improperly used or when directed into open containers of flammable and combustible liquids.
<b>TIH</b>	Toxic Inhalation Hazard. Term used to describe gases and volatile liquids that are toxic when inhaled. (Same as PIH)
<b>V</b>	Saturated vapor concentration in air of a material in mL/m <sup>3</sup> (volatility) at 20°C and standard atmospheric pressure.
<b>Vapor density</b>	Weight of a volume of pure vapor or gas (with no air present) compared to the weight of an equal volume of dry air at the same temperature and pressure. A vapor density less than 1 (one) indicates that the vapor is lighter than air and will tend to rise. A vapor density greater than 1 (one) indicates that the vapor is heavier than air and may travel along the ground.

## Glossary

<b>Vapor pressure</b>	Pressure at which a liquid and its vapor are in equilibrium at a given temperature. Liquids with high vapor pressures evaporate rapidly.
<b>Viscosity</b>	Measure of a liquid's internal resistance to flow. This property is important because it indicates how fast a material will leak out through holes in containers or tanks.
<b>Warm zone</b>	Area between Hot and Cold zones where personnel and equipment decontamination and hot zone support take place. It includes control points for the access corridor and thus assists in reducing the spread of contamination. Also referred to as the contamination reduction corridor (CRC), contamination reduction zone (CRZ), yellow zone or limited access zone in other documents. (EPA Standard Operating Safety Guidelines, OSHA 29 CFR 1910.120, NFPA 472)
<b>Water-sensitive</b>	Substances which may produce flammable and/or toxic decomposition products upon contact with water.
<b>Water spray (fog)</b>	<p>Method or way to apply or distribute water. The water is finely divided to provide for high heat absorption. Water spray patterns can range from about 10 to 90 degrees. Water spray streams can be used to extinguish or control the burning of a fire or to provide exposure protection for personnel, equipment, buildings, etc. <b>(This method can be used to absorb vapors, knock-down vapors or disperse vapors. Direct a water spray (fog), rather than a straight (solid) stream, into the vapor cloud to accomplish any of the above).</b></p> <p>Water spray is particularly effective on fires of flammable liquids and volatile solids having flash points above 37.8°C (100°F).</p> <p>Regardless of the above, water spray can be used successfully on flammable liquids with low flash points. The effectiveness depends particularly on the method of application. With proper nozzles, even gasoline spill fires of some types have been extinguished when coordinated hose lines were used to sweep the flames off the surface of the liquid. Furthermore, water spray carefully applied has frequently been used with success in extinguishing fires involving flammable liquids with high flash points (or any viscous liquids) by causing frothing to occur only on the surface, and this foaming action blankets and extinguishes the fire.</p>



## **PUBLICATION DATA**

The 2008 Emergency Response Guidebook (ERG2008) was prepared by the staff of Transport Canada, the U.S. Department of Transportation, and the Secretariat of Communications and Transport of Mexico with the assistance of many interested parties from government and industry including the collaboration of CIQUIME of Argentina. The principal authors of the ERG are Transport Canada's Michel Cloutier and U.S. DOT's George Cushmac. Printing and publication services are provided through U.S. DOT's Pipeline and Hazardous Materials Safety Administration, (PHMSA) Office of Hazardous Materials Initiatives and Training.

ERG2008 is based on earlier Transport Canada, U.S. DOT, and Secretariat of Communications and Transport emergency response guidebooks. ERG2008 is published in three languages: English, French and Spanish. The Emergency Response Guidebook has been translated and printed in other languages, including Chinese, German, Hebrew, Japanese, Portuguese, Korean, Hungarian, Polish, Turkish and Thai.

We encourage countries that wish to participate in future editions of the Guidebook to provide their emergency response center information for inclusion. Please contact any of the websites or telephone numbers in the paragraph below.

### **DISTRIBUTION OF THIS GUIDEBOOK**

The primary objective is to place one copy of the ERG2008 in each publicly owned emergency service vehicle through distribution to Federal, state, provincial and local public safety authorities. The distribution of this guidebook is being accomplished through the voluntary cooperation of a network of key agencies. Emergency service organizations that have not yet received copies of ERG2008 should contact the respective distribution center in their country, state or province. In the U.S., information about the distribution center for your location may be obtained from the Office of Hazardous Materials Safety web site at <http://hazmat.dot.gov> or call 202-366-4900. In Canada, contact CANUTEC at 613-992-4624 or via the web site at <http://www.canutec.gc.ca> for information. In Mexico, call SCT at 52-55-5684-1275 or 684-0188 or via email at [iflores@sct.gob.mx](mailto:iflores@sct.gob.mx). In Argentina, call CIQUIME at 011-4613-1100, or via the web site at <http://www.ciquime.org.ar>, or via email at [gre2008@ciquime.org.ar](mailto:gre2008@ciquime.org.ar)

### **REPRODUCTION and RESALE**

Copies of this document which are provided free of charge to fire, police and other emergency services may not be resold. ERG2008 (PHH50-ERG2008) may be reproduced without further permission subject to the following:

The names and the seals of the participating governments may not be reproduced on a copy of this document unless that copy accurately reproduces the entire content (text, format, and coloration) of this document without modification. In addition, the publisher's full name and address must be displayed on the outside back cover of each copy, replacing the wording placed on the center of the back cover.

Constructive comments concerning ERG2008 are solicited; in particular, comments concerning its use in handling incidents involving dangerous goods. Comments should be addressed to:

**In Canada:**

Director, CANUTEC  
Transport Dangerous Goods  
Transport Canada  
Ottawa, Ontario  
Canada K1A 0N5

Phone: 613-992-4624 (information)  
Fax: 613-954-5101  
Email: [canutec@tc.gc.ca](mailto:canutec@tc.gc.ca)

**In the U.S.:**

U. S. Department of Transportation  
Pipeline and Hazardous Materials Safety Administration  
Office of Hazardous Materials Initiatives and Training (PHH-50)  
Washington, DC 20590-0001

Phone: 202-366-4900  
Fax: 202-366-7342  
Email: [ERG2008@dot.gov](mailto:ERG2008@dot.gov)

**In Mexico:**

Secretariat for Communications and Transport  
Land Transport Directorate  
Hazardous Materials and Wastes Directorate  
Calz. de las Bombas No. 411-9 piso  
Col. San Bartolo Coapa  
Coyoacan 04800, D.F.  
Mexico

Phone and Fax: +52-55-5684-1275 and 684-0188

**In Argentina:**

Chemistry Information Center for Emergencies (CIQUIME)  
Juan Bautista Alberdi 2986  
C1406GSS Buenos Aires, Argentina  
Tel. +54-11-4613-1100 Fax (011) 4613-3707  
Email: [gre2008@ciquime.org.ar](mailto:gre2008@ciquime.org.ar)

## NOTES

## **NOTES**

## NOTES

## NOTES

The Emergency Response Guidebook is normally revised and reissued every four years. However, in the event of a significant mistake, omission or change in the state of knowledge, special instructions to change the guidebook (in pen-and-ink, with paste-over stickers, or with a supplement) may be issued.

Users of this guidebook should check periodically (about every 6 months) to make sure their version is current. Changes should be annotated below. Contact:

**DOT/PHMSA**

<http://hazmat.dot.gov/pubs/erg/guidebook.htm>

**TRANSPORT CANADA**

<http://www.tc.gc.ca/canutec/en/guide/guide.htm>

**CIQUIME**

<http://www.ciquime.org.ar>

*This guidebook incorporates changes dated:*

---

---

---

## EMERGENCY RESPONSE TELEPHONE NUMBERS

### MEXICO

1. SETIQ

**01-800-00-214-00** in the Mexican Republic  
For calls originating in Mexico City and the Metropolitan Area  
**5559-1588**  
For calls originating elsewhere, call  
**+52-55-5559-1588**

2. GENACOM

**01-800-00-413-00** in the Mexican Republic  
For calls originating in Mexico City and the Metropolitan Area  
**5128-0000 exts. 11470, 11471, 11472, 11473, 11474, 11475, 11476 and 11477**  
For calls originating elsewhere, call  
**+52-55-5128-0000 exts. 11470, 11471, 11472, 11474, 11475 and 11476**

### ARGENTINA

1. CIQUIME

**0-800-222-2933** in the Republic of Argentina  
For calls originating elsewhere, call  
**+54-11-4613-1100**

### BRAZIL

1. PRÓ-QUÍMICA

**0-800-118270**  
(Toll-free in Brazil)  
For calls originating elsewhere, call  
**+55-11-232-1144**  
(Collect calls are accepted)

### COLOMBIA

1. CISPROQUIM

**01-800-091-6012** in Colombia  
For calls originating in Bogotá, Colombia call  
**288-6012**  
For calls originating elsewhere call  
**+57-1-288-6012**

For additional details see the section entitled “WHO TO CALL FOR ASSISTANCE”.



## **EMERGENCY RESPONSE TELEPHONE NUMBERS**

### **CANADA**

1. **CANUTEC**

**613-996-6666**

(Collect calls are accepted)

**\*666 cellular** (in Canada only)

### **UNITED STATES**

1. **CHEMTREC®**

**1-800-424-9300**

(Toll-free in the U.S., Canada and the U.S. Virgin Islands)

**703-527-3887** For calls originating elsewhere

(Collect calls are accepted)

2. **CHEMTEL, INC.**

**1-888-255-3924**

(Toll-free in the U.S., Canada, Puerto Rico and the U.S. Virgin Islands)

**813-248-0585** For calls originating elsewhere

(Collect calls are accepted)

3. **INFOTRAC**

**1-800-535-5053**

(Toll-free in the U.S., Canada and the U.S. Virgin Islands)

**352-323-3500** For calls originating elsewhere

(Collect calls are accepted)

4. **3E COMPANY**

**1-800-451-8346**

(Toll-free in the U.S., Canada and the U.S. Virgin Islands)

**760-602-8703** For calls originating elsewhere

(Collect calls are accepted)

5. **MILITARY SHIPMENTS**

**703-697-0218 - Explosives/ammunition incidents**

(Collect calls are accepted)

**1-800-851-8061 - All other dangerous goods incidents**

6. **NATIONWIDE POISON CONTROL CENTER (United States only)**

**1-800-222-1222 (toll-free in the U.S.)**

**THIS DOCUMENT SHOULD NOT BE USED TO  
DETERMINE COMPLIANCE WITH THE  
DANGEROUS GOODS REGULATIONS  
OR  
TO CREATE WORKER SAFETY DOCUMENTS  
FOR SPECIFIC CHEMICALS**

## **NOT FOR SALE**

**This document is distributed free of charge to Public Safety Organizations  
and may not be resold.**



U.S. Department of Transportation  
Pipeline and Hazardous Materials Safety Administration



Transport Canada    Transports  
Canada                    Canada



Secretariat of Transport and Communications