Exhibit B.7 NOTICE TO WATER WELL CONTRACTOR The objiginal and first copy of this poore are to be filed with the WATER RESOURCES DEPARTMENT.

SALEM, OREGON 97310

JUN 2 7 1980

(Please type or print) within 30 days from the date State Permit No. of well completionWATER RESOURCES(DDENDE vrite above this line) SALEM, OREGON (1) OWNER: (10) LOCATION OF WELL: Lorne S. MacLean County Multnomah Name Driller's well number Route 3, Box 403 Address NE 14 NW 14 Section 10 T. 2 N R. 2 W. W.M. Hillsboro, Oregon 97123 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): NEW WEIGH Deepening 🕱 Reconditioning 

Abandon If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Driven 🗆 ft. below land surface. Date 6/23/80 650 Domestic K Industrial Municipal Static level Jetted 🔲 Bored Irrigation 
Test Well 
Other Artesian pressure lbs, per square inch. Date (5) CASING INSTALLED: Threaded [ Welded X (12) WELL LOG: Diameter of well below casing ... 4 "Diam. from 0 ft. to 800 ft. Gage PVC160 Depth drilled 140 ft. Depth of completed well .... Diam. from \_\_\_\_\_ft, to \_\_\_\_\_ft. Gage \_\_\_\_ Formation: Describe color, texture, grain size and structure of materials: " Diam. from ..... ft. to ..... and show thickness and nature of each stratum and aguifer penetrated. with at least one entry for each change of formation. Report each change in (6) PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? X Yes No. Type of perforator used Dri11 MATERIAL From SWL in by diameter in. Size of perforations Previously drilled-open hole 655 60 perforations from 780 ft. to 800 11 - fill 655 660 Hard gray-black basalt-occ. ..... perforations from \_\_\_\_\_ ft. to \_\_\_\_ ft. 660 680 gray-brown ... perforations from ...... 686 Brown basalt w/soapstone 680 (7) SCREENS: Well screen installed? | Yes | No Hard gray-black basalt-occ. Manufacturer's Name 720 gray-brown ...... Model No. ..... Gray-brown basalt & lava w Diam. ..... Slot size ...... Set from ..... ft. to .... ft. 730 soaps tone 4 gpm Diam. ..... Slot size ...... Set from ..... ft. to ..... ft. Black basalt & lava--occ. 730 soapstone 750 8 gpm Drawdown is amount water level is lowered below static level (8) WELL TESTS: Hard gray-black basalt 750 770 a pump test made? Yes No If yes, by whom? Broken brown & gray-brown 20 gal./min. with 125 ft. drawdown after basa1t 800 8 gpm hrs. er test gal./min. with ft. drawdown after Temperature of water 620 Depth artesian flow encountered ...... ft. 6/20/80 Completed Date well drilling machine moved off of well (9) CONSTRUCTION: 19 Well seal-Material used X Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. Well sealed from land surface to Diameter of well bore to bottom of seal \_\_\_\_\_ in. (Drilling Machine Operator)
Date 6/25/80, 19 Diameter of well bore below seal in. Drilling Machine Operator's License No. 523 How was cement grout placed? .....X Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? 

Yes 

No Plug S...... Size: location ...... Name A. M. JANNSEN WELL DRILLING CO., INC. Did any strata contain unusable water? Thes I No (Person, firm or corporation) (Type or print) Address 21075 SW Taalatin Valley Hwy. Aloha, Type of water? depth of strata Method of sealing strata off (Water Well Contractor) Was well gravel packed? ☐ Yes ☐ No

Contractor's License No. ...